AD 2. AERODROMES

OINZ AD 2.1 AERODROME LOCATION INDICATOR AND NAME

OINZ - SARI / DASHT-E-NAZ / Secondary International Aerodrome

OINZ AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP coordinates and site at AD*	363809N 0531137E
2	*Direction and distance from (city)*	NE, 9 NM from Sari
3	*Elevation / Reference temperature*	37 FT / 29°C
4	*MAG VAR / Annual change*	5° E / Information not available
5	*AD Administration, address, telephone, telefax, telex, AFS*	Iran Airports & Air Navigation Company (IAC) Sari / Dasht-e-Naz Airport Postal code: 48451-64811 Sari / Dasht-e-Naz , Islamic Republic of Iran Tel : +9811 – 33722401-3, 33710000 Telefax: +9811 - 33722404 Telex: NIL AFS: OINZYDYX
6	*Types of traffic permitted (IFR/VFR)*	IFR/VFR
7	*Remarks*	Website: www.sariairport.ir

OINZ AD 2.3 OPERATIONAL HOURS

1	*AD Administration*	SAT to WED 0400-1200
2	*Customs and immigration*	O/R
3	*Health and sanitation*	O/R
4	*AIS Briefing Office*	NIL
5	*ATS Reporting Office (ARO)*	Service available by ATS
6	*MET Briefing Office*	NIL
7	*ATS*	0330-2030
8	*Fuelling*	H24
9	*Handling*	Available during main carrier schedule flights, other times O/R
10	*Security*	H24
11	*De-icing*	NIL
12	*Remarks*	Other times O/R. PPR at least 48 HR before EOBT from OINZ

OINZ AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo - handling facilities*	Available by main carrier
2	*Fuel / oil types*	Jet A1- JP4
3	*Fuelling facilities/capacity*	Jet A1: 1 truck, 47000 liters, 42 liters/sec ; 1 truck, 20000 liters, 25 liters/sec ; JP4: Provided in 18 liters barrels with PPR.
4	*De - icing facilities*	NIL
5	*Hanger space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

OINZ AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Available in the city
2	*Restaurants*	Available in the city
3	*Transportation*	Taxis
4	*Medical facilities*	First aids and doctor at AD during commercial flights, Hospital in the city
5	*Bank and Post Office*	Bank at AD & in the city, Post office in the city
6	*Tourist Office*	Available in the city
7	*Remarks*	NIL

OINZ AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 7
2	*Rescue equipment*	Available in accordance with AD category for fire fighting.
3	*Capability for removal of disabled aircraft*	NIL
4	*Remarks*	CAT 8 for scheduled flights and non-scheduled flights with prior permission.

→ OINZ AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	1 Snow plough
2	*Clearance priorities*	1-RWY 16/34 2-TWY A and B 3-Apron
3	*Remarks*	NIL

OINZ AD 2.8 APRONS, TAXIWAYS

1	*Apron surface and strength*	Surface: Asphalt Strength: Information not available
2	*Taxiway width, surface and strength*	Width: 23 M Surface: Asphalt Strength: NIL
3	*Remarks*	Apron dimension: 191 x 110 M

OINZ AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and parking guidance system of aircraft stands*	Taxiing guidance signs at all intersections with TWY A , B and RWY Guide lines at apron Nose-in guidance at aircraft stand
2	*RWY and TWY markings and LGT*	RWY: Designation, THR, DTHR, TDZ, centre line, edge & RWY end marked RWY lighting: See OINZ AD 2.14 TWY: Edge marked TWY lighting: See OINZ AD 2.15
3	*Stop bars*	NIL
4	*Remarks*	NIL

OINZ AD 2.10 AERODROME OBSTACLES

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation/ HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	b	c	a	b	
16 / APCH 34 / TKOF	NDB antenna 75 FT AGL LGTD	364012.5N 0531039.6E	Camera 30 FT AMSL NIL	363840N 0531127E	
34 / APCH 16 / TKOF	Flood lights 116 FT AMSL LGTD	363806N 0531146E	Camera 27 FT AMSL NIL	363910N 0531114E	
34 / APCH 16 / TKOF	Power line 170 FT AMSL LGTD	363717N 0531203E	Camera 33 FT AMSL NIL	363922N 0531109E	
34 / APCH 16 / TKOF	Power line 213 FT AMSL LGTD	363710N 0531206E	Camera 14 FT AMSL NIL	363919N 0531055E	
34 / APCH 16 / TKOF	Power line 173 FT AMSL LGTD	363711N 0531201E	Camera 20 FT AMSL NIL	363903N 0531102E	
34 / APCH 16 / TKOF	Power line 144 FT AMSL LGTD	363711N 0531156E	Two RCAG Mast 115 FT AGL Marked /LGTD	363813N 0531148E	
34 / APCH 16 / TKOF	Power line 180 FT AMSL LGTD	363712N 0531152E	DVOR Site 17 FT AGL LGTD	363854.7N 0531120.0E	
34 / APCH 16 / TKOF	Power line 137 FT AMSL LGTD	363713N 0531150E	New control tower BLDG 139 FT AMSL LGTD	363811N 0531147E	
34 / APCH 16 / TKOF	Power line 156 FT AMSL LGTD	363706N 0531150E	Power line 203 FT AMSL NIL	363734N 0531212E	
34 / APCH 16 / TKOF	Power line 191 FT AMSL LGTD	363703N 0531149E	Power line 130 FT AMSL NIL	363716N 0531140E	
34 / APCH 16 / TKOF	Power line 145 FT AMSL LGTD	363715N 0531143E	Power line 133 FT AMSL NIL	363729N 0531204E	
34 / APCH 16 / TKOF	Power line 135 FT AMSL LGTD	363723N 0531154E	Power line 193 FT AMSL NIL	363713N 0531135E	

In approach / TKOF areas			*In circling area and at AD*		*Remarks*
1			2		3
RWY/Area affected	*Obstacle type Elevation/ HGT Markings/LGT*	*Coordinates*	*Obstacle type Elevation / HGT Markings/LGT*	*Coordinates*	
a	b	c	a	b	
34 / APCH 16 / TKOF	Power line 131 FT AMSL LGTD	363721N 0531149E	Power line 214 FT AMSL NIL	363707N 0531125E	
34 / APCH 16 / TKOF	Power line 132 FT AMSL LGTD	363718N 0531145E	Power line 133 FT AMSL LGTD	363718N 0531131E	
34 / APCH 16 / TKOF	Power line 296 FT AMSL LGTD	363530N 0531250E	Power line 223 FT AMSL NIL	363717N 0531216E	
34 / APCH 16 / TKOF	Power line 360 FT AMSL NIL	363517N 0531327E	Power line 177 FT AMSL NIL	363707N 0531217E	
34 / APCH 16 / TKOF	Power line 357 FT AMSL NIL	363504N 0531322E	Power line 130 FT AMSL NIL	363714N 0531142E	
34 / APCH 16 / TKOF	Power line 559 FT AMSL NIL	363439N 0531313E	Power line 177 FT AMSL NIL	363705N 0531141E	
34 / APCH 16 / TKOF	Power line 691 FT AMSL NIL	363424N 0531307E	Power line 149 FT AMSL NIL	363700N 0531140E	
34 / APCH 16 / TKOF	Power line 750 FT AMSL NIL	363412N 0531303E	Power line 138 FT AMSL NIL	363711N 0531136E	
34 / APCH 16 / TKOF	Power line 763 FT AMSL NIL	363348N 0531226E	Power line 205 FT AMSL NIL	363721N 0531218E	
34 / APCH 16 / TKOF	Power line 748 FT AMSL NIL	363341N 0531213E	Power line 474 FT AMSL NIL	363608N 0531345E	
34 / APCH 16 / TKOF	Power line 700 FT AMSL NIL	363343N 0531204E	Power line 315 FT AMSL NIL	363556N 0531340E	
34 / APCH 16 / TKOF	Power line 655 FT AMSL NIL	363321N 0531129E	Power line 336 FT AMSL NIL	363543N 0531336E	
34 / APCH 16 / TKOF	LOC Power Station 52 FT AMSL NIL	363751N 0531144E	Power line 359 FT AMSL NIL	363532N 0531331E	
34 / APCH 16 / TKOF	LOC building 50 FT AMSL NIL	363750.5N 0531143.7E	Power line 219 FT AMSL NIL	363653N 0531059E	
34 / APCH 16 / TKOF	LOC antenna 56 FT AMSL NIL	363749.7N 0531141.1E			
34 / APCH 16 / TKOF	GP antenna 59 FT AMSL NIL	363912.7 N 0531110.5 E			

OINZ AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET Office*	Sari / Dasht-e-Naz
2	*Hours of service* *MET Office outside hours*	H24 --
9	*ATS units provided with information*	Dasht-e-Naz TWR

OINZ AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength(PCN) and surface of RWY and SWY*	*THR coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*
1	2	3	4	5	6
16	160.85°GEO	2643 x 45	50/F/C/X/T Asphalt	363920.84N 0531101.85E GUND -26 FT	THR 5 FT
34	340.85°GEO	2643 x 45	50/F/C/X/T Asphalt	363759.86N 0531136.76E GUND -26 FT	THR 37 FT

Slope of RWY - SWY	*SWY dimensions (M)*	*CWY dimensions (M)*	*Strip dimensions (M)*	*OFZ*	*Remarks*
7	8	9	10	11	12
0.37 %	60 x 45	60 x 150	NIL	NIL	DTHR RWY 34:1046M DTHR RWY 34 coordinates: 363832.51N 0531122.69E DTHR ELEV:24FT AD Reference Code: 4D
0.37 %	60 x 45	60 x 150	NIL	NIL	

OINZ AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	2	3	4	5	6
16	2643	2703	2703	2643	NIL
34	2643	2703	2703	1597	NIL

OINZ AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT type LEN INTST*	*THR LGT colour WBAR*	*VASIS (MEHT) PAPI*	*TDZ LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour INTST*	*RWY edge LGT LEN, spacing colour, INTST*	*RWY End LGT colour WBAR*	*SWY LGT LEN colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
16	*NIL*	*Green Supplemented By WBAR*	*PAPI Left/2.6° (49 FT)*	*NIL*	*NIL*	*2650 M 60 M White, LIH*	*Red*	*NIL*	*NIL*
34	*NIL*	*NIL Supplemented By WBAR*	*NIL*	*NIL*	*NIL*	*2650 M 60 M White, LIH*	*Red*	*NIL*	*NIL*

OINZ AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN location, characteristics and hours of operation*	On top of the control Tower building, FLG G and W, EV 2 sec HN and during IMC
2	*LDI location and LGT* *Anemometer location and LGT*	NIL
3	*TWY edge and centre line lighting*	Edge: all TWY + RWY 16/34 Centre line: NIL
4	*Secondary power supply/switch-over time*	Available Switch-over time: 10 - 15 sec
5	*Remarks*	NIL

OINZ AD 2.16 HELICOPTER LANDING AREA

NIL

OINZ AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	Sari / Dasht-e-Naz CTR : A circle, radius 30 NM centered at 363853.6N 0531120.1E (DVOR/DME).	Sari / Dasht-e-Naz ATZ : A circle, radius 7 NM centered at 363809N 0531137E (ARP)
2	*Vertical limits*	FL 175	4000 FT AMSL
3	*Airspace classification*	D	
4	*ATS unit call sign* *Language(s)*	Sari / Dasht-e-Naz TWR English / Persian	
5	*Transition altitude*	15000 FT AMSL	
6	*Remarks*	APP Service is provided by Dasht-e-Naz TWR on frequency 118.450 MHZ	

OINZ AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	2	3	4	5
TWR ATIS (INFO)	Dasht-e-Naz Tower Dasht-e-Naz Information	118.450 MHZ 119.600 MHZ 121.700 MHZ 121.500 MHZ 126.850 MHZ	0330-2030 Other times O/R	For vehicular movements Emergency FREQ

OINZ AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, CAT of ILS (For VOR/ILS, give VAR)	*ID*	*Frequency*	*Hours of operation*	*Site of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	2	3	4	5	6	7
DVOR/DME (5°E)	DNZ	113.100 MHZ CH 78X	H24	363853.6N 0531120.1E		
LOC 16 ILS CAT I (5° E)	IDNZ	110.500 MHZ	H24	363749.7N 0531141.1E		
ILS GP RWY 16		329.600 MHZ	H24	363912.6N 0531110.5E		3° RDH 57 FT
ILS DME RWY 16	IDNZ	CH 42X	H24	363912.7N 0531110.5E	16 FT	

DVOR/DME unusable in counter clockwise direction in the FLW area:

- At 20 DME ARC:
1- 270°- 220° BLW 3000FT AMSL.
2- 220°- 180° BLW 5000FT AMSL.
3- 180°- 160° BLW 7000FT AMSL.
4- 110°- 075° BLW 4000FT AMSL.
5- 075°- 270° over sea.

- At 40 DME ARC:
1- 270°- 240° BLW 4000FT AMSL.
2- 240°- 220° BLW 7000FT AMSL.
3- 220°- 075° BLW 12000FT AMSL.
4- 075°- 270° over sea.

OINZ AD 2.20 LOCAL TRAFFIC REGULATIONS

1. Fuel dumping area is located on an area with the following specifications:

   a) 370601N 0532712E (on track 020°, 30NM)

   b) 364901N 0534622E (on track 065°, 30NM)

   c) 364359N 0532850E (on track 065°, 15NM)

   d) 365227N 0531914E (on track 020°, 15NM) to the point of origin.

OINZ AD 2.21 NOISE ABATEMENT PROCEDURES

NIL

OINZ AD 2.22 FLIGHT PROCEDURES

Traffic pattern is defined as below:

a. For fighter and heavy fix wing ACFT 1500 feet,
b. For other fix wing ACFT 1000 feet and
c. For helicopter 500 feet.

Note: see AD 1.1.

OINZ AD 2.23 ADDITION AL INFORMATION

1- Strolling dogs exist on the movement area.

2- Intensive birds' accumulation exist in the vicinity of AD.

3- Isolated aircraft parking position located at holding bay at the beginning of RWY 16.

OINZ AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart – ICAO ..... AD 2 OINZ ADC
Standard Departure Chart - Instrument – ICAO ..... AD 2 OINZ SID 1-1
AD 2 OINZ SID 1-2
Standard Arrival Chart - Instrument – ICAO ..... AD 2 OINZ STAR 1-1
AD 2 OINZ STAR 1-2
Instrument Approach Chart – ICAO ..... AD 2 OINZ IAC 1-1
AD 2 OINZ IAC 2-1

←