

# Introduction to Data Structures

Jinkyu Lee

Dept. of Computer Science and Engineering,  
Sungkyunkwan University (SKKU)

# Homework 2A

---

- 40 points for coding evaluation
  - Submission format
    - File name: yourid\_HW2A.c
      - Example: 2000123456\_HW2A.c
    - File type: .c (NOT .cpp)
  - Submission site: <https://icampus.skku.edu>
    - Week 5: [Homework] 2A (code)
  
- 1 point for report
  - The report is not evaluated in detail but evaluated as Pass/Fail
  - Template: Homework Report Template.docx
  - Submission format
    - File name: yourid\_HW2A.pdf
      - Example: 2000123456\_HW2A.pdf
    - File type: .pdf
  - Submission site: <https://icampus.skku.edu>
    - Week 5: [Homework] 2A (report)
  
- Due date
  - 10/13 23:59 (no late submission accepted)

# Rules for homework

---

- You should follow instructions.
  - Compiler
    - You will get **no/less point** if your program cannot be complied with the specified compiler
  - Input/output format
    - You will get **no/less point** if TA's automatic evaluation program cannot parse your input or output.
  - Permitted modification scope
    - You will get **no/less point** if you modify code outside of the permitted modification scope
  - All other rules
    - You will get **severe penalty or no/less point** if you violate the given rules.

# Compiler and input/output rules for homework

- Every implementation homework will be evaluated by TA's automatic evaluation program with the following compiler.
  - Compiler: GCC 7.X, 8.X, 9.X or 10.X
    - <https://gcc.gnu.org/>
  - You will get no/less point if your program cannot be compiled with GCC 7.X, 8.X, 9.X or 10.X.
    - For example, do not rely on visual studio.
  - You can use standard library such as *stdlib.h* and *math.h*.
- Input/output format
  - You will get no/less point if TA's automatic evaluation program cannot parse your input or output according to the following rules.
  - Use `stdin` and `stdout`

# Problem

- Problem: Conversion of Infix to Postfix, and its evaluation of 2-digit hexadecimal (16-ary) numbers.
- A 2-digit hexadecimal number is expressed as 00, 01, 02, ... 09, 0A, 0B, 0C, 0D, 0E, 0F, 10, 11, 12, ..., 1A, 1B, 1C, 1D, 1E, 1F, ..., F0, F1, ... F9, FA, FB, FC, FD, FE, or FF.
  - Be careful that each character is either 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, A, B, C, D, E or F. (i.e., decimal numbers and upper-case letters A-E).
- There are four operators: +, -, \*, and /.
- For given Infix expression of 2-digit hexadecimal numbers, you should (i) convert it to Postfix expression, and (ii) evaluate the Postfix expression.
- The length of input is at most 50 characters without any blank.

# Problem

- After calculating a sub-expression, the result should be expressed as positive (or zero) 2-digit hexadecimal numbers. You don't need to care for a number larger than FF or smaller than 00.
  - e.g., there is no input like  $99 * 99$ , which is larger than FF.
  - e.g., there is no input like A0-B7, which is smaller than 00.
- For division, you only care for the quotient.
  - e.g.,  $B / 3 = 3$ , not 3.66.

# Input/Output

---

- Input (no space)

2A+05\*1A-0F

- Output (no space)

2A051A\*+0F-  
9D

# Template

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>

#define MAX_STACK 100

typedef enum {false , true} bool;

typedef struct {
    char small;
    char large;
    // *Variable "operator"
    // used in ConvInfixToPostfix function
    char operator;
}Hexa_num;

typedef struct {
    Hexa_num items[MAX_STACK];
    int top;
}Stack;

/* Modify from here */
/* if you need any user-defined function
/* Modify to here */

Hexa_num add(Hexa_num b1,Hexa_num b2);
Hexa_num subtract(Hexa_num b1,Hexa_num b2);
Hexa_num multiply(Hexa_num b1,Hexa_num b2);
Hexa_num division(Hexa_num b1,Hexa_num b2);
```

```
void InitStack (Stack *pstack);
bool IsFull(Stack *pstack);
bool IsEmpty(Stack *pstack);
Hexa_num Peek(Stack *pstack);
void Push(Stack *pstack,Hexa_num item);
void Pop(Stack *pstack);
void ConvInfixToPostfix(char* exp,char* convExp, int
len);
Hexa_num EvalPostfix(char* exp,int len);
void print_Hexa_num(Hexa_num result);

int main() {
    char infix_exp[100];
    char postfix_exp[100];
    Hexa_num result;

    scanf("%s",infix_exp);

    ConvInfixToPostfix(infix_exp,postfix_exp,strlen(infi
x_exp));
    printf("%s\n%s\n",infix_exp,postfix_exp);
    result =
    EvalPostfix(postfix_exp,strlen(postfix_exp));
    print_Hexa_num(result);
    return 0;
}
/* Modify from here */
/* implementation of functions
/* Modify to here */
```



# Template

- You cannot modify the template except the space between /\*Modify from here\*/ and /\*Modify to here\*/
- **Do not remove** /\*Modify from here\*/ and /\*Modify to here\*/
- TA will copy the space and evaluate your code.
- In the space, you need to implement the following functions.
- You may add user-defined functions.

```
Hexa_num add(Hexa_num b1, Hexa_num b2);
Hexa_num subtract(Hexa_num b1, Hexa_num b2);
Hexa_num multiply(Hexa_num b1, Hexa_num b2);
Hexa_num division(Hexa_num b1, Hexa_num b2);

void InitStack (Stack *pstack);
bool IsFull(Stack *pstack);
bool IsEmpty(Stack *pstack);
Hexa_num Peek(Stack *pstack);
void Push(Stack *pstack, Hexa_num item);
void Pop(Stack *pstack);
void ConvInfixToPostfix(char* exp, char* convExp, int len);
Hexa_num EvalPostfix(char* exp, int len);
void print_Hexa_num(Hexa_num result);
```

# Evaluation

---

## ■ Evaluation

- TA will test several cases.
- Read Pages 8~9 (regarding template) carefully.
- For each test case,
  - If your C code results in an answer within 10 seconds on a platform with average computing power,
    - If your output is perfect for both postfix expression and evaluation result,
      - You get 100%.
    - Else if your output is perfect only for postfix expression,
      - You get 50%.
    - Else if your output is perfect only for evaluation result,
      - You get 50%.
    - Else,
      - You get 0%.
  - Else,
    - You get 0%.