

Express

A Node.js framework

Content

- [What is Express?](#)
- [Middleware capabilities](#)
- [Installing Express](#)
- [Hello World example](#)
- [Routing](#)
- [Route handlers](#)
- [Resources](#)

What is Express?

A routing and middleware Web framework.

Middleware is a function with access to the

- request object
- response object
- next middleware in app's request-response cycle

So, an express callback might look like `function(req, res, next)`

Middleware capabilities

- Execution of code.
- Making changes to request and response objects.
- End the request-response cycle.
- Call the next middleware in the stack.

NOTE: If the current middleware does not end the request-response cycle, it must call `next()` to pass control, otherwise the request will be left hanging.

Installing Express in your Node app

1. Open your terminal
2. Navigate to the directory of your Node project
3. Type `npm install express --save`

NOTE: After installing node, you'll notice a new folder in your project named *node_modules*. This is where all the Node packages you install via npm typically reside.

PRO TIP: Add `node_modules` to your `.gitignore` file.

Hello World example

app.js

```
var express = require('express'); // import express
var app = express();
```

```
app.get('/', function (req, res) {
    res.send('Hello World!');
});
```

The same request and response objects we used in our last Node app.

```
var server = app.listen(3000, function() {
    var host = server.address().address;
    var port = server.address().port;
    console.log('App listening at http://%s:%s', host, port);
});
```

app.get

```
// GET requests to our server's root (/), will respond with  
// "Hello World!"  
// We call / a route  
app.get('/', function (req, res) {  
    res.send('Hello World!');  
});
```

This is part of the code from the previous slide.

Routing

What is routing?

The definition of end-points (URIs) to an application and how it responds to client requests

Defining a route

app.METHOD(path, [callback...], callback)

An instance of the express module. Can have a different variable name.

An HTTP request method. We've been using GET.

A path on the server (e.g. /data)

Function executed when route is matched

Route path examples

```
// will match request to the root  
app.get('/', function (req, res) {  
  res.send('root');  
});
```

```
// will match requests to /about  
app.get('/about', function (req, res) {  
  res.send('about');  
});
```

Route path even more examples

// will match anything with an a in the route name

```
app.get('/a/', function (req, res) {  
  res.send('/a/');  
});
```

// will match butterfly, dragonfly, but not butterflyman or dragonflyman

// and other words that end in fly

```
app.get('/.*fly$/', function (req, res) {  
  res.send('/.*fly$/');  
});
```

Route handlers

How we use route handlers

- Provide multiple callback functions that behave like middleware to handle request
- To impose pre-conditions on a route
- To pass control to subsequent routes
- Can be in form of
 - function
 - array of functions
 - combinations of both

Route handler with >1 callbacks

```
app.get('/example/b', function (req, res, next) {  
  console.log('response will be sent by the next function ...');  
  next();  
}, function (req, res) {  
  res.send('Hello from B!');  
});
```


Route with an array of callbacks

```
var cb0 = function (req, res, next) {  
  console.log('CB0');  
  next();  
}
```

```
var cb1 = function (req, res, next) {  
  console.log('CB1');  
  next();  
}
```

```
var cb2 = function (req, res) {  
  res.send('Hello from C!');  
}
```

```
app.get('/example/c', [cb0, cb1, cb2]);
```

Resources

- [Express response methods](#)
- [Express Router object](#)