



Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs

relative

Advances

Data Hiding &

Future

References


Slide 1 of 15

Modularizing Python

Modules & Packages

Walter Cazzola

Dipartimento di Informatica
Università degli Studi di Milano
e-mail: cazzola@di.unimi.it
twitter: [@w_cazzola](https://twitter.com/w_cazzola)





Modules

Basics on Modules

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References

A **module** is a simple text file of Python's statements.

import «module name»


Lets a client (importer) fetch a module as a whole.

from «module name» **import** «name list»|*

Allows clients to fetch particular names from a module.

imp.reload «module name»

Provides a way to reload a module's code without stopping the Python interpreter.





Modules

How Imports Work

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References

Imports are run-time operations that:

1. find the module's file

```
import rectangle
```

This looks for rectangle.py through a standard module search path.


2. load module's Bytecode (from a .pyc file named after the module)

- if a source file newer than the .pyc is found or
- no Bytecode is found the module source file is compiled

compilation occurs when the module is imported

- so only imported modules will leave a .pyc file on your system.

3. run the module's code to build the objects it defines.





Modules

Python's Module Search Path

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future


References

Python looks for module in:

1. The current directory
2. PYTHONPATH directories (if set)
3. Standard library directories
4. The contents of any .pth files

The concatenation of these four components becomes `sys.path`.

```
[DING!]cazzola@hymir:~/esercizi-pa>python3
>>> import sys
>>> sys.path
['', '/usr/lib64/python3.4.zip', '/usr/lib64/python3.4',
'/usr/lib64/python3.4/plat-linux', '/usr/lib64/python3.4/lib-dynload',
'/usr/lib64/python3.4/site-packages', '/usr/lib/python3.4/site-packages']
```





Modules

Imports Happen Only Once

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References


Modules are imported only once, so, code is executed just at import time.

Let us consider

```
print('hello')
spam = 1          # Initialize variable
```

```
[16:45]cazzola@hymir:~/esercizi-pa>python3
>>> import simple    # First import: loads and runs file's code
hello
>>> simple.spam      # Assignment makes an attribute
1
>>> simple.spam = 2  # Change attribute in module
>>> import simple    # Just fetches already loaded module
>>> simple.spam      # Code wasn't rerun: attribute unchanged
2
```

- the module simple is imported just the first time
- the assignment to spam in the module is only executed the first time.





Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References

Slide 6 of 15

Modules

import and from Are Assignments

import and **from** are statements not compile-time declarations.

- they may be used in statements, in function definition, ...;
- they are not resolved or run until the execution flow reaches them.

import and **from** are assignments:


```
x = 1  
y = [1, 2]
```

- **import** assigns an entire module object to a single name

```
[23:10]cazzola@hymir:~/esercizi-pa>python3  
>>> import small  
>>> small  
<module 'small' from 'small.py'>
```

- **from** assigns new names to homonyms objects of another module.

```
>>> from small import x, y  
>>> x = 42  
>>> y[0] = 42  
>>> import small  
>>> small.x  
1  
>>> small.y  
[42, 2]
```





Modules

"Import" and "From" Equivalence

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References


The following

```
from small import x,y    # Copy these two names out (only)
```

is equivalent to

```
import small              # Fetch the module object
x = small.x               # Copy names out by assignment
y = small.y
del small                 # Get rid of the module name
```

```
[9:03]cazzola@hymir:~/esercizi-pa>python3
>>> from small import x,y
>>> small
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'small' is not defined
>>> import small
>>> small
<module 'small' from 'small.py'>
>>> x = small.x
>>> y = small.y
>>> del small
>>> small
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
NameError: name 'small' is not defined
>>> x
1
```





Modules

Module Namespaces

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs

relative

Advances

Data Hiding &

Future

References

Files generate namespaces

- module statements run once at the first import
- every name that is assigned to a value at the top level of a module file becomes one of its attributes.
- module namespaces can be accessed via `__dict__` or `dir(module)`
- module are single scope (i.e., local is global)

```
print('starting to load...')
import sys
name = 42
def func(): pass
print('done loading')
```

```
[23:37]cazzola@hymir:~/esercizi-pa>python3
>>> import module2
starting to load...
done loading
>>> module2.sys
<module 'sys' (built-in)>
>>> module2.name
42
>>> module2.func
<function func at 0xb7a0cbac>
>>> list(module2.__dict__.keys())
['name', '__builtins__', '__file__', '__package__', 'sys', 'func', '__name__', '__doc__']
```




Modules

Module Reload

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs

relative

Advances

Data Hiding &

Future

References

The `imp.reload` function forces an already loaded module's code to be reloaded and rerun.


- Assignments in the file's new code change the existing module object in-place.

```
# changer.py
message = "First version"
def printer():
    print(message)
```

```
# changer.py after the editing
message = "After editing"
def printer():
    print('reloaded:', message)
```

```
>>> import changer
>>> changer.printer()
First version
>>> ^Z
Suspended
[9:57]cazzola@hymir:~/esercizi-pa>gvim changer.py
[9:58]cazzola@hymir:~/esercizi-pa>fg
python3

>>> import changer
>>> changer.printer()
First version
>>> from imp import reload
>>> reload(changer)
<module 'changer' from 'changer.py'>
>>> changer.printer()
reloaded: After editing
```





Packages

Basics on Python's Packages

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future


References

An **import** can name a directory path.

- A directory of Python code is said to be a package, so such imports are known as package imports.
- A package import turns a directory into another Python namespace, with attributes corresponding to the subdirectories and module files that the directory contains.

Packages are organized in directories, e.g., `dir0/dir1/mod0`

- **import** are independent of the file system conventions, i.e., **import** `dir0.dir1.mod0` loads `dir0/dir1/mod0`;
- the package must be reachable via the Python's search path mechanism.





Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References

Packages

Package __init__.py files

Each directory named within the path of a package import statement must contain a file named `__init__.py`

- They contain standard python code
- They provide a hook for package-initialization-time actions, generate a module namespace for a directory, and support the **from** * when used in combination with package imports.

Package Initialization


The first time Python imports through a directory, it automatically runs all the code in the directory's `__init__.py` file.

Package Namespace Initialization

In the package import model, the directory paths in your script become real nested object paths after an import.

From * Statement Behavior

`__all__` lists in `__init__.py` files can be used to define what is exported when a directory is imported with the **from** * statement form.





Packages

Package Example

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs

relative

Advances

Data Hiding &

Future


References

```
# dir0/__init__.py
print('dir0 init')
x = 1
```

```
# dir0/dir1/__init__.py
print('dir1 init')
y = 2
```

```
# dir0/dir1/mod.py
print('in mod.py')
z = 3
```

```
[11:08]cazzola@hymir:~/esercizi-pa>python3
>>> import dir0.dir1.mod
dir0 init
dir1 init
in mod.py
>>> from imp import reload
>>> reload(dir0)
dir0 init
<module 'dir0' from 'dir0/__init__.py'>
>>> reload(dir0.dir1)
dir1 init
<module 'dir0.dir1' from 'dir0/dir1/__init__.py'>
>>> dir0.dir1
<module 'dir0.dir1' from 'dir0/dir1/__init__.py'>
>>> dir0.dir1.mod
<module 'dir0.dir1.mod' from 'dir0/dir1/mod.py'>
>>> dir0.x,dir0.dir1.y,dir0.dir1.mod.z
(1, 2, 3)
>>> from dir0.dir1.mod import z
>>> z
3
>>> import dir0.dir1.mod as mod
>>> mod.z
3
```





Packages

Absolute vs Relative Imports

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References


imports in packages have a slightly different behavior

- they are absolute with respect to the Python's search path
- to look for modules in the package you have to use the relative path search statement **from** .

```
# mypkg/spam.py
from . import eggs
print(eggs.X)
```

```
# mypkg/eggs.py
X = 99999
import string
print(string)
```

```
[11:33]cazzola@hymir:~/esercizi-pa>python3
>>> import mypkg.spam
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    import mypkg.spam
  File "mypkg/spam.py", line 2, in <module>
    from . import eggs
ImportError: No module named eggs
>>> import mypkg.spam
<module 'string' from '/usr/lib/python3.1/string.py'>
99999
>>>
```





Advances on Packages & Modules

Data Hiding & Future Extensions

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs
relative

Advances

Data Hiding &
Future

References

Data hiding in Python is only a convention

- to prefix a name with a '_' will prevent the **from** * statement to import such a name.
- to assign a list of strings to the `__all__` will force the **from** * statement to import only the listed names.


Enabling Future Language Features

Python permits a gradual introduction of new concepts in the language

```
from __future__ import featurename
```

This permits to turn on a novel featured disabled by default

- this is particularly useful for backwards compatibility.





References

Modularization

Walter Cazzola

Modules

Basics on modules

namespaces

reload

Packages

Basics on packages

__init__.py

absolute vs

relative

Advances

Data Hiding &

Future

References

- ▶ Jennifer Campbell, Paul Gries, Jason Montojo, and Greg Wilson.
Practical Programming: An Introduction to Computer Science Using Python.
The Pragmatic Bookshelf, second edition, 2009.
- ▶ Mark Pilgrim.
Dive into Python 3.
Apress*, 2009.
- ▶ Mark Summerfield.
Programming in Python 3: A Complete Introduction to the Python Language.
Addison-Wesley, October 2009.

