## Homework 1

## Cory Rindlisbacher

January 21, 2016

**Exercise 1.** It is believed that space has some graininess characterized by a length L, although this has never been measured. However, the following parameters which have been measured are believed to be relevant:  $c = 3 \times 10^8 \text{m/s}$ , the speed of light, $\hbar = 6.62 \times 10^{34} \text{kg m}^2/\text{s}$ , the Planck constant, and  $G = 6.67 \times 10^{11} \text{m/kg s}^2$ , the gravitational constant. Using only these three constants, nd a ballpark estimate for L. Compare with the radius of an atom.

**Solution** We are looking for a result with dimensions of length, which in this particular example is given by meters. Note that we obtain this result if we perform the following computation:

$$\sqrt{\frac{\hbar G}{c^3}} = \sqrt{\frac{\text{kg m}^2/\text{s} \times \text{m}^3/\text{kg s}^2}{\text{m}^3/\text{s}^3}}$$
$$= \sqrt{\frac{\text{m}^5/\text{s}^3}{\text{m}^3/\text{s}^3}}$$
$$= \sqrt{\text{m}^2}$$
$$= \text{m.}$$

The magnitude of this calculation using the specified values above yields a magnitude of  $4.04 \times 10^{-35}$ m. In comparison to the size of an atom, which from Wikipedia is roughly  $1 \times 10^{-10}$ m, the graininess of space is over 20 times smaller than the size of an atom.

**Exercise 2.** Consider a pendulum. Let T be the period of the oscillation, d be the maximum displacement of the pendulum to vertical, l be the length of the pendulum, m be the mass of the weight, and g be the acceleration due to gravity. Assuming these are the only relevant parameters, what is the form of the relation you expect to see between them?

**Exercise 3.** A farmer wants to build a windmill to generate power. Assuming that the power P generated is a function of the density of the air  $\rho$ , viscosity  $\mu$ , diameter of the windmill d, wind speed v, and rotational speed  $\omega$ , can you express P in terms of an unknown function of as few variables as possible? Can you suggest anything about the form of this function? If you were to build a scale model of the windmill, how would you do it and what

correspondence would you make between the power generated by the scale model and the expected performance of the real windmill?

Solution We have three dimensions in this problem, length mass and time. According to the Buckingham Pi theorem, since we have 6 variables we can find 3 dimensionless products with these variables. Thus, the power of the windmill can be expressed using some function  $f(\pi_1, \pi_2, \pi_3) = 0$ , where  $\pi_1, \pi_2, \pi_3$  are dimensionless products as given from the theorem. To determine what the respective  $\pi_i$  are, we examine the product

$$P^{\alpha}\rho^{\beta}\mu^{\gamma}d^{\delta}v^{\epsilon}\omega^{\nu}$$
.

From this we obtain a linear system of

$$\alpha + \beta + \gamma = 0,$$
 
$$2\alpha - 3\beta - \gamma + \delta - \nu = 0,$$
 
$$-2\alpha - \gamma - \epsilon - \nu = 0.$$

A basis for the null space is given by the three vectors

$$(1, 2, -3, 0, 0, 1),$$

$$(2, 3, -5, 0, 1, 0),$$

and

$$(-1, -1, 2, 1, 0, 0).$$

This gives a basis for all dimensionless products as  $\pi_1 = P \rho^2 \mu^{-3} v$ ,  $\pi_2 = P^2 \rho^3 \mu^{-5} \omega$ , and  $\pi_3 = P^{-1} \rho^{-1} \mu^2 d$ .

If I were to make a scale model of a windmill, my guess is that we would be very interested in Newton's Number or the Power Number which is given by  $N_p = \frac{P}{\rho\omega^3d^5}$ . I would attempt to hold Newton's Number constant between the scale model and the real windmill, which can be done by increasing either the rotational speed or the density of the air to compensate for the reduction in the diameter of the windmill.

**Exercise 4.** At a paper mill, paper is wound onto a cylinder. Suppose there is a counter which counts the number of revolutions of the cylinder. Find the appropriate relation between the length of paper wound on the cylinder and the number of revolutions. [Hint: its non-linear.] Comment on sources of error.

Solution The length of paper added each revolution is equal to the circumference of the spool with the wound paper on it. We can determine the circumference of a circle by  $2\pi r$ , where r is the radius of the circle. This means that for our problem we need to know the radius of the cylinder when empty, given by  $r_0$ , and the thickness of the paper, t. If we denote the number of turns by n, then we have that after n turns the radius of the cylinder and paper is going to be given by  $r_0 + nt$ . The  $n^{th} + 1$  turn of the cylinder adds a length of

paper given by  $2\pi(r_0 + nt)$ . The length of paper on the cylinder after n turns can then be thought of as the length of paper added on each turn of the cylinder. The formula for this is

$$\begin{split} \Sigma_{i=1}^{n} 2\pi (r_0 + (i-1)t) &= 2\pi \Sigma_{i=1}^{n} (r_0 + (i-1)t) \\ &= 2\pi (\Sigma_{i=1}^{n} r_0 + \Sigma_{i=1}^{n} (i-1)t) \\ &= 2\pi (r_0 \Sigma_{i=1}^{n} 1 + t \Sigma_{i=1}^{n} (i-1)) \\ &= 2\pi (n r_0 + t \Sigma_{i=0}^{n-1} i) \\ &= 2\pi (n r_0 + t \frac{(n-1)n}{2}) \\ &= 2\pi (n r_0 + \frac{t n^2 - t n}{2}). \end{split}$$

The final formula given is the relationship between the number of turns of the cylinder and the length of the paper added. There are potential sources of error. Any error measurement in the thickness of the paper will lead to large sources of error given enough turns. Additionally, if there are any wrinkles or bumps in the paper as it's being wound around the roll then each turn will lead to increasingly large sources of error.