

Piacente Cristian 866020

Assignment A4 – Data flow analysis

Software Quality, Academic Year 2023-2024, University of Milan – Bicocca

With reference to the sample program, consider the problem of identifying which definitions of variable sanitized can be used at the return statement at the end of the program.

ID	STATEMENT	PREVIOUS STATEMENT IDs	GEN	KILL	init		PASS 1		PASS 2		PASS 3	
					REACH	REACH-OUT	REACH	REACH-OUT	REACH	REACH-OUT	REACH	REACH-OUT
A	String sanitizeUserInput(String userInput, List<Checker> checkers) throws UncheckedInputException {											
B	String sanitized = userInput;	A	sanitized_B					sanitized_B		sanitized_B		sanitized_B
C	int warnings = 0;	B					sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B
D	if (!checkers.isEmpty()) {	C					sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B
E	boolean done = false;	D					sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B
F	for (int i = 0;	E					sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B
G	i < checkers.size() && !done;	F, O					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
H	Checker c = checkers.get(i);	G					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
I	if (c.isActive()) {	H					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
J	sanitized = c.apply(userInput);	I	sanitized_J	sanitized_B, sanitized_J			sanitized_B	sanitized_J	sanitized_J	sanitized_J	sanitized_J	sanitized_J
K	done = true;	J					sanitized_J	sanitized_J	sanitized_J	sanitized_J	sanitized_J	sanitized_J
L	} else if (c.riskDetected(userInput)) {	I					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
M	LOGGER.log("Possible issues for: " + userInput);	L					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
N	++warnings;	M					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
O	++i) }	K, L, N					sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
P	} else { throw new UncheckedInputException(); }	D					sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B	sanitized_B
Q	if (warnings > 0) {	G					sanitized_B	sanitized_B	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J	sanitized_B, sanitized_J
R	sanitized = this.defaultChecker.apply(userInput); }	Q	sanitized_R	sanitized_B, sanitized_J			sanitized_B	sanitized_R	sanitized_J	sanitized_R	sanitized_J	sanitized_R
S	return sanitized; }	Q, R					sanitized_B, sanitized_R	sanitized_B, sanitized_R	sanitized_J, sanitized_R	sanitized_J, sanitized_R	sanitized_J, sanitized_R	sanitized_J, sanitized_R

In detail (consider only variable sanitized):

- Identify an appropriate type of data flow analysis, indicating its characteristics (forward/backward, all/any path)
 - **Reaching definitions**, since we need to consider the problem of identifying which definitions can reach the return statement, w.r.t every possible program path. It is a **forward, any-path** analysis.
- Define kill and gen operations
 - **Kill**: the variable sanitized is redefined, killing any previous definitions.
 - **Gen**: a value is assigned to the variable sanitized, generating a new definition.
- Identify the kill and gen sets for the code
 - See the table above.
- Report the results of the analysis for each statement in the code
 - See the table above.

Piacente Cristian 866020

Assignment A4 – Data flow analysis

Software Quality, Academic Year 2023-2024, University of Milan – Bicocca

Furthermore, refer to your results to answer the following questions:

- Do your results indicate the danger that the initial value of variable `sanitized` (assigned at the very beginning of the program) can be returned without modifications in between?
 - **Yes:** the initial definition of `sanitized` (`sanitized_B`) belongs to the reaching definitions of the statement `S`.
This means there is the danger that the initial value of `sanitized` could be returned without modifications in between.
- If yes, can you indicate all definition-clear program paths that correspond to such dangerous behavior, by considering only the program paths that iterate at most once through the loop in the program?
 - Considering only the program paths that iterate at most once through the loop, the following paths could lead to returning the initial value of `sanitized`:
 - **A-B-C-D-E-F-G-Q-S**
 - **A-B-C-D-E-F-G-H-I-L-O-G-Q-S**
 - **A-B-C-D-E-F-G-H-I-L-M-N-O-G-Q-S**These program paths were found taking into account that we must skip the statements `J` and `R`, since they would kill any previous definitions of `sanitized`, and also we must avoid to execute the statement `P`, because it would lead to throwing an exception.
- For each program path that you indicated at the above answer (if any) say also if it is a false alarm or a true alarm, and why.
 - Let's analyze each program path from the previous answer, to find out if it's a feasible path or not.
 - **A-B-C-D-E-F-G-Q-S:** we have 0 iterations of the loop.
This means the condition `i < checkers.size() && !done` is evaluated to **false from the beginning**: since the variables `done` and `i` are initially defined as **false** and **0**, we have that `checkers.size()` **must be 0**. It is a **contradiction**: after executing the statement `D` we make sure the list `checkers` is not empty, so when reaching the statement `G` we will always have a list with a size greater than 0. This program path is **infeasible**, so it's a **false alarm**.
 - **A-B-C-D-E-F-G-H-I-L-O-G-Q-S:** we have 1 iteration of the loop, in particular the list must contain exactly **1 checker** which is **not active** and which **does not detect a risk** on the user input. After the loop, to avoid executing statement `R`, the variable **warnings must be less or equal to 0**. The program path is **feasible**: it is possible to have such a checker in the list, and in this case the variable `warnings` keeps the initial value of 0. We have a **true alarm** here.
 - **A-B-C-D-E-F-G-H-I-L-M-N-O-G-Q-S:** we have 1 iteration of the loop, in particular **1 checker that is not active** and that **detects a risk** on the user input. After the iteration, the variable **warnings must be less or equal to 0**. This is a **contradiction**: since a risk is detected, the variable `warnings` is incremented at the statement `N` and so after the loop it has the value of 1, that is greater than 0 and the statement `R` would be executed, killing the initial definition of the variable `sanitized`. This program path is **infeasible**, so it's a **false alarm**.
 - In conclusion, from our analysis we can say that the initial definition of `sanitized` gets returned iff all the following conditions are true:
 - the parameter `checkers` is a list which contains **at least 1 checker** (to skip the exception at the statement `P` that gets thrown in case of an empty list)
 - **all checkers** in the list **are not active** (to skip the statement `J`)
 - **every checker does not detect a risk** on the user input (to skip the statement `N`, which results in skipping the statement `R`).