Design Concept: The Omni-Wheel-Brake Smart Cane as a Haptic Augmentation Interface

Yange Sun
02059079

February 2, 2026

Abstract

This report proposes a design concept for a smart navigational aid intended to augment the spatial perception of visually impaired individuals. The proposed interface, the *Omni-Wheel-Brake Smart Cane*, integrates a caster wheel with an active braking mechanism controlled by sensor fusion algorithms. Unlike traditional white canes that rely on passive tactile scanning, this device augments the user's navigational function by translating environmental obstacle data into direct physical resistance. This report outlines the design rationale, analyzes the specific functional augmentation, and presents a developmental roadmap for the interface.

I acknowledge the use of ***Gemini 3 pro*** *(Google,* `https://gemini.google.com/app`*) to help me with language polishing and image generation. I confirm that no content generated by AI has been presented as my own idea.*

1 Introduction and Design Idea

Visual impairment significantly limits an individual's ability to perceive spatial layout and obstacles, reducing independent mobility. The traditional white cane is the primary assistive tool, but it suffers from limitations: it requires continuous, repetitive wrist motion (scanning), offers low spatial resolution, and often detects obstacles only upon impact.

1.1 Inspiration and Rationale

This design concept draws significant inspiration from the work of the Stanford Robotics Team (2021) on "Multimodal sensing and intuitive steering assistance" [1]. Their research demonstrated that an augmented cane with a motorized omni-wheel could significantly improve walking speed.

However, my design diverges from their "active steering" approach (where the cane pulls the user) to a **"passive braking"** mechanism. I chose this modification for several strategic reasons:

1. **Intuitive Alignment:** Passive braking aligns more closely with the traditional use of a white cane. Users are accustomed to stopping when they hit a physical barrier; my design simulates this barrier virtually, rather than forcing the user to follow a motorized pull.
2. **Efficiency and Portability:** By removing the motors, the system eliminates the need for heavy actuators and large battery packs. This significantly reduces the total weight, manufacturing cost, and power consumption, making the device more practical for all-day usage.

1.2 The Proposed Interface: The Omni-Wheel-Brake

Based on this rationale, the **Omni-Wheel-Brake Smart Cane** reimagines the structure of the cane (see Figure 1):

- **Mechanical Structure (1):** Two heavy-duty omni-directional wheels ensures continuous ground contact.
- **Active Sensing (2):** LiDAR and ultrasonic (TOF) sensors detect obstacles and drop-offs.
- **The Feedback (The Brake) (3):** A solenoid-driven locking mechanism engages when an obstacle is detected, physically increasing resistance or locking the wheel to signal "stop."

2 Augmentation Analysis

This device focuses on **Sensory Augmentation**, specifically augmenting **Range Perception** through haptic feedback.

2.1 Which function is augmented?

The primary function being augmented is the user's **anticipatory navigation**. A standard cane provides information at the point of contact (0 meters). This design augments the sensing range to 1-2 meters ahead of the user but delivers the feedback as if the contact has already happened physically.

2.2 How does it do it?

The interface utilizes a concept I term "**Subtractive Haptics**."

1. **Data Acquisition:** Sensors create a localized depth map of the environment.
2. **Translation:** An algorithm calculates the Time-to-Collision (TTC).
3. **Feedback Loop:** Instead of adding energy (like vibration), the system removes energy (momentum).
4. **User Experience:** When the user walks towards a wall, the wheel increases rolling resistance or locks completely. The user feels the cane "refuse" to move forward, effectively simulating a physical barrier before the user actually touches it.

This augments the natural function of the hand holding a stick. It makes empty space feel "smooth" and dangerous space feel "heavy" or "immovable," extending the user's sense of touch beyond their physical reach.

3 Development Roadmap

To develop this interface from a concept to a functional prototype, I propose the following three-phase plan:

3.1 Phase 1: Proof of Concept (Hardware)

The initial focus will be on the mechanical locking mechanism.

- **Components:** I will use an Arduino Nano for control, two standard ToF (Time of Flight) distance sensors, and a modified caster wheel equipped with a solenoid push-pull electromagnet.
- **Goal:** Achieve a "Stop-on-Detect" function where the wheel locks instantly when an object is within 50cm.

3.2 Phase 2: Logic and Algorithm (Software)

Refining the interaction to prevent false positives.

- **Obstacle Analysis:** Instead of simple proximity detection, the algorithm will calculate the specific **position, shape, and dimensions** (length/width) of obstacles. This allows the system to differentiate between a narrow pole (safe to pass closely) and a wide wall (requires stopping), reducing false positives.

- **Variable Resistance:** Instead of a binary lock, I will attempt to pulse the brake (PWM control) to simulate "viscosity" as the user gets closer to an obstacle, providing a gradient of warning.

3.3 Phase 3: Ergonomics and Testing

Developing the physical form factor.

- **Weight Distribution:** Ensuring the battery and motors at the bottom do not make the cane too heavy to lift.
- **User Testing:** Blindfolded trials to test the intuition of the locking mechanism. Does the user understand that a locked wheel means "obstacle ahead"?



Figure 1: **Schematic Design of the Omni-Brake Smart Cane.**(generated by AI) The diagram illustrates the placement of the forward-facing ToF sensors for obstacle detection and the omni-directional wheel assembly equipped with the braking mechanism.

References

[1] S. L. Bowman et al., "Multimodal sensing and intuitive steering assistance improve navigation and mobility for people with impaired vision," *Science Robotics*, vol. 6, no. 59, 2021.