

EISF 300V INSTRUMENTATION CABLE

Cu/PVC/ ISCR/PVC/OSCR/PVC



APPLICATION

These individually cables are used for transmission of analogue and digital signals in instrument and control systems at chemistry and petrochemistry industry plants, power plants, natural gas and petrochem plants, etc... . Instrumentation cables are not allowed for direct connection to a low impedance sources, e.g. public mains electricity supply. They are for indoor installation, in dry and wet locations; on racks, trays, in conduits.

CABLE DESIGN

Conductor	:	Stranded plain copper wires, EN 60228 Class 2
Insulation	:	90°C grade, PVC compound
Core identification	:	White & Red coloured cores
P Pair	:	Two cores twisted to a pair
I Pair separator	:	Polyester tape
M Pair screen	:	Aluminium polyester tape with tinned copper drain wire (0,22 mm ² ~7x0,20 mm)
F	:	
Pair sheath	:	90°C grade, PVC compound, flame retardant, hydrocarbon resistant, Gray or Blue
Lay-up	:	Sheathed pairs laid-up together in optimum pitch
Separator	:	Polyester tape
Screen	:	Aluminium polyester tape with tinned copper drain wire (0,22 mm ² ~7x0,20 mm)
Outer sheath	:	90°C grade, PVC compound, flame retardant, hydrocarbon resistant
Sheath colour	:	~RAL 7001, Grey or ~RAL 5015, Blue

TECHNICAL DATA @20°C

Standard	:	Acc. to NF M 87-202 & EN 50288-7
Insulation Resistance	:	Min. 20 Mohm x km
Voltage rating	:	300V
Test Voltage (AC 50 Hz)	:	2000 V
Min.bending radius	:	10 x D
Temperature Range	:	Fixed: -30 °C ~ +90 °C Installation: -5 °C ~ +50 °C
Flame test	:	IEC 60332-1 & TS EN 60332-1-2 EN IEC 60332-3-24 Cat C
Oil resistant	:	IEC 60811 (4hours @70°C in IRM 902)
Sunlight resistance	:	UL 1581 section 1200

CE : Conform to 2014/35/EU (Low Voltage Directive)

Conform to 2011/65/EU & 2015/863 (RoHS Directives)

Kesitler / Cross Sections

Cross section	Insulation Thickness	Approx. Outer Diameter	Copper Weight	Approx. Cable Weight
	(mm)	(mm)	(kg/km)	(kg/km)
4x2x0,75	0,50	16,90	69	315
8x2x0,75	0,50	22,50	138	580
12x2x0,75	0,50	26,60	206	826
4x2x0,88	0,50	17,60	79	333
8x2x0,88	0,50	23,60	158	615
12x2x0,88	0,50	28,80	237	884

*Diameter tolerance ±7%

YK 40155-31.07.2025 (YÇ)