



STANDARDS

Product IEC 60502; XP C 32-321

APPLICATION

U-1000 R2V cables can be used in all low voltage power installations. Multiconductors cables are adapted to remote control and telecontrol installations.

In case of high ambient temperature, use correction coefficient.

INSTALLATION

These cables can be fixed on cable trays, within conduits or fixed to walls. They also can be buried directly with extra mechanical protection.

Cross sections 1,5 - 2,5 and 4 mm² have to be of class 2 flexibility, if the cable is connected to equipment subject to vibration.

CHARACTERISTICS

Construction characteristics

Conductor material	Bare copper
Insulation	XLPE (chemical)
Outer sheath	PVC
Sheath colour	Black
Conductor shape	Circular

Electrical characteristics

Rated Voltage U _o /U (U _m)	0,6/1 kV
---	----------

Mechanical characteristics

Mechanical resistance to impacts	Good
Cable flexibility	Rigid

Usage characteristics

Short-circuit max. conductor temperature	250 °C
Operating temperature, range	-10 ... 60 °C
Flame retardant	C2, NF C 32-070
Weather resistance	Very good
Chemical resistance	Accidental
Bending factor when laying	6 (xD)



Rated Voltage U_o/U (U_m)
0,6/1 kV



Mechanical resistance to impacts
Good



Cable flexibility
Rigid



Operating temp.
-10 ... 60 °C



Flame retardant
C2, NF C 32-070



Weather resistance
Very good



Chemical resistance
Accidental



Bending factor when laying
6 (xD)

SINGLE CONDUCTOR

Cross section [mm²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
25	290	10.5	138	144	1.4	1000
35	390	11.5	169	174	1.0	1000
50	510	12.6	207	206	0.78	1000
70	720	14.7	268	254	0.56	1000
95	970	16.3	328	301	0.43	1000
120	1210	17.8	382	343	0.36	1000
150	1480	19.1	441	387	0.31	1000
185	1835	22.1	506	434	0.26	1000
240	2540	24.9	599	501	0.22	500
300	2945	27.7	693	565	0.19	500
400	2860	31.6	825	662	0.17	500
500	2860	31.6	825	662	0.17	500

2-CORE CABLES

Cross section [mm²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
1.5	130	10.5	24	34	24.8	100
1.5	130	10.5	24	34	24.8	100
2.5	93	8.71	24	34	21.5	2000
2.5	160	11.5	33	46	14.8	2000
4	190	13.0	45	59	9.2	1000
4	300	14.5	40	51	8.0	1000
6	290	14.0	58	74	6.2	1000
6	300	14.5	40	51	8.0	1000
10	400	16.0	80	101	3.7	1000
10	485	17.0	80	101	3.7	1000
16	550	18.5	107	128	2.4	1000
16	550	18.5	107	128	2.4	1000



Rated Voltage U_0/U
(Um)
0,6/1 kV



Mechanical
resistance to
impacts
Good



Cable flexibility
Rigid



Operating temp.
-10 ... 60 °C



Flame retardant
C2, NF C 32-070



Weather resistance
Very good



Chemical
resistance
Accidental



Bending factor
when laying
6 (xD)

3-CORE CABLES

Cross section [mm²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
1.5	145	11.0	24	34	24.8	2000
2.5	190	12.5	33	46	14.8	2000
4	250	13.5	45	59	9.2	1000
4	300	14.5	40	51	8.0	1000
6	300	14.5	40	51	8.0	1000
6	300	14.5	40	51	8.0	1000
6	300	14.5	40	51	8.0	1000
6	320	15.0	56	74	6.2	1000
10	300	14.5	40	51	8.0	1000
10	300	14.5	40	51	8.0	1000
16	700	16.5	107	128	2.4	1000
25	1080	23.5	127	141	1.37	1000
50	1845	29.0	192	206	0.76	500
70	1560	34.0	246	254	0.55	500
95	3470	38.5	298	301	0.42	1000
120	4410	42.5	346	343	0.35	500

4-CORE CABLES

Cross section [mm²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
1.5	133	9.89	24	34	21.5	2000
1.5	133	9.89	24	34	21.5	2000
4	300	14.5	40	51	8.0	1000
6	300	14.5	40	51	8.0	1000
6	300	14.5	40	51	8.0	1000
6	390	16.0	52	64	5.4	1000
10	300	14.5	40	51	8.0	1000
10	590	18.5	71	88	3.2	1000
10	590	18.5	71	88	3.2	1000
16	860	21.0	96	111	2.11	1000
16	860	21.0	96	111	2.11	1000
25	1340	25.5	127	141	1.37	1000
35	1780	28.5	158	174	1.0	500



Rated Voltage U₀/U
(Um)
0,6/1 kV



Mechanical
resistance to
impacts
Good



Cable flexibility
Rigid



Operating temp.
-10 ... 60 °C



Flame retardant
C2, NF C 32-070



Weather resistance
Very good



Chemical
resistance
Accidental



Bending factor
when laying
6 (xD)

	Cross section [mm ²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
	50	2330	32.5	192	206	0.76	500
	70	3375	34.5	246	254	0.55	500
	95	4345	42.5	298	301	0.42	1000
	120	5590	47.5	346	343	0.35	500
	150	6650	52.5	395	387	0.3	500
	240	10298	60.5	522	504	0.22	400

5-CORE CONDUCTORS

	Cross section [mm ²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
	4	255	16.0	40	46	8.2	1000
	6	490	17.5	52	58	5.5	1000
	10	725	20.0	71	79	3.3	1000
	16	300	14.5	40	51	8.0	1000
	16	1060	23.0	96	111	2.1	1000
	25	1610	28.0	127	141	1.37	500
	35	2042	30.0	157	170	1.0	1000
	50	2042	30.0	157	170	1.0	1000

3-CORE WITH NEUTRAL CONDUCTOR

	Cross section [mm ²]	Approx. weight [kg/km]	Max. outer diam. [mm]	Neutral Cond. section [mm ²]	Perm. current rating open air [A]	Current rating, buried [A]	Voltage drop, single phase [V/A.km]	Length [m]
	50	2180	31.1	35	190	204	0.78	500
	70	3050	36.2	50	242	252	0.57	500
	95	4060	40.6	50	293	302	0.44	1000
	120	5060	45.4	70	339	345	0.36	500
	150	5950	49.5	70	390	386	0.31	500
	185	7400	54.4	70	444	435	0.27	500
	240	9200	61.5	95	522	504	0.23	500



Rated Voltage U₀/U
(Um)
0,6/1 kV



Mechanical
resistance to
impacts
Good



Cable flexibility
Rigid



Operating temp.
-10 ... 60 °C



Flame retardant
C2, NF C 32-070



Weather resistance
Very good



Chemical
resistance
Accidental



Bending factor
when laying
6 (xD)