SPECT

ISA v0.1

Version: 0.1

Git tag:

Tropic Square

October 18, 2023

1 Glossary

- $P_{25519} = 2^{255} - 19$
- $P_{256} = 2^{256} - 2^{224} + 2^{192} + 2^{96} - 1$
- || – concatenation

2 Instruction set

SPECT provides 4 types of instructions:

- **R** - Register
- **I** - Immediate
- **M** - Memory
- **J** - Jump

2.1 Operand interpretation

All operands are considered as 256 bits unsigneds. Arithmetic instructions working only with 32 bit operands ignores the 224 MSBs of input and clears them in the result. Logic instructions working only with 32 bit operands also ignores the 224 MSBs of input, but passes the 224 MSBs of op2 to the result.

2.2 Instruction Format



2.3 Symbols

Following symbols are used in description of instructions:

- F – Flags set by the instruction
- #C – Number of cycles the instruction takes to execute

2.4 R instructions

Mnemonic	Name	Semantics	F	#C
32 bit arithmetic instructions				
ADD op1,op2,op3	32 bit adition	op1 = op2 + op3	Z	11
SUB op1,op2,op3	32 bit subtraction	op1 = op2 - op3	Z	11
CMP op2,op3	32 bit comparison	op2 - op3	Z	9
32 bit logic instructions				
AND op1,op2,op3	32 bit bitwise AND	op1 = op2 & op3	Z	11
OR op1,op2,op3	32 bit bitwise OR	op1 = op2 | op3	Z	11
XOR op1,op2,op3	32 bit bitwise Exclusive OR	op1 = op2 ^ op3	Z	11
NOT op1,op2	32 bit bitwise NOT	op1 = ~op2	Z	10
Shift Instructions				
LSL op1,op2	Logic shift left	op1 = op2[254:0] || 0	C	10
LSR op1,op2	Logic shift right	op1 = 0 || op2[255:1]	C	10
ROL op1,op2	Rotating shift left	op1 = op2[254:0] || op2[255]	C	10
ROR op1,op2	Rotating shift right	op1 = op2[0] || op2[255:1]	C	10
ROL8 op1,op2	Rotating byte shift left	op1 = op2[247:0] || op2[255:248]		10
ROR8 op1,op2	Rotating byte shift right	op1 = op2[7:0] || op2[255:8]		10
SWE op1,op2	Swap endianity	op1[255:248] = op2[7:0] op1[247:240] = op2[15:8] ... op1[7:0] = op2[255:248]		10
Modular arithmetic instructions				
MUL25519 op1,op2,op3	Multiplication in $GF(P_{25519})$	op1 = (op2 * op3) % P_{25519}		91
MUL256 op1,op2,op3	Multiplication in $GF(P_{256})$	op1 = (op2 * op3) % P_{256}		139
ADDP op1,op2,op3	Generic Modular Addition	op1 = (op2 + op3) % R31		16
SUBP op1,op2,op3	Generic Modular Subtraction	op1 = (op2 - op3) % R31		16

Mnemonic	Name	Semantics	F	#C
MULP op1,op2,op3	Generic Modular Multiplication	op1 = (op2 * op3) % R31		597
REDP op1,op2,op3	Generic Modular Reduction	op1 = (op2 || op3) % R31		528
Other Instructions				
MOV op1,op2	Move register	op1 = op2		7
CSWAP op1,op2	Conditional swap	***if* C** == 1 ***then:*** op1 = op2 op2 = op1		11
HASH op1,op2	Hash	tmp = *SHA512*(op2+3||op2+2||op2+1||op2) op1 = tmp[255:0] op1+1 = tmp[511:256]		347
GRV op1	Get Random Value	op1 = Random number		–
SCB op1,op2,op3	Blind scalar	B = *Blind*(op2, op3, R31) op1 = B[255:0] op1+1 = B[511:256]		88

2.5 I instructions

Mnemonic	Name	Semantics	F	#C
32 bit arithmetic instructions				
ADDI op1,op2,Immediate	32 bit addition	op1 = op2 + Immediate	Z	11
SUBI op1,op2,Immediate	32 bit subtraction	op1 = op2 - Immediate	Z	11
CMPI op2,Immediate	32 bit comparison	op2 - Immediate	Z	9
12 bit logic instructions				
ANDI op1,op2,Immediate	12 bit bitwise logic AND	op1 = op2 & Immediate	Z	11
ORI op1,op2,Immediate	12 bit bitwise logic OR	op1 = op2 | Immediate	Z	11
XORI op1,op2,Immediate	12 bit bitwise exclusive OR	op1 = op2 ^ Immediate	Z	11

Mnemonic	Name	Semantics	F	#C
Other Instructions				
CMPA op2,Immediate	comparison	***if*** op2 == Immediate ***then:*** Z = 1 ***else:*** Z = 0	Z	9
MOVI op1,Immediate	Move immediate	op1[11:0] = Immediate, op1[255:12] = 0		6
HASH_IT	Hash init	Reset hash calculation.		9
GPK op1, Immediate	Get Private Key	op1 = Private key, Key index = immediate		–

Due to not enought space in the 32 bit instruction format, the immediate operand is just 12 bit. Because of that, the logic instructions works only with the 12 LSBs of op2. E.g. 0xFF12 & 0xF0F = 0xFF02.

2.6 M instructions

Mnemonic	Name	Semantics	F	#C
LD op1,Addr	Load	op1[31:0] = Mem[Addr] op1[63:32] = Mem[Addr+0x4] ... op1[255:224] = Mem[Addr+0x1C]		21
ST op2,Addr	Store	Mem[Addr] = op1[31:0] Mem[Addr+0x4] = op1[63:32] = ... Mem[Addr+0x1C] = op1[255:224]		12

2.7 J instructions

Mnemonic	Name	Semantics	F	#C
CALL NewPC	Subroutine call	push(RAR, PC+0x4), PC = NewPC		5
RET	Return from subroutine	PC = pop(RAR)		5
BRZ NewPC	Branch on Zero	***if*** Z == 1 ***then:*** PC = NewPC		5
BRNZ NewPC	Branch on not Zero	***if*** Z == 0 ***then:*** PC = NewPC		5
BRC NewPC	Branch on Carry	***if*** C == 1 ***then:*** PC = NewPC		5
BRNC NewPC	Branch on not Carry	***if*** C == 0 ***then:*** PC = NewPC		5
JMP NewPC	Unconditional jump	PC = NewPC		5
END	End of program, stops FW execution and sets **STATUS[DONE]**.	–		4
NOP	Does nothing.	–		3

3 Flags

3.1 Zero Flag – Z

Zero flag is set to 1, if instruction changing the flag is executed and:

- bits 31:0 of op1 are 0
- op2[31:0] - op3[31:0] = 0 in case of CMP and CMPI instructions

and cleared otherwise.
Zero flag keeps its value if instruction that does not modify it is executed.

3.2 Cary Flag – C

Carry flag is set to 1, if instruction changing the flag is executed and:

- op2[255] = 1 in case of LSL and ROL instructions
- op2[0] = 1 in case of LSR and ROR instructions

and cleared otherwise.
Carry flag keeps its value if instruction that does not modify it is executed.