

MongoDB and PHP

César D. Rodas

crodas@ferpectos.com

<http://cesarodas.com/>

Latinoware 2010

Foz do Iguaçu, Brasil

Who is this fellow?

- ⊙ Paraguayan :-)
- ⊙ Zealot of
 - Open Source (BSD-license)
 - PHP
 - MongoDB
- ⊙ PECL Developer
- ⊙ Work for a cool company (btw, we're hiring)
- ⊙ ... and few other things

Agenda

- ① Introduction to MongoDB
- ① MongoDB Queries
- ① Real life example:
 - Designing data model for a Wordpress.com like site
 - Optimize our data model to run in sharded environment

MongoDB

- ⊙ $\langle \text{EN} \rangle \text{Mongo} \langle / \text{EN} \rangle \neq \langle \text{PT} \rangle \text{Mongo} \langle / \text{PT} \rangle$
- ⊙ Document oriented database
- ⊙ Fast, Scalable, Easy to use (devel-friendly)
- ⊙ Support Indexes
 - Simple
 - Compound
 - Geo spatial
- ⊙ Schemaless
- ⊙ Support sharding
- ⊙ Nested documents
- ⊙ PECL client

Documents?

It's just an `Array()`

In fact everything is an `Array()` in MongoDB

<http://bit.ly/mongodb-php>

Documents?

It's just an `Array()`

In fact everything is an `Array()` in MongoDB

<http://bit.ly/mongodb-php>

MongoDB - Operations

⦿ Select

- \$gt, \$lt, \$gte, \$lte, \$eq, \$neq: >, <, >=, <=, ==, !=
- \$in, \$nin, \$or
- \$size, \$exists
- \$where: Any javascript expression
- group()
- limit()
- skip()

⦿ Update

- \$set
- \$unset
- \$push
- \$pull
- \$inc
- findAndModify()


Is it better than my MySQL (or Pg)?

NO.

It is different.

Differences with a rel. database

- ⊙ Denormalize data is not bad
 - It makes queries simplest and faster
 - Disk-space is much cheaper than CPU (and your user's time)
 - Much simple to distribute data across multiple nodes
- ⊙ No CPU wasting doing ORM
 - Objects in the programming language and in the database
 - No abstraction to generate SQL
- ⊙ No SQL injection :-)
- ⊙ No Joins (they are evil!)
- ⊙ Batch processing
- ⊙ No CREATE TABLE (or ALTER TABLE) needed



The fun part

Data-structure

```
$user = array(  
    'name' => 'crodas',  
    'email' => 'crodas@ferpectos.com',  
    'website' => 'http://cesarodas.com',  
);
```

```
$category = array(  
    array('name' => 'Sport'),  
    array('name' => 'Politcs')  
);
```

```
$comment = array(  
    'news' => $news['_id'],  
    'text' => 'I like MongoDB',  
    // these are duplicated!  
    'name' => $user['name'], /* 'crodas' */  
    'website' => $user['website'], /* 'http://cesarodas.com', */  
);
```

```
$news = array(  
    'title' => 'My Talk about MongoDB',  
    'content' => 'MongoDB rules, bla, bla!',  
    'author' => $user['_id'],  
    // duplicated items  
    'authorName' => $user['user'],  
    'categories' => array(  
        // copy all categories (incuding _id and name)  
        $category[0], $category[1] ... $category[$x]  
    ),  
    'comments' => array(  
        // copy 10 comments (we show 10 comments and pagination buttons)  
        $comment[0],  
        $comment[1],  
    ),  
    // total comments for this news, to made easier pagination  
    'totalComments' => count($comment),  
);
```

Select

// MySQL

```
"SELECT news.*, user.name FROM news  
INNER JOIN user ON user.id = news.author_id WHERE id = 1"
```

```
"SELECT category.category FROM category_has_news  
INNER JOIN category ON category WHERE news_id = 1"
```

```
"SELECT * FROM comments  
INNER JOIN user ON user.id = comments.user_id  
WHERE news_id = 1"
```

// In MongoDB

```
$mongo = new MongoDB;  
$db = $mongo->database;
```

```
$news = $db->news->find(array('_id' => 1));
```

Select

```
// MySQL
```

```
"Too bored to think in SQL"
```

```
// Get 10-most commented news
```

```
$db->news->find(array())->sort(array('totalComments' => -1))->limit(5);
```

Add new comment

```
$query = array('_id' => $_POST['news_id']);
$properties = array('totalComments' => true);
$news = $db->news->findOne($query, $properties);

if (empty($news)) throw new Exception("not valid news");

$new_comment = array(
    'name' => $_SESSION['user']['name'],
    'website' => $_SESSION['user']['website'],
    'text' => $_POST['text'],
    'news' => $_POST['news_id'],
);
$db->comment->save($new_comment);
$update = array('$inc' => array('totalComments' => 1));
if ($news['totalComments'] < 10) {
    $update['$push'] = array('comments' => $new_comment);
}
$db->news->update($news, $update);
```


What if the user changes its name?

Update

// Catch the update event somewhere in your app and run this:

// update comments

```
$update = array(  
    '$set' => array('name' => $new_name)  
);  
$db->comments->update(array('news' => 1), $update, array('multiple' => true));
```

// update news (and embed comments)

```
$update = array(  
    '$set' => array(  
        'category' => $list_of_first_10_comments,  
        'authorName' => $new_name,  
    )  
);  
$db->news->update(array('_id' => 1), $update, array('multiple' => true));
```

Questions?

Thanks

@crodas

crodas.org