COMPLETE LEARNING SESSION

Earthquake Risk and Resilient Construction - Learning Session

GS-III Disaster Management | Seismic risk, resilient construction, PYQ and answer writing

TEACHING NAVIGATION

Earthquake Risk and Resilient Construction

1. Tectonic mechanism and the seismic-risk equation
2. Magnitude, intensity and observed effects
3. India's seismic zones and the 59 per cent exposure fact
4. Site effects, liquefaction and microzonation
5. Built-environment vulnerability and historical lessons
6. Structural and non-structural mitigation
7. Codes, ductile detailing and verified construction quality
8. NDMA's six pillars of seismic safety
9. Existing-stock audit, retrofitting and lifeline priorities
10. NERMP, BMTPC and the Vulnerability Atlas
11. Risk-sensitive land use and development control
12. NCS monitoring, prediction limits and current status
13. Preparedness, Incident Response System and Emergency Operations Centres
14. The compliance chain: regulation, professionals and enforcement
15. Synthesis, 2021 PYQ route and the 2026 adjacent boundary

Learning Session Contents

Major learning parts and meaningful subtopics are listed in document order. Page numbers are generated from the final PDF layout; PDF bookmarks mirror the same hierarchy.

Earthquake Risk and Resilient Construction - Complete Learning Session 5

BASIC LEARNING SESSION 5

SESSION 1 - FOUNDATION - TECTONIC MECHANISM AND THE SEISMIC-RISK EQUATION 5

SESSION 2 - FOUNDATION - MAGNITUDE, INTENSITY AND OBSERVED EFFECTS 6

SESSION 3 - FOUNDATION - INDIA'S SEISMIC ZONES AND THE 59 PER CENT EXPOSURE FACT 6

SESSION 4 - CORE - SITE EFFECTS, LIQUEFACTION AND MICROZONATION 7

SESSION 5 - CORE - BUILT-ENVIRONMENT VULNERABILITY AND HISTORICAL LESSONS 8

SESSION 6 - CORE - STRUCTURAL AND NON-STRUCTURAL MITIGATION 9

SESSION 7 - CORE - CODES, DUCTILE DETAILING AND VERIFIED CONSTRUCTION QUALITY 9

SESSION 8 - CORE - NDMA'S SIX PILLARS OF SEISMIC SAFETY 10

SESSION 9 - CORE - EXISTING-STOCK AUDIT, RETROFITTING AND LIFELINE PRIORITIES 11

SESSION 10 - CORE - NERMP, BMTPC AND THE VULNERABILITY ATLAS 11

SESSION 11 - CORE - RISK-SENSITIVE LAND USE AND DEVELOPMENT CONTROL 12

SESSION 12 - CORE - NCS MONITORING, PREDICTION LIMITS AND CURRENT STATUS 13

SESSION 13 - CORE - PREPAREDNESS, INCIDENT RESPONSE SYSTEM AND EMERGENCY OPERATIONS CENTRES 14

SESSION 14 - CORE SYNTHESIS - THE COMPLIANCE CHAIN: REGULATION, PROFESSIONALS AND ENFORCEMENT 15

SESSION 15 - CORE SYNTHESIS - SYNTHESIS, 2021 PYQ ROUTE AND THE 2026 ADJACENT BOUNDARY 15

BASIC MCQS / REMEDIATION 16

Q1. What initiates a tectonic earthquake? 16

Q2. Why does intensity vary across locations for one event? 16

Q3. Which statement about India is correct? 16

Q4. What is microzonation? 17

Q5. Which is a built-environment vulnerability? 17

Q6. Which pairing is correct? 17

Q7. Ductility is best understood as: 17

Q8. Which is NOT one of NDMA's six pillars? 17

Q9. What is the first step in existing-stock retrofitting? 17

Q10. Why do hospitals require lifeline resilience? 17

Q11. Which institution publishes the Vulnerability Atlas? . . . 18
Q12. Which statement about land use is correct? . . . 18
Q13. What is the current NCS fact set used here? . . . 18
Q14. What does IRS provide after an earthquake? . . . 18
Q15. What is the strongest compliance-chain test? . . . 18
Q16. Which PYQ routing is correct? . . . 18
PYQS AND ANSWER PRACTICE . . . 18
DIRECT PYQ - 2021 GS-III Q8 - 10 marks, 150 words . . . 18
2026 ADJACENT APPLICATION - NOT PRIMARY OWNERSHIP . . . 19
SIX ANSWER-WRITING DRILLS . . . 19
OPTIONAL ADVANCED DEPTH - NOT REQUIRED FOR A CORE ANSWER . . . 19
Compliance-chain diagnosis . . . 19
Prediction and early-warning firewall . . . 19
Equity refinement . . . 19
Zonation as a techno-legal instrument . . . 19
Financing the retrofit gap . . . 20
Federal pace of retrofitting . . . 20
COMPLETE TOPIC ASCII MASTER FLOW DIAGRAM . . . 20
ASCII MASTER FLOW - PANEL 1/12: Tectonic risk chain . . . 20
ASCII MASTER FLOW - PANEL 2/12: Magnitude and intensity . . . 20
ASCII MASTER FLOW - PANEL 3/12: India seismic map . . . 20
ASCII MASTER FLOW - PANEL 4/12: Site-effect route . . . 20
ASCII MASTER FLOW - PANEL 5/12: Constructed vulnerability . . . 20
ASCII MASTER FLOW - PANEL 6/12: Mitigation system . . . 20
ASCII MASTER FLOW - PANEL 7/12: NDMA six pillars . . . 21
ASCII MASTER FLOW - PANEL 8/12: Compliance chain . . . 21
ASCII MASTER FLOW - PANEL 9/12: Existing stock and lifelines . . . 21
ASCII MASTER FLOW - PANEL 10/12: Institutions and tools . . . 21
ASCII MASTER FLOW - PANEL 11/12: Preparedness and response . . . 21
ASCII MASTER FLOW - PANEL 12/12: Answer spine and PYQ boundary . . . 21
CONSOLIDATED REGISTER NOTES . . . 21
1. Physical foundation . . . 21

2. Measurement 22

3. India's zones 22

4. Risk variation 22

5. Constructed vulnerability 22

6. Six pillars 22

7. Codes and compliance 22

8. Existing stock and institutions 22

9. Current NCS facts 23

10. Preparedness and response 23

11. PYQ route 23

Earthquake Risk and Resilient Construction - Complete Learning Session

BASIC LEARNING SESSION

SESSION 1 - FOUNDATION - TECTONIC MECHANISM AND THE SEISMIC-RISK EQUATION

```
INDIAN PLATE converges with EURASIAN PLATE (~5 cm/year)
              -> stress accumulates along faults
              -> rupture releases seismic waves
HAZARD x EXPOSURE x VULNERABILITY / CAPACITY -> DISASTER RISK
RULE -> occurrence cannot be prevented; vulnerability can be reduced
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: An earthquake is ground shaking caused by sudden energy release during fault rupture.

Technical definition: Seismic risk arises when tectonic hazard interacts with exposed people, assets and vulnerable construction, moderated by preparedness and response capacity.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Earthquake occurrence is uncontrollable, but disaster loss is largely constructed through where and how India builds.

MUST-WRITE KEYWORDS

fault rupture | **seismic waves** | **hazard** | **exposure** | **vulnerability** | **capacity**

CORE EXPLANATION

The convergent Alpine-Himalayan Belt, where the Indian plate thrusts beneath the Eurasian plate at about 5 cm/year, continuously loads faults. Fourteen States across the western and central Himalayas, North-East and Indo-Gangetic basin are highly earthquake-prone. The Gulf of Khambhat and Rann of Kutch, parts of peninsular India, Lakshadweep and Andaman and Nicobar Islands show that seismic risk is not confined to one belt. Rupture releases stored energy as seismic waves.

The hazard cannot be stopped and its exact time, place and magnitude cannot be predicted. Policy must therefore reduce exposure and vulnerability through land use, safe construction, retrofitting and preparedness. A moderate event can become disastrous where buildings are weak and services fail.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Earthquake occurrence is uncontrollable, but disaster loss is largely constructed through where and how India builds. **Named evidence:** VisionIAS identifies plate-boundary movement and fault rupture as the physical basis and explicitly states that earthquakes cannot be prevented or precisely predicted. **Analysis:** This shifts the answer from forecasting the event to governing the built environment before it occurs. **Qualification:** Physical mechanism belongs partly to Geography; Disaster Management owns the risk-reduction and response consequences.

EXAM TRAP AND RECALL

- **Trap:** Do not call vulnerability a natural property of the earthquake.
- **Recall:** Uncontrollable hazard + constructed vulnerability = reducible disaster risk.

SESSION 2 - FOUNDATION - MAGNITUDE, INTENSITY AND OBSERVED EFFECTS

```
ONE EARTHQUAKE
  -> MAGNITUDE: energy at source; one event value; commonly Mw
  -> INTENSITY: observed effects at a place; varies by location
       distance + depth + soil + building stock
  -> MMI / MSK describe intensity; Richter is older local magnitude scale
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Magnitude measures source energy; intensity records observed effects at a particular place.

Technical definition: Moment magnitude is commonly used for large events, while MMI or MSK intensity varies spatially with shaking, site conditions and vulnerability.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> One earthquake has a source magnitude but many local intensities, which is why identical events do not produce identical damage.

MUST-WRITE KEYWORDS

moment magnitude | **intensity** | **MSK** | **MMI** | **site effect** | **observed damage**

CORE EXPLANATION

Magnitude is an event-level estimate of energy release. Intensity describes how shaking is experienced at a location and can differ across neighbourhoods because of distance, depth, soil amplification and construction quality.

The distinction prevents a common error: using Richter and Mercalli or MSK as if they measure the same quantity. Damage cannot be inferred from magnitude alone; vulnerability and site response remain essential.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: One earthquake has a source magnitude but many local intensities, which is why identical events do not produce identical damage. **Named evidence:** The Basic source requires magnitude-intensity separation and identifies MSK alongside MMI as an intensity scale. **Analysis:** Intensity links physical shaking to place-specific effects, making it more useful for damage mapping and response prioritisation. **Qualification:** Do not attach an intensity value or damage outcome without a location-specific assessment.

EXAM TRAP AND RECALL

- **Trap:** Richter, Mw, MMI and MSK are not interchangeable labels.
- **Recall:** Magnitude at source; intensity at site.

SESSION 3 - FOUNDATION - INDIA'S SEISMIC ZONES AND THE 59 PER CENT EXPOSURE FACT

```
IS 1893 (PART 1): 2016
ZONE II -> lower hazard
ZONE III -> ~30% land area
ZONE IV -> ~18%
ZONE V -> ~11%, highest hazard
ZONES III-V -> ~59% prone to moderate-to-severe earthquakes
ZONE V -> whole NE + A&N + parts of Bihar, J&K/Ladakh,
          Himachal, Uttarakhand and Gujarat
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: India's seismic zoning classifies expected hazard into Zones II to V, with Zone V highest.

Technical definition: IS 1893 (Part 1): 2016 supplies the operative four-zone framework used for design loading and risk-sensitive planning.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> India's seismic risk is extensive but spatially differentiated: about 59 per cent of the landmass lies in Zones III to V, not all of it in Zone V.

MUST-WRITE KEYWORDS

IS 1893:2016 | **Zone II** | **Zone III** | **Zone IV** | **Zone V** | **59 per cent**

CORE EXPLANATION

Approximate land shares are Zone V 11 per cent, Zone IV 18 per cent and Zone III 30 per cent. Zone V covers the whole North-East and Andaman and Nicobar Islands, plus parts of northern Bihar, J&K/Ladakh, Himachal Pradesh, Uttarakhand and Gujarat.

This wording avoids the false claim that the entire Himalayan belt is Zone V. Zoning describes regional hazard for design; it does not predict an earthquake or determine the safety of an individual building.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: India's seismic risk is extensive but spatially differentiated: about 59 per cent of the landmass lies in Zones III to V, not all of it in Zone V. **Named evidence:** PIB/MoES reported the zone shares and approximately 59 per cent landmass figure on 30 July 2021; IS 1893:2016 remains operative. **Analysis:** The figures justify nationwide compliance while preserving higher design demands and retrofitting priorities in more hazardous zones. **Qualification:** A proposed revised zonation was withdrawn in March 2026; do not claim that a new five-zone map is operative.

EXAM TRAP AND RECALL

- **Trap:** Do not place every Himalayan State wholly in Zone V.
- **Recall:** II-V; V highest; III-V together about 59 per cent.

SESSION 4 - CORE - SITE EFFECTS, LIQUEFACTION AND MICROZONATION

```
REGIONAL ZONE
     + local soil / basin / slope / groundwater
     + building density / lifelines
     = NEIGHBOURHOOD-SCALE RISK
MICROZONATION -> finer hazard and site-response mapping
LAND-USE / DESIGN -> local action
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Microzonation refines broad seismic zones using local geology, soil and exposure.

Technical definition: Seismic microzonation maps variations in amplification, liquefaction, slope instability and related site effects to guide planning and design.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> A national zone map sets the regional baseline; microzonation explains why adjacent neighbourhoods can experience sharply different shaking and damage.

MUST-WRITE KEYWORDS

microzonation | **soil amplification** | **liquefaction** | **basin effect** | **slope instability** | **local planning**

CORE EXPLANATION

Soft sediments may amplify shaking, saturated loose soils may liquefy, and steep slopes may fail. Dense exposure and weak access can compound these physical effects.

Microzonation supports local land-use decisions, design parameters and emergency planning. It should not be confused with prediction: it identifies relative spatial risk, not the date of the next event.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: A national zone map sets the regional baseline; microzonation explains why adjacent neighbourhoods can experience sharply different shaking and damage. **Named evidence:** Bhuj damage and later GIS-based assessment illustrate why local built and ground conditions matter alongside regional seismicity. **Analysis:** Finer mapping directs stronger design, restricted siting or emergency access planning to the places where regional zoning is too coarse. **Qualification:** A microzonation map is an input; planning rules and construction compliance determine whether it changes risk.

EXAM TRAP AND RECALL

- **Trap:** Do not call microzonation an earthquake forecast.
- **Recall:** Regional zone + local ground + exposure = microzonated risk.

SESSION 5 - CORE - BUILT-ENVIRONMENT VULNERABILITY AND HISTORICAL LESSONS

```
GROUND SHAKING
  -> weak masonry / soft storey / poor connections
  -> falling components / blocked access / fire
  -> collapse + service failure
CASES -> Latur 1993 | Bhuj 2001 | Kashmir 2005 | Sikkim 2011
LESSON -> construction and access shape loss
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Built-environment vulnerability is the susceptibility of structures and services to damage under shaking.

Technical definition: Constructed vulnerability arises from unsafe siting, deficient design, poor materials and workmanship, non-structural hazards and weak enforcement.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Earthquakes kill mainly through unsafe buildings and failed lifelines, making construction quality the decisive disaster-management variable.

MUST-WRITE KEYWORDS

unreinforced masonry | **soft storey** | **connection failure** | **non-structural hazard** | **lifeline failure** | **historical lessons**

CORE EXPLANATION

Unreinforced masonry, irregular plans, open ground floors, heavy roofs and weak wall-roof connections can fail under lateral loads. Falling parapets, equipment and services may cause injury even when the main frame survives.

Latur showed that damaging earthquakes are not confined to the Himalaya; Bhuj exposed urban and masonry vulnerability; Kashmir and Sikkim highlighted mountainous access and service challenges. Examples should demonstrate mechanisms, not become casualty lists.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Earthquakes kill mainly through unsafe buildings and failed lifelines, making construction quality the decisive disaster-management variable. **Named evidence:** The Basic claim-to-evidence bank uses Bhuj and Latur to counter the idea that tectonic location alone explains loss. **Analysis:** Historical cases make the compliance thesis concrete: similar shaking can produce different outcomes because building stock and response access differ. **Qualification:** Avoid unsourced magnitudes, casualty numbers or monocausal claims about any event.

EXAM TRAP AND RECALL

- **Trap:** Do not describe peninsular India as aseismic.
- **Recall:** Shaking becomes disaster through deficient stock and disrupted services.

SESSION 6 - CORE - STRUCTURAL AND NON-STRUCTURAL MITIGATION

```
STRUCTURAL -> foundation, frame, walls, connections, ductility
NON-STRUCTURAL -> parapets, ceilings, tanks, shelves, equipment, utilities
HOUSEHOLD -> anchor, brace, clear exits, shut-off awareness
SYSTEM -> inspect + maintain + drill
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Structural mitigation strengthens the load-resisting system; non-structural mitigation secures components and contents.

Technical definition: Seismic safety integrates engineered resistance and ductility with anchoring of architectural, service and equipment elements.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> A standing frame can still become a disaster if ceilings fall, oxygen lines rupture or exits are blocked.

MUST-WRITE KEYWORDS

structural mitigation | **non-structural mitigation** | **anchoring** | **bracing** | **utility safety** | **maintenance**

CORE EXPLANATION

Structural measures include appropriate foundations, regular configuration, reinforced connections and ductile load paths. Non-structural measures secure tanks, shelves, ceilings, façades, equipment and utility lines.

Household measures are useful but cannot compensate for an unsafe structure. Hospitals and EOCs especially need both frame safety and functional equipment continuity.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: A standing frame can still become a disaster if ceilings fall, oxygen lines rupture or exits are blocked. **Named evidence:** VisionIAS separates structural and non-structural dimensions under the National Earthquake Risk Mitigation Project and BMTPC's disaster-resistant construction role. **Analysis:** The distinction widens mitigation from collapse prevention to injury reduction and service continuity. **Qualification:** Anchoring furniture is not a substitute for engineering audit or code compliance.

EXAM TRAP AND RECALL

- **Trap:** Do not classify every household preparedness action as structural retrofitting.
- **Recall:** Safe frame + secured contents + usable exits and utilities.

SESSION 7 - CORE - CODES, DUCTILE DETAILING AND VERIFIED CONSTRUCTION QUALITY

```
HAZARD ZONE / SITE DATA
        -> ENGINEERED DESIGN (IS 1893 / relevant standards)
        -> DUCTILE DETAILING
        -> APPROVED MATERIALS + WORKMANSHIP
        -> INSPECTION / CERTIFICATION
        -> MAINTENANCE
CODE ON PAPER != SAFE BUILDING
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Earthquake-resistant construction aims at life safety through appropriate design, detailing and execution.

Technical definition: Code compliance requires design loads, continuous load paths, ductility, quality materials, competent professionals and verified construction.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Seismic safety is a chain from map to design to workmanship; failure at any link can nullify the code.

MUST-WRITE KEYWORDS

National Building Code | IS 1893 | ductility | load path | workmanship | inspection

CORE EXPLANATION

Ductility is the capacity to deform and dissipate energy without sudden brittle collapse. It is an exam-safe life-safety concept, not a claim that damage will be zero.

The National Building Code and BIS standards guide design, but approval drawings alone do not verify materials, reinforcement placement or connections. Professional training, licensing, site inspection and accountability are binding constraints.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Seismic safety is a chain from map to design to workmanship; failure at any link can nullify the code. **Named evidence:** NDMA's May 2021 simplified earthquake-safety guideline draws from NBC 2016; the Basic source lists weak enforcement and absent engineer/mason licensing as challenges. **Analysis:** The compliance chain explains why technically adequate standards may coexist with unsafe urban and rural construction. **Qualification:** Code-compliant design is not identical to verified as-built quality or post-occupancy maintenance.

EXAM TRAP AND RECALL

- **Trap:** Do not claim earthquake-resistant means earthquake-proof.
- **Recall:** Design -> detail -> build -> inspect -> maintain.

SESSION 8 - CORE - NDMA'S SIX PILLARS OF SEISMIC SAFETY

```
1 NEW EARTHQUAKE-RESISTANT CONSTRUCTION
2 SELECTIVE RETROFITTING OF PRIORITY STRUCTURES
3 REGULATION AND ENFORCEMENT
4 AWARENESS AND PREPAREDNESS
5 CAPACITY DEVELOPMENT
6 EMERGENCY RESPONSE
ALL SIX -> SEISMIC SAFETY SYSTEM
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: NDMA's framework organises seismic safety into six linked pillars.

Technical definition: The pillars integrate new-build safety, existing-stock strengthening, regulation, preparedness, professional capacity and response.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> India's earthquake framework is not a list of isolated schemes; its six pillars form a chain from safer construction to emergency response.

MUST-WRITE KEYWORDS

six pillars | new construction | retrofitting | enforcement | capacity development | emergency response

CORE EXPLANATION

New construction prevents future vulnerable stock; selective retrofitting addresses existing lifelines and priority buildings; regulation makes standards enforceable; awareness and preparedness shape behaviour; capacity development improves professional execution; response reduces consequences after impact.

The pillars must be read together. Awareness cannot repair a weak hospital, and codes cannot rescue occupants after collapse. Governance should identify the weakest pillar in the place or sector being analysed.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: India's earthquake framework is not a list of isolated schemes; its six pillars form a chain from safer construction to emergency response. **Named evidence:** VisionIAS reproduces NDMA's six-pillar framework from the earthquake-management guidelines. **Analysis:** The framework gives a complete Mains structure and prevents answers from overemphasising either engineering or response alone. **Qualification:** Naming all six pillars does not prove implementation; attach an enforcement or financing gap.

EXAM TRAP AND RECALL

- **Trap:** Do not omit existing-stock retrofitting while discussing new construction.
- **Recall:** Build safe, retrofit, regulate, prepare, train and respond.

SESSION 9 - CORE - EXISTING-STOCK AUDIT, RETROFITTING AND LIFELINE PRIORITIES

```
INVENTORY -> SCREENING -> ENGINEERING AUDIT
          -> PRIORITY LIST
          -> RETROFIT DESIGN + FINANCE
          -> EXECUTION + QUALITY CHECK
          -> FUNCTIONAL CONTINUITY TEST
LISTED != RETROFITTED
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Retrofitting strengthens an existing deficient structure to improve seismic performance.

Technical definition: A retrofit programme needs inventory, vulnerability screening, detailed audit, prioritisation, design, finance, execution and verification.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> The hardest seismic problem is not writing a code for tomorrow's building but strengthening the vulnerable stock already in use.

MUST-WRITE KEYWORDS

structural audit | **retrofitting** | **priority structure** | **lifeline** | **functional continuity** | **verification**

CORE EXPLANATION

States are responsible for identifying priority structures such as Raj Bhavans, legislatures, courts, academic institutions, reservoirs, dams and multi-storeyed buildings of five or more floors, while ULBs and PRIs support implementation. Hospitals, schools, bridges, EOCs and utilities deserve priority because their failure multiplies disaster effects.

A priority list is not completed mitigation. Funding, relocation during works, engineering design, procurement and quality verification determine delivery. Lifeline resilience also requires backup power, water, communication and staffing.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: The hardest seismic problem is not writing a code for tomorrow's building but strengthening the vulnerable stock already in use. **Named evidence:** VisionIAS places responsibility for identifying priority structures with State Governments and distinguishes retrofitting from safe new construction. **Analysis:** Prioritisation directs scarce resources toward buildings whose collapse or service failure would create cascading loss. **Qualification:** Identification, sanction and completed retrofit are different evidence stages.

EXAM TRAP AND RECALL

- **Trap:** Do not treat cosmetic repair as seismic retrofitting.
- **Recall:** Audit -> prioritise -> finance -> execute -> verify service continuity.

SESSION 10 - CORE - NERMP, BMTPC AND THE VULNERABILITY ATLAS

```
NERMP -> structural + non-structural risk-reduction route
BMTPC -> disaster-resistant materials and construction promotion
VULNERABILITY ATLAS 2019 -> multi-hazard + housing-stock vulnerability
USE -> planning, awareness, screening and priority
LIMIT -> programme or atlas existence != local compliance
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: National programmes and technical institutions support seismic mitigation through guidance, mapping and capacity.

Technical definition: NERMP addresses structural and non-structural earthquake vulnerability, while BMTPC promotes disaster-resistant construction and publishes the Vulnerability Atlas of India.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Maps and technical programmes create a decision base; risk falls only when local planning and construction systems act on it.

MUST-WRITE KEYWORDS

NERMP | **BMTPC** | **Vulnerability Atlas** | **housing stock** | **technical promotion** | **implementation**

CORE EXPLANATION

The National Earthquake Risk Mitigation Project is a named mitigation route for structural and non-structural vulnerability. BMTPC promotes resource-efficient disaster-resistant construction and supports lifeline retrofitting.

The guideline chronology is also exam-relevant: NDMA's 2007 earthquake guidelines provide the six-pillar framework, the June 2014 guidelines address seismic retrofitting of deficient buildings and structures, and the May 2021 simplified guideline translates NBC 2016 earthquake-safety provisions for buildings. The Vulnerability Atlas third edition (2019) maps earthquake and other hazards State/UT-wise and includes housing-stock vulnerability. It supports screening and awareness but does not replace building-specific audit or current local data. Use the correct acronym BMTPC, not the source typo BMPTC.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Maps and technical programmes create a decision base; risk falls only when local planning and construction systems act on it. **Named evidence:** The Basic source names NERMP, BMTPC and the Vulnerability Atlas as distinct mitigation and knowledge tools. **Analysis:** Together they connect national technical knowledge to prioritisation, but local enforcement remains the conversion mechanism. **Qualification:** Do not claim a current budget or latest-edition status without a dated official source.

EXAM TRAP AND RECALL

- **Trap:** An atlas classifies vulnerability; it does not certify an individual building.
- **Recall:** Programme + institution + atlas -> evidence for action, not proof of action.

SESSION 11 - CORE - RISK-SENSITIVE LAND USE AND DEVELOPMENT CONTROL

```
HAZARD / MICROZONE + SLOPE / LIQUEFACTION
          -> LAND-USE CONTROL
          -> DENSITY / ACCESS / OPEN SPACE
          -> SAFE SITING + DEVELOPMENT CONTROL
CONTROL -> site, density, access and critical-facility rules
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Risk-sensitive land use avoids concentrating vulnerable development where shaking and secondary hazards are greatest.

Technical definition: Planning integrates seismic zones, microzonation, density, access, open space, critical facilities and enforceable development controls.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Resilient construction cannot compensate for every unsafe site, blocked access route or unregulated concentration of exposure.

MUST-WRITE KEYWORDS

risk-sensitive land use | **development control** | **access** | **open space** | **critical facilities** | **enforcement**

CORE EXPLANATION

Planning should restrict unsafe slopes or liquefaction-prone sites, protect emergency access and locate critical facilities with functional continuity in mind. Town-planning Acts, zoning regulations, DCRs and bye-laws must incorporate seismic safety.

Development control must also preserve evacuation space, emergency routes and utility access. A technically safe building can remain part of an unsafe urban system if surrounding density and access prevent rescue or service restoration.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Resilient construction cannot compensate for every unsafe site, blocked access route or unregulated concentration of exposure. **Named evidence:** The Basic source records expert recommendations to incorporate seismic safety into town-planning Acts, zoning regulations, development-control regulations and building bye-laws. **Analysis:** Planning controls reduce exposure before it becomes locked into dense, inaccessible or geotechnically unsafe development. **Qualification:** Land-use control must use current local evidence and cannot substitute for building-specific engineering.

EXAM TRAP AND RECALL

- **Trap:** Do not treat enforcement and affordability as opposing goals.
- **Recall:** Safe site + controlled exposure + protected access and lifelines.

SESSION 12 - CORE - NCS MONITORING, PREDICTION LIMITS AND CURRENT STATUS

```
170-OBSERVATORY NATIONAL SEISMOLOGICAL NETWORK
          -> EVENT DETECTION + PARAMETER ESTIMATION
          -> NCS INFORMATION + BhooKamp APP
PREDICTION FIREWALL -> exact time/place/magnitude not predicted
WITHDRAWN REVISION -> IS 1893:2016 remains operative
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: NCS monitors and reports earthquakes; it does not precisely predict their occurrence.

Technical definition: The National Centre for Seismology operates the national network, analyses seismic events and disseminates parameters through official services including BhooKamp.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Monitoring tells India what has begun or occurred; mitigation remains necessary because monitoring cannot announce the exact future earthquake.

MUST-WRITE KEYWORDS

NCS | 170 observatories | BhooKamp | monitoring | event parameters | prediction firewall

CORE EXPLANATION

PIB/MoES reported a 170-observatory National Seismological Network and identified BhooKamp as the official earthquake-information app on 1 April 2026. This corrects the stale India Quake label in older material.

Event detection and rapid parameter dissemination are not prediction. Network and app information supports situational awareness after an event begins or occurs, while loss reduction still depends on safer buildings and preparedness. The proposed zonation revision was withdrawn in March 2026, leaving IS 1893:2016 operative.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Monitoring tells India what has begun or occurred; mitigation remains necessary because monitoring cannot announce the exact future earthquake. **Named evidence:** NCS current facts and the withdrawn-zonation status are dated to PIB/MoES, 1 April 2026. **Analysis:** The status distinction prevents technology optimism from displacing the central mitigation task of safer construction. **Qualification:** Network size and app availability do not prove warning lead time, reach or reduced loss.

EXAM TRAP AND RECALL

- **Trap:** Do not call BhooKamp an earthquake-prediction app.
- **Recall:** Monitor and report; do not claim precise prediction.

SESSION 13 - CORE - PREPAREDNESS, INCIDENT RESPONSE SYSTEM AND EMERGENCY OPERATIONS CENTRES

```
BEFORE -> plans, drills, household safety, response inventory
IMPACT -> EOC activates Incident Response System
IRS -> command, operations, planning, logistics, finance/admin
COMMUNITY + SERVICES + SPECIALIST TEAMS
AFTER -> search, medical aid, damage and needs assessment
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: Preparedness organises people, information and resources before shaking; IRS structures command after impact.

Technical definition: Local administration coordinates earthquake response through Emergency Operations Centres and the Incident Response System with community, services and specialist teams.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> Because warning time may be absent, earthquake response quality is largely determined before impact through drills, inventories and command clarity.

MUST-WRITE KEYWORDS

preparedness | **IRS** | **EOC** | **command** | **logistics** | **damage assessment**

CORE EXPLANATION

Households should know Drop-Cover-Hold, secure heavy contents, keep exits clear and understand utility safety. Institutions need evacuation and reunification plans, while hospitals and utilities require continuity arrangements. NDMA preparedness support includes handbooks, homeowner seismic-safety manuals, structural-safety audit manuals, vulnerability maps and the streamlining of NGO and volunteer groups.

After impact, EOCs support situational awareness and IRS organises command, operations, planning, logistics and finance or administration. Search and rescue, medical triage and damage assessment must account for blocked roads, aftershocks and lifeline failure.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: Because warning time may be absent, earthquake response quality is largely determined before impact through drills, inventories and command clarity. **Named evidence:** VisionIAS identifies IRS coordinated by local administration through the EOC network and involving community, corporate and specialist teams. **Analysis:** Prepared structures and command systems reduce the delay and confusion created by a no-prediction hazard. **Qualification:** A drill or EOC building is an input; activation performance and service continuity require separate evidence.

EXAM TRAP AND RECALL

- **Trap:** Do not reduce preparedness to a household emergency kit.
- **Recall:** Prepare before -> activate EOC/IRS -> coordinate safe response -> assess and recover.

SESSION 14 - CORE SYNTHESIS - THE COMPLIANCE CHAIN: REGULATION, PROFESSIONALS AND ENFORCEMENT

```
ZONE / MICROZONE
 -> CODE + BYE-LAW
 -> TRAINED / LICENSED PROFESSIONAL
 -> APPROVAL
 -> SITE INSPECTION
 -> AS-BUILT VERIFICATION
 -> MAINTENANCE / AUDIT
WEAKEST LINK -> REAL VULNERABILITY
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: The compliance chain is the sequence that converts technical standards into actual building safety.

Technical definition: Effective regulation links planning law, codes, professional competence, permitting, inspection, verification and accountability.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> India's seismic deficit is less a shortage of standards than a failure to carry them through the entire construction chain.

MUST-WRITE KEYWORDS

compliance chain | **licensing** | **bye-law** | **inspection** | **as-built verification** | **accountability**

CORE EXPLANATION

VisionIAS lists inadequate code enforcement, missing seismic features, weak professional training, low awareness and absent licensing systems. These are connected, not separate. A sound design can be defeated by poor detailing; an inspection regime can be defeated by unqualified staff or corruption.

Central ministries and States are responsible for structures under their administrative control, while States identify priority retrofits through local bodies. Monitoring should report audits, corrections and verified completion, not only code adoption.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: India's seismic deficit is less a shortage of standards than a failure to carry them through the entire construction chain. **Named evidence:** A national expert group recommended technical changes to planning Acts, zoning regulations, DCRs and building bye-laws. **Analysis:** Tracing the chain identifies the actual failure point and produces more actionable recommendations than repeating 'strict enforcement'. **Qualification:** Enforcement must be paired with training and transparent accountability.

EXAM TRAP AND RECALL

- **Trap:** Do not infer safety from code adoption alone.
- **Recall:** Map -> code -> professional -> permit -> inspect -> verify -> maintain.

SESSION 15 - CORE SYNTHESIS - SYNTHESIS, 2021 PYQ ROUTE AND THE 2026 ADJACENT BOUNDARY

```
2021 DIRECT OWNER
INDIA VULNERABILITY -> tectonic setting + zones + unsafe stock + capacity
EXAMPLES -> Latur 1993 | Bhuj 2001 | Kashmir 2005 | Sikkim 2011
MEASURES -> six pillars + compliance chain

2026 Q7 ADJACENT SUPPORT ONLY
primary ownership -> ecologically sensitive infrastructure / lifelines
earthquake contribution -> risk-sensitive siting and resilient design
```

DEFINITION / WHAT THIS IS CALLED

Plain definition: A complete earthquake answer integrates hazard geography, constructed vulnerability, historical evidence and enforceable mitigation.

Technical definition: The topic directly owns the 2021 GS-III vulnerability demand and supports, but does not own, the 2026 infrastructure-versus-DRR question.

ANSWER-GRABBING OPENING - WRITE/ADAPT IN THE EXAM

> India's earthquake vulnerability is national in spread but local in consequence, because seismic hazard becomes disaster through site, stock and compliance.

MUST-WRITE KEYWORDS

2021 PYQ | vulnerability | historical examples | six pillars | compliance | 2026 boundary

CORE EXPLANATION

For 2021, structure the answer as: tectonic and zonal exposure; vulnerable buildings, lifelines and enforcement; historical examples from different regions; and a concise mitigation close using NDMA's six pillars.

The 2026 question on rapid infrastructure development in ecologically sensitive areas is primarily owned by landslide and critical-infrastructure topics. Earthquake content supports it through seismic siting, microzonation, resilient design and lifecycle compliance, but should not displace the broader ecological-risk demand.

NAMED-EVIDENCE PARAGRAPH DEMONSTRATION

Claim: India's earthquake vulnerability is national in spread but local in consequence, because seismic hazard becomes disaster through site, stock and compliance. **Named evidence:** The 2021 routing ledger assigns Q8 directly to this topic; the 2026 routing ledger assigns Q7 primarily to Topics 10 and 14. **Analysis:** Clear ownership prevents force-fitting while preserving useful cross-topic evidence. **Qualification:** Use historical examples to demonstrate mechanisms and regional spread, not to invent unsupported event statistics.

EXAM TRAP AND RECALL

- **Trap:** Do not claim that 2026 Q7 is a direct earthquake PYQ.
- **Recall:** 2021 direct: vulnerability + cases; 2026 adjacent: siting and resilient infrastructure.

BASIC MCQS / REMEDIATION

Q1. What initiates a tectonic earthquake?

A. Sudden fault rupture after stress accumulation B. Daily temperature variation C. Only volcanic ash D. Building collapse itself

Answer: A.

Explanation: Fault rupture releases stored elastic energy as seismic waves.

Q2. Why does intensity vary across locations for one event?

A. Magnitude changes at every town B. Distance, depth, ground conditions and buildings differ C. MSK measures energy at source D. All sites receive identical shaking

Answer: B.

Explanation: Intensity is a site-specific effect measure.

Q3. Which statement about India is correct?

A. All Himalayas are Zone V B. Only the Himalayas are seismic C. About 59 per cent lies in Zones III-V D. India has an operative new five-zone map

Answer: C.

Explanation: The four-zone 2016 system remains operative and III-V cover about 59 per cent.

Q4. What is microzonation?

A. Prediction of the next event B. A national response command C. A building certificate D. Finer local mapping of site effects and risk

Answer: D.

Explanation: Microzonation refines broad zones using local ground and exposure.

Q5. Which is a built-environment vulnerability?

A. Weak masonry and poor wall-roof connections B. Plate convergence C. Moment magnitude D. NCS event detection

Answer: A.

Explanation: Unsafe construction converts shaking into collapse.

Q6. Which pairing is correct?

A. Foundation strengthening is non-structural B. Frame strengthening is structural; anchoring equipment is non-structural C. A drill is structural retrofitting D. Zoning is household preparedness

Answer: B.

Explanation: The distinction is between the load-resisting system and contents/components.

Q7. Ductility is best understood as:

A. Zero damage B. Prediction capability C. Capacity to deform and dissipate energy without sudden brittle collapse D. A soil classification

Answer: C.

Explanation: Ductility is a life-safety property, not earthquake proofing.

Q8. Which is NOT one of NDMA's six pillars?

A. Safe new construction B. Selective retrofitting C. Capacity development D. Precise earthquake prediction

Answer: D.

Explanation: Prediction is not a pillar; mitigation and preparedness substitute for it.

Q9. What is the first step in existing-stock retrofitting?

A. Inventory and vulnerability screening B. Cosmetic painting C. Demolition of every old structure D. Issue an all-clear

Answer: A.

Explanation: Programmes begin by identifying and screening stock.

Q10. Why do hospitals require lifeline resilience?

A. Only because they are tall B. They must remain functional after shaking, not merely avoid collapse C. They replace EOCs D. They issue seismic zones

Answer: B.

Explanation: Continuity of health services, power, water and equipment is critical.

Q11. Which institution publishes the Vulnerability Atlas?

A. NCS B. IMD C. BMTPC D. NDRF

Answer: C.

Explanation: BMTPC publishes the multi-hazard Vulnerability Atlas.

Q12. Which statement about land use is correct?

A. Codes remove all site risk B. Density never affects risk C. Informal housing should be excluded from support D. Planning should integrate zones, microzonation, access and critical facilities

Answer: D.

Explanation: Risk-sensitive land use manages exposure and response feasibility.

Q13. What is the current NCS fact set used here?

A. 170 observatories and BhooKamp app B. A precise prediction service C. A five-zone 2026 map D. Only one Himalayan station

Answer: A.

Explanation: PIB/MoES reported the network and official app on 1 April 2026.

Q14. What does IRS provide after an earthquake?

A. A magnitude scale B. Structured incident command and coordination through EOCs C. A replacement for construction codes D. A land-title system

Answer: B.

Explanation: IRS organises command, operations, planning and logistics.

Q15. What is the strongest compliance-chain test?

A. Whether a code exists B. Whether awareness material was printed C. Whether design, workmanship, inspection and verification all function D. Whether one engineer was trained

Answer: C.

Explanation: Safety depends on the full chain, not one input.

Q16. Which PYQ routing is correct?

A. 2026 Q7 is owned solely by earthquake risk B. 2021 Q8 belongs only to Geography C. Neither question uses seismic evidence D. 2021 Q8 is direct; 2026 Q7 receives bounded earthquake support

Answer: D.

Explanation: This preserves direct and adjacent ownership.

PYQS AND ANSWER PRACTICE

DIRECT PYQ - 2021 GS-III Q8 - 10 marks, 150 words

Question: Discuss about the vulnerability of India to earthquake related hazards. Give examples including the salient features of major disasters caused by earthquakes in different parts of India during the last three decades.

Model answer: India is highly earthquake-vulnerable because tectonic hazard combines with dense exposure and unsafe construction. The Himalayan convergence zone, North-East, Andaman and Nicobar Islands and Kachchh face high hazard, while damaging peninsular events show risk is not confined to the Himalaya. About 59 per cent of India's landmass lies in seismic Zones III-V.

Vulnerability is amplified by unreinforced masonry, soft-storey buildings, weak code enforcement, deficient professional training and vulnerable lifelines. Latur (1993) exposed rural masonry vulnerability in peninsular India; Bhuj (2001) showed severe urban and housing-stock failure in Gujarat; Kashmir (2005) highlighted mountainous

access and building weakness; Sikkim (2011) demonstrated cascading slope and connectivity problems.

India therefore needs NDMA's six-pillar approach: safe new construction, priority retrofitting, regulation, awareness, capacity development and emergency response. Since earthquakes cannot be precisely predicted, enforced compliance and preparedness are the central safeguards.

2026 ADJACENT APPLICATION - NOT PRIMARY OWNERSHIP

The 2026 GS-III Q7 asks how rapid infrastructure development and disaster-risk reduction can be reconciled in ecologically sensitive areas. Primary ownership lies with landslide/GLOF and critical-infrastructure topics. Use earthquake evidence only as a supporting dimension: seismic microzonation, risk-sensitive siting, resilient design, lifeline continuity and enforceable lifecycle compliance.

SIX ANSWER-WRITING DRILLS

1. Draw the magnitude-intensity distinction with one site-effect example.
2. Correct the statement "the entire Himalayan belt is Zone V".
3. Turn NDMA's six pillars into a 150-word answer structure.
4. Separate priority-list preparation from completed retrofitting.
5. Explain why NCS monitoring and BhooKamp are not prediction.
6. Use Bhuj and Latur to show how construction shapes loss.

OPTIONAL ADVANCED DEPTH - NOT REQUIRED FOR A CORE ANSWER

Compliance-chain diagnosis

Link	Typical failure	Consequence	Corrective route
Hazard knowledge	Coarse zone used as building certificate	Local site risk ignored	Microzonation and site investigation
Design	Inadequate load path or detailing	Brittle failure	Competent seismic design and review
Construction	Poor materials or workmanship	Design intent lost	Inspection and as-built verification
Existing stock	Priority list without finance	Vulnerability persists	Phased retrofit programme
Lifelines	Frame safe but services fail	Hospital/EOC unusable	Functional continuity audit

Prediction and early-warning firewall

Precise prediction of time, place and magnitude is not an available capability. Rapid event detection and parameter reporting are different. Earthquake early warning, where supported, detects initial waves after rupture and may create seconds of action; it is not prediction and should not be claimed as nationally operational without dated evidence.

Equity refinement

Informal and rural households often face the highest compliance barriers because engineers, trained masons, finance and formal approval systems are scarce. Effective enforcement therefore combines rules with affordable technical assistance, mason training and retrofit support.

Zonation as a techno-legal instrument

Seismic zoning is not only a scientific map. Upgrading an area can raise design loads, construction costs, insurance pricing and the potential retrofitting liability of existing stock. A revision therefore creates distributional and legal consequences that scientific updating alone cannot settle. The March 2026 withdrawal of the proposed revised zonation sharply illustrates the compliance thesis: a technical announcement does not become operative risk governance until the standard, liabilities and implementation route are settled.

Financing the retrofit gap

The State and National Disaster Mitigation Funds provide the structurally appropriate ex-ante financing window, primarily owned by the risk-financing topic. However, no dated official source in the owner material establishes a nationwide seismic-retrofitting programme financed through that window. This absence is analytically significant when compared with demonstrated mitigation-fund financing for urban-flood and GLOF risk. Any claim about seismic insurance or other risk-transfer coverage also requires current verification rather than assumption.

Federal pace of retrofitting

Because State Governments identify priority structures for retrofitting, national seismic-safety improvement is only as fast as its slowest State. Central codes and guidance can establish a baseline, but inventories, audits, finance and completed works remain dependent on uneven State and local capacity.

COMPLETE TOPIC ASCII MASTER FLOW DIAGRAM

ASCII MASTER FLOW - PANEL 1/12: Tectonic risk chain

```
PLATE CONVERGENCE -> FAULT STRESS -> RUPTURE -> SEISMIC WAVES
HAZARD x EXPOSURE x VULNERABILITY / CAPACITY -> RISK
OCCURRENCE UNCONTROLLABLE -> VULNERABILITY REDUCIBLE
```

ASCII MASTER FLOW - PANEL 2/12: Magnitude and intensity

```
MAGNITUDE -> source energy; commonly Mw; one event value
INTENSITY -> observed effects at a place; MMI / MSK
VARIES WITH -> distance, depth, ground and building stock
```

ASCII MASTER FLOW - PANEL 3/12: India seismic map

```
IS 1893:2016 -> ZONES II, III, IV, V
ZONE V -> whole NE + A&N + parts of northern Bihar,
          J&K/Ladakh, Himachal, Uttarakhand and Gujarat
ZONE V 11% | IV 18% | III 30%
ZONES III-V -> about 59% of landmass
MARCH 2026 REVISION WITHDRAWN -> IS 1893:2016 OPERATIVE
```

ASCII MASTER FLOW - PANEL 4/12: Site-effect route

```
REGIONAL ZONE + SOIL / BASIN / SLOPE / GROUNDWATER
-> AMPLIFICATION / LIQUEFACTION / SLOPE FAILURE
-> MICROZONATION
-> LOCAL LAND-USE AND DESIGN ACTION
```

ASCII MASTER FLOW - PANEL 5/12: Constructed vulnerability

```
WEAK MASONRY / SOFT STOREY / POOR CONNECTIONS
FALLING COMPONENTS / FIRE / BLOCKED ACCESS
LIFELINE FAILURE -> CASCADING LOSS
CASES -> LATUR | BHUJ | KASHMIR | SIKKIM
```

ASCII MASTER FLOW - PANEL 6/12: Mitigation system

```
STRUCTURAL -> frame, walls, foundation, connections, ductility
NON-STRUCTURAL -> tanks, ceilings, shelves, equipment, utilities
HOUSEHOLD -> anchor, brace, clear exits
ALL LEVELS -> INSPECT AND MAINTAIN
```

ASCII MASTER FLOW - PANEL 7/12: NDMA six pillars

```
1 SAFE NEW CONSTRUCTION
2 SELECTIVE RETROFITTING
3 REGULATION AND ENFORCEMENT
4 AWARENESS AND PREPAREDNESS
5 CAPACITY DEVELOPMENT
6 EMERGENCY RESPONSE
```

ASCII MASTER FLOW - PANEL 8/12: Compliance chain

```
ZONE / SITE -> DESIGN -> DETAIL -> MATERIAL / WORKMANSHIP
-> INSPECTION -> AS-BUILT VERIFICATION -> MAINTENANCE
CODE ON PAPER != SAFE BUILDING
```

ASCII MASTER FLOW - PANEL 9/12: Existing stock and lifelines

```
INVENTORY -> SCREEN -> AUDIT -> PRIORITISE
-> FINANCE -> RETROFIT -> VERIFY
HOSPITAL / SCHOOL / BRIDGE / EOC / UTILITY
COLLAPSE PREVENTION + FUNCTIONAL CONTINUITY
```

ASCII MASTER FLOW - PANEL 10/12: Institutions and tools

```
NERMP -> structural and non-structural mitigation
BMTPC -> disaster-resistant construction
VULNERABILITY ATLAS 2019 -> hazard + housing stock
NCS -> 170 observatories + BhooKamp (1 April 2026)
```

ASCII MASTER FLOW - PANEL 11/12: Preparedness and response

```
BEFORE -> drill, household safety, inventory, continuity plan
IMPACT -> EOC ACTIVATES IRS
IRS -> command, operations, planning and logistics
AFTER -> rescue, medical aid, damage and needs assessment
```

ASCII MASTER FLOW - PANEL 12/12: Answer spine and PYQ boundary

```
2021 DIRECT -> vulnerability + regional examples + mitigation
2026 ADJACENT -> risk-sensitive infrastructure support only
THESIS -> no precise prediction; compliance is mitigation
VERDICT -> safer stock, lifelines and accountable enforcement
```

CONSOLIDATED REGISTER NOTES

1. Physical foundation

- Plate motion loads faults; rupture releases seismic waves.
- The Alpine-Himalayan Belt is the convergent boundary where the Indian plate thrusts beneath Eurasia at about 5 cm/year.
- Fourteen States across the western/central Himalayas, North-East and Indo-Gangetic basin are highly earthquake-prone.
- Other active areas include the Gulf of Khambhat/Rann of Kutch, parts of peninsular India, Lakshadweep and Andaman and Nicobar Islands.
- Earthquakes cannot be precisely prevented or predicted by time, place and magnitude.

2. Measurement

- Magnitude = source energy; commonly Mw for large events.
- Intensity = observed effects at a place; MMI or MSK.
- One event can have one magnitude and many intensities.

3. India's zones

- IS 1893 (Part 1): 2016; Zones II-V; Zone V highest.
- Zone V about 11%, IV 18%, III 30%; Zones III-V about 59% of landmass.
- Whole North-East and A&N are Zone V; only parts of Bihar, J&K/Ladakh, Himachal, Uttarakhand and Gujarat are Zone V.
- Proposed revision withdrawn March 2026; four-zone 2016 standard remains.

4. Risk variation

- Microzonation adds soil, basin, slope, groundwater and exposure detail.
- Liquefaction and amplification are local site effects, not predictions.
- Peninsular India is not aseismic: Latur and Koyna are counterexamples.

5. Constructed vulnerability

- Unreinforced masonry, soft storey, irregular form and poor connections raise collapse risk.
- Non-structural components can injure and disable services even when frames survive.
- Historical route: Latur 1993, Bhuj 2001, Kashmir 2005 and Sikkim 2011.

6. Six pillars

- Safe new construction.
- Selective strengthening and retrofitting.
- Regulation and enforcement.
- Awareness and preparedness.
- Capacity development.
- Emergency response.

7. Codes and compliance

- NBC and BIS standards require competent design, ductile detailing and verified construction.
- Code adoption is not compliance.
- Full chain: zone/site -> design -> workmanship -> inspection -> verification -> maintenance.

8. Existing stock and institutions

- States identify priority structures; lifelines need functional continuity.
- Priority structures include Raj Bhavans, legislatures, courts, academic institutions, reservoirs, dams and buildings of five or more floors.
- NERMP addresses structural and non-structural mitigation.
- BMTPC promotes disaster-resistant construction and publishes the Vulnerability Atlas (third edition 2019).
- Guideline chronology: NDMA earthquake guidelines 2007; deficient-building retrofit guidelines June 2014; simplified NBC 2016 earthquake-safety guideline May 2021.

9. Current NCS facts

- National Seismological Network: 170 observatories.
- Official app: BhooKamp.
- Source date: PIB/MoES, 1 April 2026.
- Monitoring and rapid reporting are not prediction.

10. Preparedness and response

- Household: Drop-Cover-Hold, secure contents, clear exits and utility awareness.
- Institutions: drills, continuity plans and response inventories.
- Preparedness tools include handbooks, homeowner safety manuals, structural-audit manuals, vulnerability maps and organised NGO/volunteer support.
- EOC and IRS organise command, operations, planning and logistics.

11. PYQ route

- 2021 direct: India's vulnerability plus salient features of major disasters in different regions.
- 2026 Q7 adjacent only: use seismic siting/design within wider ecologically sensitive infrastructure analysis.