

MPC for Group Reconstruction Circuits

Lúcas Críostóir Meier

June 7, 2022

Abstract

In this paper, we present a thing.

1 Introduction

Write the introduction

2 Background

Throughout this paper, we let \mathbb{G} denote a group of prime order q , with generators G and H . Let \mathbb{F}_q denote the scalar field associated with this group, and let $\mathbb{Z}/(q)$ denote the additive group of elements in this field.

We make heavy use of group homomorphisms throughout this paper. We let

$$\varphi(P_1, \dots, P_m) : \mathbb{A} \rightarrow \mathbb{B}$$

denote a homomorphism from \mathbb{A} to \mathbb{B} , parameterized by some public values P_1, \dots, P_m . Commonly \mathbb{A} will be a product of several groups $\mathbb{G}_1, \dots, \mathbb{G}_n$, in which case we'd write:

$$\varphi(P_1, \dots, P_m)(x_1, \dots, x_n)$$

to denote the application of φ to an element (x_1, \dots, x_n) of the product group. We also often leave the public values P_i implicit.

2.1	Pedersen Commitments
2.2	Sigma Protocols
2.3	Maurer's φ -Proof
2.4	UC Security and the Hybrid Model
2.5	Ideal Functionalities for Sigma Protocols
2.6	Broadcast Functionalities
3	Group Reconstruction Circuits
3.1	Formal Definition
3.2	Normalized Form
4	MPC Protocol for GRCs
5	Security Analysis
6	Applications
7	Limitations and Further Work
8	Conclusion
	References