PHSM8

Platform	Crossbar DARIC BGA
OS	Crossbar Security OS base on ThreadX User-customized OS
RAM	2MB internal SRAM
ROM	1MB internal security ReRAM 128MB external ROM
Size	86 mm * 54 mm * 5.5 mm
Form	Full-Touch Slate Phone
LCM	2.8” EINK, 600*480 with 4bits grayscale
Indicator	RGB LED Haptic Linear Motor
Battery	220mAh USB Type C
Connectivity	BT5.2 with BLE NFC Wireless Charger
Sensor	Fingerprint under Power KEY
SW Key Feature	MPCAA, FIDO2 User-customized Firmware

Copyright © 2026 CrossBar, Inc.

PHSM6

Platform	Crossbar DARIC BGA
OS	Crossbar Security OS base on ThreadX User-customized OS
RAM	2MB internal SRAM
ROM	1MB internal security ReRAM 128MB external ROM (optional)
Size	63.5 mm * 25.4 mm * 6.9 mm
Form	Dongle
LCM	1.09” Mono OLED, 128*64
Keys	Up / Down / OK
Battery	w/o battery, USB Type C Port
Connectivity	BT5.2 with BLE (optional)
Sensor	Fingerprint
SW Key Feature	MPCAA, FIDO2 User-customized Firmware

Copyright © 2026 CrossBar, Inc.