ksformat :: Cheat Sheet

SAS-style **PROC FORMAT** for R — value→label mappings, numeric ranges, reverse formatting (invalue), date/time/datetime, expression labels, multilabel & more

INSTALL & LOAD

```
# From CRAN
install.packages("ksformat")
# From GitHub (dev)
remotes::install_github("crow16384/ksformat")
library(ksformat)
```

FORMAT CREATION

FNEW() — DISCRETE VALUE→LABEL `VALUE`

```
fnew(..., name=NULL, type="auto", default=NULL, multilabel=FALSE, ignore_case=FALSE)
... = named pairs key="label" | .missing/.other = special labels | name = register in library
```

```
fnew(
  "M" = "Male",
  "F" = "Female",
  .missing = "Unknown",
  .other = "Other Gender",
  name = "sex"
)
```

sex `CHAR`

```
M → Male
F → Female
.missing → Unknown
.other → Other Gender
```

FINPUT() — REVERSE (LABEL→VALUE) `INVALUE`

```
finput(..., name=NULL, target_type="numeric", missing_value=NA)
... = named pairs label=value | target_type = "numeric"|"character" output type
```

```
finput(
  "Male" = 1,
  "Female" = 2,
  name = "sex_inv"
)
```

sex_inv `INVALUE` `→NUM`

```
Male → 1
Female → 2
```

FNEW_BID() — BIDIRECTIONAL `VALUE` + `INVALUE`

```
fnew_bid(..., name=NULL, type="auto")
Creates both a VALUE format and matching _inv INVALUE simultaneously
```

```
fnew_bid(
  "A" = "Active",
  "I" = "Inactive",
  name = "status"
)
```

Creates **both**:

- `"status"` VALUE format
- `"status_inv"` INVALUE

FNEW_DATE() — DATE/TIME/DATETIME FORMAT

```
fnew_date(pattern, name=NULL, type="auto", .missing=NULL)
pattern = SAS format name (DATE9.) or R strftime pattern (%d.%m.%Y)
```

```
fnew_date("DATE9.", name="bday")
fnew_date("%d.%m.%Y",
  name="ru", type="date")
fnew_date("MMDDYY10.",
  name="us", .missing="NO DATE")
```

bday `DATE`

Pattern: `%d%b%Y` (DATE9.)

SAS names auto-resolved; R patterns also supported

OPTIONS FOR FNEW()

PARAM	DEFAULT	WHAT IT DOES
`name`	NULL	Register in format library
`type`	"auto"	"numeric"/"character" key type
`multilabel`	FALSE	Allow multiple labels per value
`ignore_case`	FALSE	Case-insensitive matching
`.missing`	–	Label for NA/NaN/""
`.other`	–	Fallback for unmatched values

FORMAT APPLICATION

FPUT() — APPLY FORMAT (GENERIC)

```
fput(x, format, ..., keep_na=FALSE)
x = values | format = name or object | ... = extra args for expression labels
```

```
fput(
  c("M", "F", "M", NA, "X"),
  "sex"
)
```

`"Male"` `"Female"` `"Male"` `"Unknown"` `"Other Gender"`

FPUTN() FPUTC() — TYPED APPLY

```
fputn(x, format_name, ...) · fputc(x, format_name, ...)
Numeric/character shorthand — format_name is always a string name
```

```
fputn(c(5, 30, 70), "age")
fputc(c("M", "F"), "sex")
```

`"Child"` `"Adult"` `"Senior"` `"Male"` `"Female"`

FPUTK() — COMPOSITE KEY APPLY

```
fputk(..., format, sep="|", keep_na=FALSE)
... = vectors pasted into composite key (e.g. SUBJ|VISIT) before lookup
```

```
fnew("A|1"="2025-01-15",
  "A|2"="2025-02-20",
  "B|1"="2025-03-10",
  .other="NOT FOUND",
  name="vd")
fputk(c("A","A","B","B"),
  c(1,2,1,3), format="vd")
```

`"2025-01-15"` `"2025-02-20"` `"2025-03-10"` `"NOT FOUND"`

FPUTK() + FMAP() / FPARSE() — DATE LOOKUP

```
# Data-driven from data frame
fnew(fmap(paste(SV$SUBJ,
    SV$VISIT, sep="|"),
  as.Date(SV$DTC)),
  name="svdtn", type="Date")
# Or via fparse() text:
# VALUE svdtn (Date,
#   format: %Y-%m-%d, nocase)
#  "S1|1"="2025-01-15" ;
fputk(QS$SUBJ, QS$VISIT,
  format="svdtn")
```

`2025-01-15` `2025-02-20` `NA`

Returns native Date — arithmetic works

fmap() for data · **fparse()** for text defs

FPUT_DF() — FORMAT DATA FRAME COLUMNS

```
fput_df(data, ..., suffix="_fmt", replace=FALSE)
... = col=format pairs | suffix = new column suffix | replace = overwrite original
```

```
fput_df(df,
  sex = format_get("sex"),
  age = format_get("age"),
  suffix = "_lbl"
)
```

SEX	AGE	SEX_LBL	AGE_LBL
M	15	Male	Child
F	25	Female	Adult
NA	35	Unknown	Adult

MISSING VALUE HANDLING

#	CONDITION	RESULT
①	NA / NaN / ""	`.missing` label
②	Exact match	Mapped label
③	Range match	Range label
④	No match	`.other` / original

IS_MISSING() — CHECK FOR MISSING VALUES

```
is_missing(x)
Returns TRUE for NA, NaN, and empty string ""
```

```
is_missing(NA)    # TRUE
is_missing(NaN)   # TRUE
is_missing("")    # TRUE
is_missing("x")  # FALSE
```

`TRUE` `TRUE` `TRUE` `FALSE`

KEEP_NA OPTION

```
fput(c("M", NA), "sex")

fput(c("M", NA), "sex",
  keep_na = TRUE)
```

`"Male"` `"Unknown"`

`"Male"` `NA`

TEXT PARSING & NUMERIC RANGES

FPARSE() — PARSE VALUE/INVALUE TEXT

```
fparse(text=NULL, file=NULL)
text = format definition string | file = path to .txt file with definitions
```

```
fparse(text = '
VALUE age (numeric)
  [0, 18)    = "Child"
  [18, 65)   = "Adult"
  [65, HIGH] = "Senior"
  .missing   = "Age Unknown"
;')
fputn(c(5,18,65,NA), "age")
```

`"Child"` `"Adult"` `"Senior"` `"Age Unknown"`

RANGE SYNTAX REFERENCE

SYNTAX	MEANING	MATH
[a, b]	both inclusive	a ≤ x ≤ b
[a, b)	right exclusive	a ≤ x < b
(a, b]	left exclusive	a < x ≤ b
(a, b)	both exclusive	a < x < b
HIGH	+∞ upper bound	
LOW	−∞ lower bound	

BMI WITH DECIMALS + .MISSING

```
fparse(text = '
VALUE bmi (numeric)
  [0, 18.5)  = "Underweight"
  [18.5, 25) = "Normal"
  [25, 30)   = "Overweight"
  [30, HIGH] = "Obese"
  .missing   = "No data"
;')
```

BMI	RESULT
16.2	Underweight
25.0	Overweight
35.1	Obese
NA	No data

EXCLUSIVE / INCLUSIVE BOUNDS + .OTHER

```
fparse(text = '
VALUE score (numeric)
  (0, 50]   = "Low"
  (50, 100] = "High"
  .other    = "Out of range"
;')
```

SCORE	LABEL
0	Out of range
50	Low
51	High
101	Out of range

PARSE MULTIPLE FORMATS AT ONCE

```
fparse(text = '
VALUE race (character)
  "W"="White" "B"="Black"
  "A"="Asian"
  .missing = "Unknown"
;
INVALUE race_inv
  "White"=1 "Black"=2
  "Asian"=3
;')
```

Registers **both** in library:

race `VALUE` (char)

race_inv `INVALUE` (num)

RANGE_SPEC() — BUILD RANGE STRINGS

```
range_spec(low, high, label, inc_low=TRUE, inc_high=FALSE)
Programmatic range key builder for fnew() — returns "low,high,inc_low,inc_high"
```

```
range_spec(0, 18)

range_spec(18, Inf,
  inc_high = FALSE)
```

`"0,18,TRUE,FALSE"`

`"18,Inf,TRUE,FALSE"`

REVERSE FORMATTING (INVALUE)

FINPUTN() — LABELS → NUMERIC

```
finputn(x, invalue_name)
Applies named invalue, returns numeric vector
```

```
finputn(
  c("Male", "Female", "Unknown"),
  "sex_inv"
)
```

`1` `2` `NA`

FINPUTC() — LABELS → CHARACTER

```
finputc(x, invalue_name)
Applies named invalue, returns character vector
```

```
finputc(
  c("Active", "Pending"),
  "status_inv"
)
```

`"A"` `"P"`

ROUND-TRIP: VALUE ⇔ INVALUE

`"A"` → `fputc "status"` → `"Active"` → `finputc "status_inv"` → `"A"`

DATE, TIME & DATETIME

SAS DATE FORMATS (AUTO-RESOLVED)

```
fputn(Sys.Date(), "DATE9.")
fputn(Sys.Date(), "MMDDYY10.")
fputn(Sys.Date(), "YYMMDD10.")
fputn(Sys.Date(), "WORDDATE.")
fputn(Sys.Date(), "QTR.")
```

FORMAT	→ RESULT
DATE9.	18MAR2026
MMDDYY10.	03/18/2026
YYMMDD10.	2026-03-18
WORDDATE.	March 18, 2026
QTR.	1

TIME FORMATS (SECONDS SINCE MIDNIGHT)

SECS	TIME8.	TIME5.	HHMM.
0	0:00:00	0:00	00:00
3600	1:00:00	1:00	01:00
45000	12:30:00	12:30	12:30
86399	23:59:59	23:59	23:59

DATETIME FORMATS

```
fputn(Sys.time(),
  "DATETIME20.")
```

FORMAT	→ RESULT
DATETIME20.	18MAR2026:13:48:58
DATETIME13.	18MAR26:13:48
DTDATE.	18MAR2026
DTYYMMDD.	2026-03-18

CUSTOM DATE FORMAT + .MISSING

```
v <- fnew_date("DATE9.",
  name = "vfmt",
  .missing = "NOT RECORDED")

fput_df(patients,
  visit_date = v)
```

ID	VISIT_DATE	VISIT_FMT
1	2025-01-10	10JAN2025
2	2025-02-15	15FEB2025
3	<NA>	NOT RECORDED

PUTN WORKFLOW (SAS-STYLE DYNAMIC DISPATCH)

```
fnew(
  "1" = "date9.",
  "2" = "mmddyy10.",
  name = "wfmt",
  type = "numeric")

datefmt <- fputn(key, "wfmt")
date <- fputn(number, datefmt)
```

NUM	KEY	FMT	DATE
12103	1	date9.	03FEB2003
10899	2	mmddyy10.	11/07/1999

FORMAT LIBRARY

FPRINT() — INSPECT REGISTERED FORMATS

```
fprint(name=NULL)
No args = list all | name = show detail for one format
```

```
fprint()      # list all
fprint("sex")  # detail
```

age `VALUE` (num) 3

sex `VALUE` (char) 2

sex_inv `INVALUE` (num) 2

FORMAT_GET() FCLEAR()

```
format_get(name) — retrieve format object   fclear(name=NULL) — remove one or all
```

```
fmt <- format_get("sex")

fclear("sex")  # remove one
fclear()       # clear all
```

Retrieve format object
Remove single format
Clear entire library

FEXPORT() — EXPORT TO PARSEABLE TEXT

```
fexport(..., formats=NULL, file=NULL)
... or formats = format objects | file = write to file (else returns string)
```

```
cat(fexport(bmi = bmi_fmt))
```

```
VALUE bmi (numeric)
  [0, 18.5) = "Underweight"
  [18.5, 25) = "Normal"
  [25, 30) = "Overweight"
  [30, HIGH] = "Obese"
;
```

FIMPORT() — SAS CNTLOUT CSV

```
fimport(file, register=TRUE, overwrite=TRUE)
file = CNTLOUT CSV path | register = auto-add to library | overwrite = replace existing
```

```
x <- fimport("cntlout.csv")

m <- fimport(csv,
  register = FALSE)

fput(v, m[["GENDER"]])
```

AGEGRP `VALUE` (num)

BMICAT `VALUE` (num)

GENDER `VALUE` (char)