Java Class Name: Date		**Method Signature:** public boolean isValid()	
Test Case #	**Functional Requirement, or Test Objective**	**Test description and input data**	**Expected result/output**
1	The method returns false if the date provided has a year that starts before 1000	• Create an instance of date where the year given is a number less than 1000, but the month and day are valid • Test input: “01/23/999”	false
2	The method returns false if the date provided has a month greater than 12 or less than 1.	• Create an instance of the date where the year and day are valid but the month provided is either less than 1 or greater than 12 • Test input: “13/22/2025”	false
3	The method returns false if the date provided has a day greater than the maximum number of days in that month	• Create an instance of date where the year and month are valid, but the day provided is more than the maximum number of days in that month • Test input: “01/34/2024”	false
4	The method returns false if the date provided is February 29, yet the year is not a leap year.	• Create an instance of date where the year is divisible by 4 and 100, but not 400, the month is february (2), and the day is 29. • Test input: “02/29/2100”	false
5	The method returns true when the date provided’s month is between(inclusive) 1 and 12 and day is between 1 and the maximum number of days in that month (inclusive).	• Create an instance of date where the month, day, and year are all valid and it is not february 29th. • Test case: “12/31/2024”	true
6	The method returns true when the year is a leap year and the date is February 29.	• Create an instance of date where it is february 29th, and the year is divisible by 4, and divisible by either both 100 and 400, or not divisible by 100. • Test case: “02/29/2400”	true

Java Class Name: Vehicle		**Method Signature:** public int compareTo(Vehicle other)	
Test Case #	**Functional Requirement, or Test Objective**	**Test description and input data**	**Expected result/output**
1	The method returns 0 if the vehicle provided as an argument (vehicle two) has the same make and obtained date as the original vehicle (vehicle one).	• Create two instances of Vehicle where the make and date obtained both match. • Test input: ○ Vehicle one: ■ 1/15/2008 ■ Chevy ○ Vehicle two: ■ 1/15/2008 ■ Chevy	0
2	The method returns -1 if the vehicle provided as an argument (vehicle two) has the same make but the obtained date is later than the original vehicle (vehicle one).	• Create two instances of Vehicle with the same Make. However, the second vehicle will have a later obtained date. • Test input: ○ Vehicle one: ■ 1/15/2008 ■ Chevy ○ Vehicle two: ■ 1/16/2008 ■ Chevy	-1
3	The method returns 1 if the vehicle provided as an argument (vehicle two) has a make that comes earlier alphabetically than the original vehicle's (vehicle one) make.	• Create two instances of Vehicle. However, the second vehicle will have a make that is earlier alphabetically. • Test input: ○ Vehicle one: ■ 1/15/2008 ■ Ford ○ Vehicle two: ■ 1/16/2008 ■ Chevy	1