```
<%=a0%>=theArgs.a;
                                                                                                                                0: out
                                                                                                                               1: in
                                                                                                                           <\%=a0\%> = {};
                                                                                                                      <%=a0%>['a'] = <%=a1%>; 2: in
                                                                                                                0: out <%=a0%>['b'] = <%=a2%>;
                         if(<%=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                                                                  1: in 3. out0: in
                                                     0: out_
                                        <%=a0%> = isEqual;
                                            <%=a0%> = active;
                                                  0: out
                                                      Q: in 1: out/
                                                 <\%=a1\%> = <\%=a0\%>;
                                                 <\%=a2\%> = <\%=a0\%>;
                                                 <%=a3%> = <%=a0%>;
                                                    2: out 3: out
                                                                 2: in1: in
                                                                <\%=a0\%> = {};
                                                         <%=a0%>['cond'] = <%=a1%>;
                                                                                                           <%=a0%>=theInterface.theNumber;
                                                        <%=a0%>['source'] = <%=a2%>;
                                                                                                                        0: out
                                                                  0; out
                                                                                                                         1: in
                                                                                                    if(<%=a0%> === active) {<%=a2%> = <%=a1%>;}
                                                                                                               2: out
                                                                                                                         /0: in
                                                                                                                             1: out
                                                                                                                       <%=a1%> = <%=a0%>['a'];
                                                                                                                       <%=a2%> = <%=a0%>['b'];
                                                                                                                           0: in 2: out
                                                                                                                  15_
                                                0: in 2: in
                                                                                             3: out
                                                                                                                       if(<%=a0%> === active) {<%=a1%> = <%=a2%>;}
if(<%=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                                                                                                                        2: in___
                                                                                         <%=a0%>=null;
                                                                                      if(<%=a0%>===null){
                                                                                        < = a0 > = < = a1 >;
                                                                                                                                                              0: out
                                                                                 } else if (<%=a1%> !== null){
                                           throw ('error:multiple active assignments to the same signal <\%=a0\%>: '+<\%=a0\%> + ' and ' + <\%=a1\%>);
                                                                                                                                                             <\%=a0\%> = -8000;
                                                                                     }if(<%=a0%>===null ){
                                                                                        <\%=a0\%> = <\%=a2\%>;
                                                                                 } else if (<%=a2%> !== null){
                                          throw ('error:multiple active assignments to the same signal <%=a0%> : '+<%=a0%> + ' and ' + <%=a2%>);
                                                                                             0: out
                                                                                             16
                                                                                                                                                                            0: out
                                                                                theInterface.theResult=<%=a0%>;
                                                                                                                                                                          <\%=a0\%> = 1;
                             0: out
```

<%=a0%> = whenThenElse;