```
<%=a0%>=theInterface.theNumber;
                                                                                                   0: Number out
                                                                                                   2: Number in
                                                                                                   <\%=a0\%> = \{\};
                                                                                              <%=a0%>['a'] = <%=a1%>;
                                                                                             <\%=a0\%>['b'] = <\%=a2\%>;
                                                                            0: {a: Number, b: Number} out Number in
                                                       2: {a: Number, b: Number} in
if(<=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                                                                                                                          <%=a0%> = inactive; //Fake sender node
                                                                                                                                     0: Void out
                                                         1:{{a: Number, b: Number} -> Numbet}: Activation in
                                       3: Number out
                                0: {{a: Numbey, b: Number} -> Number} out
                                                             <%=a0%> = addition;
                                                               <%=a0%> = return1;
                                                       0: {Void -> Number} out
                                                                                <%=a0%> = active;
                                                                              Q: Activation out
                                                                                                       2: Activation out
                                                                                  0: Activation in
                                                                                        <\%=a1\%> = <\%=a0\%>;
                                                                                        <\%=a2\%> = <\%=a0\%>;
                                                                         3: Activation out <%=a3%> = <%=a0%>;
                                                                                         1: Activation out
                                                                                            1:{Void-> Number} in 3: Numberivation in
                                 2: Number in
                                                       0: Activation in
                                                                                                                                  ▶ 2⁄: Void in
                                                                          if(<=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                  if(<%=a0%> === active) {<%=a1%> = <%=a2%>;}
                                  1: Number out
                                  0: Number in/
```

theInterface.theResult=<%=a0%>;