node_907
$withbehaviour$
0: {theNumber: Number in, theOther: Number in, theResult: Number out}
1: ?
2: ?

0: {theNumber: Number in, theOther: Number in, theResult: Number out}
edge_910

1
edge_908
0

2
edge_909

0: {theNumber: Number out, theOther: Number out, theResult: Number in}

node_876
{theNumber:$theOther:$theResult:$}
0: {theNumber: Number out, theOther: Number out, theResult: Number in}
1: Number in
2: Number in
3: Number out

node_891
{theNumber:$theOther:$theResult:$}
0: ?
1: ?
2: ?
3: ?

1: Number in: theNumber
edge_877

2: Number in: theOther
edge_878

3: Number out: theResult
edge_879

1
edge_911

2
edge_912

3
edge_913

3

0

node_870
<%=a0%>=theInterface.theNumber;
0: Number out

node_872
<%=a0%>=theInterface.theOther;
0: Number out

node_874
theInterface.theResult=<%=a0%>;
0: Number in

0: Number out

0: Number out

0: Number in

node_902
applytoandget$
0: ?
1: {{a: Number, b: Number} -> Number} in
2: ?
3: ?

1: {{a: Number, b: Number} -> Number} in
edge_905

0: {{a: Number, b: Number} -> Number} out
edge_904

node_898
{a:$b:$}
0: ?
1: ?
2: ?

1

2

0

2

node_896
functionaddition
0: {{a: Number, b: Number} -> Number} out