```
<%=a0%>=theInterface.theNumber;
                                                                                 <%=a0%> = active;
                                       0: out
                                                                                       0: out
                                                                                        0: in
                                        0: in
                                                                                 <\%=a1\%> = <\%=a0\%>;
                                                                                <%=a2%> = <%=a0%>;
<%=a3%> = <%=a0%>;
4: out
          // We dont care about <%=a0%>, this is a fake receiver node
                                                                           1: out <%=a4%> = <%=a0%>; 2: out
                                                                                3: out
                                                            0: in
                                      if(<%=a0%> === active) {
                                                                                                                                                                                                if(<%=a0%> === active) {
                                                                             if(<%=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                              <%=a1%> = previousState['state 1951'];
                                                                                                                                                                                           nextState['state 1951'] = <%=a1%>;
                                                                                                            2: in
                                                                                                                             1: in
                                                                                                                                    3: out
                                                                                                                                                                                                          1: in
                                                1: out
                                                 2: in
                                                                3: out
                                                                                                                        0: out/
                                                                                                                                                                                                         0: out
                                                                                                                                                    \theta: in
if(<\$=a0\$> === active \&\& <\$=a1\$>!==null \&\& <\$=a1\$>!==undefined) {<\$=a3\$> = <\$=a1\$>(<\$=a2\$>);}
                                                                                                                  <%=a0%> = boolNot;
                                                                                                                                           theInterface.theResult=<%=a0%>;
                                                                                                                                                                                                       <%=a0%> = 1;
                                               1: in
                                              0: out
```

<%=a0%> = isActive;