```
if(<%=a0%> === active && <%=a1%>!==null && <%=a1%>!==undefined) {<%=a3%> = <%=a1%>(<%=a2%>);}
                                                                                                                                        0: [object Object]
                                                                                                     <%=a0%> = whenThenElse;
                                                                                                                                      <%=a0%> = active;
                                                                                                                                                                <%=a0%> = isEqual;
                                                                                                                            0: [object[Ohjpect] 0: [object Object]
                                                                                                                               0: [object Object]
                                                                                                                  apply$to$andget$
                                                                                                                                                2: [object Object]
    {a:$b:$}
                     {theNumber:$,theResult:$}
                                                                {theNumber:$theResult:$}
                                                                                                              <\%=a0\%> = -8000;
                                                                                                                                         {cond:\$source:\$}
                                                0: [object Object]
                                                                   1: theNumber theResult 0: [object Object]
                                                                                                          0: [object Object]
                                                                                                                                                               0; [object Object]
                                                                                                             2: [object Object]
1: [object Object]2
                                                                                                                  {theNumber:$,theResult:$}
          $=$
                                                                                                                                                        apply$to$andget$
                                                                                                                                                                              <%=a0%>=theArgs.a;
                                                                                                                                                                                                        <\%=a0\%> = 1;
                   <%=a0%>=theInterface.theNumber;
                                                              theInterface.theResult=<%=a0%>;
1: [object Object]
                                                                                                                                                                          0: [object Object] 0: [object Object]
                                                                                                                                                                                        1: [object Object]
                                                                                                                                                                                    {a:$,b:$} 2: [object Object]
                                                            1: [object Object]
                                        1: [object Object]
```