



[SFTP Delivered Data Documentation](#) > [Service Data](#) > OEM Service Schedules

OEM Service Schedules

DataOne's OEM Service Schedules data contains vehicle-referenced maintenance information, including descriptions of service to be performed, the condition upon which to perform service, special operating cases under which maintenance must be performed, and OEM-specific naming for maintenance patterns (for example, Premium Maintenance or Maintenance Schedule II). Service conditions include:

- Miles
- Months
- Operating hours
- Computer code
- Special events

Data Tables

The DataOne service schedules database includes several database tables, listed and described as follows:

DEF_MAINTENANCE

This table contains the definition of a service to be performed on the vehicle. Datapoints include a maintenance category name (Engine, Exhaust System, Coolant System, etc...), a maintenance name (Replace engine oil and oil filter, etc...), and an additional 'maintenance_notes' field to display any additional relevant information.

maintenance_name	text	
maintenance_notes	text	

DEF_MAINTENANCE_SCHEDULE

This table contains OEM labeling for specific maintenance patterns. Datapoints include schedule name and schedule description. Schedules are not used for all OEMs/services, and should be joined to the corresponding maintenance lookup table using an outer join, not an inner join.

Field	Type	Description
maintenance_schedule_id	int unsigned	
schedule_name	varchar(255)	
schedule_description	text	

DEF_MAINTENANCE_INTERVAL

This table defines the interval at which a service may be performed. The table is composed of all unique interval records, and shares a many-to-many relationship with the corresponding maintenance lookup table. Records in the maintenance lookup table are referenced to records in DEF_MAINTENANCE_INTERVAL by way of the corresponding maintenance interval lookup table. Datapoints in DEF_MAINTENANCE_INTERVAL include interval_type (the "At/Every" component of "At 3000 miles" vs. "Every 3000 miles"), a value, units for the value (months, miles, hours), and an initial offset value (for example, you may want to perform an oil change every 3000 miles, but start at 5000 miles).

value	float unsigned	
units	varchar(32)	
initial_value	float unsigned	

DEF_MAINTENANCE_OPERATING_PARAMETER

This table defines special operating conditions, for example "dusty driving conditions." Operating parameters often affect the interval at which a service is performed. Data in this table is referenced to the corresponding maintenance lookup table by way of the corresponding maintenance interval lookup table.

Field	Type	Description
maintenance_operating_parameter_id	int	
operating_parameter	text	
operating_parameter_notes	text	

DEF_MAINTENANCE_COMPUTER_CODE

This table defines special computer codes issued by the vehicle in order to indicate that service is needed. These computer codes are often displayed on the instrumental panel of the vehicle. Records in this table are referenced to the corresponding maintenance lookup table by way of the corresponding maintenance event computer code lookup table.

DEF_MAINTENANCE_EVENT

This table defines events that may cause service to be necessary. For example: submersion of vehicle in water. Records in this table are referenced to the corresponding maintenance lookup table by way of the corresponding maintenance event computer code lookup table.

Field	Type	Description
maintenance_event_id	int	
event	varchar(255)	

LKP_VIN_MAINTENANCE

This table provides a lookup between a DataOne Software vehicle_id and engine_id, and a unique service definition. It includes foreign keys maintenance_id and maintenance_schedule_id, which reference DEF_MAINTENANCE and DEF_MAINTENANCE_SCHEDULE, respectively. Each of these two tables shares a one-to-many relationship with LKP_VIN_MAINTENANCE. Note that some services may be transmission specific; these will be identified using the trans_notes field.

Field	Type	Description
vin_maintenance_id	int unsigned	
squish	varchar(16)	
trans_notes	varchar(255)	

maintenance_id	int unsigned	
----------------	--------------	--

LKP_VIN_MAINTENANCE_INTERVAL

This table is used to join records in LKP_VIN_MAINTENANCE with records in DEF_MAINTENANCE_INTERVAL and DEF_MAINTENANCE_OPERATING_PARAMETER. Note that some records in LKP_VIN_MAINTENANCE may be based upon computer code or event only, and thus will not have corresponding records in LKP_VIN_MAINTENANCE_INTERVAL. Therefore, this table should be joined using an outer join, not an inner join.

Field	Type	Description
vin_maintenance_interval_id	int unsigned	
vin_maintenance_id	int unsigned	
maintenance_interval_id	int unsigned	
maintenance_operating_parameter_id	int	

LKP_VIN_MAINTENANCE_EVENT_COMPUTER_CODE

This table is used to join records in LKP_VIN_MAINTENANCE with records in DEF_MAINTENANCE_COMPUTER_CODE and DEF_MAINTENANCE_EVENT. Note that some records in LKP_VIN_MAINTENANCE may be based upon a regular service interval only, and thus will not have corresponding records in LKP_VIN_MAINTENANCE_EVENT_COMPUTER_CODE. Therefore, this table should be joined using an outer join, not an inner join.

maintenance_event_id	int	
vin_maintenance_id	int	

LKP_YMM_MAINTENANCE

This table provides a lookup between a DataOne Software vehicle_id and engine_id, and a unique service definition. It includes foreign keys maintenance_id and maintenance_schedule_id, which reference DEF_MAINTENANCE and DEF_MAINTENANCE_SCHEDULE, respectively. Each of these two tables shares a one-to-many relationship with LKP_YMM_MAINTENANCE. Note that some services may be transmission specific; these will be identified using the trans_notes field.

Field	Type	Description
ymm_maintenance_id	int unsigned	
year	smallint	
make	varchar(24)	
model	varchar(32)	
eng_notes	varchar(128)	
trans_notes	varchar(255)	
trim_notes	mediumtext	
maintenance_schedule_id	int unsigned	
maintenance_id	int unsigned	

LKP_YMM_MAINTENANCE_INTERVAL

This table is used to join records in LKP_YMM_MAINTENANCE with records in DEF_MAINTENANCE_INTERVAL and DEF_MAINTENANCE_OPERATING_PARAMETER. Note that some records in LKP_YMM_MAINTENANCE may be based upon computer code or event only, and thus will not have corresponding records in LKP_YMM_MAINTENANCE_INTERVAL. Therefore, this table should be joined using an outer join, not an inner join.

Field	Type	Description
ymm_maintenance_interval_id	int unsigned	
ymm_maintenance_id	int unsigned	
maintenance_interval_id	int unsigned	
maintenance_operating_parameter_id	int	

LKP_YMM_MAINTENANCE_EVENT_COMPUTER_CODE

This table is used to join records in LKP_YMM_MAINTENANCE with records in DEF_MAINTENANCE_COMPUTER_CODE and DEF_MAINTENANCE_EVENT. Note that some records in LKP_YMM_MAINTENANCE may be based upon a regular service interval only, and thus will not have corresponding records in LKP_YMM_MAINTENANCE_EVENT_COMPUTER_CODE. Therefore, this table should be joined using an outer join, not an inner join.

Field	Type	Description
ymm_maintenance_event_computer_code_id	int	
maintenance_computer_code_id	int	



--	--	--