

**AC Adapter**

|                            |                     |
|----------------------------|---------------------|
| Input voltage              | 100–240 VAC         |
| Input current<br>(maximum) | 1.5 A               |
| Input frequency            | 50–60 Hz            |
| Output power               | 65 W                |
| Output current             | 3.34 A (continuous) |
| Rated output voltage       | 19.5 ± 1 VDC        |

*Dimensions:*

|                      |                     |
|----------------------|---------------------|
| Height               | 16 mm (0.63 inches) |
| Width                | 66 mm (2.6 inches)  |
| Length               | 127 mm (5 inches)   |
| Weight (with cables) | 0.25 kg (0.55 lbs)  |

**AC Adapter***Temperature range*

|           |                              |
|-----------|------------------------------|
| Operating | 0° to 35°C (32° to 95°F)     |
| Storage   | –30° to 65°C (–22° to 149°F) |

**Physical**

|        |                                                    |
|--------|----------------------------------------------------|
| Height | 16.4 mm to 25.8 mm<br>(0.64 inches to 1.01 inches) |
| Width  | 292 mm (11.49 inches)                              |
| Depth  | 214 mm (8.42 inches)                               |

*Weight (with 3-cell battery):*

|                           |                    |
|---------------------------|--------------------|
| Configurable to less than | 1.35 kg (2.98 lbs) |
|---------------------------|--------------------|