Forces and Work

Patrick Chen

Nov 4, 2024

Motions of Systems

- Internal forces is between objects in the system.
- External forces are form outside the system.

$$\begin{aligned} Ma_{cm} &= \sum_j F_{net,j} \\ &= \sum_j F^{ext}_{net,j} + \sum_j F^{int}_{net,j} \\ &= \sum_j F^{ext}_{net,j} + 0 \\ &= \sum_j F^{ext}_{net,j} \end{aligned}$$

Choosing a system depending on the problem can help solve the problem. When choosing a system, having friction on the boundary of the system will make analysis more difficult. Gravity will either be a change in potential energy or a force doing work on a system depending if it is in the system or not.

Work

Work is the change in the energy of a system due to external forces. Work is a signed scalar quantity measured in joules (J) in the SI system.

$$\begin{aligned} W &= \mathbf{F} \cdot \mathbf{d} = Fd\cos\theta \\ W &= \Delta E \end{aligned}$$

For non-constant forces, the work must be integrated

$$W = \int_{x_i}^{x_f} F \cdot \ dx$$

Force displacement is how far the point where the force is applied moves. In order for a force to do work, the point where the force is being applied must undergo a force displacement.

Momentum and Energy

$$\Delta p = J \qquad \Delta E = W$$
$$J = 0 \qquad \Delta E = 0$$
$$J = \sum f \Delta t \qquad W = \sum F \Delta x$$

Example 1

Suppose there is a object with a horizontal for applied on a frictionless surface from point x_i to x_f.

$$\begin{aligned}
W &= \Delta E \\
&= \Delta K + \Delta U + \Delta E_{th} \\
&= \Delta K + 0 + 0 \\
&= \Delta K \\
F &= m a_{cm} \\
&= m \frac{dv_{cm}}{dt} \\
&= m \frac{dv_{cm}}{dx_{cm}} \frac{dx_{cm}}{dt} \\
&= m v_{cm} \frac{dv_{cm}}{dx_{cm}} \\
F\ dx_{cm} &= m v_{cm} dv_{cm} \\
\int_{x_i}^{x_f} F\ dx_{cm} &= \int_{v_i}^{v_f} m v_{cm}\ dv_{cm} \\
&= \frac{1}{2} m v_{cm}^2 \Big|_{v_i}^{v_f} \\
&= \Delta K_{cm} \\
F \Delta x_{cm} &= \Delta K_{cm}
\end{aligned}$$

Example 2

Suppose there is a object with two horizontal forces in opposite directions on a frictionless surface.

$$\begin{aligned}
W &= \Delta K \\
F_{net} &= m a_{cm} \\
F_{net} &= F_1 - F_2 \\
W &= \int_{x_i}^{x_f} (F_1 - F_2)\ dx_{cm} \\
W_{net} &= \int_{x_i}^{x_f} F_1\ dx_{cm} - \int_{x_i}^{x_f} F_2\ dx_{cm}
\end{aligned}$$

Example 3

Suppose there is a object sliding with a friction force. F_k is a constant force. We can choose the system to be the object and the surface.

$$\begin{aligned}
\Delta E &= \Delta K + \Delta E_{th} \\
\Delta E &= 0 \\
\Delta E_{th} &= -\Delta K \\
&= -(K_f - K_i) \\
&= K_i \\
\Delta K_{cm} &= -\int_{x_{cm,i}}^{x_{cm,f}} f_x \; dx_{cm} \\
&= -f_k \Delta x_c m
\end{aligned}$$