


000012e0	29	00	00	00	09	00	00	00	02	00	00	00	bc	84	00	00).....
000012f0	ba	04	00	00	98	00	00	00	03	00	00	00	06	00	00	00
00001300	04	00	00	00	08	00	00	00	2d	00	00	00	01	00	00	00
00001310	00	00	00	00	00	00	00	00	54	00	00	00	f8	00	00	00T.....T.....
00001320	00	00	00	00	00	00	00	00	04	00	00	00	00	00	00	00
00001330	32	00	00	00	01	01	00	00	06	00	00	00	50	86	00	002.....F.....
00001340	50	06	00	00	e8	02	00	00	00	00	00	00	00	00	00	00P.....
00001350	10	00	00	00	00	00	00	00	38	00	00	01	01	00	00	002.....8.....
00001360	00	00	00	00	38	89	00	00	38	09	00	00	e0	02	00	002.....8.....
00001370	00	00	00	00	00	00	00	00	04	00	00	00	01	00	00	00B.....
00001380	00	00	00	00	10	00	00	00	00	00	00	00	00	00	00	00G.....
00001390	00	10	00	00	08	00	00	00	00	00	00	00	00	00	00	00+.....0.....
000013a0	01	00	00	00	00	00	00	00	4f	00	00	00	0e	00	00	00
000013b0	03	00	00	00	08	90	00	00	08	10	00	00	08	00	00	00
000013c0	00	00	00	00	00	00	00	00	01	00	00	00	00	00	00	00
000013d0	5b	00	00	00	0f	00	00	00	03	00	00	00	10	90	00	00[.....
000013e0	10	10	00	00	08	00	00	00	00	00	00	00	00	00	00	00
000013f0	01	00	00	00	00	00	00	00	67	00	00	00	01	00	00	00g.....
00001400	00	00	00	00	00	13	00	00	00	00	00	00	00	00	00	00
00001410	00	00	00	00	00	00	00	00	01	00	00	00	00	00	00	00
00001420	ee	00	00	00	06	00	00	00	03	00	00	00	20	90	00	00n.....
00001430	20	10	00	00	c8	00	00	00	04	00	00	00	00	00	00	00
00001440	04	00	00	00	08	00	00	00	77	00	00	00	01	00	00	00-.....M.....X.....
00001450	03	00	00	00	e8	90	00	00	e8	10	00	00	58	00	00	00
00001460	00	00	00	00	00	00	00	00	04	00	00	00	04	00	00	00



Who am i?

whoami

```
#!/usr/bin/perl -w
my $self = {
    realname => 'Axelle Apvrille',
    nickname => 'Crypto Girl',
    twitter => '@cryptax',
    job => 'Malware Analyst and Researcher',
    # reverse engineering of incoming mobile malware
    # research and tools in related areas
    title => 'Senior', # white hair
    company => 'Fortinet, FortiGuard Labs',
    before => 'Security software eng.: protocols, crypto...',
    languages => 'French, English, Hexadecimal :)'
};
```

Quick background

Android mobile phone




Quick background

Android mobile phone



Applications: APK




Quick background

Android mobile phone



Applications: APK



Inside the APK: DEX

Dalvik Executable with Dalvik bytecode


dex.035.V..d..\$g

Quick background

Android mobile phone



Applications: APK



Inside the APK: DEX

Dalvik Executable with Dalvik bytecode

`dex.035.V..d..$g`

Inside the DEX

Classes, methods, fields, strings

`'bytes', '** I am Mr Hyde **', '<init>'...`


Part 1: Hiding a method

Application source code

```
public void thisishidden(boolean ismrhyde) {  
    Log.i("HideAndSeek",  
        "In thisishidden(): set mrhyde=" +  
        ismrhyde);  
    try {  
        File dir;  
        if (context !=null) {  
            ...  
        }  
    }  
}
```

Method thisishidden(): hidden to dissassemblers

- ▶ Baksmali does not see it
- ▶ dex2jar does not see it
- ▶ IDA Pro does not see it
- ▶ Androguard does not see it



Demo

<https://github.com/cryptax/dextools>



Demo

<https://github.com/cryptax/dextools>

Format of a DEX file




Header

Arrays

Data

Format of a DEX file



Inside the list of class definitions

encoded_method

- ▶ **access_flags:**
ACC_PUBLIC,
ACC_PRIVATE,
ACC_STATIC...
- ▶ **code_off:** offset to
code from
beginning of DEX
file
- ▶ **method_idx_diff:**
increment to
method indexes

Header

class_def_item


Arrays

Data

Inside the list of class definitions

encoded_method

- ▶ **access_flags:**
ACC_PUBLIC,
ACC_PRIVATE,
ACC_STATIC...
- ▶ **code_off:** offset to
code from
beginning of DEX
file
- ▶ **method_idx_diff:**
increment to
method indexes



Inside the list of class definitions

encoded_method

- ▶ **access_flags:**
ACC_PUBLIC,
ACC_PRIVATE,
ACC_STATIC...
- ▶ **code_off:** offset to
code from
beginning of DEX
file
- ▶ **method_idx_diff:**
increment to
method indexes

Offset to class_data_item

Header

class_def_item

Type Ids

Arrays

List of fields

Direct methods:

encoded_method

class_data_item

Virtual methods:

encoded_method




Trick

Modify the chaining of methods and skip the hidden method
The info for the hidden method is still there, but won't be read


Implementation

- ▶ **method_idx_diff:**
 - ▶ modify for hidden method
 - ▶ + modify for the 'other' method
- ▶ **code_off:** refer the other method
- ▶ **access_flags:** nothing to do
- ▶ **direct_methods_size** (or **virtual_methods_size**): nothing to do


Visual representation of chaining




Visual representation of chaining




Visual representation of chaining



Visual representation of chaining



Visual representation of chaining





Some more tricks

- ▶ **Access flags:** you *may* modify but must choose a flag within *direct* methods or *virtual* methods
- ▶ **Single method?** Set *direct_methods_size* (or *virtual_methods_size*) and nullify *encoded_method*

3980h:	81 80 04 80 23 05 01 06 00 10 1A 01 0A 01 0A 02	.€.€#.....
3990h:	1A 01 09 13 02 1C 88 80 04 98 23 01 81 80 04 A4^€.~#..€.x
39A0h:	3C 01 00 00 00 01 00 04 3E 01 09 C8 3E 01 09 B8	<..À<...>..È>..
39B0h:	31 00 00 00 00 00 00 00 00 00 00 00 00 00 00	?.....
39C0h:	01 00 00 00 00 00 00 00 01 00 00 00 D5 01 00 00Ö...



Build a valid DEX

- ▶ Compute the SHA-1 of the new DEX
- ▶ Write to header
- ▶ Compute the checksum of the new DEX
- ▶ Write to header
- ▶ <https://github.com/cryptax/dextools>


Re-build APK

- ▶ Unzip original APK: retrieve manifest, resources...
- ▶ Zip new APK with new DEX + same manifest and resources
- ▶ Sign package (jarsigner)

Part 2: calling the hidden method

calling thisishidden()

- ▶ The method is hidden to disassemblers
- ▶ ... but it can be run!



The strange case of Dr Jekyll and Mr Hyde – R. Stevenson

- ▶ Split personalities: Dr Jekyll or Mr Hyde
- ▶ Only one way to change into MrHyde: call thisishidden()
- ▶ Current personality displayed in main activity



DEMO :)



Load the current DEX file

`openNonAsset()` not directly accessible → use reflection

```
// get AssetManager class via reflection
Class localClass = Class.forName("...AssetManager");
Class[] arrayOfClass = new Class[1];
arrayOfClass[0] = String.class;
// get openNonAsset method
Method localMethod = localClass.getMethod("openNonAsset", ...
AssetManager localAssetManager = this.context.getAssets();
Object[] arrayOfObject = new Object[1];
arrayOfObject[0] = paramString;
// invoke method
InputStream localInputStream = (InputStream)localMethod.invoke(...);
```



Patch the DEX

Undo what we did - re-chain the hidden method, re-hash and checksum the DEX

```
int patch_index = 0x2c99;  
dex[patch_index++] = 1; // method_idx  
dex[patch_index++] = 1; // access_flag  
dex[patch_index++] = (byte)0xcc; // code_offset  
dex[patch_index++] = (byte)0x28;  
dex[patch_index++] = 1;
```



Open the modified DEX

- ▶ use reflection to call `openDexFile()`
`native private static int
openDexFile(byte[] fileContents);`
- ▶ returns a cookie = pointer to internal struct for DEX
- ▶ load modified class using `defineClass()`

```
Class patchedHyde = null;  
Log.i("HideAndSeek", "retrieving patched MrHyde class");  
if (defineClassMethod != null) {  
    patchedHyde = (Class) defineClassMethod.invoke(  
        dexFileClass, params);  
}
```





Invoke the hidden method

- ▶ Search for the hidden method (`getDeclaredMethods()`)
- ▶ Instantiate an object
- ▶ Call `thisishidden()`


```
Object obj = patchedHyde.getDeclaredConstructor(Context.class)
    .newInstance(context);
Log.i("HideAndSeek", "after new Instance");
arg[0] = Boolean.valueOf(true);
Log.i("HideAndSeek", "invoking thisishidden()..");
thisishiddenMethod.invoke(obj, arg);
```

It's two different classes




It's two different classes


Does not work!



It's two different classes



It's two different classes





Dangers

It can be used to hide some malicious feature

Detection

The strings are not hidden

The bytecode is there

Solutions

- ▶ Use my patch/unpatch tool: `hidex.pl`
- ▶ Disassemble bytecode at a given location: `androdis.py`
- ▶ Fix Android: verify consistency of `encoded_method`
- ▶ Google notified in June 2013

Thank You !

Where's the source code?

<https://github.com/cryptax/dextools>

FortiGuard Labs

Follow us on twitter: **@FortiGuardLabs**

or on our blog <http://blog.fortinet.com>

Me

twitter: @cryptax

e-mail: aapvrille at fortinet dot com



Are those PowerPoint slides? No way! It's L^AT_EX + TikZ + Beamer + [Lobster](#)