



Cryptnox CLI Manual

Release 1.0.5

June 20, 2026

Contents

1	Cryptnox CLI Overview	1
1.1	Supported Hardware	1
1.2	Installation	1
1.3	Quick Usage Examples	1
1.4	License	2
2	Command Line Interface	3
2.1	Installation	3
2.2	Basic Usage	3
2.3	Global Options	3
2.4	Commands Overview	3
2.5	Interactive Mode	10
2.6	BIP39 Passphrase Support	11
2.7	Exit Codes	12
2.8	Error Handling	12
2.9	Examples	12
2.10	See Also	13
3	API Reference	14
3.1	cryptnox_cli package (Cryptnox CLI)	14
4	License	53

1 Cryptnox CLI Overview

cryptnox-cli is a command-line interface for managing **Cryptnox Smart cards**, enabling secure seed initialization and cryptographic signing for **Bitcoin** and **Ethereum**.

1.1 Supported Hardware

- **Cryptnox Smart cards**
- **Standard PC/SC Smart card Readers:** either USB NFC reader or a USB smart card reader

Get your card and readers here: shop.cryptnox.com

1.2 Installation

Note

This is only a minimal setup. Additional packages may be required depending on your operating system.

1.2.1 From PyPI

```
pip install cryptnox-cli
```

1.2.2 From source

```
git clone https://github.com/cryptnox/cryptnox-cli.git
cd cryptnox-cli
pip install .
```

This installs the package and makes the cryptnox command available (if your Python installation is in your system PATH).

1.3 Quick Usage Examples

Note

The examples below are only a subset of available commands. The complete list of commands and detailed usage instructions is described in the [Command Line Interface](#) section.

1.3.1 1. Dual initialization

1. Factory reset each card:

`cryptnox reset` → enter PUK → verify reset.

2. Initialize each card:

`cryptnox init` → (optional) set name/email → set **PIN** (4–9 digits) → set or generate **PUK** → verify init.

3. Run dual seed procedure:

`cryptnox seed dual` — follow prompts: insert Card A (enter PIN), swap to Card B (enter PIN), swap back as requested.

1.3.2 2. Sign and send a Bitcoin transaction

1. Create or obtain a raw unsigned transaction externally.
2. Run the signing & send command:

`cryptnox btc send <recipient_address> <amount> [-f <fees>]`

1.3.3 3. Change PIN code

1. Run command: `cryptnox change_pin`
2. Enter current PIN → enter new PIN → verify change.
3. Check with `cryptnox info` using new PIN (BTC & ETH accounts displayed).

1.3.4 4. Get extended public key (xpub)

1. Run command: `cryptnox get_xpub`
2. Enter **PIN** → enter **PUK**
3. The card returns the **xpub**

1.4 License

`cryptnox-cli` is dual-licensed:

- **LGPL-3.0** for open-source projects and proprietary projects that comply with LGPL requirements
- **Commercial license** for projects that require a proprietary license without LGPL obligations (see `COMMERCIAL.md` for details)

For commercial inquiries, contact: contact@cryptnox.com

2 Command Line Interface

The `cryptnox` command provides a comprehensive CLI for managing Cryptnox cards and performing cryptocurrency operations.

2.1 Installation

After installing the `cryptnox-cli` package, the `cryptnox` command becomes available in your system:

```
pip install cryptnox-cli
```

2.2 Basic Usage

```
cryptnox [OPTIONS] COMMAND [ARGS]...
```

2.3 Global Options

-v, --version

Show the version and exit.

--verbose

Turn on logging for detailed output.

-s, --serial SERIAL

Serial number of the card to be used for the command.

--port PORT

Define port to enable remote feature.

2.4 Commands Overview

2.4.1 Card Management Commands

list

List all connected Cryptnox cards.

```
cryptnox list
```

init

Initialize a Cryptnox card with owner information and PIN/PUK codes.

```
cryptnox init [OPTIONS]
```

Options:

- `-e, --easy_mode`: Initialize card in easy mode (sets PIN and PUK to all zeros)

reset

Reset the card to factory defaults.

```
cryptnox reset
```

Warning: This will erase all data on the card.

info

Display default accounts information for the card.

```
cryptnox info
```

Shows:

- Card serial number and type
- Ethereum and Bitcoin addresses
- Public keys
- Derivation information

cert

Retrieve and display the manufacturer certificate from the card in a human-readable format.

```
cryptnox cert
```

Features:

- Retrieves the full manufacturer certificate from the card
- Displays certificate details (Issuer, Subject, Validity, Public Key, Signature)
- Human-readable format similar to `openssl x509 -text`

2.4.2 Seed Management Commands

seed chip

Generate new root key directly in the card's secure chip.

```
cryptnox seed chip
```

Note: The seed never leaves the card and cannot be backed up.

seed dual

Generate the same seed on two cards for redundancy.

```
cryptnox seed dual
```

Requirements: Two initialized Cryptnox cards

Process:

1. Generate seed on first card
2. Swap cards
3. Load same seed on second card
4. Results in two cards with identical keys

seed recover

Recover a wallet from an existing BIP39 mnemonic phrase (12 or 24 words).

```
cryptnox seed recover
```

Input Required:

- Existing BIP39 mnemonic (12 or 24 words)
- Optional: BIP39 passphrase (13th/25th word)

Use Cases:

- Restoring existing wallet
- Migrating wallet from another device
- Recovering from backup mnemonic

Important: If the original wallet used a BIP39 passphrase, you **must** provide the same passphrase during recovery.

seed upload

Generate new random seed, upload to card, and display BIP39 mnemonic for backup.

```
cryptnox seed upload
```

Features:

- Generates new 32-byte random seed using card's hardware RNG
- Converts to BIP39 mnemonic (12 or 24 words)
- Optional: Add BIP39 passphrase (13th/25th word) for extra security
- Displays mnemonic for manual backup

Output: The generated mnemonic phrase (save it securely!)

Important: If you use a BIP39 passphrase, you **must** remember it. It cannot be recovered.

2.4.3 Security Commands

change_pin

Change the PIN code of the card.

```
cryptnox change_pin
```

Requirements: Current PIN code

change_puk

Change the PUK (PIN Unblocking Key) code of the card.

```
cryptnox change_puk
```

Requirements: Current PUK code

unlock_pin

Unlock a card with blocked PIN using the PUK code and set a new PIN.

```
cryptnox unlock_pin
```

Requirements: PUK code

Note: PIN becomes blocked after multiple failed attempts.

2.4.4 Card Configuration

card_conf

Show or modify card configuration settings.

```
cryptnox card_conf [KEY] [VALUE]
```

Available Settings:

- pinless: Enable/disable PIN-less path
- pin: Enable/disable PIN authentication

Values: yes or no

Examples:

```
# Show current configuration
cryptnox card_conf

# Enable PIN-less path
cryptnox card_conf pinless yes

# Disable PIN-less path
cryptnox card_conf pinless no
```

2.4.5 Bitcoin Commands

btc send

Send Bitcoin to an address.

```
cryptnox btc send ADDRESS AMOUNT [OPTIONS]
```

Arguments:

- ADDRESS: Bitcoin address (P2PKH, P2SH, or Bech32)
- AMOUNT: Amount in BTC

Options:

- `-n, --network {mainnet,testnet}`: Network to use
- `-f, --fees SATOSHIS`: Transaction fees in satoshis per byte

Example:

```
cryptnox btc send 1A1zP1eP5QGefi2DMPTfTL5SLmv7DivfNa 0.001 -n mainnet -f 10
```

btc config

View or modify Bitcoin configuration.

```
cryptnox btc config [KEY] [VALUE]
```

Settings:

- network: mainnet or testnet
- derivation: Key derivation method

2.4.6 Ethereum Commands

eth send

Send Ether (ETH) to an address.

```
cryptnox eth send ADDRESS AMOUNT [OPTIONS]
```

Arguments:

- ADDRESS: Ethereum address (0x...)
- AMOUNT: Amount in ETH

Options:

- `-n, --network {mainnet,sepolia,goerli}`: Network to use
- `--price GWEI`: Gas price in Gwei
- `--limit GAS`: Gas limit

Example:

```
cryptnox eth send 0x742d35Cc6634C0532925a3b844Bc9e7595f0bEb 0.1 -n mainnet --  
↪price 20
```

eth config

View or modify Ethereum configuration.

```
cryptnox eth config [KEY] [VALUE]
```

Settings:

- network: mainnet, sepolia, or other networks
- derivation: Key derivation method

- `api_key`: Etherscan/Infura API key
- `endpoint`: RPC endpoint

2.4.7 ERC Token Commands

eth erc20 init

Initialize ERC-20 token contract for transactions.

```
cryptnox eth erc20 init CONTRACT_ADDRESS [OPTIONS]
```

eth erc20 info

Display information about configured ERC-20 tokens.

```
cryptnox eth erc20 info
```

eth erc20 send

Send ERC-20 tokens.

```
cryptnox eth erc20 send TOKEN_ADDRESS RECIPIENT_ADDRESS AMOUNT [OPTIONS]
```

transfer

Transfer ERC-20 or ERC-721 tokens.

```
cryptnox transfer ADDRESS AMOUNT [OPTIONS]
```

Options:

- `--price GWEI`: Gas price
- `--limit GAS`: Gas limit

2.4.8 Configuration Commands

config

List or modify blockchain configurations.

```
cryptnox config [SECTION] [KEY] [VALUE]
```

Examples:

```
# Show all configuration
cryptnox config

# Show Ethereum configuration
cryptnox config eth

# Set Ethereum network
cryptnox config eth network mainnet
```

```
# Set Bitcoin derivation
cryptnox config btc derivation DERIVE
```

2.4.9 History and Information

history

List performed signatures and transactions.

```
cryptnox history [PAGE]
```

Arguments:

- PAGE: Page number to display (default: 1)

Note: Shows up to 148 entries, 25 per page.

2.4.10 Advanced Commands

get_xpub

Get extended public key (xpub) for hierarchical deterministic wallets.

```
cryptnox get_xpub [OPTIONS]
```

Options:

- Derivation path
- Key type

get_clearpubkey

Get clear (uncompressed) public key from the card.

```
cryptnox get_clearpubkey [OPTIONS]
```

decrypt

Decrypt data using the card's private key.

```
cryptnox decrypt [OPTIONS]
```

2.4.11 User Key Management

user_key list

List all configured user keys for authentication.

```
cryptnox user_key list
```

user_key add

Add a new user key for authentication (PIV card, Windows Hello).

```
cryptnox user_key add TYPE [DESCRIPTION]
```

Available Types:

- piv: PIV-compatible smart card
- hello: Windows Hello (biometric)

Example:

```
cryptnox user_key add piv "My PIV Key"
```

user_key delete

Delete a user key.

```
cryptnox user_key delete TYPE
```

2.4.12 Server Mode

server

Start a server or establish connection to a remote server.

```
cryptnox server [OPTIONS]
```

Options:

- --port PORT: Server port (default: 5050)
- --host HOST: Server host (default: 0.0.0.0)

Use Case: Remote card access over network

2.5 Interactive Mode

Launch interactive CLI mode:

```
cryptnox
```

In interactive mode, you can:

- Execute commands without repeating cryptnox
- Use use command to switch between multiple cards
- Use exit to quit

Example Session:

```
$ cryptnox
Cryptnox CLI 1.0.5

> list
```

```
[Shows available cards]

> info
[Shows card information]

> exit
```

2.6 BIP39 Passphrase Support

The seed recover and seed upload commands support BIP39 passphrases (also known as the 13th/25th word).

2.6.1 What is a BIP39 Passphrase?

A BIP39 passphrase is an optional additional word that enhances security:

- Acts as a “second factor” for your seed
- Creates a completely different wallet from the same mnemonic
- Must be remembered separately (not stored with the mnemonic)
- Cannot be recovered if forgotten

2.6.2 Using BIP39 Passphrase

During seed upload (new wallet):

```
cryptnox seed upload
```

The command will prompt:

```
Do you want to use a BIP39 passphrase? [y/N]
```

If you choose yes:

- Enter your desired passphrase
- Confirm the passphrase
- **Remember it!** You'll need it for recovery

During seed recover (existing wallet):

```
cryptnox seed recover
```

If your wallet was created with a passphrase, you **must** provide the same passphrase when recovering.

Important Notes:

- **!** If you forget your passphrase, your funds are **permanently lost**
- ✓ Same mnemonic + different passphrase = completely different wallet
- ✓ Passphrase can be any UTF-8 string (including spaces and special characters)

2.7 Exit Codes

The CLI returns the following exit codes:

- 0: Success
- -1: Error occurred
- -2: Card error or card not found

2.8 Error Handling

When errors occur:

- Detailed error messages are displayed
- Errors are logged to: ~/.local/share/cryptnox-cli/error.log (Linux/macOS) or %LOCALAPPDATA%\cryptnox\cryptnox-cli\error.log (Windows)
- You can report errors to help improve the application

2.9 Examples

Initialize a new card:

```
cryptnox init
```

Generate and upload a seed:

```
cryptnox seed upload
```

Recover from existing mnemonic:

```
cryptnox seed recover
```

Send Bitcoin:

```
cryptnox btc send 1A1zP1eP5QGefi2DMPTfTL5SLmv7DivfNa 0.001 -n testnet
```

Send Ethereum:

```
cryptnox eth send 0x742d35Cc6634C0532925a3b844Bc9e7595f0bEb 0.1 -n mainnet
```

View card info:

```
cryptnox info
```

Change PIN:

```
cryptnox change_pin
```

2.10 See Also

- [Cryptnox CLI Overview](#) - Overview of Cryptnox CLI
- `cryptnox_cli.command.seed` - Seed command implementation details
- [cryptnox_cli.command package](#) - All command implementations
- [API Reference](#) - Complete API Reference

3 API Reference

3.1 cryptnox_cli package (Cryptnox CLI)

3.1.1 Subpackages

cryptnox_cli.command package

Subpackages

cryptnox_cli.command.card package

Submodules

cryptnox_cli.command.card.info module

cryptnox_cli.command.card.initialize module

Module contents

The `cryptnox_cli.command.card` package provides card management functionality and exports:

class `cryptnox_cli.command.card.Info`

Command class for displaying card information. See `cryptnox_cli.command.card.info.Info` for details.

class `cryptnox_cli.command.card.Initialize`

Command class for initializing cards. See `cryptnox_cli.command.card.initialize.Initialize` for details.

cryptnox_cli.command.erc_token package

Submodules

cryptnox_cli.command.erc_token.contract module

cryptnox_cli.command.erc_token.info module

cryptnox_cli.command.erc_token.initialize module

Module contents

The `cryptnox_cli.command.erc_token` package provides ERC token management and exports:

class `cryptnox_cli.command.erc_token.Info`

Command class for displaying ERC token information. See `cryptnox_cli.command.erc_token.info.Info` for details.

class `cryptnox_cli.command.erc_token.Initialize`

Command class for initializing ERC tokens. See `cryptnox_cli.command.erc_token.initialize` for details.

`cryptnox_cli.command.helper` package

Submodules

`cryptnox_cli.command.helper.cards` module

`cryptnox_cli.command.helper.config` module

`cryptnox_cli.command.helper.helper_methods` module

`cryptnox_cli.command.helper.notification` module

`cryptnox_cli.command.helper.security` module

`cryptnox_cli.command.helper.ui` module

Module contents

The `cryptnox_cli.command.helper` package provides utility functions and helper modules for command implementations. This package contains shared functionality used across multiple commands, including user interface components, security helpers, and configuration management.

`cryptnox_cli.command.options` package

Submodules

`cryptnox_cli.command.options.common` module

`cryptnox_cli.command.options.eth` module

`cryptnox_cli.command.options.options` module

Module contents

The `cryptnox_cli.command.options` package provides command-line argument parsing and exports:

`cryptnox_cli.command.options.add(subparsers, command_class)`

Add command-line options for a command class. See `cryptnox_cli.command.options.options.add()` for details.

`cryptnox_cli.command.user_keys` package

Subpackages

`cryptnox_cli.command.user_keys.hello` package

Submodules

`cryptnox_cli.command.user_keys.hello.exceptions` module

cryptnox_cli.command.user_keys.hello.hello module

cryptnox_cli.command.user_keys.hello.windows_hello module

Module contents

cryptnox_cli.command.user_keys.piv package

Submodules

cryptnox_cli.command.user_keys.piv.piv module

cryptnox_cli.command.user_keys.piv.piv_card module

Module contents

Submodules

cryptnox_cli.command.user_keys.authentication module

cryptnox_cli.command.user_keys.user_key_base module

Module containing base class for user key.

exception cryptnox_cli.command.user_keys.user_key_base.**UserKeyException**

Bases: Exception

Base exception for all exceptions for UserKey

exception cryptnox_cli.command.user_keys.user_key_base.**ExitException**

Bases: [UserKeyException](#)

The user has exited the request

exception cryptnox_cli.command.user_keys.user_key_base.**NotFoundException**

Bases: [UserKeyException](#)

The user key hasn't been found

exception cryptnox_cli.command.user_keys.user_key_base.**NotSupportedException**

Bases: [UserKeyException](#)

The user key is not supported

exception cryptnox_cli.command.user_keys.user_key_base.**ProcessingException**

Bases: [UserKeyException](#)

There was an issue in processing the user key

class cryptnox_cli.command.user_keys.user_key_base.**UserKey**(*target: str = ''*)

Bases: object

Base class on top of which other user key classes should be implemented

priority: int = 0

__init__(*target: str = ''*)

abstractmethod delete() → None

Delete the key from the user key provider

abstract property description: str

Description of the user key service :rtype: str

Type

return

abstract property name: str

Name of the user key service :rtype: str

Type

return

abstract property public_key: bytes

Public key of the user key service :rtype: bytes

Type

return

abstractmethod sign(*message: bytes*) → bytes

Get signature of message from user key service

Parameters

message (bytes) – Message to sign

Returns

Signature of the given message

Return type

bytes

abstract property slot_index: cryptnox_sdk_py.SlotIndex

Compatible slot index on the card :rtype: cryptnox_sdk_py.SlotIndex

Type

return

property custom_bit: int

Custom bit to use for checking if method is enabled, -1 for not used :rtype: int

Type

return

added(*card*)

classmethod enabled(*card: cryptnox_sdk_py.Card*) → bool

Module contents

The `cryptnox_cli.command.user_keys` package provides authentication functionality and exports:

`cryptnox_cli.command.user_keys.add(data)`

Add a new authentication method. See `cryptnox_cli.command.user_keys.authentication.add()` for details.

`cryptnox_cli.command.user_keys.authenticate(data)`

Authenticate using a configured method. See `cryptnox_cli.command.user_keys.authentication.authenticate()` for details.

`cryptnox_cli.command.user_keys.delete(data)`

Delete an authentication method. See `cryptnox_cli.command.user_keys.authentication.delete()` for details.

`cryptnox_cli.command.user_keys.get(data)`

Get information about authentication methods. See `cryptnox_cli.command.user_keys.authentication.get()` for details.

Submodules

`cryptnox_cli.command.btc` module

`cryptnox_cli.command.card_configuration` module

`cryptnox_cli.command.cards` module

`cryptnox_cli.command.change_pin` module

`cryptnox_cli.command.change_puk` module

`cryptnox_cli.command.command` module

`cryptnox_cli.command.config` module

`cryptnox_cli.command.decrypt` module

`cryptnox_cli.command.eth` module

`cryptnox_cli.command.factory` module

`cryptnox_cli.command.get_clearpubkey` module

`cryptnox_cli.command.get_xpub` module

`cryptnox_cli.command.history` module

`cryptnox_cli.command.info` module

`cryptnox_cli.command.initialize` module

`cryptnox_cli.command.manufacturer_certificate` module

`cryptnox_cli.command.reset` module

`cryptnox_cli.command.seed` module

`cryptnox_cli.command.server` module

`cryptnox_cli.command.transfer` module

`cryptnox_cli.command.unknown` module

cryptnox_cli.command.unlock_pin module

cryptnox_cli.command.user_key module

Module contents

Module to work with commands given by the user in a command line

The `cryptnox_cli.command` package provides command-line interface commands for interacting with Cryptnox cards. This package contains all command implementations that can be executed from the CLI.

cryptnox_cli.lib package

Subpackages

cryptnox_cli.lib.cryptos package

Subpackages

cryptnox_cli.lib.cryptos.coins package

Submodules

cryptnox_cli.lib.cryptos.coins.base module

Base classes and shared logic for UTXO-based coin implementations.

```
class cryptnox_cli.lib.cryptos.coins.base.BaseCoin(testnet=False, **kwargs)
    Bases: object

    Base implementation of crypto coin class All child coins must follow same pattern.

    coin_symbol = None

    display_name = None

    enabled = True

    segwit_supported = None

    magicbyte = None

    script_magicbyte = None

    segwit_hrp = None

    client_kwargs = {'host': None, 'loop': None, 'max_servers': 5, 'port': 50001,
                     'server_file': 'bitcoin.json', 'servers': (), 'timeout': 15}

    testnet_overrides = {}

    hashcode = 1

    hd_path = 0

    wif_prefix = 128
```

```
wif_script_types = {'p2pkh': 0, 'p2sh': 5, 'p2wpkh': 1, 'p2wpkh-p2sh': 2,
                    'p2wsh': 6, 'p2wsh-p2sh': 7}
```

```
xprv_headers = {'p2pkh': 76066276, 'p2wpkh': 78791436, 'p2wpkh-p2sh':
77428856, 'p2wsh': 44726937, 'p2wsh-p2sh': 43364357}
```

```
xpub_headers = {'p2pkh': 76067358, 'p2wpkh': 78792518, 'p2wpkh-p2sh':
77429938, 'p2wsh': 44728019, 'p2wsh-p2sh': 43365439}
```

```
electrum_xprv_headers = {'p2pkh': 76066276, 'p2wpkh': 78791436,
                          'p2wpkh-p2sh': 77428856, 'p2wsh': 44726937, 'p2wsh-p2sh': 43364357}
```

```
electrum_xpub_headers = {'p2pkh': 76067358, 'p2wpkh': 78792518,
                          'p2wpkh-p2sh': 77429938, 'p2wsh': 44728019, 'p2wsh-p2sh': 43365439}
```

```
__init__(testnet=False, **kwargs)
```

```
is_testnet = False
```

```
address_prefixes = ()
```

```
secondary_hashcode = None
```

```
property rpc_client
```

```
    Connect to remove server
```

```
unspent(*addrs)
```

```
    Get unspent transactions for addresses
```

```
history(*addrs, **kwargs)
```

```
    Get transaction history for addresses
```

```
fetchtx(tx)
```

```
    Fetch a tx from the blockchain
```

```
txinputs(tx)
```

```
    Fetch inputs of a transaction on the blockchain
```

```
pushtx(tx)
```

```
    Push/ Broadcast a transaction to the blockchain
```

```
privtopub(privkey)
```

```
    Get public key from private key
```

```
pubtoaddr(pubkey)
```

```
    Get address from a public key
```

```
privtoaddr(privkey)
```

```
    Get address from a private key
```

```
electrum_address(masterkey, n, for_change=0)
```

```
    For old electrum seeds
```

```
is_address(addr)
```

```
    Check if addr is a valid address for this chain
```

is_p2sh(*addr*)

Check if *addr* is a pay to script address

output_script_to_address(*script*)

Convert an output script to an address

scripttoaddr(*script*)

Convert an input public key hash to an address

p2sh_scriptaddr(*script*)

Convert an output p2sh script to an address

addrtoscript(*addr*)

Convert an output address to a script

pubtop2w(*pub*)

Convert a public key to a pay to witness public key hash address (P2WPKH, required for segwit)

privtop2w(*priv*)

Convert a private key to a pay to witness public key hash address

hash_to_segwit_addr(*hash*)

Convert a hash to the new segwit address format outlined in BIP-0173

privtosegwit(*privkey*)

Convert a private key to the new segwit address format outlined in BIP01743

pubtosegwit(*pubkey*)

Convert a public key to the new segwit address format outlined in BIP01743

script_to_p2wsh(*script*)

Convert a script to the new segwit address format outlined in BIP01743

mk_multisig_address(args*)**

Parameters

args – List of public keys to used to create multisig and M, the number of signatures required to spend

Returns

multisig script

is_segwit(*priv*, *addr*)

Check if *addr* was generated from *priv* using segwit script

sign(*txobj*, *i*, *priv*)

Sign a transaction input with index using a private key

signall(*txobj*, *priv*)

Sign all inputs to a transaction using a private key

multisign(*tx*, *i*, *script*, *pk*)

mktx(*args)

[in0, in1...],[out0, out1...] or in0, in1 ... out0 out1 ...

Make an unsigned transaction from inputs and outputs. Change is not automatically included so any difference in value between inputs and outputs will be given as a miner's fee (transactions with too high fees will normally be blocked by the explorers)

For Bitcoin Cash and other hard forks using SIGHASH_FORKID, ins must be a list of dicts with each containing the outpoint and value of the input.

Inputs originally received with segwit must be a dict in the format: {'outpoint': "tx-hash:index", value:0, "segwit": True}

For other transactions, inputs can be dicts containing only outpoints or strings in the outpoint format. Outpoint format: txhash:index

mksend(*args, segwit=False)

[in0, in1...],[out0, out1...] or in0, in1 ... out0 out1 ...

Make an unsigned transaction from inputs, outputs change address and fee. A change output will be added with change sent to the change address.

For Bitcoin Cash and other hard forks using SIGHASH_FORKID and segwit, ins must be a list of dicts with each containing the outpoint and value of the input.

For other transactions, inputs can be dicts containing only outpoints or strings in the outpoint format. Outpoint format: txhash:index

preparesignedtx(privkey, to, value, fee=10000, change_addr=None, segwit=False, addr=None)

Prepare a tx with a specific amount from address belonging to private key to another address, returning change to the from address or change address, if set. Requires private key, target address, value and optionally the change address and fee segwit paramater specifies that the inputs belong to a segwit address addr, if provided, will explicitly set the from address, overriding the auto-detection of the address from the private key. It will also be used, along with the privkey, to automatically detect a segwit transaction for coins which support segwit, overriding the segwit kw

send(privkey, to, value, fee=10000, change_addr=None, segwit=False, addr=None)

Send a specific amount from address belonging to private key to another address, returning change to the from address or change address, if set. Requires private key, target address, value and optionally the change address and fee segwit paramater specifies that the inputs belong to a segwit address addr, if provided, will explicitly set the from address, overriding the auto-detection of the address from the private key. It will also be used, along with the privkey, to automatically detect a segwit transaction for coins which support segwit, overriding the segwit kw

preparesignedmultitx(privkey, *args, change_addr=None, segwit=False, addr=None)

Prepare transaction with multiple outputs, with change sent back to from address. Requires private key, address:value pairs and optionally the change address and fee segwit paramater specifies that the inputs belong to a segwit address addr, if provided, will explicitly set the from address, overriding the auto-detection of the

address from the private key. It will also be used, along with the `privkey` to automatically detect a segwit transaction for coins which support segwit, overriding the `segwit kw`

`sendmultitx(privkey, *args, change_addr=None, segwit=False, addr=None)`

Send transaction with multiple outputs, with change sent back to from address. Requires private key, address:value pairs and optionally the change address and fee. `segwit` parameter specifies that the inputs belong to a segwit address `addr`, if provided, will explicitly set the from address, overriding the auto-detection of the address from the private key. It will also be used, along with the `privkey` to automatically detect a segwit transaction for coins which support segwit, overriding the `segwit kw`

`preparetx(frm, to, value, fee, change_addr=None, segwit=False)`

Prepare a transaction using from and to addresses, value and a fee, with change sent back to from address

`preparemultitx(frm, *args, change_addr=None, segwit=False)`

Prepare transaction with multiple outputs, with change sent to from address. Requires from address, to_address:value pairs and fees

`block_height(txhash)`

`current_block_height()`

`block_info(height)`

`inspect(tx)`

`merkle_prove(txhash)`

Prove that information an explorer returns about a transaction in the blockchain is valid. Only run on a tx with at least 1 confirmation.

`encode_privkey(privkey, format, script_type='p2pkh')`

`wallet(seed, passphrase=None, **kwargs)`

`watch_wallet(xpub, **kwargs)`

`p2wpkh_p2sh_wallet(seed, passphrase=None, **kwargs)`

`watch_p2wpkh_p2sh_wallet(xpub, **kwargs)`

`p2wpkh_wallet(seed, passphrase=None, **kwargs)`

`watch_p2wpkh_wallet(xpub, **kwargs)`

`electrum_wallet(seed, passphrase=None, **kwargs)`

`watch_electrum_wallet(xpub, **kwargs)`

`watch_electrum_p2wpkh_wallet(xpub, **kwargs)`

cryptnox_cli.lib.cryptos.coins.bitcoin module

Bitcoin-specific constants, scripts, and address helpers.

```
class cryptnox_cli.lib.cryptos.coins.bitcoin.Bitcoin(testnet=False, **kwargs)
    Bases: BaseCoin

    coin_symbol = 'BTC'

    display_name = 'Bitcoin'

    segwit_supported = True

    magicbyte = 0

    script_magicbyte = 5

    segwit_hrp = 'bc'

    client_kwargs = {'server_file': 'bitcoin.json'}

    testnet_overrides = {'client_kwargs': {'server_file':
        'bitcoin_testnet.json'}, 'coin_symbol': 'BTCTEST', 'display_name': 'Bitcoin
        Testnet', 'hd_path': 1, 'magicbyte': 111, 'script_magicbyte': 196,
        'segwit_hrp': 'tb', 'wif_prefix': 239, 'xprv_headers': {'p2pkh': 70615956,
        'p2wpkh': 70615956, 'p2wpkh-p2sh': 71978536, 'p2wsh': 44726937, 'p2wsh-p2sh':
        43364357}, 'xpub_headers': {'p2pkh': 70617039, 'p2wpkh': 70617039,
        'p2wpkh-p2sh': 71979618, 'p2wsh': 44728019, 'p2wsh-p2sh': 43365439}}
```

Module contents

Re-exports available coin implementations for convenience.

```
class cryptnox_cli.lib.cryptos.coins.Bitcoin(testnet=False, **kwargs)
    Bases: BaseCoin

    coin_symbol = 'BTC'

    display_name = 'Bitcoin'

    segwit_supported = True

    magicbyte = 0

    script_magicbyte = 5

    segwit_hrp = 'bc'

    client_kwargs = {'server_file': 'bitcoin.json'}

    testnet_overrides = {'client_kwargs': {'server_file':
        'bitcoin_testnet.json'}, 'coin_symbol': 'BTCTEST', 'display_name': 'Bitcoin
        Testnet', 'hd_path': 1, 'magicbyte': 111, 'script_magicbyte': 196,
        'segwit_hrp': 'tb', 'wif_prefix': 239, 'xprv_headers': {'p2pkh': 70615956,
        'p2wpkh': 70615956, 'p2wpkh-p2sh': 71978536, 'p2wsh': 44726937, 'p2wsh-p2sh':
        43364357}, 'xpub_headers': {'p2pkh': 70617039, 'p2wpkh': 70617039,
        'p2wpkh-p2sh': 71979618, 'p2wsh': 44728019, 'p2wsh-p2sh': 43365439}}
```

The `cryptnox_cli.lib.cryptos.coins` package provides cryptocurrency coin implementations and exports:

class `cryptnox_cli.lib.cryptos.coins.Bitcoin`
Bitcoin cryptocurrency implementation. See `cryptnox_cli.lib.cryptos.coins.bitcoin.Bitcoin` for details.

Submodules

`cryptnox_cli.lib.cryptos.blocks` module

Block header encoding/decoding utilities and related primitives.

`cryptnox_cli.lib.cryptos.blocks.serialize_header(inp)`

`cryptnox_cli.lib.cryptos.blocks.deserialize_header(inp)`

`cryptnox_cli.lib.cryptos.blocks.mk_merkle_proof(header, hashes, index)`

`cryptnox_cli.lib.cryptos.composite` module

High-level composition utilities combining deterministic keys and transactions.

`cryptnox_cli.lib.cryptos.composite.bip32_hdm_script(*args)`

`cryptnox_cli.lib.cryptos.composite.bip32_hdm_addr(*args)`

`cryptnox_cli.lib.cryptos.composite.setup_coinvault_tx(tx, script)`

`cryptnox_cli.lib.cryptos.composite.sign_coinvault_tx(tx, priv)`

`cryptnox_cli.lib.cryptos.constants` module

Core constants and magic values used across cryptocurrency modules.

`cryptnox_cli.lib.cryptos.deterministic` module

Deterministic key and path derivation utilities (BIP32-like logic).

`cryptnox_cli.lib.cryptos.deterministic.electrum_stretch(seed)`

`cryptnox_cli.lib.cryptos.deterministic.electrum_mpk(seed)`

`cryptnox_cli.lib.cryptos.deterministic.electrum_privkey(seed, n, for_change=0)`

`cryptnox_cli.lib.cryptos.deterministic.electrum_pubkey(masterkey, n, for_change=0)`

`cryptnox_cli.lib.cryptos.deterministic.electrum_address(masterkey, n, for_change=0,
magicbyte=0)`

`cryptnox_cli.lib.cryptos.deterministic.crack_electrum_wallet(mpk, pk, n,
for_change=0)`

`cryptnox_cli.lib.cryptos.deterministic.raw_bip32_ckd(rawtuple, i, prefixes=DEFAULT)`

`cryptnox_cli.lib.cryptos.deterministic.bip32_serialize(rawtuple, prefixes=DEFAULT)`

```
cryptnox_cli.lib.cryptos.deterministic.bip32_deserialize(data, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.is_xprv(text, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.is_xpub(text, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.raw_bip32_privtopub(rawtuple,
                                                           prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_privtopub(data, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_ckd(key, path, prefixes=DEFAULT,
                                                  public=False)
cryptnox_cli.lib.cryptos.deterministic.bip32_master_key(seed, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_bin_extract_key(data,
                                                             prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_extract_key(data, prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_derive_key(key, path, prefixes=DEFAULT,
                                                         **kwargs)
cryptnox_cli.lib.cryptos.deterministic.raw_crack_bip32_privkey(parent_pub, priv,
                                                              prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.crack_bip32_privkey(parent_pub, priv,
                                                           prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.coinvault_pub_to_bip32(*args,
                                                             prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.coinvault_priv_to_bip32(*args,
                                                               prefixes=DEFAULT)
cryptnox_cli.lib.cryptos.deterministic.bip32_descend(*args, prefixes=DEFAULT)
    Descend masterkey and return privkey
cryptnox_cli.lib.cryptos.deterministic.parse_bip32_path(path)
    Takes bip32 path, "m/0'/2H" or "m/0H/1/2H/2/10000000000.pub", returns list of ints
```

cryptnox_cli.lib.cryptos.keystore module

HD wallet structures, serialization, derivation, and key store helpers.

```
class cryptnox_cli.lib.cryptos.keystore.KeyStore(coin, addresses=())
    Bases: object
    __init__(coin, addresses=())
    has_seed()
    is_watching_only()
    can_import()
```

```
    get_tx_derivations(tx)

    can_sign(tx)

class cryptnox_cli.lib.cryptos.keystore.Software_KeyStore(coin, addresses=())
    Bases: KeyStore

    may_have_password()

class cryptnox_cli.lib.cryptos.keystore.Imported_KeyStore(d, coin)
    Bases: Software_KeyStore

    __init__(d, coin)

    is_deterministic()

    can_change_password()

    get_master_public_key()

    dump()

    can_import()

    check_password(password=None)

    import_privkey(sec, password=None)

    delete_imported_key(key)

    get_private_key(pubkey, password=None)

    get_pubkey_derivation(x_pubkey)

    update_password(old_password, new_password)

class cryptnox_cli.lib.cryptos.keystore.Deterministic_KeyStore(d, coin)
    Bases: Software_KeyStore

    __init__(d, coin)

    is_deterministic()

    dump()

    has_seed()

    is_watching_only()

    can_change_password()

    add_seed(seed)

    get_seed(password)

    get_passphrase(password)

class cryptnox_cli.lib.cryptos.keystore.Xpub
    Bases: object
```

```
__init__()

get_master_public_key()

derive_pubkey(for_change, n)

classmethod get_pubkey_from_xpub(xpub, sequence, bip39_prefixes)

class cryptnox_cli.lib.cryptos.keystore.BIP32_KeyStore(d, coin)
    Bases: Deterministic_KeyStore, Xpub
    __init__(d, coin)

    format_seed(seed)

    dump()

    get_master_private_key(password=None)

    check_password(password=None)

    update_password(old_password, new_password)

    is_watching_only()

    add_xprv(xprv)

    add_xpub(xpub, xtype, electrum=False)

    add_xprv_from_seed(bip32_seed, xtype, derivation, electrum=False)

    get_private_key(sequence, password)

class cryptnox_cli.lib.cryptos.keystore.Hardware_KeyStore(d, coin)
    Bases: KeyStore, Xpub
    max_change_outputs = 1
    __init__(d, coin)

    set_label(label)

    may_have_password()

    is_deterministic()

    dump()

    unpaired()
        A device paired with the wallet was diconnected. This can be called in any thread
        context.

    paired()
        A device paired with the wallet was (re-)connected. This can be called in any
        thread context.

    can_export()
```

is_watching_only()

The wallet is not watching-only; the user will be prompted for pin and passphrase as appropriate when needed.

can_change_password()

`cryptnox_cli.lib.cryptos.keystore.bip39_to_seed(mnemonic, passphrase)`

`cryptnox_cli.lib.cryptos.keystore.bip39_is_checksum_valid(mnemonic)`

`cryptnox_cli.lib.cryptos.keystore.from_bip39_seed(seed, passphrase, derivation, coin)`

`cryptnox_cli.lib.cryptos.keystore.standard_from_bip39_seed(seed, passphrase, coin)`

`cryptnox_cli.lib.cryptos.keystore.p2wpkh_from_bip39_seed(seed, passphrase, coin)`

`cryptnox_cli.lib.cryptos.keystore.p2wpkh_p2sh_from_bip39_seed(seed, passphrase,
coin)`

`cryptnox_cli.lib.cryptos.keystore.xtype_from_derivation(derivation)`

Returns the script type to be used for this derivation.

`cryptnox_cli.lib.cryptos.keystore.is_xpubkey(x_pubkey)`

`cryptnox_cli.lib.cryptos.keystore.parse_xpubkey(x_pubkey)`

`cryptnox_cli.lib.cryptos.keystore.xpubkey_to_address(x_pubkey, coin)`

`cryptnox_cli.lib.cryptos.keystore.xpubkey_to_pubkey(x_pubkey, coin)`

`cryptnox_cli.lib.cryptos.keystore.register_keystore(hw_type, constructor)`

`cryptnox_cli.lib.cryptos.keystore.hardware_keystore(d)`

`cryptnox_cli.lib.cryptos.keystore.is_address_list(text, coin)`

`cryptnox_cli.lib.cryptos.keystore.get_private_keys(text)`

`cryptnox_cli.lib.cryptos.keystore.is_private_key_list(text)`

`cryptnox_cli.lib.cryptos.keystore.is_private(x)`

`cryptnox_cli.lib.cryptos.keystore.is_master_key(x)`

`cryptnox_cli.lib.cryptos.keystore.is_private_key(x)`

`cryptnox_cli.lib.cryptos.keystore.is_bip32_key(x)`

`cryptnox_cli.lib.cryptos.keystore.from_electrum_seed(seed, passphrase, is_p2sh, coin)`

`cryptnox_cli.lib.cryptos.keystore.from_private_key_list(text, coin)`

`cryptnox_cli.lib.cryptos.keystore.from_xpub(xpub, coin, xtype, electrum=False)`

`cryptnox_cli.lib.cryptos.keystore.from_xprv(xprv, coin)`

`cryptnox_cli.lib.cryptos.keystore.from_master_key(text, coin)`

cryptnox_cli.lib.cryptos.main module

Core cryptographic and encoding primitives used by higher-level modules.

This module is based on code from pybitcointools: <https://github.com/primal100/pybitcointools/blob/master/cryptos/main.py>

```
cryptnox_cli.lib.cryptos.main.change_curve(p, n, a, b, gx, gy)
cryptnox_cli.lib.cryptos.main.getG()
cryptnox_cli.lib.cryptos.main.inv(a, n)
cryptnox_cli.lib.cryptos.main.access(obj, prop)
cryptnox_cli.lib.cryptos.main.multiaccess(obj, prop)
cryptnox_cli.lib.cryptos.main.slice(obj, start=0, end=2**200)
cryptnox_cli.lib.cryptos.main.count(obj)
cryptnox_cli.lib.cryptos.main.sum(obj)
cryptnox_cli.lib.cryptos.main.isinf(p)
cryptnox_cli.lib.cryptos.main.to_jacobian(p)
cryptnox_cli.lib.cryptos.main.jacobian_double(p)
cryptnox_cli.lib.cryptos.main.jacobian_add(p, q)
cryptnox_cli.lib.cryptos.main.from_jacobian(p)
cryptnox_cli.lib.cryptos.main.jacobian_multiply(a, n)
cryptnox_cli.lib.cryptos.main.fast_multiply(a, n)
cryptnox_cli.lib.cryptos.main.fast_add(a, b)
cryptnox_cli.lib.cryptos.main.get_pubkey_format(pub)
cryptnox_cli.lib.cryptos.main.encode_pubkey(pub, fmt)
cryptnox_cli.lib.cryptos.main.decode_pubkey(pub, fmt=None)
cryptnox_cli.lib.cryptos.main.get_privkey_format(priv)
cryptnox_cli.lib.cryptos.main.encode_privkey(priv, fmt, vbyte=128)
cryptnox_cli.lib.cryptos.main.decode_privkey(priv, fmt=None)
cryptnox_cli.lib.cryptos.main.add_pubkeys(p1, p2)
cryptnox_cli.lib.cryptos.main.add_privkeys(p1, p2)
cryptnox_cli.lib.cryptos.main.mul_privkeys(p1, p2)
cryptnox_cli.lib.cryptos.main.multiply(pubkey, privkey)
```

`cryptnox_cli.lib.cryptos.main.divide(pubkey, privkey)`
`cryptnox_cli.lib.cryptos.main.compress(pubkey)`
`cryptnox_cli.lib.cryptos.main.decompress(pubkey)`
`cryptnox_cli.lib.cryptos.main.privkey_to_pubkey(privkey)`
`cryptnox_cli.lib.cryptos.main.privtopub(privkey)`
`cryptnox_cli.lib.cryptos.main.privkey_to_address(priv, magicbyte=0)`
`cryptnox_cli.lib.cryptos.main.privtoaddr(priv, magicbyte=0)`
`cryptnox_cli.lib.cryptos.main.neg_pubkey(pubkey)`
`cryptnox_cli.lib.cryptos.main.neg_privkey(privkey)`
`cryptnox_cli.lib.cryptos.main.subtract_pubkeys(p1, p2)`
`cryptnox_cli.lib.cryptos.main.subtract_privkeys(p1, p2)`
`cryptnox_cli.lib.cryptos.main.bin_hash160(string)`
`cryptnox_cli.lib.cryptos.main.hash160(string)`
`cryptnox_cli.lib.cryptos.main.hex_to_hash160(s_hex)`
`cryptnox_cli.lib.cryptos.main.bin_sha256(string)`
`cryptnox_cli.lib.cryptos.main.sha256(string)`
`cryptnox_cli.lib.cryptos.main.bin_ripemd160(string)`
`cryptnox_cli.lib.cryptos.main.ripemd160(string)`
`cryptnox_cli.lib.cryptos.main.bin_dbl_sha256(s)`
`cryptnox_cli.lib.cryptos.main.dbl_sha256(string)`
`cryptnox_cli.lib.cryptos.main.bin_slowsha(string)`
`cryptnox_cli.lib.cryptos.main.slowsha(string)`
`cryptnox_cli.lib.cryptos.main.hash_to_int(x)`
`cryptnox_cli.lib.cryptos.main.num_to_var_int(x)`
`cryptnox_cli.lib.cryptos.main.electrum_sig_hash(message)`
`cryptnox_cli.lib.cryptos.main.random_key()`
`cryptnox_cli.lib.cryptos.main.random_electrum_seed()`
`cryptnox_cli.lib.cryptos.main.b58check_to_bin(inp)`
`cryptnox_cli.lib.cryptos.main.get_version_byte(inp)`
`cryptnox_cli.lib.cryptos.main.hex_to_b58check(inp, magicbyte=0)`

```
cryptnox_cli.lib.cryptos.main.b58check_to_hex(inp)
cryptnox_cli.lib.cryptos.main.pubkey_to_hash(pubkey)
cryptnox_cli.lib.cryptos.main.pubkey_to_hash_hex(pubkey)
cryptnox_cli.lib.cryptos.main.pubkey_to_address(pubkey, magicbyte=0)
cryptnox_cli.lib.cryptos.main.pubtoaddr(pubkey, magicbyte=0)
cryptnox_cli.lib.cryptos.main.is_privkey(priv)
cryptnox_cli.lib.cryptos.main.is_pubkey(pubkey)
cryptnox_cli.lib.cryptos.main.encode_sig(v, r, s)
cryptnox_cli.lib.cryptos.main.decode_sig(sig)
cryptnox_cli.lib.cryptos.main.deterministic_generate_k(msghash, priv)
cryptnox_cli.lib.cryptos.main.ecdsa_raw_sign(msghash, priv)
cryptnox_cli.lib.cryptos.main.ecdsa_sign(msg, priv, coin)
cryptnox_cli.lib.cryptos.main.ecdsa_raw_verify(msghash, vrs, pub)
cryptnox_cli.lib.cryptos.main.ecdsa_verify_addr(msg, sig, addr, coin)
cryptnox_cli.lib.cryptos.main.ecdsa_verify(msg, sig, pub, coin)
cryptnox_cli.lib.cryptos.main.ecdsa_raw_recover(msghash, vrs)
cryptnox_cli.lib.cryptos.main.ecdsa_recover(msg, sig)
cryptnox_cli.lib.cryptos.main.add(p1, p2)
cryptnox_cli.lib.cryptos.main.subtract(p1, p2)
cryptnox_cli.lib.cryptos.main.magicbyte_to_prefix(magicbyte)
```

cryptnox_cli.lib.cryptos.mnemonic module

Mnemonic phrase generation and seed handling (BIP39-style operations).

This module is based on code from pybtctools: <https://github.com/danvergara/pybtctools/blob/master/bitcoin/mnemonic.py>

```
cryptnox_cli.lib.cryptos.mnemonic.is_CJK(c)
cryptnox_cli.lib.cryptos.mnemonic.normalize_text(seed)
cryptnox_cli.lib.cryptos.mnemonic.eint_to_bytes(entint, entbits)
cryptnox_cli.lib.cryptos.mnemonic.mnemonic_int_to_words(mint, mint_num_words,
                                                         wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.entropy_cs(entbytes)
```

```
cryptnox_cli.lib.cryptos.mnemonic.entropy_to_words(entbytes, wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.words_bisect(word, wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.words_split(wordstr, wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.words_to_mnemonic_int(words,
                                                         wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.words_verify(words, wordlist=wordlist_english)
cryptnox_cli.lib.cryptos.mnemonic.bip39_normalize_passphrase(passphrase)
cryptnox_cli.lib.cryptos.mnemonic.bip39_is_checksum_valid(mnemonic)
cryptnox_cli.lib.cryptos.mnemonic.mnemonic_to_seed(mnemonic_phrase, passphrase="",
                                                    passphrase_prefix=b'mnemonic')
cryptnox_cli.lib.cryptos.mnemonic.bip39_mnemonic_to_seed(mnemonic_phrase,
                                                         passphrase="")
cryptnox_cli.lib.cryptos.mnemonic.electrum_mnemonic_to_seed(mnemonic_phrase,
                                                             passphrase="")
cryptnox_cli.lib.cryptos.mnemonic.is_old_seed(seed)
cryptnox_cli.lib.cryptos.mnemonic.seed_prefix(seed_type)
cryptnox_cli.lib.cryptos.mnemonic.seed_type(x)
cryptnox_cli.lib.cryptos.mnemonic.is_seed(x)
cryptnox_cli.lib.cryptos.mnemonic.words_mine(prefix, entbits, satisfuction,
                                              wordlist=wordlist_english,
                                              randombits=random.getrandbits)
```

cryptnox_cli.lib.cryptos.pbkdf2 module

PBKDF2 key derivation function implementation and helpers.

```
cryptnox_cli.lib.cryptos.pbkdf2.isunicode(s)
cryptnox_cli.lib.cryptos.pbkdf2.isbytes(s)
cryptnox_cli.lib.cryptos.pbkdf2.isinteger(n)
cryptnox_cli.lib.cryptos.pbkdf2.callable(obj)
cryptnox_cli.lib.cryptos.pbkdf2.b(s)
cryptnox_cli.lib.cryptos.pbkdf2.binxor(a, b)
cryptnox_cli.lib.cryptos.pbkdf2.b64encode(data, chars='+/')
cryptnox_cli.lib.cryptos.pbkdf2.b2a_hex(s)
```

```
class cryptnox_cli.lib.cryptos.pbkdf2.PBKDF2(passphrase, salt, iterations=1000,  
                                             digestmodule=SHA1, macmodule=HMAC)
```

Bases: object

```
__init__(passphrase, salt, iterations=1000, digestmodule=SHA1, macmodule=HMAC)
```

```
static crypt(word, salt=None, iterations=None)
```

PBKDF2-based unix crypt(3) replacement.

The number of iterations specified in the salt overrides the 'iterations' parameter.

The effective hash length is 192 bits.

```
read(bytes)
```

Read the specified number of key bytes.

```
hexread(octets)
```

Read the specified number of octets. Return them as hexadecimal.

Note that `len(obj.hexread(n)) == 2*n`.

```
close()
```

Close the stream.

```
cryptnox_cli.lib.cryptos.pbkdf2.crypt(word, salt=None, iterations=None)
```

PBKDF2-based unix crypt(3) replacement.

The number of iterations specified in the salt overrides the 'iterations' parameter.

The effective hash length is 192 bits.

cryptnox_cli.lib.cryptos.ripemd module

RIPEMD-160 hash function implementation in pure Python.

```
class cryptnox_cli.lib.cryptos.ripemd.RIPEMD160(arg=None)
```

Bases: object

Return a new RIPEMD160 object. An optional string argument may be provided; if present, this string will be automatically hashed.

```
__init__(arg=None)
```

```
update(arg)
```

```
digest()
```

```
hexdigest()
```

```
copy()
```

```
cryptnox_cli.lib.cryptos.ripemd.new(arg=None)
```

Return a new RIPEMD160 object. An optional string argument may be provided; if present, this string will be automatically hashed.

```
class cryptnox_cli.lib.cryptos.ripemd.RMDContext
```

Bases: object

`__init__()`

`copy()`

`cryptnox_cli.lib.cryptos.ripemd.ROL(n, x)`

`cryptnox_cli.lib.cryptos.ripemd.F0(x, y, z)`

`cryptnox_cli.lib.cryptos.ripemd.F1(x, y, z)`

`cryptnox_cli.lib.cryptos.ripemd.F2(x, y, z)`

`cryptnox_cli.lib.cryptos.ripemd.F3(x, y, z)`

`cryptnox_cli.lib.cryptos.ripemd.F4(x, y, z)`

`cryptnox_cli.lib.cryptos.ripemd.R(a, b, c, d, e, Fj, Kj, sj, rj, X)`

`cryptnox_cli.lib.cryptos.ripemd.RMD160Transform(state, block)`

`cryptnox_cli.lib.cryptos.ripemd.RMD160Update(ctx, inp, inplen)`

`cryptnox_cli.lib.cryptos.ripemd.RMD160Final(ctx)`

cryptnox_cli.lib.cryptos.segwit_addr module

SegWit address encoding/decoding utilities (bech32/bech32m).

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_polymod(values)`

Internal function that computes the Bech32 checksum.

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_hrp_expand(hrp)`

Expand the HRP into values for checksum computation.

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_verify_checksum(hrp, data)`

Verify a checksum given HRP and converted data characters.

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_create_checksum(hrp, data)`

Compute the checksum values given HRP and data.

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_encode(hrp, data)`

Compute a Bech32 string given HRP and data values.

`cryptnox_cli.lib.cryptos.segwit_addr.bech32_decode(bech)`

Validate a Bech32 string, and determine HRP and data.

`cryptnox_cli.lib.cryptos.segwit_addr.convertbits(data, frombits, tobits, pad=True)`

General power-of-2 base conversion.

`cryptnox_cli.lib.cryptos.segwit_addr.decode(hrp, addr)`

Decode a segwit address.

`cryptnox_cli.lib.cryptos.segwit_addr.encode(hrp, witver, witprog)`

Encode a segwit address.

cryptnox_cli.lib.cryptos.specials module

Low-level helpers, type adapters, and encoding utilities shared across modules.

```
cryptnox_cli.lib.cryptos.specials.bin_dbl_sha256(s)
cryptnox_cli.lib.cryptos.specials.lpad(msg, symbol, length)
cryptnox_cli.lib.cryptos.specials.get_code_string(base)
cryptnox_cli.lib.cryptos.specials.changebase(string, frm, to, minlen=0)
cryptnox_cli.lib.cryptos.specials.bin_to_b58check(inp, magicbyte=0)
cryptnox_cli.lib.cryptos.specials.bytes_to_hex_string(b)
cryptnox_cli.lib.cryptos.specials.safe_from_hex(s)
cryptnox_cli.lib.cryptos.specials.from_int_representation_to_bytes(a)
cryptnox_cli.lib.cryptos.specials.from_int_to_byte(a)
cryptnox_cli.lib.cryptos.specials.from_byte_to_int(a)
cryptnox_cli.lib.cryptos.specials.from_string_to_bytes(a)
cryptnox_cli.lib.cryptos.specials.safe_hexlify(a)
cryptnox_cli.lib.cryptos.specials.encode(val, base, minlen=0)
cryptnox_cli.lib.cryptos.specials.decode(string, base)
cryptnox_cli.lib.cryptos.specials.random_string(x)
```

cryptnox_cli.lib.cryptos.stealth module

Stealth address generation and parsing utilities.

```
cryptnox_cli.lib.cryptos.stealth.shared_secret_sender(scan_pubkey, ephem_privkey)
cryptnox_cli.lib.cryptos.stealth.shared_secret_receiver(ephem_pubkey,
                                                         scan_privkey)
cryptnox_cli.lib.cryptos.stealth.uncover_pay_pubkey_sender(scan_pubkey,
                                                           spend_pubkey,
                                                           ephem_privkey)
cryptnox_cli.lib.cryptos.stealth.uncover_pay_pubkey_receiver(scan_privkey,
                                                             spend_pubkey,
                                                             ephem_pubkey)
cryptnox_cli.lib.cryptos.stealth.uncover_pay_privkey(scan_privkey, spend_privkey,
                                                         ephem_pubkey)
cryptnox_cli.lib.cryptos.stealth.pubkeys_to_basic_stealth_address(scan_pubkey,
                                                                    spend_pubkey,
                                                                    magic_byte=42)
```

```
cryptnox_cli.lib.cryptos.stealth.basic_stealth_address_to_pubkeys(stealth_address)
cryptnox_cli.lib.cryptos.stealth.mk_stealth_metadata_script(ephem_pubkey, nonce)
cryptnox_cli.lib.cryptos.stealth.mk_stealth_tx_outputs(stealth_addr, value,
                                                    ephem_privkey, nonce,
                                                    network='btc')
cryptnox_cli.lib.cryptos.stealth.ephem_pubkey_from_tx_script(stealth_tx_script)
```

cryptnox_cli.lib.cryptos.transaction module

Transaction building, serialization, signing, and parsing utilities.

```
cryptnox_cli.lib.cryptos.transaction.json_is_base(obj, base)
cryptnox_cli.lib.cryptos.transaction.json_changebase(obj, changer)
cryptnox_cli.lib.cryptos.transaction.encode_1_byte(val)
cryptnox_cli.lib.cryptos.transaction.encode_4_bytes(val)
cryptnox_cli.lib.cryptos.transaction.encode_8_bytes(val)
cryptnox_cli.lib.cryptos.transaction.list_to_bytes(vals)
cryptnox_cli.lib.cryptos.transaction.dbl_sha256_list(vals)
cryptnox_cli.lib.cryptos.transaction.is_segwit(tx)
cryptnox_cli.lib.cryptos.transaction.deserialize(tx)
cryptnox_cli.lib.cryptos.transaction.serialize(txobj, include_witness=True)
cryptnox_cli.lib.cryptos.transaction.uahf_digest(txobj, i)
cryptnox_cli.lib.cryptos.transaction.signature_form(tx, i, script,
                                                    hashcode=SIGHASH_ALL)
cryptnox_cli.lib.cryptos.transaction.der_encode_sig(v, r, s)
cryptnox_cli.lib.cryptos.transaction.der_decode_sig(sig)
cryptnox_cli.lib.cryptos.transaction.is_bip66(sig)
    Checks hex DER sig for BIP66 consistency
cryptnox_cli.lib.cryptos.transaction.txhash(tx, hashcode=None, wtxid=True)
cryptnox_cli.lib.cryptos.transaction.public_txhash(tx, hashcode=None)
cryptnox_cli.lib.cryptos.transaction.bin_txhash(tx, hashcode=None)
cryptnox_cli.lib.cryptos.transaction.ecdsa_tx_sign(tx, priv,
                                                    hashcode=SIGHASH_ALL)
cryptnox_cli.lib.cryptos.transaction.ecdsa_tx_verify(tx, sig, pub,
                                                    hashcode=SIGHASH_ALL)
```

`cryptnox_cli.lib.cryptos.transaction.ecdsa_tx_recover(tx, sig,`
`hashcode=SIGHASH_ALL)`

`cryptnox_cli.lib.cryptos.transaction.mk_pubkey_script(addr)`

Used in converting p2pkh address to input or output script

`cryptnox_cli.lib.cryptos.transaction.mk_scripthash_script(addr)`

Used in converting p2sh address to output script

`cryptnox_cli.lib.cryptos.transaction.output_script_to_address(script, magicbyte=0)`

`cryptnox_cli.lib.cryptos.transaction.mk_p2w_scripthash_script(witver, witprog)`

Used in converting a decoded pay to witness script hash address to output script

`cryptnox_cli.lib.cryptos.transaction.mk_p2wpkh_redeemscript(pubkey)`

Used in converting public key to p2wpkh script

`cryptnox_cli.lib.cryptos.transaction.mk_p2wpkh_script(pubkey)`

Used in converting public key to p2wpkh script

`cryptnox_cli.lib.cryptos.transaction.mk_p2wpkh_scriptcode(pubkey)`

Used in signing for tx inputs

`cryptnox_cli.lib.cryptos.transaction.p2wpkh_nested_script(pubkey)`

`cryptnox_cli.lib.cryptos.transaction.deserialize_script(script)`

`cryptnox_cli.lib.cryptos.transaction.serialize_script_unit(unit)`

`cryptnox_cli.lib.cryptos.transaction.serialize_script(script)`

`cryptnox_cli.lib.cryptos.transaction.mk_multisig_script(*args)`

Parameters

args – List of public keys to used to create multisig and M, the number of signatures required to spend

Returns

multisig script

`cryptnox_cli.lib.cryptos.transaction.verify_tx_input(tx, i, script, sig, pub)`

`cryptnox_cli.lib.cryptos.transaction.multisign(tx, i, script, pk,`
`hashcode=SIGHASH_ALL)`

`cryptnox_cli.lib.cryptos.transaction.apply_multisignatures(txobj, i, script, *args)`

`cryptnox_cli.lib.cryptos.transaction.is_inp(arg)`

`cryptnox_cli.lib.cryptos.transaction.select(unspent, value)`

cryptnox_cli.lib.cryptos.wallet module

Simple wallet abstractions for addresses, balances, and signing flows.

This module is based on code from pybtctools: <https://github.com/primal100/pybitcointools/blob/master/cryptos/wallet.py>

```
class cryptnox_cli.lib.cryptos.wallet.HDWallet(keystore, num_addresses=0,  
                                              last_receiving_index=0,  
                                              last_change_index=0)  
  
Bases: object  
  
__init__(keystore, num_addresses=0, last_receiving_index=0, last_change_index=0)  
  
privkey(address, fmt='wif_compressed', password=None)  
  
export_privkeys(password=None)  
  
pubkey_receiving(index)  
  
pubkey_change(index)  
  
pubtoaddr(pubkey)  
  
receiving_address(index)  
  
change_address(index)  
  
property receiving_addresses  
  
property change_addresses  
  
new_receiving_address_range(num)  
  
new_change_address_range(num)  
  
new_receiving_addresses(num=10)  
  
new_change_addresses(num=10)  
  
new_receiving_address()  
  
new_change_address()  
  
balance()  
  
unspent()  
  
select()  
  
history()  
  
sign(tx, password=None)  
  
mksend(outs)  
  
sign_message(message, address, password=None)  
  
is_mine(address)  
  
is_change(address)  
  
account(address, password=None)  
  
details(password=None)
```

cryptnox_cli.lib.cryptos.wallet_utils module

General wallet helper functions (formatting, hashing, conversions).

`cryptnox_cli.lib.cryptos.wallet_utils.hmac_sha_512(x, y)`

`cryptnox_cli.lib.cryptos.wallet_utils.rev_hex(s)`

`cryptnox_cli.lib.cryptos.wallet_utils.int_to_hex(i, length=1)`

exception `cryptnox_cli.lib.cryptos.wallet_utils.InvalidPassword`

Bases: Exception

exception `cryptnox_cli.lib.cryptos.wallet_utils.InvalidPasswordException`

Bases: Exception

exception `cryptnox_cli.lib.cryptos.wallet_utils.InvalidPadding`

Bases: Exception

`cryptnox_cli.lib.cryptos.wallet_utils.assert_bytes(*args)`

porting helper, assert args type

`cryptnox_cli.lib.cryptos.wallet_utils.append_PKCS7_padding(data)`

`cryptnox_cli.lib.cryptos.wallet_utils.strip_PKCS7_padding(data)`

`cryptnox_cli.lib.cryptos.wallet_utils.aes_encrypt_with_iv(key, iv, data)`

`cryptnox_cli.lib.cryptos.wallet_utils.aes_decrypt_with_iv(key, iv, data)`

`cryptnox_cli.lib.cryptos.wallet_utils.EncodeAES(secret, s)`

`cryptnox_cli.lib.cryptos.wallet_utils.DecodeAES(secret, e)`

`cryptnox_cli.lib.cryptos.wallet_utils.pw_encode(s, password)`

`cryptnox_cli.lib.cryptos.wallet_utils.pw_decode(s, password)`

`cryptnox_cli.lib.cryptos.wallet_utils.is_new_seed(x, prefix=version.SEED_PREFIX)`

`cryptnox_cli.lib.cryptos.wallet_utils.seed_type(x)`

`cryptnox_cli.lib.cryptos.wallet_utils.is_seed(x)`

`cryptnox_cli.lib.cryptos.wallet_utils.inv_dict(d)`

`cryptnox_cli.lib.cryptos.wallet_utils.is_minkey(text)`

`cryptnox_cli.lib.cryptos.wallet_utils.minikey_to_private_key(text)`

`cryptnox_cli.lib.cryptos.wallet_utils.get_pubkeys_from_secret(secret)`

`cryptnox_cli.lib.cryptos.wallet_utils.xprv_header(xtype)`

`cryptnox_cli.lib.cryptos.wallet_utils.xpub_header(xtype)`

`cryptnox_cli.lib.cryptos.wallet_utils.number_of_significant_digits(number: float) → int`

Module contents

Cryptocurrency utilities package - aggregates and re-exports submodules for easier imports.

The `cryptnox_cli.lib.cryptos` package provides cryptocurrency utilities and re-exports functionality from:

- `cryptnox_cli.lib.cryptos.blocks` - Block-related utilities
- `cryptnox_cli.lib.cryptos.composite` - Composite key handling
- `cryptnox_cli.lib.cryptos.deterministic` - Deterministic wallet functions
- `cryptnox_cli.lib.cryptos.main` - Main crypto operations
- `cryptnox_cli.lib.cryptos.mnemonic` - Mnemonic phrase handling
- `cryptnox_cli.lib.cryptos.specials` - Special cryptocurrency operations
- `cryptnox_cli.lib.cryptos.stealth` - Stealth address support
- `cryptnox_cli.lib.cryptos.transaction` - Transaction handling
- `cryptnox_cli.lib.cryptos.coins` - Coin implementations
- `cryptnox_cli.lib.cryptos.keystore` - Key storage utilities
- `cryptnox_cli.lib.cryptos.wallet` - Wallet functionality

All public members from these modules are available directly from `cryptnox_cli.lib.cryptos`.

Module contents

The `cryptnox_cli.lib` package provides library functionality for cryptocurrency operations. The main subpackage is `cryptnox_cli.lib.cryptos` which contains comprehensive cryptocurrency utilities.

`cryptnox_cli.wallet` package

Subpackages

`cryptnox_cli.wallet.eth` package

Submodules

`cryptnox_cli.wallet.eth.api` module

A basic Ethereum wallet library

`cryptnox_cli.wallet.eth.api.address(public_key: str) → str`

`cryptnox_cli.wallet.eth.api.checksum_address(public_key: str) → str`

`class cryptnox_cli.wallet.eth.api.Api(endpoint: str, network: EthNetwork | str, api_key: str)`

Bases: object

`PATH = "m/44'/60'/0'/0/0"`

```
SYMBOL = 'eth'

__init__(endpoint: str, network: EthNetwork | str, api_key: str)

property block_number

contract(address="", abi=")

get_transaction_count(address: str, blocks: str = None) → int

get_balance(address: str) → int

property gas_price

property network

transaction_hash(transaction: Dict[str, Any], vrs: bool = False)

push(transaction, signature, public_key)

class cryptnox_cli.wallet.eth.api.EthValidator(endpoint: str = 'publicnode', network: str
                                              = 'sepolia', price: int = 8, limit: int =
                                              2500, derivation: str = 'DERIVE',
                                              api_key=")

Bases: object

Class defining Ethereum validators

__init__(endpoint: str = 'publicnode', network: str = 'sepolia', price: int = 8, limit: int =
        2500, derivation: str = 'DERIVE', api_key=")

endpoint
    Validator to validate endpoints for the Ethereum network

network
    Class for validating if value is part of the enum

price
    Class for validating if value is integer

limit
    Class for validating if value is integer

derivation
    Class for validating if value is part of the enum

api_key

validate()
```

`cryptnox_cli.wallet.eth.endpoint module`

Module for endpoints that can be used for working with the Ethereum network

```
class cryptnox_cli.wallet.eth.endpoint.EndpointValidator(valid_values: str = None)
    Bases: Validator
    Validator to validate endpoints for the Ethereum network
```

```
__init__(valid_values: str = None)
```

```
validate(value)
```

Parameters

value – Evaluated value

Returns

None

Raises

ValidationError – Validation criteria not satisfied

```
class cryptnox_cli.wallet.eth.endpoint.Endpoint(network: EthNetwork, api_key: str = "")
```

Bases: object

Abstract base class for interface for endpoint implementations

```
__init__(network: EthNetwork, api_key: str = "")
```

```
abstract property available_networks: List[EthNetwork]
```

Ethereum networks handled by the endpoint implementation :rtype: List[enums.EthNetwork]

Type

return

```
abstract property domain: str
```

Domain that is used by the endpoint implementation :rtype: str

Type

return

```
abstract property name: str
```

Name of the endpoint implementation :rtype: str

Type

return

```
abstract property provider: str
```

Full URL that can be used as Web3 provider :rtype: str

Type

return

```
class cryptnox_cli.wallet.eth.endpoint.InfuraEndpoint(network: EthNetwork, api_key: str = "")
```

Bases: [Endpoint](#)

Implementation of the Infura endpoint

```
name = 'infura'
```

```
available_networks = ['MAINNET', 'KOVAN', 'GOERLI', 'RINKEBY', 'SEPOLIA']
```

```
__init__(network: EthNetwork, api_key: str = "")
```

property domain: str

Domain that is used by the endpoint implementation :rtype: str

Type

return

property provider: str

Full URL that can be used as Web3 provider :rtype: str

Type

return

```
class cryptnox_cli.wallet.eth.endpoint.CryptnoxEndpoint(network: EthNetwork,  
                                                         api_key: str = "")
```

Bases: [Endpoint](#)

Implementation of the Cryptnox endpoint

name = 'cryptnox'

available_networks = ['MAINNET', 'SEPOLIA']

property domain: str

Domain that is used by the endpoint implementation :rtype: str

Type

return

property provider: str

Full URL that can be used as Web3 provider :rtype: str

Type

return

```
class cryptnox_cli.wallet.eth.endpoint.PublicNodeEndpoint(network: EthNetwork,  
                                                           api_key: str = "")
```

Bases: [Endpoint](#)

Implementation of the PublicNode public RPC endpoint (free, no API key required)

name = 'publicnode'

available_networks = ['MAINNET', 'SEPOLIA']

property domain: str

Domain that is used by the endpoint implementation :rtype: str

Type

return

property provider: str

Full URL that can be used as Web3 provider :rtype: str

Type

return

```
class cryptnox_cli.wallet.eth.endpoint.DirectEndpoint(url: str, network: EthNetwork)
```

Bases: object

```
__init__(url: str, network: EthNetwork)
```

property provider: str

```
cryptnox_cli.wallet.eth.endpoint.factory(endpoint: str, network: EthNetwork, api_key:  
                                         str = "") → Endpoint
```

Factory method for Endpoint instances

Parameters

- **endpoint** – Name of the endpoint to use
- **network** – Ethereum network to use
- **api_key** – API key to use on the endpoint

Type

str

Type

[enums.EthNetwork](#)

Type

str

Returns

Return an Endpoint instance that can be used to get the urls

Return type

[Endpoint](#)

Raises

ValueError – In case endpoint with endpoint name wasn't found

Module contents

Ethereum wallet utilities - aggregates and re-exports API components for easier imports.

The `cryptnox_cli.wallet.eth` package provides Ethereum wallet utilities and exports:

`cryptnox_cli.wallet.eth.address(public_key)`

Generate an Ethereum address from a public key. See `cryptnox_cli.wallet.eth.api.address()` for details.

class `cryptnox_cli.wallet.eth.Api`

Ethereum API interface. See `cryptnox_cli.wallet.eth.api.Api` for details.

`cryptnox_cli.wallet.eth.checksum_address(address_str)`

Convert an address to checksummed format. See `cryptnox_cli.wallet.eth.api.checksum_address()` for details.

class `cryptnox_cli.wallet.eth.EthValidator`

Ethereum address and transaction validator. See `cryptnox_cli.wallet.eth.api.EthValidator` for details.

Submodules

cryptnox_cli.wallet.btc module

A basic BTC wallet library

class cryptnox_cli.wallet.btc.**BtcNetworks**(**values*)

Bases: Enum

Class defining possible Bitcoin networks

MAINNET = 'mainnet'

TESTNET = 'testnet'

TESTNET4 = 'testnet4'

class cryptnox_cli.wallet.btc.**BlockCypherApi**

Bases: object

__init__(*api_key*, *network*)

get_data(*endpoint: str*, *params: Dict = None*, *data: bytes = None*) → None

Return type

None

Parameters

- **endpoint** – str
- **params** – dict
- **data** – bytes

check_api_resp() → None

Return type

None

get_utx_os(*addr: str*, *n_conf*) → List

Parameters

- **addr** – str
- **n_conf** – int (0 or 1)

Returns

List

push_tx(*tx_hex: str*) → Dict

Parameters

tx_hex

Returns

str

get_key(*key_char: str*) → Dict

:param key_char:str :return: Dict

class cryptnox_cli.wallet.btc.BlkHubApi

Bases: object

__init__(network, api_key: str = "", endpoint: str = "")

static get_api(network: str) → str

Get API url for given network

Parameters

network (str)

Returns

API url

Return type

str

get_data(endpoint: str, params: Dict = None, data: bytes = None) → None

Parameters

- endpoint – str
- params – dict
- data – bytes

Returns

None

check_api_resp() → None

Return type

None

get_fee_estimates(blocks=6) → int

get_utx_os(addr: str, _n_conf: int) → List

:param addr:str :param int _n_conf: 0 or 1 :return: list

push_tx(tx_hex: str) → List

Parameters

tx_hex – str

Returns

List

get_key(key_char: str) → List

Parameters

key_char – str

Returns

list

cryptnox_cli.wallet.btc.test_addr(btc_addr: str)

Parameters

btc_addr – str

Returns

class cryptnox_cli.wallet.btc.BTCwallet

Bases: object

Parameters

- **pubkey** – str
- **coin_type** – str
- **api**
- **connection**

PATH = "m/44'/0'/0'/0/0"

__init__(pubkey: str, coin_type: str, api, card) → None

Parameters

- **pubkey** – str
- **coin_type** – str
- **api**
- **connection**

get_utx_os(n_conf: int = 0)

Parameters

n_conf – int (0 or 1)

Returns

get_balance() → float

Returns

float

get_fee_estimate()

prepare(to_addr: str, payment_value: float, fee: float, utx_os: List = None) → float | int

Parameters

- **to_addr** – str
- **payment_value** – float
- **fee** – float
- **utx_os** – pre-fetched UTXOs (fetched in parallel with fee estimate)

Returns

Union[float, int]

send(to_addr: str, payment_value: float, signature: List[bytes]) → str

Parameters

- **to_addr** – str
- **payment_value** – float

Returns

str

static `balance_fm_utxos(utxos)` → float**Parameters**

utxos

Returns

float

static `select_utxos(amount: float, utxos)` → List**Parameters**

- `amount` – float
- `utxos`

Returns

float

```
class cryptnox_cli.wallet.btc.BtcValidator(network: str = 'testnet', fees: int = 2000,  
derivation: str = 'DERIVE', api_key: str = "",  
endpoint: str = "")
```

Bases: object

Class defining Bitcoin validators

```
__init__(network: str = 'testnet', fees: int = 2000, derivation: str = 'DERIVE', api_key:  
str = "", endpoint: str = "")
```

network

Class for validating if value is part of the enum

fees

Class for validating if value is integer

derivation

Class for validating if value is part of the enum

api_key**endpoint****`cryptnox_cli.wallet.validators` module**

Module for defining validators

exception `cryptnox_cli.wallet.validators.ValidationError`

Bases: Exception

Exception for indicating that validation criteria are not met

class `cryptnox_cli.wallet.validators.Validator(valid_values: str = None)`

Bases: ABC

Validator class defining setters and getters

```
__init__(valid_values: str = None)
```

```
abstractmethod validate(value)
```

Parameters

value – Evaluated value

Returns

None

Raises

ValidationError – Validation criteria not satisfied

```
class cryptnox_cli.wallet.validators.AnyValidator(valid_values: str = None)
```

Bases: **Validator**

```
validate(value)
```

Parameters

value – Evaluated value

Returns

None

Raises

ValidationError – Validation criteria not satisfied

```
class cryptnox_cli.wallet.validators.IntValidator(max_value: int = None, min_value:
                                                    int = None)
```

Bases: **Validator**

Class for validating if value is integer

```
__init__(max_value: int = None, min_value: int = None)
```

```
validate(value) → int
```

Parameters

value – Evaluated value

Returns

None

Raises

ValidationError – Validation criteria not satisfied

```
class cryptnox_cli.wallet.validators.EnumValidator(current_enum)
```

Bases: **Validator**

Class for validating if value is part of the enum

```
__init__(current_enum)
```

```
validate(value) → None
```

Parameters

value – Evaluated value

Returns

None

Raises**ValidationError** – Validation criteria not satisfied**class** cryptnox_cli.wallet.validators.**UrlValidator**(*valid_values: str = None*)Bases: **Validator**

Class for validating URLs

validate(*value: str*) → str**Parameters****value** – Evaluated value**Returns**

None

Raises**ValidationError** – Validation criteria not satisfiedcryptnox_cli.wallet.validators.**is_int**(*value: Any*) → bool**Module contents**

The cryptnox_cli.wallet package provides wallet functionality for various cryptocurrencies. It includes Bitcoin wallet operations, Ethereum wallet utilities, and validation functions.

3.1.2 Submodules**3.1.3 cryptnox_cli.config module****3.1.4 cryptnox_cli.enums module**

Module for defining enumerations used throughout the CryptnoxPro application.

class cryptnox_cli.enums.**EthNetwork**(**values*)

Bases: Enum

Class defining possible Ethereum networks

MAINNET = 1**KOVAN** = 42**GOERLI** = 5**RINKEBY** = 4**SEPOLIA** = 11155111**class** cryptnox_cli.enums.**SolanaNetwork**(**values*)

Bases: Enum

Class defining possible Solana networks

MAINNET = 1**DEVNET** = 2**TESTNET** = 3

```
class cryptnox_cli.enums.Command(*values)
    Bases: Enum

    BTC = 'btc'

    CARD_CONFIGURATION = 'card_conf'

    CHANGE_PIN = 'change_pin'

    CHANGE_PUK = 'change_puk'

    CONFIG = 'config'

    ETH = 'eth'

    HISTORY = 'history'

    INFO = 'info'

    INITIALIZE = 'init'

    CARD = 'list'

    SERVER = 'server'

    RESET = 'reset'

    SEED = 'seed'

    SOLANA = 'solana'

    UNLOCK_PIN = 'unlock_pin'

    USER_KEY = 'user_key'

    TRANSFER = 'transfer'

    CERTIFICATE = 'cert'

    MUSIG2 = 'musig2'
```

3.1.5 cryptnox_cli.constants module

Centralized constants for the Cryptnox CLI.

3.1.6 cryptnox_cli.interactive_cli module

3.1.7 cryptnox_cli.main module

3.1.8 Module contents

The main cryptnox_cli package (Cryptnox CLI) exports:

```
cryptnox_cli.__version__: str = "1.0.5"
```

Current version of the Cryptnox CLI package.

4 License

This project is available under the terms of the GNU LESSER GENERAL PUBLIC LICENSE (LGPL) v3.

GNU LESSER GENERAL PUBLIC LICENSE
Version 3, 29 June 2007

Copyright (C) 2007 Free Software Foundation, Inc. <<https://fsf.org/>>
Everyone is permitted to copy and distribute verbatim copies
of this license document, but changing it is not allowed.

This version of the GNU Lesser General Public License incorporates
the terms and conditions of version 3 of the GNU General Public
License, supplemented by the additional permissions listed below.

0. Additional Definitions.

As used herein, "this License" refers to version 3 of the GNU Lesser
General Public License, and the "GNU GPL" refers to version 3 of the GNU
General Public License.

"The Library" refers to a covered work governed by this License,
other than an Application or a Combined Work as defined below.

An "Application" is any work that makes use of an interface provided
by the Library, but which is not otherwise based on the Library.
Defining a subclass of a class defined by the Library is deemed a mode
of using an interface provided by the Library.

A "Combined Work" is a work produced by combining or linking an
Application with the Library. The particular version of the Library
with which the Combined Work was made is also called the "Linked
Version".

The "Minimal Corresponding Source" for a Combined Work means the
Corresponding Source for the Combined Work, excluding any source code
for portions of the Combined Work that, considered in isolation, are
based on the Application, and not on the Linked Version.

The "Corresponding Application Code" for a Combined Work means the
object code and/or source code for the Application, including any data
and utility programs needed for reproducing the Combined Work from the
Application, but excluding the System Libraries of the Combined Work.

1. Exception to Section 3 of the GNU GPL.

You may convey a covered work under sections 3 and 4 of this License without being bound by section 3 of the GNU GPL.

2. Conveying Modified Versions.

If you modify a copy of the Library, and, in your modifications, a facility refers to a function or data to be supplied by an Application that uses the facility (other than as an argument passed when the facility is invoked), then you may convey a copy of the modified version:

- a) under this License, provided that you make a good faith effort to ensure that, in the event an Application does not supply the function or data, the facility still operates, and performs whatever part of its purpose remains meaningful, or
- b) under the GNU GPL, with none of the additional permissions of this License applicable to that copy.

3. Object Code Incorporating Material from Library Header Files.

The object code form of an Application may incorporate material from a header file that is part of the Library. You may convey such object code under terms of your choice, provided that, if the incorporated material is not limited to numerical parameters, data structure layouts and accessors, or small macros, inline functions and templates (ten or fewer lines in length), you do both of the following:

- a) Give prominent notice with each copy of the object code that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the object code with a copy of the GNU GPL and this license document.

4. Combined Works.

You may convey a Combined Work under terms of your choice that, taken together, effectively do not restrict modification of the portions of the Library contained in the Combined Work and reverse engineering for debugging such modifications, if you also do each of the following:

- a) Give prominent notice with each copy of the Combined Work that the Library is used in it and that the Library and its use are covered by this License.
- b) Accompany the Combined Work with a copy of the GNU GPL and this license document.

c) For a Combined Work that displays copyright notices during execution, include the copyright notice for the Library among these notices, as well as a reference directing the user to the copies of the GNU GPL and this license document.

d) Do one of the following:

0) Convey the Minimal Corresponding Source under the terms of this License, and the Corresponding Application Code in a form suitable for, and under terms that permit, the user to recombine or relink the Application with a modified version of the Linked Version to produce a modified Combined Work, in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.

1) Use a suitable shared library mechanism for linking with the Library. A suitable mechanism is one that (a) uses at run time a copy of the Library already present on the user's computer system, and (b) will operate properly with a modified version of the Library that is interface-compatible with the Linked Version.

e) Provide Installation Information, but only if you would otherwise be required to provide such information under section 6 of the GNU GPL, and only to the extent that such information is necessary to install and execute a modified version of the Combined Work produced by recombining or relinking the Application with a modified version of the Linked Version. (If you use option 4d0, the Installation Information must accompany the Minimal Corresponding Source and Corresponding Application Code. If you use option 4d1, you must provide the Installation Information in the manner specified by section 6 of the GNU GPL for conveying Corresponding Source.)

5. Combined Libraries.

You may place library facilities that are a work based on the Library side by side in a single library together with other library facilities that are not Applications and are not covered by this License, and convey such a combined library under terms of your choice, if you do both of the following:

a) Accompany the combined library with a copy of the same work based on the Library, uncombined with any other library facilities, conveyed under the terms of this License.

b) Give prominent notice with the combined library that part of it is a work based on the Library, and explaining where to find the accompanying uncombined form of the same work.

6. Revised Versions of the GNU Lesser General Public License.

The Free Software Foundation may publish revised and/or new versions of the GNU Lesser General Public License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns.

Each version is given a distinguishing version number. If the Library as you received it specifies that a certain numbered version of the GNU Lesser General Public License "or any later version" applies to it, you have the option of following the terms and conditions either of that published version or of any later version published by the Free Software Foundation. If the Library as you received it does not specify a version number of the GNU Lesser General Public License, you may choose any version of the GNU Lesser General Public License ever published by the Free Software Foundation.

If the Library as you received it specifies that a proxy can decide whether future versions of the GNU Lesser General Public License shall apply, that proxy's public statement of acceptance of any version is permanent authorization for you to choose that version for the Library.