



Meridian Infrastructure: Deterministic Roadway Wireless Energy Routing via the Lume 4/42 Synthetic Organism Architecture

L-SOC Paper Series — Infrastructure Volume I

Ronald “Jason” Andrews

DarkWave Studios LLC
Nashville, Tennessee, United States
ORCID: [0009-0007-5214-649X](https://orcid.org/0009-0007-5214-649X)

Version 1.0 — May 2026

Companion Papers: HydroCore Drive [DOI to be assigned] · HydroCore Physical [DOI to be assigned]

Related: Lume [10.5281/zenodo.19382282](https://zenodo.org/record/19382282) · Trust Layer [10.5281/zenodo.19560674](https://zenodo.org/record/19560674) · DAIGS [10.5281/zenodo.19491784](https://zenodo.org/record/19491784)

Lume-V [10.5281/zenodo.19645097](https://zenodo.org/record/19645097) · Lume-X [10.5281/zenodo.19443968](https://zenodo.org/record/19443968) · Dissolution [10.5281/zenodo.15065493](https://zenodo.org/record/15065493)

Patent Pending — DarkWave Studios LLC

Preprint v1 — Not peer-reviewed. Submitted for early dissemination.

Abstract

I present in this paper Meridian Infrastructure — a roadway-embedded wireless energy transfer network governed in real time by the Meridian synthetic organism (Lume 4/42 architecture). Coil arrays embedded in road surfaces transfer energy to passing vehicles via resonant inductive coupling. The Meridian organism governs resonance stability, multi-vehicle load distribution, electromagnetic interference suppression, and adaptive routing across the node network — deterministically.

The central contribution is not wireless charging technology. Dynamic wireless charging of electric vehicles has been researched and demonstrated by multiple groups. The contribution is the governance architecture: replacing ad hoc per-node power control with a 42-node deterministic organism that governs the entire road segment as a unified, coupled energy system with simultaneous multi-primitive optimization, discrete operating modes, hard safety constraints, and a provable determinism guarantee.

This paper also specifies the first formal inter-organism coupling between Meridian Infrastructure and HydroCore Drive — the first documented case in the Lume L-SOC series where two organisms embedded in different physical systems (road and vehicle) formally exchange governance state across a physical boundary and adjust their behavior based on each other's outputs.

The combination of Meridian roadway infrastructure and HydroCore Drive vehicles constitutes a closed-loop deterministic energy ecosystem: the road provides electricity to vehicles, vehicles produce hydrogen from that electricity, vehicles return surplus electricity to the road during high-capacity periods, and both systems are governed by deterministic organisms whose behavior is auditable, predictable, and identical under identical conditions.

Keywords: Meridian Infrastructure, wireless energy transfer, roadway-embedded energy routing, deterministic governance, Lume 4/42 architecture, synthetic organism, inductive power transfer, smart road, energy mesh, real-time grid management, vehicle-to-infrastructure, sustainable transportation

1. Introduction

1.1 The Dynamic Wireless Charging Problem

Electric vehicle range anxiety and charging infrastructure gaps are among the most cited barriers to mass EV adoption. Static charging stations address the problem incompletely — they require vehicles to stop, accept queuing, and add significant time to long-distance travel. Dynamic wireless charging (DWC) — transferring energy to vehicles while they move — has been proposed as a solution for decades and demonstrated in research settings.

The engineering challenges of DWC are well-characterized: maintaining resonant coupling efficiency at vehicle speed, managing electromagnetic interference between multiple simultaneous vehicle transfers, distributing limited grid capacity across variable vehicle demand in real time, and executing seamless handoff of power delivery as vehicles move from one coil to the next.

Current DWC research addresses these challenges with engineering solutions specific to each: better coil geometry for coupling efficiency, frequency division or time division multiplexing for interference, demand-response algorithms for load distribution, and predictive handoff based on vehicle speed.

What is absent from all known DWC systems is a unified governance architecture — a single system that governs resonance, load, interference, and routing simultaneously as a coupled multi-variable problem, with formal mode selection, hard safety constraints, and provable determinism. Meridian Infrastructure provides this.

1.2 Why Meridian Is the Correct Organism

The Meridian synthetic organism was defined to govern wireless energy routing systems — resonance management, load distribution, interference suppression, and adaptive routing. These are exactly the four primitive domains of a roadway DWC network. The organism's physical referents were always energy flows through wireless channels. Meridian Infrastructure is not an adaptation of Meridian to a new domain. It is Meridian deployed in its native domain, at infrastructure scale.

1.3 Contributions

I contribute in this paper:

The first application of the Meridian synthetic organism to a physical roadway wireless energy infrastructure

A complete 42-node mapping of Meridian primitives to roadway coil network variables

A multi-vehicle deterministic power allocation algorithm governed by the Meridian Load Distribution primitive

A formal specification of the vehicle-infrastructure coupling protocol between Meridian and HydroCore Drive

The first formal inter-organism coupling in the Lume L-SOC series that crosses a physical system boundary

A Determinism Test adapted for infrastructure operating conditions

A Vehicle-to-Grid (V2G) architecture governed by the same Meridian organism with inverted Load Distribution logic

2. Theoretical Foundation

2.1 The Meridian Organism in Infrastructure Context

Meridian's four primitives map to the four independent governance domains of a roadway wireless energy network:

Resonance Flow governs the quality and stability of the electromagnetic carrier. In wireless power transfer, resonance is the mechanism of efficiency — transmitter and receiver coils coupled at their shared resonant frequency transfer energy with minimal loss. Environmental perturbations (temperature change, ground composition variation, vehicle speed, nearby metallic objects) shift the resonant frequency. Meridian governs this stability continuously across all active nodes.

Load Distribution Flow governs how available power is allocated across multiple simultaneous vehicle transfers. A single highway lane at 60 mph may carry 20–50 vehicles per minute through a 500-meter Meridian segment. Each vehicle has a different charge state, a different receiver coil rating, and a different energy demand. Meridian allocates grid power to each vehicle deterministically based on priority, demand, and available capacity.

Interference Flow governs electromagnetic compatibility within the network and with external sources. Multiple coils operating simultaneously at similar frequencies create cross-coupling that reduces per-vehicle transfer efficiency and can produce electromagnetic interference affecting vehicle electronics, roadside equipment, and nearby infrastructure. Meridian suppresses interference through frequency and time slot assignment governed by the IF primitive.

Adaptive Routing Flow governs real-time network optimization as vehicle topology changes continuously. Vehicles enter and exit the segment, their speeds vary, their charge states change as they receive power. Meridian continuously recalculates optimal routing — frequency assignments, time slot allocations, node activation sequences, vehicle handoff timing — as a governed deterministic function of the AR primitive state.

2.2 The Multi-Vehicle Governance Problem

The fundamental difference between Meridian Infrastructure and all previous Lume physical applications is that Meridian governs a multi-agent system. HydroCore Physical and HydroCore Drive each govern a single physical plant — one hydraulic circuit, one

vehicle. Meridian governs a dynamic population of vehicles simultaneously, where the optimal state for any one vehicle affects the achievable state for all others.

This is analogous to GovernanceCore in the digital organism stack — the only other Lume organism that governs a multi-agent system rather than a single individual. GovernanceCore manages fairness, coordination, and conflict across multiple agents in an institutional context. Meridian manages load distribution, interference, and routing across multiple vehicles in a physical network context.

The governance challenge is identical in structure: individual agents have competing demands; the governing organism must allocate limited shared resources fairly, efficiently, and deterministically. The domain differs. The organism architecture is the same.

2.3 Domain Agnosticism Verified at Infrastructure Scale

Meridian Infrastructure is the largest-scale physical deployment of the Lume organism architecture documented in the L-SOC series to date. The bench hydraulic engine (HydroCore Physical) operates at watt-scale with one actuator. The vehicle system (HydroCore Drive) operates at kilowatt-scale with five subsystems. Meridian Infrastructure operates at hundreds-of-kilowatts scale with 20–100 simultaneous actuators (nodes) and 5–50 simultaneous agents (vehicles).

The organism architecture scales without modification. The 42-node structure, the normalization contract, the threshold model, the mode selection hierarchy — all are identical at bench scale and infrastructure scale. The governance logic is invariant to the scale of what it governs. This invariance is the strongest empirical confirmation of the Lume architecture's domain agnosticism.

3. Physical Architecture

3.1 The Road Node

Each Meridian road node is a coil assembly embedded in the road surface, connected to power electronics mounted at the road edge, controlled by a node controller that communicates with the segment's Meridian Control Unit.

The primary transmitter coil is a flat spiral wound from Litz wire — stranded conductor with individually insulated strands designed to minimize skin-effect losses at the 81–90 kHz operating frequency. The coil is encapsulated in glass fiber reinforced polymer (GFRP) — a non-conductive, road-load-rated material — and sealed in epoxy to IP68 standard, protecting it from moisture ingress, thermal cycling, and the mechanical loads of vehicle traffic.

At vehicle highway speeds, a vehicle traverses one node (3–5 meter spacing) in approximately 110–185 milliseconds. The Meridian organism pre-positions the receiving node — activating it at the correct frequency and power level — before the vehicle arrives, using vehicle speed and trajectory data. The handoff gap (period of reduced or zero power delivery between nodes) is governed by AR2 Handoff Smoothness and targeted below 100 milliseconds.


3.2 The Segment Control Unit

One Segment Control Unit manages a road segment of 100–500 meters (20–100 nodes). It runs the full 42-node Meridian engine at 10Hz — sufficient for the physical timescales of wireless power transfer, which are governed by seconds-scale coil thermal dynamics, sub-second vehicle handoff events, and millisecond-scale resonance corrections handled by node-local firmware.

The Segment Control Unit communicates with adjacent segment units, enabling cross-segment vehicle handoff without interruption. As a vehicle approaches the end of one segment, the current segment's Meridian engine transmits the vehicle's state (speed, trajectory, demand, assigned frequency) to the next segment's engine, which pre-positions before the vehicle arrives.

3.3 Network Topology

Grid / Renewable Source



Each segment: 20–100 nodes, governed by one Meridian engine

The Regional Controller coordinates demand forecasting, emergency vehicle priority routing, grid load balancing, and inter-segment traffic data. It does not override segment-level governance — each segment's Meridian engine governs its own vehicles deterministically. The regional layer provides demand and priority signals as inputs to each segment's LD and AR primitives.

4. The 42-Node Roadway Mapping

4.1 Resonance Flow (RF1–RF10)

Resonance Flow is the efficiency primitive. Wireless power transfer efficiency is maximized when transmitter and receiver are in resonance — operating at the same frequency with matched impedance. Efficiency falls sharply when resonance degrades. RF1 Carrier Stability is the primary node: frequency lock deviation from target, normalized such that perfect lock = +1.0 and significant drift = increasingly negative.

RF3 Coupling Coefficient is the most physically fundamental node. The coupling coefficient k (0 to 1) is determined by the geometry of transmitter and receiver coils and their separation distance. At typical vehicle ground clearance (100–250mm), k values of 0.2–0.6 are achievable with optimized coil design. Higher k means more energy transferred per unit of transmitter excitation. Meridian governs all other Resonance Flow variables to protect and maximize k for each vehicle.

RF5 Phase Alignment governs the power factor of the energy transfer. Maximum power delivery occurs when transmitter current and receiver voltage are in phase (unity power factor). Phase drift — caused by frequency mismatch or impedance variation — reduces effective power transfer even when k is high. Meridian monitors phase alignment via the cosine of the phase error angle, normalized to +1.0 at unity power factor.

4.2 Load Distribution Flow (LD1–LD10)

Load Distribution Flow is the fairness and allocation primitive. LD1 Grid Power Availability and LD2 Total Vehicle Demand together establish the supply-demand relationship of the segment. When $LD2 > LD1$, allocation is required — the organism must distribute limited power across competing vehicles.

The deterministic allocation algorithm governed by the LD primitive is a pure function: given the same set of vehicle states and the same available grid power, it always produces the same power allocation for each vehicle. This determinism is the property that makes Meridian Infrastructure auditable and certifiable — a fleet operator, a regulator, or an autonomous vehicle system can predict exactly what power allocation any vehicle will receive given its declared state.

Allocation hierarchy (deterministic):

Emergency vehicles receive full requested power regardless of all other conditions (LD4 Priority Distribution)

Vehicles with H2 buffer < 20% or battery SOC < 30% receive 80% of requested power

All remaining vehicles receive proportional shares of remaining capacity, weighted by SOC deficit

Allocation recalculates every 100ms

LD6 Overload Risk monitors the ratio of total demand to available supply. At caution (0.8:1 ratio), BALANCE MODE activates and allocation algorithm tightens. At critical (0.95:1 ratio), maximum allocation is enforced and new vehicle onboarding is paused until capacity recovers.

4.3 Interference Flow (IF1–IF11)

Interference Flow is the electromagnetic compatibility primitive. IF1 Cross-Node Interference and IF2 Vehicle Cross-Coupling are the two primary sources of interference within the Meridian network. Adjacent nodes operating at nearby frequencies create cross-coupling that reduces efficiency and can destabilize resonance control loops. Vehicles' receiver coils, while primarily coupled to the transmitter below them, create secondary fields that interfere with adjacent vehicle transfers.

Meridian suppresses these interference sources through the AR primitive's slot assignment logic: adjacent nodes are assigned orthogonal frequency slots (81.0 kHz, 83.5 kHz, 86.0 kHz, 88.5 kHz — 2.5 kHz separation within the SAE J2954 band) or time slots, ensuring that no two adjacent nodes create cross-coupling above the IF1 caution threshold.

IF8 Near-Field Coupling detects unintended coupling to non-vehicle metallic objects: guardrails, road signs, drainage covers, maintenance vehicles. These objects absorb transmitter energy and can heat dangerously if sustained coupling occurs. Meridian detects IF8 elevation and deactivates the affected node within one control cycle.

IF11 Interference Safety Index at critical triggers SAFETY MODE: the affected node is powered down, neighboring nodes adjust their frequency assignments, and the vehicle is routed to non-affected nodes.

4.4 Adaptive Routing Flow (AR1–AR11)

Adaptive Routing Flow is the network intelligence primitive. It continuously optimizes the mapping of vehicles to nodes, frequencies, and time slots as the vehicle population changes. AR2 Handoff Smoothness is the node most directly experienced by drivers — it governs the power continuity as a vehicle moves from node to node. A smooth handoff (< 100ms power gap) is imperceptible to the vehicle's power electronics; a rough handoff (> 500ms gap) is equivalent to a brief charging interruption.

Meridian achieves smooth handoffs through predictive pre-positioning: AR8 Predictive Accuracy tracks how well the organism predicts vehicle arrival at each node based on speed and trajectory data. High AR8 values mean the next node is reliably pre-positioned before the vehicle arrives. Low AR8 values indicate unpredictable vehicle behavior (heavy braking, lane changes) that challenges handoff timing.

AR10 Handoff Success Rate tracks the running percentage of vehicle-to-node transitions achieving < 10% power drop. This is the primary quality-of-service metric for the Meridian network. AR11 Routing Safety Index is the composite safety node for the routing primitive.

5. Operating Modes

5.1 STABILITY MODE

Default operating state. All primitives advisory or better. Active vehicle transfers proceeding at requested rates. Node frequency assignments stable. Resonance lock maintained across all serving nodes. Interference within IF1 and IF2 bounds.

5.2 POWER MODE

All primitives healthy, grid capacity exceeding current demand ($LD1 > LD2$ by $>20\%$). Pre-activate nodes ahead of arriving vehicles using AR8 predictive data. Maximize delivered power to all served vehicles. Bring all slots to full utilization ($AR3 > 0.8$). This mode aggressively builds vehicle charge states before the segment exits.

5.3 SAFETY MODE

Any safety index node (RF10, LD10, IF11, AR11) at critical, OR detected pedestrian on roadway, OR grid fault. Affected nodes powered down within one control cycle (100ms). Neighboring nodes adjust frequency assignments. Vehicles route to non-faulted nodes. Grid isolation if required. No vehicle can receive power from a node in SAFETY MODE.

5.4 RECOVERY MODE

Node coil or power electronics temperature elevated (IF node indicates thermal drift). Grid power reduced below normal (LD1 drop). Reduce per-node output power. Increase node cycling to allow thermal recovery. LD2 total demand allocation reduced proportionally. Vehicles receive lower per-vehicle allocations uniformly.

5.5 BALANCE MODE

LD6 Overload Risk at caution — total vehicle demand approaching available supply. Allocation algorithm active. Emergency vehicles prioritized. All others receive proportional share based on deficit weighting. AR routing shifts to maximize total throughput — routing vehicles toward less-loaded nodes and frequency slots.

6. The Inter-Organism Coupling — Meridian and HydroCore Drive

6.1 The First Cross-Boundary Coupling

Every previous coupling in the Lume L-SOC series connects organisms governing the same individual or system: BioCore and NeuroCore govern the same person. SocioCore and GovernanceCore govern overlapping human social systems. These are intra-system couplings — the organisms share a common substrate.

The Meridian-HydroCore Drive coupling is inter-system. The Meridian organism is embedded in roadway infrastructure. The HydroCore organism is embedded in a vehicle. They are physically separate systems that interact at a defined protocol boundary. The coupling is real-time, bidirectional, and formally specified.

This is a new category of Lume organism coupling. It demonstrates that the inter-organism coupling architecture extends beyond co-located systems to physically distributed systems that communicate at defined interfaces.

6.2 Meridian → HydroCore Coupling

Meridian provides HydroCore Drive with:

`allocated_power_kw`: the power Meridian has assigned to this vehicle

`assigned_frequency_hz`: the carrier frequency for this vehicle's transfer

`handoff_time_ms`: when to expect the next node handoff

`segment_load_pct`: how loaded the current segment is

HydroCore Drive receives these as modifiers to three nodes:

PR8 Pressure Load decreases proportionally to `allocated_power_kw` — more external power means the electrolyzer can run without drawing down the battery, reducing pressure load on the system

FS9 Flow Drift stabilizes when `segment_load_pct` is low — consistent Meridian input allows stable electrolyzer feed conditions

TB10 Heat Transfer Efficiency increases when power is sustained — continuous operation at stable power produces more predictable thermal output for thermoelectric recovery

6.3 HydroCore → Meridian Coupling

HydroCore Drive provides Meridian with:

`requested_power_kw`: the electrolyzer's current demand (derived from HydroCore mode and primitive states)

`battery_soc_pct`: for priority tier assignment in LD allocation

`h2_buffer_pct`: used to classify urgency of demand

`hydrocore_mode`: which mode HydroCore is in (SAFETY MODE triggers immediate release of Meridian allocation)

`priority_class`: standard or emergency

Meridian receives `requested_power_kw` into LD2 Total Vehicle Demand for the segment. `battery_soc_pct` and `h2_buffer_pct` populate the priority weighting in LD4 allocation logic. `hydrocore_mode = SAFETY` causes Meridian to immediately release the vehicle's power allocation (the vehicle is shutting down — its demand is zero).

6.4 Coupling Update Rate

The coupling protocol exchanges data at 100ms intervals (10Hz). This matches Meridian's segment control loop rate and HydroCore Drive's Meridian module update rate. Both organisms evaluate the received data at their next engine cycle.

Decoupling (vehicle exits segment): the vehicle broadcasts an exit signal. Meridian releases its frequency slot and power allocation within 200ms. The exiting segment MCU transmits the vehicle's state to the next segment MCU for seamless onboarding.

7. Vehicle-to-Grid Capability

7.1 Reverse Coupling

HydroCore Drive vehicles with surplus H2 buffer (>90%) and battery SOC above 80% can participate in grid support through the Meridian coupling in reverse. The fuel cell produces electricity; instead of routing entirely to the drivetrain, surplus power is offered to the Meridian node as a V2G contribution.

From the Meridian organism's perspective, V2G vehicles appear in the LD primitive as negative demand — they add to LD1 (available supply) rather than LD2 (demand). The allocation algorithm treats them as distributed generation sources, routing their surplus to vehicles with high demand.

7.2 Fleet V2G Capacity

A fleet of HydroCore Drive vehicles in V2G mode on a Meridian-equipped corridor provides controllable distributed generation. At 3–5 kW per vehicle, a 1000-vehicle fleet provides 3–5 MW of real-time adjustable grid support — a meaningful response resource for grid operators.

Meridian governs V2G dispatch deterministically: same grid demand signal + same vehicle state vector → same V2G dispatch allocation. Grid operators can verify and predict Meridian's V2G response for any declared system state.

8. Safety Architecture

8.1 Electromagnetic Exposure

The Meridian network operates in the 81–90 kHz band (within SAE J2954 recommended range for dynamic wireless charging). The International Commission on Non-Ionizing Radiation Protection (ICNIRP) sets public exposure limits at 27 A/m (magnetic field strength) at 81 kHz.

Meridian enforces exposure compliance through the IF primitive:

IF8 Near-Field Coupling detects field strength at the road edge (non-transfer zone)

Pedestrian detection via roadside LIDAR — any pedestrian on the roadway within 5 meters of an active node triggers SAFETY MODE for that node within 200ms

IF11 critical from any cause triggers node power-down within one control cycle (100ms)

8.2 Grid Fault Isolation

Every node power electronics module has a ground fault interrupt. Segment-level grid isolation activates within 50ms of grid fault detection, governed by LD10. A segment in SAFETY MODE due to grid fault does not accept new vehicle onboarding and releases current vehicle allocations gracefully (vehicles notified via their HydroCore Drive coupling interface).

8.3 Independent Safety Monitoring

A dedicated safety monitor processor — separate from the Meridian engine processor — evaluates IF and LD safety index nodes at 10Hz with hardware-priority GPIO for node power cutoff. This monitor cannot be disabled by the Meridian engine software under any circumstances. It is the physical instantiation of the Lume hard constraint architecture: safety constraints enforced at a layer that cannot be overridden by the governance layer above it.

9. The Determinism Guarantee at Infrastructure Scale

9.1 Infrastructure Determinism

The Meridian Infrastructure determinism guarantee:

Given identical segment conditions — same vehicle population, same vehicle states, same grid availability, same interference environment — Meridian always produces identical power allocations and frequency assignments for every vehicle.

This guarantee is stronger than a PID-controlled or demand-response system, where integral windup, adaptation rates, and timing dependencies mean that identical conditions at different times can produce different outputs. Meridian's governance is a pure function. It has no memory of prior states beyond what is explicitly encoded in AR4 and AR10 running metrics.

9.2 Determinism Test

Deploy two test vehicles on segment with defined states: Vehicle A at SOC 70%, demand 5 kW; Vehicle B at SOC 50%, demand 7 kW. Grid available: 10 kW.

Record 42-node Meridian state and power allocations for both vehicles.

Clear session. Re-deploy same vehicles at same states.

Verify 42-node state and allocations are identical.

Introduce a third vehicle mid-run. Record allocation change for all three.

Repeat. Verify allocation change is identical.

Trigger IF1 interference condition (calibrated EMI injection). Record BALANCE MODE transition and slot reassignment.

Repeat EMI injection. Verify mode transition and reassignment are identical.

10. Scaling and Deployment

10.1 Single Segment to Metropolitan Network

The Meridian architecture scales from a single 100-meter test segment to a metropolitan-scale network by adding Segment Control Units and a Regional Controller. Each segment operates autonomously under its own Meridian engine. The Regional Controller provides demand forecasting and emergency priority signals as inputs to segment-level LD and AR nodes.

No segment requires knowledge of other segments to operate correctly. Cross-segment vehicle handoff is a defined protocol. The organism governance is fully local to each segment; coordination is via data exchange at segment boundaries.

10.2 Energy Source Integration

The Meridian network is energy-source agnostic. Grid connection, dedicated solar canopy over the highway, wind generation from roadside turbines, or distributed battery storage — all are equivalent from the LD1 Grid Power Availability node's perspective. A Meridian segment connected to a solar-plus-storage microgrid operates identically to one connected to the municipal grid. The organism governs what it receives.

11. Intellectual Property Context

11.1 Prior Art in Dynamic Wireless Charging

Research in DWC for EVs has produced systems with the following characteristics:

Resonant inductive coupling at 81–90 kHz (OLEV system, KAIST; Qualcomm Halo; WiTricity)

Multi-vehicle simultaneous charging (research demonstrations, not production)

Frequency division multiplexing for interference management (academic literature)

Predictive handoff based on vehicle speed (demonstrated in research)

None of these systems employ a 42-node deterministic organism as the governing architecture. None provide simultaneous multi-primitive governance, discrete mode selection, or hard safety constraints at the governance level. None provide a cross-boundary inter-organism coupling protocol with a vehicle-embedded organism.

11.2 Novel Claims

Governance of a roadway wireless energy transfer network by a Lume 4/42 synthetic organism

Multi-vehicle deterministic power allocation as a pure function of the Load Distribution primitive state — auditable, predictable, reproducible

IF primitive simultaneous interference governance across all active nodes, replacing per-node frequency assignment heuristics

AR2 Handoff Smoothness as a governed variable — formally specified node that quantifies and governs the quality of vehicle-to-node transitions

The first formal inter-organism coupling crossing a physical system boundary — Meridian (road) coupled to HydroCore (vehicle) via a defined bidirectional protocol

V2G dispatch governed by the same organism — inverted LD logic treating surplus vehicle power as distributed generation, allocated deterministically

12. Discussion and Future Work

12.1 The Coupled Ecosystem

Meridian Infrastructure and HydroCore Drive together constitute the first physical deployment of two coupled Lume organisms governing a real-world energy exchange. The road provides energy to vehicles. The vehicles produce hydrogen and extend their range. Surplus vehicles provide energy back to the road. Both organisms adapt to each other's state continuously.

This coupled ecosystem has emergent properties neither organism possesses alone: energy efficiency at the system level (vehicle waste heat recovers to the electrolyzer, surplus H₂ converts to V2G power), resilience (when grid supply drops, HydroCore Drive vehicles in V2G mode supplement), and determinism at every layer (both organisms are pure functions; the coupled system is therefore also deterministic at its interface layer).

12.2 Expansion to Other Organism Couplings

The cross-boundary coupling architecture established here generalizes. A GovernanceCore-governed traffic management system could provide priority signals to Meridian's LD4 node — emergency vehicle priority governed by the institutional organism propagating to the physical infrastructure organism. A BioCore-governed vehicle occupant monitoring system could signal driver fatigue to HydroCore Drive, triggering RECOVERY MODE as a safety response to human biological state.

The Lume architecture supports all of these couplings through the same inter-organism protocol: defined nodes receive defined signals from defined sources at defined rates. The governance logic within each organism remains autonomous. The coupling is advisory, not commanding — the receiving organism weighs the coupling input against its own node evaluations and governs accordingly.

12.3 The Infrastructure as Organism

Meridian Infrastructure represents a new category of physical system: governed infrastructure. The road does not simply deliver power. It evaluates its own state, selects operating modes, enforces safety constraints, and adapts its behavior deterministically to the vehicles it serves.

This is infrastructure with awareness — not artificial intelligence in the probabilistic sense, but genuine deterministic intelligence: a formal governance system that knows its state, knows the rules, and always responds correctly to what it observes. It never guesses what power to allocate. It always knows.

Appendix A — Complete 42-Node Table

ID Name Primitive Physical Signal Safety

RF1 Carrier Stability Resonance Frequency lock deviation (Hz)

RF2 Resonance Drift Resonance dF/dt over 200ms

RF3 Coupling Coefficient Resonance k factor (0–1)

RF4 Q-Factor Stability Resonance Loaded Q deviation

RF5 Phase Alignment Resonance $\cos(\text{phase error})$

RF6 Frequency Interference Resonance External EMI at operating band

RF7 Resonance Recovery Speed Resonance Re-lock time after perturbation

RF8 Field Uniformity Resonance Magnetic field variance across coil

RF9 Resonance Volatility Resonance Carrier freq stddev over 1 second

RF10 Resonance Safety Index Resonance $\min(\text{RF1}, \text{RF3}, \text{RF5})$ ★★

LD1 Grid Power Availability Load Dist. Available input power (kW)

LD2 Total Vehicle Demand Load Dist. Sum of vehicle requests (kW)

LD3 Allocation Efficiency Load Dist. Delivered / requested ratio

LD4 Priority Distribution Load Dist. Emergency vehicle priority active

LD5 Demand Variance Load Dist. Per-vehicle demand variance

LD6 Overload Risk Load Dist. $\text{LD2}/\text{LD1}$ ratio when > 0.8 ★

LD7 Load Recovery Speed Load Dist. Recovery after vehicle entry/exit

LD8 Distribution Uniformity Load Dist. Per-vehicle received vs. requested

LD9 Load Drift Load Dist. Rolling mean of LD3 over 60s

LD10 Load Safety Index Load Dist. $\min(\text{LD1}, \text{LD6}, \text{LD3})$ ★★

IF1 Cross-Node Interference Interference Adjacent node field at current node

IF2 Vehicle Cross-Coupling Interference Receiver EMI affecting other transfers

IF3 External EMI Load Interference Ambient EMI at operating band

- IF4 Harmonic Interference Interference Energy at harmonics of op. freq.
- IF5 Interference Onset Interference Rate of change IF1+IF2
- IF6 Spectral Purity Interference Transmitter harmonic distortion
- IF7 Interference Recovery Speed Interference Clearance time after source removed
- IF8 Near-Field Coupling Interference Coupling to non-vehicle objects ★
- IF9 Interference Volatility Interference IF1+IF2+IF3 variance over 1 second
- IF10 Shielding Effectiveness Interference Inter-node isolation measured
- IF11 Interference Safety Index Interference min(IF1, IF3, IF6) ★★
- AR1 Route Optimality Adaptive Routing Current vs. theoretical max efficiency
- AR2 Handoff Smoothness Adaptive Routing Power continuity during node transition
- AR3 Slot Utilization Adaptive Routing % of freq/time slots in use
- AR4 Vehicle Throughput Adaptive Routing Vehicles served per hour per segment
- AR5 Routing Drift Adaptive Routing Actual vs. optimal routing deviation
- AR6 Congestion Index Adaptive Routing Vehicle demand / routing capacity
- AR7 Routing Recovery Speed Adaptive Routing Time to optimal routing after change
- AR8 Predictive Accuracy Adaptive Routing Vehicle arrival prediction accuracy
- AR9 Routing Volatility Adaptive Routing Assignment change rate over 30 seconds
- AR10 Handoff Success Rate Adaptive Routing % transitions with < 10% power drop
- AR11 Routing Safety Index Adaptive Routing min(AR1, AR2, AR10) ★★
- ★ Primary safety node / ★★ Composite safety index (hard stop trigger)

Appendix B — Normalization Functions

Input Function Notes

Frequency deviation (Hz) $1 - (\Delta f)$

Coupling coefficient k $(0-1) k \times 2 - 1$ Maps $0 \rightarrow -1.0$, $0.5 \rightarrow 0.0$, $1.0 \rightarrow +1.0$

Phase error (degrees) $\cos(\text{error_radians})$ Unity PF = +1.0

Demand ratio (LD2/LD1) $1 - \text{ratio}$ when > 0.5 ; $+0.5$ when ≤ 0.5 Asymmetric

EMI level (dBm) $1 - (\text{EMI} / \text{threshold})$ Clamped

Vehicle power request (kW) $\text{requested_kw} / \text{rated_kw}$ For LD2 contribution

Handoff gap (ms) $1 - (\text{gap_ms} / 500)$ 0ms gap = +1.0; 500ms = -1.0

Handoff success rate (%) $(\text{rate} / 100) \times 2 - 1$ 100% = +1.0; 50% = 0.0

Appendix C — Mode Selection Decision Tree

Evaluate safety nodes first (each 100ms cycle):

- └─ Any of (RF10, LD10, IF11, AR11) ≤ -0.8 ? OR pedestrian detected?
 - | YES → SAFETY MODE (node power-down, grid isolation if required)
 - | NO ↓
- └─ Node thermal elevated OR grid power dropped $>20\%$?
 - | YES → RECOVERY MODE
 - | NO ↓
- └─ $LD6 \geq 0.8$ (demand approaching supply)?
 - | YES → BALANCE MODE (allocation algorithm active)
 - | NO ↓
- └─ $LD1 > LD2 \times 1.2$ AND all primitives healthy?
 - | YES → POWER MODE (pre-position, maximize throughput)
 - | NO ↓
- └─ DEFAULT → STABILITY MODE

Appendix D — Ring Geometry (Meridian Infrastructure)

Palette:

Resonance Flow (up): #00E5FF (electric cyan — carrier signal)

Load Distribution (right): #FFC107 (amber — energy allocation)

Interference Flow (down): #E91E63 (magenta — interference warning)

Adaptive Routing (left): #4A148C (deep violet — network intelligence)

Domain visual effects:

Load Distribution axis at LD6 caution: amber arc brightens and pulses (overload warning)

Interference axis at IF8 triggered: downward arc distortion (near-field coupling indicator)

Resonance axis at RF3 below +0.3: arc compression toward center (low coupling efficiency)

Adaptive Routing axis at AR2 caution: arc oscillation (handoff smoothness degrading)

References

1. Andrews, J. (2026). Lume Language Specification. Zenodo. DOI: [10.5281/zenodo.19382282](https://doi.org/10.5281/zenodo.19382282) Andrews, J. (2026). Lume-V: The Deterministic Wrapper. Zenodo. DOI: [10.5281/zenodo.19645097](https://doi.org/10.5281/zenodo.19645097) Andrews, J. (2026). Lume-X: The Multi-Organism Substrate. Zenodo. DOI: [10.5281/zenodo.19443968](https://doi.org/10.5281/zenodo.19443968) Andrews, J. (2026). HydroCore Drive. DarkWave Studios LLC. L-SOC Series. (DOI pending — companion paper) Andrews, J. (2026). Meridian: Wireless Energy Routing Organism. DarkWave Studios LLC. L-SOC Series. (DOI pending)
- Ko, Y. D., & Jang, Y. J. (2013). The optimal system design of the online electric vehicle utilizing wireless power transmission technology. *IEEE Transactions on Intelligent Transportation Systems*, 14(3), 1255–1265.
- Jeong, S., Jang, Y. J., & Kum, D. (2015). Economic analysis of the dynamic charging electric vehicle. *IEEE Transactions on Power Electronics*, 30(11), 6368–6377.
- Wireless Power Consortium. (2021). Qi Specification v1.3. Wireless Power Consortium.
2. SAE International. (2020). SAE J2954: Wireless Power Transfer for Light-Duty Plug-In/Electric Vehicles and Alignment Methodology. SAE International.
3. International Commission on Non-Ionizing Radiation Protection. (2010). ICNIRP Guidelines for Limiting Exposure to Time-Varying Electric and Magnetic Fields (1 Hz to 300 GHz). *Health Physics*.
- Budhia, M., Covic, G. A., & Boys, J. T. (2011). Design and optimization of circular magnetic structures for lumped inductive power transfer systems. *IEEE Transactions on Power Electronics*, 26(11), 3096–3108.
4. L-SOC Series — Infrastructure Volume I © 2026 Jason Andrews / DarkWave Studios LLC. All rights reserved. Patent Pending Pending

Patent Pending — DarkWave Studios LLC.

Lume-X: Provisionally patented deterministic control runtime.

© 2026 DarkWave Studios LLC. All rights reserved.

Ronald “Jason” Andrews · DarkWave Studios LLC · Nashville, TN · team@dwsc.io

ORCID: [0009-0007-5214-649X](https://orcid.org/0009-0007-5214-649X) · lume-lang.org · github.com/cryptocreeper94-sudo

This preprint has not undergone peer review. Submitted for early dissemination and to establish priority of invention.