



Verdara Ultra: A Four-Primitive Deterministic Outdoor Flow Organism for Ultra-Distance Navigation, Safety, and Environmental Governance

*Terrain Flow · Weather Flow · Environmental Flow · Biological Flow —
The Lume 4/42 Architecture Applied to the Outdoor Physical Domain*

Ronald “Jason” Andrews

*DarkWave Studios LLC
Nashville, Tennessee, United States
ORCID: [0009-0007-5214-649X](https://orcid.org/0009-0007-5214-649X)*

Version 1.0 — May 2026

Related: Lume [10.5281/zenodo.19382282](https://zenodo.org/record/19382282) · Trust Layer [10.5281/zenodo.19560674](https://zenodo.org/record/19560674) · DAIGS
[10.5281/zenodo.19491784](https://zenodo.org/record/19491784)
Lume-V [10.5281/zenodo.19645097](https://zenodo.org/record/19645097) · Lume-X [10.5281/zenodo.19443968](https://zenodo.org/record/19443968) · Dissolution
[10.5281/zenodo.15065493](https://zenodo.org/record/15065493)

Patent Pending — DarkWave Studios LLC
Systems and Methods for Deterministic Multi-Layer Wireless Energy Routing
Lume-X: Provisionally patented deterministic control runtime
Patent Pending — DarkWave Studios LLC

Preprint v1 — Not peer-reviewed. Submitted for early dissemination.

Abstract

I present Verdara Ultra, a Lume-native deterministic outdoor flow organism designed for ultra-distance navigation, environmental safety governance, and continuous terrain-weather-biological state management. Verdara Ultra implements the Lume 4/42 organism architecture — four irreducible flow primitives governing forty-two operational nodes — in the outdoor physical domain. The four primitives are Terrain Flow, Weather Flow, Environmental Flow, and Biological Flow. The forty-two nodes encode the full state space of outdoor conditions from elevation and slope grade through lightning risk, air quality, wildlife hazard, and rescue accessibility.

Unlike conventional navigation systems that provide static route suggestions or probabilistic hazard warnings, Verdara Ultra operates as a deterministic organism: it maintains a continuous internal state of outdoor equilibrium, enforces hard constraint rules that halt forward progress when any node crosses a critical threshold, and re-routes deterministically when conditions degrade. The organism never guesses, never hides risk, and never produces recommendations that violate its governing invariants.

Verdara Ultra is governed by a seven-rule deterministic routing engine that integrates risk-weighted path scoring, time-window alignment with safe weather corridors, resource-aware routing (water, shelter, bailout points), and user-aligned risk envelope calibration. The system is scale-invariant and fractal: any spatial segment from a one-kilometer trail section to a multi-day expedition can be represented as its own 4/42 micro-organism, enabling recursive environmental state modeling at any resolution.

The architecture includes a formal 2D/3D visual geometry specification mapping all forty-two node states to a polar coordinate ring with radial state encoding, four-axis primitive core, and extruded three-dimensional time and scale stacks. No deployment system currently exists for Verdara Ultra. This paper establishes the formal theoretical, architectural, and geometric foundation.

Keywords: deterministic outdoor navigation, Lume synthetic organism, environmental flow governance, ultra-distance safety, 4/42 organism architecture, terrain flow, weather flow, biological hazard, deterministic routing, outdoor equilibrium

1 Introduction

1.1 The Problem with Outdoor Navigation Today

Every year, experienced outdoor practitioners — trail runners, mountaineers, backpackers, ski tourers, expedition athletes — make decisions in complex, dynamic environments with fragmented information and no coherent decision framework. Weather data arrives from one source. Terrain information from another. Wildlife hazard from a third. Air quality from a fourth. None of these sources communicate. None enforce priority relationships between domains. None maintain a continuous internal model of environmental state that could catch a cascade before it becomes a crisis.

The result is predictable: decisions are made sequentially across disconnected data streams, risk factors are evaluated in isolation, and the interactions between domains — the weather condition that makes a technically simple terrain segment lethal, the hydration constraint that makes an otherwise acceptable route a survival decision, the wildlife hazard that closes an apparent bailout option — are left to human judgment under stress.

No existing navigation system solves this problem. GPS systems provide routing without environmental awareness. Weather apps provide atmospheric data without terrain integration. Hazard alert systems provide warnings without routing consequence. None maintain a unified model of outdoor state across all relevant domains simultaneously. None enforce hard constraints. None re-route automatically when a threshold is crossed. None operate deterministically.

1.2 The Organism Reframe

The foundational insight of this work is that outdoor navigation is not a routing problem in the map-theoretic sense. It is a flow governance problem. The outdoors is a system of continuous, interacting flows — terrain flows that govern traversability and effort, weather flows that govern exposure and thermal risk, environmental flows that govern sensory clarity and physiological comfort, and biological flows that govern encounter hazard and resource availability. A human moving through this system is not following a static graph. They are navigating a dynamic field that changes continuously and interacts with itself.

Verdara Ultra treats outdoor navigation as a flow governance problem and implements it as a Lume-native deterministic organism. The 4/42 organism architecture — four irreducible flow primitives governing forty-two operational nodes — is the natural

structure for a system that must maintain equilibrium across multiple continuous interacting domains, enforce hard safety constraints, and adapt its outputs deterministically as conditions change.

1.3 The Verdara Ultra Architecture

Verdara Ultra is a 4/42 deterministic outdoor flow organism. The four primitives are Terrain Flow, Weather Flow, Environmental Flow, and Biological Flow. The forty-two nodes encode the full outdoor state space:

- **Terrain Flow (T1–T10):** Elevation, slope, terrain type, surface stability, technicality, trail quality, obstacle density, traction quality, water crossing complexity, route ambiguity.
- **Weather Flow (W1–W10):** Temperature, wind speed, wind direction, precipitation type and intensity, storm proximity, lightning risk, thermal load, weather volatility, safe weather window.
- **Environmental Flow (E1–E11):** Humidity, dew point, fog presence, visibility distance, sunlight intensity, UV index, air quality index, pressure trend, day/night phase, light pollution, sensory clarity index.
- **Biological Flow (B1–B11):** Wildlife density and risk, insect density, pathogen risk, vegetation density, edible resource availability, water availability, allergen load, human density, land use constraints, rescue accessibility.

1.4 Novel Contributions

1. **The first formal 4/42 outdoor flow organism specification** — applying the Lume synthetic organism architecture to the outdoor physical domain with complete node definitions and threshold tables.
2. **Deterministic hard constraint routing** — a formal rule system that halts forward progress and re-routes deterministically when any node crosses a critical threshold.
3. **Cross-domain interaction modeling** — a unified state model capturing interactions between terrain, weather, environmental, and biological conditions.
4. **Scale-invariant fractal organism structure** — any spatial segment from one kilometer to a full multi-day expedition can be represented as its own 4/42 micro-organism.
5. **Formal visual geometry specification** — a 2D polar coordinate ring and 3D extrusion model with deterministic, reproducible, state-driven encoding.

6. **User-aligned risk envelope calibration** — adjusting node thresholds to individual user profiles while preserving deterministic routing logic.

1.5 Scope and Honest Limitations

Verdara Ultra is a theoretical and architectural framework. No deployment system exists at time of writing. All node thresholds and scoring functions are initial specifications subject to empirical validation. The system is designed for the domain of ultra-distance outdoor movement. It is not designed for urban navigation, indoor environments, or vehicular routing.

2 Background and Related Work

2.1 Outdoor Navigation Systems

Modern outdoor navigation systems divide into three categories. Turn-by-turn GPS navigation systems (Garmin InReach, Coros, Apple Maps) provide route guidance against static map data with limited environmental input. Weather overlay systems (Windy, Mountain Forecast, Dark Sky) provide atmospheric data with no terrain integration and no routing consequence. Hazard alert systems (AvalancheCenter, lightning warning services, fire watch platforms) provide domain-specific warnings with no cross-domain synthesis. The gap between what these systems provide and what a coherent outdoor state model would provide is structural, not incremental.

2.2 Multi-Domain Environmental Risk Assessment

Academic literature on multi-domain environmental risk assessment is extensive but fragmented. Research in mountaineering risk assessment focuses primarily on avalanche, rockfall, and weather exposure as independent hazard categories. Wilderness medicine literature addresses biological and thermal hazards but does not integrate them into navigation frameworks. Ultra-distance sports science models physiological thresholds without environmental state integration. No published framework unifies terrain, weather, environmental, and biological hazard assessment into a continuous, routing-coupled state model.

2.3 Deterministic Control Systems for Physical Domains

The Lume ecosystem has established a formal framework for deterministic control of physical flow domains. Meridian demonstrated the complete instantiation of the 4/42 organism architecture in the energy domain. The Trust Layer Ecosystem established the governance framework under which Lume organisms operate. Verdara Ultra is the second complete physical instantiation of the Lume 4/42 organism architecture, following Meridian, and the first in a non-infrastructure physical domain.

2.4 The Synthetic Organism Model

The Lume Synthetic Organism model defines deterministic constructs that exhibit biological structural properties — identity, metabolism, homeostasis, self-healing — without being alive. Verdara Ultra is a Type 3 Synthetic Organism: it maintains continuous environmental homeostasis (outdoor equilibrium), heals routing decisions when conditions change, and enforces identity constraints against every output it produces.

3 System Overview — The Verdara Ultra Organism

3.1 Core Thesis

Verdara Ultra ingests outdoor signals — terrain, weather, environmental, biological — maintains a stable internal state of outdoor equilibrium, and outputs deterministic routing, warnings, and recommendations for ultra-distance movement and survival. Outdoor equilibrium is not a static condition. It is a continuously maintained relationship between the organism's four flow primitives.

3.2 The 4/42 Structure

```
Primitive State Vector P:
  P = [TerrainFlow, WeatherFlow, EnvironmentalFlow, BiologicalFlow]
  Each element is a scalar in [-1.0, +1.0]

Node State Ring R:
  R = [T1, T2, ..., T10, W1, W2, ..., W10, E1, E2, ..., E11, B1,
  B2, ..., B11]
  Each element is a normalized scalar in [-1.0, +1.0]
```

The organism's routing engine, warning system, and constraint enforcement logic all operate on P and R. They never operate on raw sensor data directly.

3.3 Fractal and Scale-Invariant Structure

Verdara Ultra is fractal. Any spatial or temporal segment of the outdoor environment can be represented as its own 4/42 micro-organism: a one-kilometer trail section has its own P and R vectors; a day's route has its own P and R vectors computed as a spatial average or worst-case envelope; a multi-day expedition has its own P and R vectors computed as a temporal envelope. This enables the routing engine to operate simultaneously at multiple scales.

3.4 Organism Identity

Verdara Ultra maintains a fixed organism identity across all operations, defined by its governing invariants, primitive definitions, node definitions and threshold table, and routing engine rules. No recommendation produced by Verdara Ultra can violate these identity constraints. An output that violates a governing invariant is not a Verdara Ultra output. This is the organism's primary safety guarantee.

4 The Four Verdara Primitives

4.1 Terrain Flow

Terrain Flow governs traversability, effort, risk, and speed envelope across the physical landscape. It represents the mechanical interaction between the user and the ground. A positive Terrain Flow state indicates a surface that is stable, well-defined, technically accessible, and unambiguous. A negative state indicates instability, technical demand, obstacle density, or route ambiguity.

Terrain Flow is governed by ten nodes (T1–T10). The dominant nodes are T2 (Slope/Grade), T4 (Surface Stability), and T5 (Technicality), as these most directly govern whether forward progress is physically possible. T10 (Route Ambiguity) is particularly important for ultra-distance navigation, where loss of route definition compounds with fatigue and weather exposure to produce disproportionate risk.

4.2 Weather Flow

Weather Flow governs exposure risk, thermal load, and safe operational windows across all atmospheric conditions. A positive Weather Flow state indicates stable, benign atmospheric conditions. A negative state indicates exposure risk, thermal stress, or imminent closure of safe operational windows.

Weather Flow is governed by ten nodes (W1–W10). The most safety-critical nodes are W7 (Lightning Risk) and W6 (Storm Proximity), which can cross from advisory to critical faster than any other nodes. W10 (Safe Weather Window) is the temporal integration node — it synthesizes the current state of all other Weather Flow nodes into a time-bounded estimate. Weather Flow is the most dynamic primitive.

4.3 Environmental Flow

Environmental Flow governs sensory clarity, physiological comfort, and the quality of the human-environment interface. It captures properties that change more slowly (humidity, air quality, UV, pressure trend) and those related to light and visibility. A positive state indicates good judgment and efficient movement are supported. A negative state indicates degraded perception, increased fatigue, or impaired physiological function.

Environmental Flow is governed by eleven nodes (E1–E11). The most pervasive influence is E4 (Visibility Distance), which interacts with T5 (Technicality) to produce disproportionate risk when both are degraded. E7 (Air Quality) is particularly relevant in fire-prone landscapes. E11 (Sensory Clarity Index) is a composite node integrating all other Environmental Flow nodes.

4.4 Biological Flow

Biological Flow governs encounter risk, resource availability, and biological safety across the living landscape. A positive state indicates low encounter risk, adequate resources, and accessible support. A negative state indicates elevated hazard, depleted resources, or inaccessible rescue.

Biological Flow is governed by eleven nodes (B1–B11). The most operationally significant for ultra-distance navigation are B7 (Water Availability), B11 (Rescue Accessibility), and B10 (Land Use Constraints). B2 (Wildlife Risk) is the most safety-critical biological hazard node.

5 The 42-Node Outdoor State Ring

5.1 Terrain Flow Nodes (T1–T10)

Node	Name	Description
T1	Elevation	Absolute altitude. Governs oxygen availability, weather exposure, and effort.
T2	Slope/Grade	Percentage grade. Primary determinant of uphill effort and downhill stability risk.
T3	Terrain Type	Categorical: trail, gravel, scree, talus, snow, ice, rock slab, or open vegetation.
T4	Surface Stability	Dynamic assessment of surface reliability under load.
T5	Technicality	Required skill level, mapped to the Yosemite Decimal System (Class 1–5).
T6	Trail Quality	Condition of established trail infrastructure: clear, faint, intermittent, or absent.
T7	Obstacle Density	Frequency and severity of physical obstacles: blowdown, boulder fields, stream crossings.
T8	Traction Quality	Effective friction between footwear and surface. Low traction on steep terrain is the primary fall risk factor.
T9	Water Crossing	Technical difficulty and risk of river/creek crossings: ankle-depth through waist-depth+.
T10	Route Ambiguity	Number of plausible but incorrect route choices visible from current position.

5.2 Weather Flow Nodes (W1–W10)

Node	Name	Description
W1	Temperature	Ambient dry-bulb temperature at current elevation with lapse rate correction.
W2	Wind Speed	Mean wind speed. Interacts with W1 via wind chill for effective thermal exposure.
W3	Wind Direction	Cardinal direction relative to route. Headwind, crosswind, and tailwind effects.
W4	Precipitation Type	Classification: none, light rain, heavy rain, hail, sleet, snow, whiteout.
W5	Precipitation Intensity	Rate of precipitation with nonlinear saturation effects on traction and crossings.
W6	Storm Proximity	Distance to nearest active thunderstorm cell in miles. Most time-sensitive node.
W7	Lightning Risk	Integrated lightning strike probability. Binary-threshold: critical overrides all routing.
W8	Thermal Load	Combined physiological heat/cold burden from temperature, wind, humidity, solar radiation.
W9	Weather Volatility	Rate and unpredictability of atmospheric change. Triggers conservatism multiplier.
W10	Safe Weather Window	Estimated remaining time in safe operating window. Temporal integration node.

5.3 Environmental Flow Nodes (E1–E11)

Node	Name	Description
E1	Humidity	Relative humidity. Impairs thermoregulation at high temps, condensation risk at low temps.
E2	Dew Point	Atmospheric dew point. When approaching ambient, moisture condensation impacts traction/stability.
E3	Fog/Cloud Presence	Density of fog, mist, or cloud at surface level. Proximate cause of visibility degradation.
E4	Visibility Distance	Effective sighting distance. Most operationally critical Environmental node.
E5	Sunlight Intensity	Available solar illumination combining cloud cover, time of day, and terrain shading.
E6	UV Index	UV radiation intensity, increasing sharply with altitude. Cumulative physiological stressor.
E7	Air Quality Index	Airborne particulates and pollutants. Critical in fire-smoke environments.
E8	Pressure Trend	Rate and direction of barometric pressure change. Leading indicator for weather deterioration.
E9	Day/Night Phase	Position relative to sunrise/sunset. Governs lighting, wildlife activity, thermoregulation.
E10	Light Pollution	Ambient artificial light interference with night navigation.
E11	Sensory Clarity Index	Composite node integrating E1–E10 into overall perceptual quality assessment.

5.4 Biological Flow Nodes (B1–B11)

Node	Name	Description
B1	Wildlife Density	Estimated population density of potentially hazardous wildlife in current zone.
B2	Wildlife Risk	Probability and severity of dangerous encounter given B1 and behavioral context.
B3	Insect Density	Density of biting/stinging insects. At extreme levels, a genuine safety hazard.
B4	Pathogen Risk	Exposure probability for waterborne, vector-borne, or contact-transmitted pathogens.
B5	Vegetation Density	Density of movement-impeding vegetation: brush, deadfall, dense undergrowth.
B6	Edible Resources	Emergency forageable food availability. Resilience node for extreme duration.
B7	Water Availability	Distance to nearest reliable water source. Highest-weight biological node for ultra-distance.
B8	Allergen Load	Environmental allergen concentration. User-profile-dependent threshold node.
B9	Human Density	Other human presence density. Affects rescue access and resource competition.
B10	Land Use Constraints	Regulatory/legal restrictions: open, advisory, restricted, prohibited. Hard boundary.
B11	Rescue Accessibility	Estimated time to emergency rescue. Single most important resilience node.

6 Node Threshold Architecture

6.1 Three-Band Threshold Model

- **Advisory:** Conditions outside optimal, heightened awareness required. No routing changes triggered.
- **Caution:** Meaningful risk requiring behavioral modification. Routing engine applies conservatism multipliers and evaluates alternatives.

- **Critical:** Safety constraint violation. Routing engine halts forward progress, proposes alternatives, and escalates warnings.

6.2 Normalized State Mapping

```
if raw_value is within optimal band:      s = +0.3 to +1.0
if raw_value crosses advisory threshold:  s =  0.0 to -0.3
if raw_value crosses caution threshold:   s = -0.4 to -0.7
if raw_value crosses critical threshold:  s = -0.8 to -1.0
```

6.3 Primitive State Aggregation

```
TerrainFlow =  $\Sigma(w_i \times T_i) / \Sigma(w_i)$  for  $i = 1$  to 10
```

Safety-critical nodes receive elevated weights:

```
T2, T4, T5 elevated within Terrain Flow
W6, W7, W10 elevated within Weather Flow
E4, E11 elevated within Environmental Flow
B7, B11 elevated within Biological Flow
```

7 The Deterministic Routing Engine

7.1 Inputs and Outputs

Inputs: Current position and elevation; waypoints, bailout points, destination; complete 42-node state vector R ; time budget; user profile (fitness, gear, experience, risk tolerance); historical node data.

Outputs: Recommended next route segment; pace envelope (min/max speed); ordered warning list; opportunity signals; adaptation suggestions (rest, shelter, hydration, bailout evaluation).

7.2 The Seven Routing Rules

Rule 1 — Hard Constraint Enforcement: If any node crosses its critical threshold ($s \leq -0.8$), the routing engine halts forward progress, computes alternatives, escalates the critical node to primary warning position, and suppresses all “continue forward” recommendations until the node returns to caution-band or better. Hard constraints are not negotiable.

Special case: W7 (Lightning Risk) and B10 (Land Use — Illegal) trigger hard constraints at the caution threshold, not the critical threshold. These nodes have asymmetric consequence structures justifying lower trigger thresholds.

Rule 2 — Risk-Weighted Path Scoring:

$$\text{Score} = \alpha \cdot \text{Progress} - \beta \cdot \text{Risk} + \gamma \cdot \text{Resilience} - \delta \cdot \text{Effort}$$

Progress = advancement toward route objective (distance, elevation)

Risk = function of node states across segment, weighted by criticality

Resilience = access to water (B7), bailout points, and rescue (B11)

Effort = metabolic cost given terrain, grade, and user fitness

$\alpha, \beta, \gamma, \delta$ = weighting coefficients set by user risk profile

Rule 3 — Time-Window Alignment: All route segments are scored against W10 (Safe Weather Window). If segment duration exceeds W10, a time-window penalty is applied. If W10 falls below 30 minutes, caution-level weather warning triggers. Below 10 minutes: critical constraint — halt and shelter.

Rule 4 — Resource-Aware Routing: No route segment may extend beyond safe water carry capacity (B7). When thermal load (W8) is at caution, routing prioritizes shelter. Routing maintains a minimum viable bailout option at all times.

Rule 5 — Dynamic Re-Evaluation: All forty-two nodes are recomputed at every sensing cycle. The routing engine re-evaluates at each cycle. A segment recommended in cycle N may not be recommended in cycle N+1 if node states have changed.

Rule 6 — User-Aligned Risk Envelope: The user risk profile modifies threshold sensitivity without changing underlying logic. High experience/gear widens advisory bands. Low experience/gear narrows them. Critical thresholds are never modifiable by user profile.

Rule 7 — Conservatism Multiplier: When W9 (Weather Volatility) or E11 (Sensory Clarity) is at caution or above, advisory thresholds are treated as caution; caution thresholds are treated as critical. This prevents recommendations safe in current conditions but with high exposure if conditions deteriorate rapidly.

8 Visual Geometry — 2D and 3D Representation

8.1 Geometry Purpose

Verdara Ultra's visual geometry is a direct, deterministic encoding of outdoor state — not a dashboard readout but a living organism diagram where the shape, color, and position of every visual element is driven by the live state vector. A practitioner who knows the geometry can read outdoor equilibrium at a glance.

8.2 The 4/42 Core and Ring

The organism renders as a center core with four primitive axes and an outer ring of forty-two nodes:

```
Core (four axes, clockwise from top):
Up (0°):      Terrain Flow      - earth brown/ochre
Right (90°):   Weather Flow     - storm grey/electric white
Down (180°):   Environmental Flow - sky blue/mist cyan
Left (270°):   Biological Flow  - forest green/deep moss
```

Each axis length encodes aggregate primitive health (−1.0 to +1.0). Axis thickness encodes volatility (rate of change). A thick, short axis signals a rapidly degrading primitive requiring immediate attention.

```
Ring (42 nodes, clockwise from top):
Arc 1 (0°-85.7°):    T1-T10, Terrain nodes
Arc 2 (85.7°-171.4°): W1-W10, Weather nodes
Arc 3 (171.4°-265.7°): E1-E11, Environmental nodes
Arc 4 (265.7°-360°): B1-B11, Biological nodes
```

Each node is a small circle or hexagon. Fill color encodes state: green (optimal), yellow (advisory), orange (caution), red (critical). Radial position encodes state value: nodes pulse outward at +1.0, rest on the base ring at 0.0, and retract inward at −1.0.

8.3 2D View

The primary 2D view renders the core and ring top-down with: intra-primitive arc connections (faint lines linking nodes within the same primitive); key correlation links (T2–T8, W1–W8, E3–E4, B1–B2); primitive envelopes (smooth contour lines forming

four colored “petals” from the core); route overlay (recommended path color-coded by risk level, with waypoints and bailout markers); and hard constraint indicator (blocked arc segment with stop symbol when Rule 1 triggers).

8.4 3D Representation

The 3D view extrudes the 2D organism along the Z-axis with two options:

- **Time Stack:** Each Z-slice is a snapshot of the organism at a point in time. Node trajectories become vertical ribbons. Threshold crossings appear as sharp color transitions. Post-expedition analysis mode.
- **Scale Stack:** Bottom slice is the micro-scale (current 500 m segment), middle slice is the route-day scale, top slice is the expedition scale. Vertical pillars connect corresponding nodes across scales, revealing how local conditions aggregate into higher-level risk.

Primitive lobes — semi-transparent 3D volumes enclosing each primitive’s nodes — expand and contract with aggregate primitive state. A collapsing lobe provides immediate gestalt-level recognition of a failing primitive without requiring node-by-node inspection.

9 Runtime Behavior and Operating Modes

9.1 Core Runtime Loop

```
Sense → Interpret → Decide → Act
```

```
Sense:      Ingest all available data sources – GPS, atmospheric
sensors, weather feed,
```

```
            wildlife databases, map overlays, user self-report.
```

```
Interpret: Map raw inputs to the 42-node state ring. Compute P.
Identify threshold
```

```
            crossings. Update the route segment model.
```

```
Decide:      Apply the seven routing rules. Compute segment scores.
Generate warnings.
```

```
Act:         Emit recommendations, warnings, pace envelope, adaptation
suggestions.
```

```
            Update the visual geometry. Prepare for next cycle.
```

9.2 Operating Modes

Mode	Condition	Behavior
Nominal	All primitives advisory or better	Standard thresholds. Standard pace envelope. Informational warnings.
Caution	One or more primitives at caution	Conservatism multiplier active. Pace reduced. Alternatives computed and held ready. Elevated warnings.
Constraint	One or more nodes at critical	Hard constraint Rule 1 active. Alternatives proposed. Progress may halt. Mandatory warnings.
Emergency	Multiple critical nodes across multiple primitives, or W7/B11 at extreme-critical	All routing suspended except toward nearest bailout. Emergency communication recommended. Highest alert state.

10 Global Invariant Enforcement

Verdara Ultra enforces ten global invariants inherited from the Lume organism framework. Every output is validated against all ten before emission.

INV-1 Determinism: Given identical inputs, Verdara Ultra produces identical outputs. No randomness, no probabilistic guessing.

INV-2 Identity Primacy: The organism's governing rules take precedence over any user preference or external instruction that would violate them.

INV-3 Safety Dominance: Safety constraints (hard constraint Rule 1) cannot be overridden by routing efficiency, user preference, or time pressure.

INV-4 Governance Supremacy: Land use constraints (B10) are enforced as hard constraints regardless of routing cost.

INV-5 Physical Realism: All recommendations are physically achievable within the user's current conditions and profile. The organism never recommends biomechanically or physiologically impossible actions.

INV-6 Domain Integrity: Terrain, weather, environmental, and biological assessments are maintained as distinct primitives. No primitive's state masks or overrides another.

INV-7 Abstraction Coherence: Node states are always derived from raw inputs via the normalized mapping function. No node state is manually overridden.

INV-8 Semantic Graph Consistency: Cross-domain node interactions ($T2 \leftrightarrow T8$, $W1 \leftrightarrow W8$, $E3 \leftrightarrow E4$) are always evaluated bidirectionally.

INV-9 Ontology Alignment: All node definitions, threshold bands, and primitive groupings are consistent with the published Verdara Ultra specification.

INV-10 Safety-First Failure: When sensor data is unavailable, corrupted, or ambiguous, the organism defaults to the most conservative interpretation. Missing data defaults to caution-band, not optimal-band.

11 Implementation Considerations

11.1 Data Inputs

- **Full sensor mode:** GPS position with sub-10 m accuracy, real-time atmospheric data from on-body or nearby sensors, live weather feed with storm-cell tracking, wildlife hazard database access, satellite communication for rescue accessibility updates.
- **Partial sensor mode:** GPS position, cached weather forecast, manual terrain assessment. Nodes without live data default to caution-band values, and the conservatism multiplier is applied automatically.
- **Minimal mode:** GPS position and user self-report only. Verdara Ultra can operate using historical terrain classifications and climatological baselines.

11.2 User Profile Integration

Parameter	Effect
Fitness Level	Affects metabolic effort calculation (Rule 2, δ coefficient)
Gear Inventory	Affects thermal threshold sensitivity (W1, W8 advisory bands)
Experience Rating	Affects technicality threshold (T5 advisory band)
Risk Tolerance	Affects α and β weighting in path scoring function
Medical Constraints	Adds hard-constraint nodes for individual conditions (altitude sensitivity, allergy history)

11.3 Communication Architecture

Verdara Ultra requires a communication architecture for full capability: inbound (weather data, wildlife alerts, land use updates, satellite position) and outbound (route plan, emergency beacon activation, status transmission). In satellite communication blackout conditions, the organism operates in offline mode with cached data and automatic conservatism multipliers.

12 Evaluation Framework

12.1 Phase 1 — Simulation Validation

Validate the routing engine against a library of historical outdoor incident case studies. For each incident, reconstruct the 42-node state vector at the time of the decision that led to the incident. Verify that the routing engine would have triggered the appropriate warning or hard constraint. Target: 90% correct constraint identification on a test library of 100 documented incidents across terrain, weather, and biological domains.

12.2 Phase 2 — Controlled Field Testing

Deploy Verdara Ultra with a test cohort of experienced ultra-distance athletes across three terrain and climate domains (alpine, desert, forest). Collect continuous node state data and routing recommendations. Validate normalized state mapping calibration against direct observational assessment by domain experts.

12.3 Phase 3 — Production Deployment

Deploy in a production companion application for ultra-distance athletes. Collect continuous operational data. Validate node threshold calibrations against actual incident rates. Refine weight tables and scoring function coefficients. Publish empirically validated threshold tables as an open specification update.

Appendix A — Complete Node Definitions and Threshold Table

Node	Description	Advisory	Caution	Critical
T1	Elevation	10,000 ft	12,000 ft	14,000 ft
T2	Slope/Grade	15%	25%	35%
T3	Terrain Type	gravel	scree	ice
T4	Surface Stability	moderate	low	collapse risk
T5	Technicality	Class 2	Class 3	Class 4–5
T6	Trail Quality	faint	intermittent	off-trail
T7	Obstacle Density	moderate	high	impassable
T8	Traction Quality	reduced	poor	none
T9	Water Crossing	ankle-deep	knee-deep	waist-deep+
T10	Route Ambiguity	2–3 choices	4–5 choices	>5 choices
W1	Temperature	<40 or >80°F	<32 or >90°F	<20 or >100°F
W2	Wind Speed	15 mph	25 mph	40 mph
W3	Wind Direction	headwind	crosswind	gusting crosswind
W4	Precipitation Type	light rain	heavy rain	hail/whiteout
W5	Precipitation Intensity	moderate	heavy	extreme
W6	Storm Proximity	10 miles	5 miles	2 miles
W7	Lightning Risk	elevated	high	imminent
W8	Thermal Load	moderate	high	extreme
W9	Weather Volatility	unstable	rapid change	chaotic
W10	Safe Weather Window	<2 hours	<1 hour	<30 minutes
E1	Humidity	70%	85%	95%
E2	Dew Point	10°F below ambient	5°F below ambient	equal to ambient

E3	Fog/Cloud Presence	patchy	dense	whiteout
E4	Visibility Distance	500 m	200 m	50 m
E5	Sunlight Intensity	low	very low	dark
E6	UV Index	6	8	10
E7	Air Quality (AQI)	75	125	175
E8	Pressure Trend	falling	rapidly falling	collapse
E9	Day/Night Phase	dusk	twilight	night
E10	Light Pollution	moderate	low	none
E11	Sensory Clarity Index	reduced	poor	extremely poor
B1	Wildlife Density	moderate	high	very high
B2	Wildlife Risk	possible	likely	confirmed
B3	Insect Density	moderate	heavy	extreme
B4	Pathogen Risk	suspected	likely	confirmed
B5	Vegetation Density	moderate	heavy	impassable
B6	Edible Resources	scarce	very scarce	none
B7	Water Availability	3 miles	6 miles	10 miles
B8	Allergen Load	moderate	high	extreme
B9	Human Density	moderate	high	very high
B10	Land Use Constraints	advisory	restricted	prohibited
B11	Rescue Accessibility	2 hours	4 hours	8 hours

Appendix B — Normalized State Mapping

```
function normalize(raw, advisory, caution, critical, direction):  
    // direction: "low_bad" (lower raw = worse) or "high_bad" (higher  
    raw = worse)  
  
    if direction == "high_bad":  
        if raw < advisory: return lerp(+0.3, +1.0, ...)  
        if raw < caution:  return lerp(0.0, -0.3, ...)  
        if raw < critical: return lerp(-0.4, -0.7, ...)  
        else:              return lerp(-0.8, -1.0, ...)  
  
    if direction == "low_bad":  
        if raw > advisory: return lerp(+0.3, +1.0, ...)  
        if raw > caution:  return lerp(0.0, -0.3, ...)  
        if raw > critical: return lerp(-0.4, -0.7, ...)  
        else:              return lerp(-0.8, -1.0, ...)
```

Categorical nodes (T3, T4, T5, T6, W3, W4) use a lookup table rather than continuous mapping.

Appendix C — Routing Decision Logic

```

function route(position, waypoints, R, user_profile, time_budget):
    candidates = generate_candidate_segments(position, waypoints)

    for segment in candidates:
        // Rule 1: Hard constraint check
        if any(node.state ≤ -0.8 for node in R if
node.affects(segment)):
            segment.score = -infinity
            continue

        // Special hard constraints at caution
        if W7.state ≤ -0.4 or B10.state ≤ -0.4:
            segment.score = -infinity
            continue

        // Rule 3: Time window check
        if segment.duration > W10_estimate:
            segment.score -= time_window_penalty

        // Rule 4: Resource check
        if not segment.has_water_within(user_profile.carry_capacity):
            segment.score -= resource_penalty

        // Rule 2: Score computation
        segment.score = (
            user_profile.alpha × progress(segment, waypoints)
            - user_profile.beta × risk(segment, R)
            + user_profile.gamma × resilience(segment, B7, B11)
            - user_profile.delta × effort(segment, user_profile)
        )

        // Rule 5: Apply conservatism if W9 or E11 are elevated
        if W9.state ≤ -0.4 or E11.state ≤ -0.4:
            apply_conservatism_multiplier(candidates)

    return argmax(candidates, key=lambda s: s.score)

```

Appendix D — Geometry Data Model

```
{
  "organism": "verdara_ultra",
  "core": {
    "axes": [
      {"id": "terrain",      "angle_deg": 0,   "color": "#8B5E3C",
"state": 0.0},
      {"id": "weather",     "angle_deg": 90,   "color": "#A0A0B0",
"state": 0.0},
      {"id": "environmental", "angle_deg": 180, "color": "#87CEEB",
"state": 0.0},
      {"id": "biological",   "angle_deg": 270, "color": "#228B22",
"state": 0.0}
    ],
  },
  "ring": {
    "base_radius": 1.0,
    "nodes": [
      {"id": "T1",  "primitive": "terrain",   "angle_deg": 0,
"state": 0.0},
      {"id": "T2",  "primitive": "terrain",   "angle_deg": 8.571,
"state": 0.0},
      "...",
      {"id": "B11", "primitive": "biological", "angle_deg": 351.429,
"state": 0.0}
    ]
  }
}
```

References

1. Williamson, J. (2003). *Accidents in North American Mountaineering*. American Alpine Club. Annual series.
2. Fogarty, S., & Runje, J. (2018). Multi-hazard risk assessment in alpine environments: A systematic review. *Mountain Research and Development*, 38(2), 112–124.
3. Auerbach, P. S. (2017). *Wilderness Medicine* (7th ed.). Elsevier.
4. Johnson, C., Anderson, S., & Dallimore, J. (2015). *Oxford Handbook of Expedition and Wilderness Medicine* (2nd ed.). Oxford University Press.
5. Hoffman, M. D., & Krishnan, E. (2014). Health and exercise-related medical issues among 1,212 ultramarathon runners. *PLOS ONE*, 9(1), e83867.
6. Scheer, V., Vieluf, S., & Janssen, M. (2021). Environmental factors affecting ultra-endurance performance: A systematic review. *Sports Medicine*, 51(4), 713–730.
7. Andrews, J. (2026). *Lume Language Specification*. DarkWave Studios LLC. DOI: [10.5281/zenodo.19382282](https://doi.org/10.5281/zenodo.19382282)
8. Andrews, J. (2026). *Trust Layer Ecosystem*. DarkWave Studios LLC. DOI: [10.5281/zenodo.19560674](https://doi.org/10.5281/zenodo.19560674)
9. Andrews, J. (2026). *DAIGS Framework*. DarkWave Studios LLC. DOI: [10.5281/zenodo.19491784](https://doi.org/10.5281/zenodo.19491784)
10. Andrews, J. (2026). *Lume-V Verification Suite*. DarkWave Studios LLC. DOI: [10.5281/zenodo.19645097](https://doi.org/10.5281/zenodo.19645097)
11. Andrews, J. (2026). *Lume-X Multi-Agent Cognition*. DarkWave Studios LLC. DOI: [10.5281/zenodo.19443968](https://doi.org/10.5281/zenodo.19443968)
12. Andrews, J. (2026). *Deterministic Dissolution*. DarkWave Studios LLC. DOI: [10.5281/zenodo.15065493](https://doi.org/10.5281/zenodo.15065493)
13. Andrews, J. (2026). *Meridian: A Four-Layer Deterministic Wireless Energy Routing Architecture*. DarkWave Studios LLC. L-SOC Paper Series.
14. Andrews, J. (2026). *Meridian as Synthetic Organism*. DarkWave Studios LLC. L-SOC Paper Series.

Patent Pending — Patent Pending.

Patent Pending — DarkWave Studios LLC

Lume-X: Provisionally patented deterministic control runtime.

© 2026 DarkWave Studios LLC. All rights reserved.

Ronald “Jason” Andrews · DarkWave Studios LLC · Nashville, TN · team@dwsc.io

ORCID: [0009-0007-5214-649X](https://orcid.org/0009-0007-5214-649X) · lume-lang.org · github.com/cryptocreper94-sudo

This preprint has not undergone peer review. Submitted for early dissemination and to establish priority of invention.