Python Programming Language

Prepared by: Mohamed Ayman

Algorithm Engineer at Valeo
Deep Learning Researcher and Teaching Assistant
at The American University in Cairo (AUC)
spring 2020





- sw.eng.MohamedAyman@gmail.com
- f facebook.com/cs.MohamedAyman
- in linkedin.com/in/cs-MohamedAyman
- github.com/cs-MohamedAyman
- codeforces.com/profile/Mohamed_Ayman

Lecture 5 Loops

Course Roadmap



Part 1: Python Basics and Functions

Lecture 1: Python Overview

Lecture 2: Variable Types

Lecture 3: Basic Operations

Lecture 4: Conditions

Lecture 5: Loops

Lecture 6: Functions

Lecture Agenda

We will discuss in this lecture the following topics

- 1- Loop Definition
- 2- While Loop Statements
- 3- Else with While Loop
- 4- For Loop Statements
- 5- Else with For Loop
- 6- Nested Loops
- 7- Loop Control Statements



Lecture Agenda



Section 1: Loop Definition

Section 2: While Loop Statements

Section 3: Else with While Loop

Section 4: For Loop Statements

Section 5: Else with For Loop

Section 6: Nested Loops


Section 7: Loop Control Statements



Loop Definition



- In general, statement are executed sequentially The first statement in a function is executed first, followed by the second, and so on.
- There may be a situation when you need to execute a block of code several number of times.
- Programming language provide various control structure that allow more complicated execution paths.
- A loop statement allows us to execute a statement of group of statement multiple times.



Types of Loops



- Python programming language provides the following types of loops to handle looping requirement.
- The while loop in Python is used to iterate over a block of code as long as the test expression (condition) is true, We generally use this loop when we don't know beforehand, the number of times to iterate.
- The for loop in Python is used to iterate over a sequence (list, tuple, string) or other iterable objects. Iterating over a sequence is called traversal.

Loop Type	Description
while loop	Repeats a statement or group of statements while a given condition is TRUE. It tests the condition before executing the loop body.
for loop	Executes a sequence of statements multiple times and abbreviates the code that manages the loop variable.
nested loops	You can use one or more loop inside any another while, or for loop.

Lecture Agenda



✓ Section 1: Loop Definition

Section 2: While Loop Statements

Section 3: Else with While Loop

Section 4: For Loop Statements

Section 5: Else with For Loop

Section 6: Nested Loops

Section 7: Loop Control Statements






 A while loop statement in Python programming language repeatedly executes a target statement as long as given condition is true.

```
while expression:
    statement(s)
```

- Expression can be TRUE by any non-zero value. The loop iterates while the condition is true. When the condition becomes false, program control passes to the line immediately following the loop.
- In while loop, test expression is checked first. The body of the loop is entered only if the expression evaluates to True. After one iteration, the test expression is checked again. This process continues until the expression evaluates to False.
- In Python, the body of the while loop is determined through indentation, Body starts with indentation and the first unindented line marks the end.
- Python interprets any non-zero value as True. None and 0 are interpreted as False.





Example:

```
i = 0
while i < 3:
    print(i)
    i += 1
print('the program completed')</pre>
```

Output:

```
0
1
2
the program completed
```



Iterations Trace:

1 - i = 0

```
while i < 3:
    print(i)
    i += 1
print('the program completed')

2- i = 0
while i < 3:
    print(i)</pre>
```

print('the program completed')

i += 1



Iterations Trace:

while i < 3:

l - i = 0

```
i = 0
while i < 3:
    print(i)
    i += 1
print('the program completed')
i = 0
while i < 3:
    print(i)
    i += 1
print('the program completed')
```



Iterations Trace:

1 - i = 0

```
while i < 3:
    print(i)
    i += 1
print('the program completed')

4- i = 0
while i < 3:
    print(i)
    i += 1
print('the program completed')</pre>
```

i = 0

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements

Section 3: Else with While Loop

Section 4: For Loop Statements

Section 5: Else with For Loop

Section 6: Nested Loops

Section 7: Loop Control Statements





- Python support having an else statement associated with a loop statement.
- If the else statement is used with a while loop, the else statement is executed when the condition becomes false.
- The else part is executed if the condition in the while loop evaluates to False. The while loop can be terminated with a break statement.
- The while loop can be terminated with a break statement. In such case, the else part is
 ignored. Hence, a while loop's else part runs if no break occurs and the condition is false.

```
while expression:
    statement(s)
else:
    statement(s)
```



Example:

```
i = 0
while i < 3:
    print(i)
    i += 1
else:
    print('i not less than 3')</pre>
```

Output:

```
0
1
2
i not less than 3
```



```
i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
2 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```

```
3 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
4 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```



```
1 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
  i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```

```
J- i = 0
    while i < 3:
        print(i)
        i += 1
    else:
        print('i not less than 3')</pre>
```



```
1 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
7 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```

```
3 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```



```
1 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
7 - i = 0
   while i < 3:
       print(i)
       i += 1
   else:
       print('i not less than 3')
```

```
i = 0
while i < 3:
    print(i)
    i += 1
else:
    print('i not less than 3')</pre>
```

Quiz



What is the output of the following code?

```
i, sum = 0, 0
i, sum = 0, 0
while i <= 4:
                                   while i >= 4:
    sum += i
                                       sum += i
    i += 1
                                       i += 1
print(sum)
                                   print(sum)
                                   0
                                   10
10
                                   4
4
                                   none of the above
none of the above
```

Quiz Solution



What is the output of the following code?

```
i, sum = 0, 0
                                   i, sum = 0, 0
                                   while i >= 4:
while i <= 4:
    sum += i
                                       sum += i
    i += 1
                                        i += 1
print(sum)
                                   print(sum)
                                   0
                                   10
10
                                   4
4
                                   none of the above
none of the above
```

Practice



Problem: Calculate factorial of n



 Find the factorial of the input number using python loops, such that the input number data type will be integer and non-negative.

•	Test Cases:	Hint:	n! = 1 * 2 * 3 * 4 * * n
---	-------------	-------	--------------------------

Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	3	5	6
1	6	120	720

Problem Solution



 Find the factorial of the input number using python loops, such that the input number data type will be integer and non-negative.

	.	~
•	1291	Cases:

print(res)

```
Hint: n! = 1 * 2 * 3 * 4 * ... * n
```

Test Case 3 Test Case 4

120 720

© Prepared by: Mohamed Ayman

Problem: The power of 2



• Find the powers of 2 from 0 to the input number using python loops, such that the input number data type will be integer and non-negative.

 Test Cases 		Hint:	$2^0 \ 2^1 \ 2^2 \ 2^3 \dots \ 2^n$
Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	2	4	6
1	1 2 4	1 2 4 8 16	1 2 4 8 16 32 64

Problem Solution



 \mathbf{n}

• Find the powers of 2 from 0 to the input number using python loops, such that the input number data type will be integer and non-negative.

number data type will be integer and non-negative.
 Test Cases
 Hint: 20 21 22 23

			2 2 2 2
Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	2	4	6
1	1 2 4	1 2 4 8 16	1 2 4 8 16 32 64

```
n = int(input())
i = 0
while i <= n:
    print(2**i, end = ' ')
    i += 1</pre>
```

Problem: The factors of n



- Find the factors of the input number using python loops, such that the input number data type will be integer and positive.
- Test Cases

Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	5	8	12
1	1 5	1 2 4 8	1 2 3 4 6 12

Problem Solution



- Find the factors of the input number using python loops, such that the input number data type will be integer and positive.
- Test Cases

Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	5	8	12
1	1 5	1 2 4 8	1 2 3 4 6 12
<pre>n = int(input()) i = 1 while i <= n: if n % i == 0: print(i, end = ' ') i += 1</pre>			

Problem: The summation of n



• Find the summation from 1 to the input number using python loops, such that the input number data type will be integer and positive.

 Test Cases 		Hint:	$1 + 2 + 3 + 4 + \cdots + n$
Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	3	4	6
1	6	10	21

Problem Solution



Find the summation from 1 to the input number using python loops, such that the input number data type will be integer and positive.

	T .	~
•	Inct	ו זרחר
•	16/1	Cases
		CUJCJ

i += 1

print(res)

Test Case 1	Test Case 2
1	3
1	6
<pre>n = int(input()) i, res = 1, 0 while i <= n: res += i</pre>	

```
Hint:
    1+2+3+4+\cdots+n
```

Test Case 3	Test Case 4
4	6

10

21

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements
- ✓ Section 3: Else with While Loop

Section 4: For Loop Statements

Section 5: Else with For Loop

Section 6: Nested Loops

Section 7: Loop Control Statements




For Loop Statements



• The for loop in Python is used to iterate over a sequence (list, tuple, string) or other iterable objects. Iterating over a sequence is called traversal.

```
for iterating_var in sequence:
    statement(s)
```

- If a sequence contains an expression list, it is evaluated first. Then, the first item in the sequence is assigned to the iterating variable iterating var. Next, the statement block is executed. Each item in the list is assigned to iterating var, and the statement(s) blocks is executed until the entire sequence is exhausted.
- Loop continues until we reach the last item in the sequence. The body of for loop is separated from the rest of the code using indentation.



For Loop Statements



```
for i in 'python':
    print(i)
print('the program completed')

t
h
o
n
the program completed
```

For Loop Statements



```
l- for i in 'python':
       print(i)
   print('the program completed')
2- for i in 'python':
       print(i)
   print('the program completed')
3- for i in 'python':
       print(i)
   print('the program completed')
```

```
5- for i in 'python':
         print(i)
    print('the program completed')
```

```
6- for i in 'python':
     print(i) t
print('the program completed')
```



```
l- for i in 'python':
       print(i)
   print('the program completed')
2- for i in 'python':
       print(i)
                                 h
   print('the program completed')
   for i in 'python':
       print(i)
   print('the program completed')
```

```
5- for i in 'python':
        print(i)
    print('the program completed')
```



```
l- for i in 'python':
        print(i)
    print('the program completed')

2- for i in 'python':
        print(i)
    print('the program completed')
```



Example:

```
fruits = ['banana', 'apple', 'orange']
for i in fruits:
    print(i)
print('the program completed')
```

Output:

banana
apple
orange
the program completed



```
['banana', 'apple', 'orange'] 4- fruits = ['banana', 'apple', 'orange']
   for i in fruits:
                                              for i in fruits:
       print(i)
                                                  print(i)
   print('the program completed')
                                              print('the program completed')
7- fruits = ['banana', 'apple', 'orange'] 5- fruits = ['banana', 'apple', 'orange']
   for i in fruits:
                                              for i in fruits:
                                                                               apple
       print(i)
                                                  print(i)
                                              print('the program completed')
   print('the program completed')
3- fruits = ['banana', 'apple', 'orange']
   for i in fruits:
       print(i)
                                   banana
   print('the program completed')
```



```
fruits = ['banana', 'apple', 'orange']
for i in fruits:
    print(i)
print('the program completed')

7- fruits = ['banana', 'apple', 'orange']
for i in fruits:
    print(i)
print('the program completed')

7- fruits = ['banana', 'apple', 'orange']
for i in fruits:
    print(i)
    print(i)
    print(i)
    print('the program completed')

8- fruits = ['banana', 'apple', 'orange']
for i in fruits:
    print(i)
print('the program completed')
```



- Python has a built-in function, called range, which allows you to easily construct sequences of integers. The function range does not return a list, rather it returns a special range object. However, you can pass it to the list function to convert the range object into a list, if you need or want a list instead. The range function takes from 1 to 3 arguments. These arguments are converted into a start, stop, and step value as follows:
 - If a single argument is passed to range, the start value will be 0, the stop value will be the argument, and the step value will be 1.
 - If two arguments are passed to range, the start value will be the first argument, the stop value will be the second argument, and the step value will be 1.
 - If three arguments are passed to range, the start value will be the first argument, the stop value will be the second argument, and the step value will be the third argument.
- The range will then contain the sequence of integers which starts at the start value. Each successive value in the range will be the previous value in the range plus the step value. The range will continue up to (or down to, if the step is negative), but not including, the stop value.



- The built-in function range() is the right function to iterate over a sequence of numbers. It generates an iterator of arithmetic progressions.
- range() generates an iterator to progress integers starting with 0 up to n-1. To obtain a list object of the sequence, it is type casted to list(). Now this list can be iterated using the for statement. We can also define the start, stop and step size as range(start, stop, step). step size defaults to 1 if not provided.
- This function does not store all the values in memory, it would be inefficient. So it remembers the start, stop, step size and generates the next number on the go. To force this function to output all the items, we can use the function list().



Example:

```
print(list(range(5)))
print(list(range(2, 7)))
print(list(range(3, 11, 2)))
print(list(range(8, 3, -1)))
```

Output:



Example:

```
fruits = ['banana', 'apple', 'orange']
for i in range(len(fruits)):
    print(fruits[i])
print('the program completed')
```

Output:

```
banana
apple
orange
the program completed
```



Example:

```
x = ['c', 'java', 'c++', 'python', 'scala', 'R', 'matlab']
for i in range(2, len(x)-2):
    print(x[i])
print('the program completed')
```

Output:

```
c++
python
scala
the program completed
```

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements
- ✓ Section 3: Else with While Loop
- ✓ Section 4: For Loop Statements

Section 5: Else with For Loop

Section 6: Nested Loops

Section 7: Loop Control Statements





- Python support having an else statement associated with a loop statement.
- If the else statement is used with a for loop, the else blocks is executed only if for loops terminates normally (and not by encountering break statement)
- A for loop can have an optional else block as well. The else part is executed if the items in the sequence used in for loop exhausts.
- break statement can be used to stop a for loop. In such case, the else part is ignored. Hence,
 a for loop's else part runs if no break occurs.

```
for iterative_var in sequence:
    statement(s)
else:
    statement(s)
```



Example:

```
x = [48, 67, 73]
for i in range(len(x)):
    print(x[i])
else:
    print('we reach the end of the list')
```

Output:

48
67
73
we reach the end of the list



```
1- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
  else:
      print('we reach the end of the list')
2- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
  else:
      print('we reach the end of the list')
3- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
                                          48
  else:
      print('we reach the end of the list')
```

```
4- x = [48, 67, 73]
   for i in range(len(x)):
       print(x[i])
   else:
       print('we reach the end of the list')
5- x = [48, 67, 73]
   for i in range(len(x)):
       print(x[i])
                                           67
   else:
       print('we reach the end of the list')
```



```
1- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
  else:
      print('we reach the end of the list')
2- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
                                          73
  else:
      print('we reach the end of the list')
3- x = [48, 67, 73]
  for i in range(len(x)):
      print(x[i])
  else:
      print('we reach the end of the list')
```

```
4- x = [48, 67, 73]
   for i in range(len(x)):
       print(x[i])
   else:
       print('we reach the end of the list')
5- x = [48, 67, 73]
   for i in range(len(x)):
       print(x[i])
   else:
       print('we reach the end of the list')
```

Quiz



What is the output of the following code?

```
x = [1, 2, [3, 4], 5]
                                  for i in [1, 0]:
for i in x:
                                      print(i+1)
    print(i)
                                   [2, 1]
                [3, 4]
5
                                   [2, 0]
```

Quiz Solution



What is the output of the following code?

```
x = [1, 2, [3, 4], 5]
                                 for i in [1, 0]:
for i in x:
                                      print(i+1)
    print(i)
                [3, 4]
5
                                   [2, 0]
```

Practice



Problem: Calculate factorial of n



 Find the factorial of the input number using python loops, such that the input number data type will be integer and non-negative.

Test (ises:	Hint:	n! = 1 * 2 * 3 * 4	1 * * n
--------------------------	-------	-------	--------------------	---------

Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	3	5	6
1	6	120	720

Problem Solution



 Find the factorial of the input number using python loops, such that the input number data type will be integer and non-negative.

Test Cases:

print(res)

Hint: n! = 1 * 2 * 3 * 4 * ... * n

Test Case 1	Test Case 2	Test Case 3	Test Case	
0	3	5	6	
1	6	120	720	
<pre>n = int(input()) res = 1 for i in range(1, n+1): res *= i</pre>				

Problem: The power of 2



• Find the powers of 2 from 0 to the input number using python loops, such that the input number data type will be integer and non-negative.

• Test Cases Hi			$0 \ 2^1 \ 2^2 \ 2^3 \dots \ 2^n$
Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	2	4	6
1	1 2 4	1 2 4 8 16	1 2 4 8 16 32 64

Problem Solution



• Find the powers of 2 from 0 to the input number using python loops, such that the input number data type will be integer and non-negative.

• Test Cases H			$2^{0} \ 2^{1} \ 2^{2} \ 2^{3} \dots 2^{n}$
Test Case 1	Test Case 2	Test Case 3	Test Case 4
0	2	4	6
1	1 2 4	1 2 4 8 16	1 2 4 8 16 32 64

```
n = int(input())
for i in range(n+1):
    print(2**i, end = ' ')
```

Problem: The factors of n



- Find the factors of the input number using python loops, such that the input number data type will be integer and positive.
- Test Cases

Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	5	8	12
1	1 5	1 2 4 8	1 2 3 4 6 12

Problem Solution



- Find the factors of the input number using python loops, such that the input number data type will be integer and positive.
- Test Cases

Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	5	8	12
1	1 5	1 2 4 8	1 2 3 4 6 12
<pre>n = int(input()) for i in range(1 if n % i == print(i,</pre>			

Problem: The summation of n



• Find the summation from 1 to the input number using python loops, such that the input number data type will be integer and positive.

 Test Cases 		Hint:	$1+2+3+4+\cdots+n$
Test Case 1	Test Case 2	Test Case 3	Test Case 4

1 3 4 6

1 6 10 21

Problem Solution



• Find the summation from 1 to the input number using python loops, such that the input number data type will be integer and positive.

Test Cases

Hint: $1+2+3+4+\cdots+n$

Test Case 1	Test Case 2	Test Case 3	Test Case 4
1	3	4	6
1	6	10	21

```
n = int(input())
res = 0
for i in range(1, n+1):
    res += i
print(res)
```

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements
- ✓ Section 3: Else with While Loop
- ✓ Section 4: For Loop Statements
- ✓ Section 5: Else with For Loop

Section 6: Nested Loops

Section 7: Loop Control Statements





• Python programming language allows the use of one loop inside another loop.

```
while expression:
    while expression:
        statement(s)
    statement(s)

for iterating_var in sequence:
    for iterating_var in sequence:
        statement(s)
    statement(s)
```



Example:

```
i = 1
while i < 4:
    j = 1
    while j < 4:
        print(i*j, end = ' ')
        j += 1
    print()
    i += 1</pre>
```

Output:



Iterations Trace:

```
l - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
2 - i = 1
   while i < 4:
       j = 1
       while j < 4:
          print(i*j, end = ' ')
           j += 1
       print()
       i += 1
```

```
3 - i = 1
  while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
4 - i = 1
  while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
```

i += 1

i = 1 j = 1



Iterations Trace:

```
1 - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
2 - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
```

```
3 - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
4-i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
```

i = 1 j = 2



```
| - i = 1
  while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
2 - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
```

```
i = 1 j = 3 i = 1
```

```
3 - i = 1
   while i < 4:
        j = 1
        while j < 4:
            print(i*j, end = ' ')
            j += 1
        print()
        i += 1
4- i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
        i += 1
```



Iterations Trace:

```
| - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
2 - i = 1
   while i < 4:
       j = 1
       while j < 4:
           print(i*j, end = ' ')
           j += 1
       print()
       i += 1
```

```
3- i = 1
   while i < 4:
        j = 1
        while j < 4:
            print(i*j, end = ' ')
            j += 1
            print()</pre>
```

i += 1

i = 2 j = 4

and so on ...



Example:

```
for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

Output:



```
l- for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

```
i = 1 j = 1
```

```
4- for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```



```
l- for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

```
i = 1 j = 2
```

Nested loops



Iterations Trace:

```
l- for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

```
for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

```
i = 1 j = 3
```

```
4- for i in range(1, 4):
    for j in range(1, 4):
        print(i*j, end = ' ')
    print()
```

and so on ...

Practice



Problem: Identity Matrix



 Print the Identity Matrix I with size n*n using python loops, such that the input number data type will be integer and positive.

Test Case 1	Test Case 2	Test Case 3
2	3	4
1 0	1 0 0	1 0 0 0
0 1	0 1 0	0 1 0 0
	0 0 1	0 0 1 0
		0 0 0 1

Problem Solution



• Print the Identity Matrix I with size n*n using python loops, such that the input number data type will be integer and positive.

	Test Case 3	
3	4	<pre>n = int(input())</pre>
		<pre>for i in range(n):</pre>
1 0 0	1 0 0 0	<pre>for j in range(n):</pre>
0 1 0		if i == j:
0 0 1	0 0 1 0	<pre>print(1, end = ' ')</pre>
		else:
		<pre>print(0, end = ' ')</pre>
		print()
	1 0 0 0 1 0	1 0 0 1 0 0 0 0 0 1 0 0

Problem Solution



• Print the Identity Matrix I with size n*n using python loops, such that the input number data type will be integer and positive.

Test Case 2	Test Case 3	
3	4	n = int(input()) i = 0
1 0 0 0 1 0 0 0 1	1 0 0 0 0 1 0 0 0 0 1 0 0 0 0 1	<pre>while i < n: j = 0 while j < n: if i == j: print(1, end = ' ') else: print(0, end = ' ') j += 1 print() i += 1</pre>
	3 1 0 0 0 1 0	3 4 1 0 0 1 0 0 0 0 1 0 0 1 0 0 0 0 1 0 0 1 0

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements
- ✓ Section 3: Else with While Loop
- ✓ Section 4: For Loop Statements
- ✓ Section 5: Else with For Loop
- ✓ Section 6: Nested Loops

Section 7: Loop Control Statements



Loop Control Statements




- In Python, break and continue statements can alter the flow of a normal loop.
- Loops iterate over a block of code until test expression is false, but sometimes we wish to terminate the current iteration or even the whole loop without checking test expression.
- Loop control statements change execution from its normal sequence. When execution leaves a scope, all automatic objects that were created in that scope are destroyed. Python supports the following control statements.

Control Statement	Description
break statement	Terminates the loop statement and transfers execution to the statement immediately following the loop.
continue statement	Causes the loop to skip the remainder of its body and immediately retest its condition prior to reiterating.
pass statement	The pass statement in Python is used when a statement is required syntactically but you do not want any command or code to execute.



- The break statement is used for premature termination of the current loop. After abandoning the loop, execution at the next statement is resumed.
- The most common use of break is when some external condition is triggered requiring a hasty exit from a loop. The break statement can be used in both while and for loops.
- If you are using nested loops, the break statement stops execution of the innermost loop and starts executing the next line of the code after the block.





 The working of break statement in for loop and while loop is shown below.

```
while expression:
    statement(s)
    if expression:
        statement(s)
        break
    statement(s)
statement(s)
for var in sequence:
    statement(s)
    if expression:
        statement(s)
        break
    statement(s)
statement(s)
```



Example:

```
i = 0
while i < 4:
    if i == 2:
        break
    print(i)
    i += 1
print('the program completed')</pre>
```

Output:

```
0
1
the program completed
```



```
l- i = 0
    while i < 4:
        if i == 2:
            break
        print(i)
        i += 1
    print('the program completed')</pre>
```



```
1 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
7 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
```

```
3 - i = 0
  while i < 4:
       if i == 2:
           break
      print(i)
                                0
       i += 1
  print('the program completed')
4 - i = 0
  while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
  print('the program completed')
```



```
1 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
7 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
```

```
3_{-} i = 0
  while i < 4:
       if i == 2:
           break
      print(i)
       i += 1
  print('the program completed')
4 - i = 0
  while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
  print('the program completed')
```



```
1 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
7 - i = 0
   while i < 4:
       if i == 2:
           break
       print(i)
       i += 1
   print('the program completed')
```

```
3 - i = 0
  while i < 4:
      if i == 2:
           break
      print(i)
       i += 1
  print('the program completed')
4 - i = 0
  while i < 4:
      if i == 2:
          break
      print(i)
      i += 1
  print('the program completed')
```



Example:

```
for i in 'python':
    if i == 't':
        break
    print(i)
print('the program completed')
```

Output:

```
y
the program completed
```



```
l- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
2- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
3- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
```

```
4- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
5- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
6- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
```




```
l- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
2- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
3- for i in 'python':
       if i == 't':
           break
       print(i)
   print('the program completed')
```

```
4- for i in 'python':
    if i == 't':
        break
    print(i)
print('the program completed')
```



- The continue statement in Python returns the control to the beginning of the current loop. When encountered, the loop starts next iteration without executing the remaining statements in the current iteration.
- The continue statement is used to skip the rest of the code inside a loop for the current iteration only. Loop does not terminate but continues on with the next iteration.





• The working of continue statement in for loop and while loop is shown below.

```
while expression:
    statement(s)
    if expression:
        statement(s)
        continue
    statement(s)
statement(s)
for var in sequence:
    statement(s)
    if expression:
        statement(s)
        continue
    statement(s)
statement(s)
```



Example:

```
i = 0
while i < 4:
    i += 1
    if i == 2:
        continue
    print(i)
print('the program completed')</pre>
```

Output:

```
1
3
4
the program completed
```



```
l- i = 0
    while i < 4:
        i += 1
        if i == 2:
            continue
        print(i)
    print('the program completed')</pre>
```



```
1 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
7 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```

```
3 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
4 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```



```
1 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
7 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```

```
3 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
4 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```



```
1 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
7 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```

```
3 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
4 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```



```
1 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
7 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```

```
3 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
4 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```



```
1 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
7 - i = 0
   while i < 4:
       i += 1
       if i == 2:
           continue
       print(i)
   print('the program completed')
```



Example:

```
for i in 'python':
    if i == 't':
        continue
    print(i)
print('the program completed')
```

Output:

p
y
h
o
n
the program completed



```
for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
    print('the program completed')
                                                 print('the program completed')
7- for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
                                                 print('the program completed')
    print('the program completed')
                                                 for i in 'python':
    for i in 'python':
                                                     if i == 't':
        if i == 't':
                                                         continue
            continue
                                                     print(i)
        print(i)
                                                 print('the program completed')
    print('the program completed')
```



```
for i in 'python':
                                                for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
    print('the program completed')
                                                 print('the program completed')
7- for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
                                                 print('the program completed')
    print('the program completed')
                                                 for i in 'python':
    for i in 'python':
                                                     if i == 't':
        if i == 't':
                                                         continue
            continue
                                                     print(i)
        print(i)
                                                 print('the program completed')
    print('the program completed')
```



```
for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
    print('the program completed')
                                                 print('the program completed')
7- for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
                                                 print('the program completed')
    print('the program completed')
    for i in 'python':
                                                 for i in 'python':
        if i == 't':
                                                     if i == 't':
            continue
                                                         continue
        print(i)
                                                     print(i)
    print('the program completed')
                                                 print('the program completed')
```



```
for i in 'python':
    if i == 't':
        continue
    print(i)
print('the program completed')

for i in 'python':
    if i == 't':
        continue
    print(i)
print('the program completed')
```

Loop Control Statements - pass



- In Python programming, pass is a null statement. The difference between a comment and pass statement in Python is that, while the interpreter ignores a comment entirely, pass is not ignored, however, nothing happens when pass is executed. It results into no operation.
- Suppose we have a loop or a function that is not implemented yet, but we want to implement it in the future. They cannot have an empty body. The interpreter would complain. So, we use the pass statement to construct a body that does nothing.
- However, nothing happens when pass is executed. It results into no operation (NOP).

```
if expression:
    pass

while expression:
    pass

for var in sequence:
    pass
```

Loop Control Statements - pass



 It is used when a statement is required syntactically but you do not want any command or code to execute. The pass statement is a null operation nothing happens when it executes. The pass statement is also useful in places where your code will eventually go, but has not been written yet i.e. in stubs).

```
n = int(input())
if n < 0:
    pass

n = int(input())
for i in range(n):
    pass</pre>
```

Quiz



• Which of the following statement is true?

The break statement terminates the loop containing it.	The Python interpreter ignores the pass statement like comments.
The continue statement is used to skip the rest of the code inside the loop.	The pass statement terminates the loop containing it.
The break and continue statements are almost always used with if, ifelse and ifelifelse statements.	The pass is used as a placeholder for future implementation of functions, loops etc
All of the above.	All of the above.

Quiz Solution



• Which of the following statement is true?

	The break statement terminates the loop containing it.		The Python interpreter ignores the pass statement like comments.
	The continue statement is used to skip the rest of the code inside the loop.		The pass statement terminates the loop containing it.
	The break and continue statements are almost always used with if, ifelse and ifelifelse statements.	\checkmark	The pass is used as a placeholder for future implementation of functions, loops etc
Y	All of the above.		All of the above.

Quiz



```
for i in 'PYTHON STRING':
for i in 'PYTHON STRING':
                                                 if i == ' ':
    if i == ' ':
                                                     continue
        break
                                                 print(i, end='')
    print(i, end='')
                                                 if i == '0':
    if i == '0':
                                                     break
        continue
PYTHON
                                             PYTHON
PYTHONSTRING
                                             PYTHONSTRING
PYTHN
                                             PYTHN
PYTHO
                                             PYTHO
```

Quiz Solution



```
for i in 'PYTHON STRING':
for i in 'PYTHON STRING':
                                                 if i == ' ':
    if i == ' ':
                                                     continue
        break
                                                 print(i, end='')
    print(i, end='')
                                                 if i == '0':
    if i == '0':
                                                     break
        continue
PYTHON
                                             PYTHON
PYTHONSTRING
                                             PYTHONSTRING
PYTHN
                                             PYTHN
PYTHO
                                             PYTHO
```

Quiz



```
x = [11, 33, 22, 55, 66, 77]
for i in x:
    if i % 2 == 0:
        print('the list contains even numbers')
       break
else:
   print('the list does not contain even numbers')
    the list does not contain even numbers
    the list contains even numbers
    the list does not contain even numbers
    none of the above
```

```
x = [11, 33, 22, 55, 66, 77]
i = 0
while i < len(x):
    if x[i] % 2 == 0:
        break
        print('the list contains even numbers')
    i += 1
else:
    print('the list does not contain even numbers')
      the list does not contain even numbers
      the list contains even numbers
      the list does not contain even numbers
      none of the above
```

Quiz Solution



```
x = [11, 33, 22, 55, 66, 77]
for i in x:
    if i % 2 == 0:
        print('the list contains even numbers')
       break
else:
   print('the list does not contain even numbers')
    the list does not contain even numbers
    the list contains even numbers
    the list does not contain even numbers
    none of the above
```

```
x = [11, 33, 22, 55, 66, 77]
i = 0
while i < len(x):
    if x[i] % 2 == 0:
        break
        print('the list contains even numbers')
    i += 1
else:
    print('the list does not contain even numbers')
      the list does not contain even numbers
      the list contains even numbers
      the list does not contain even numbers
      none of the above
```

Practice



Problem: Prime number



• Find if the input number is prime or not using python loops, such that the input number data type will be integer and positive.

Test Case 1	Test Case 2	Test Case 3	Test Case 4
2	4	5	9
YES	NO	YES	NO

Problem Solution



• Find if the input number is prime or not using python loops, such that the input number data type will be integer and positive.

Test Case 1	Test Case 2	Test Case 3	Test Case 4
2	4	5	9
YES	NO	YES	NO
<pre>n = int(input()) i = 2 while i < n: if n % i == print('N break i += 1 else: print('YES')</pre>			

Problem Solution



• Find if the input number is prime or not using python loops, such that the input number data type will be integer and positive.

Test Case 1	Test Case 2	Test Case 3	Test Case 4		
2	4	5	9		
YES	NO	YES	NO		
<pre>n = int(input()) for i in range(2, n): if n % i == 0: print('NO') break</pre>					
<pre>else: print('YES')</pre>					

Lecture Agenda



- ✓ Section 1: Loop Definition
- ✓ Section 2: While Loop Statements
- ✓ Section 3: Else with While Loop
- ✓ Section 4: For Loop Statements
- ✓ Section 5: Else with For Loop
- ✓ Section 6: Nested Loops
- ✓ Section 7: Loop Control Statements



