Network Monitoring and Management

NfSen

Netflow Sensor INNOG 6

March 22 - 25, 2023




What is NfSen

- Companion to NfDump tools
- NfDump tools collect netflow data and store them in files
- Processing netflow data with NfDump tools can only be done on the command line
- NfSen is a graphical (Web Based) front end to NfDump
- Creates RRD graphs based on stored data
- Plugins extend the functionality of base (e.g. PortTracker and SURFmap)

What can you do with NfSen

- NfSen allows you to:
 - Easily navigate through the netflow data
 - Process the netflow data within the specified time span
 - Create history as well as continuous profiles
 - Set alerts, based on various conditions
 - Write your own plugins to process netflow data on a regular interval

NfSen Architecture



NfSen: Points to note

- Every 5 minutes nfcapd starts a new file, and nfsen processes the previous one
- Hence each graph point covers 5 minutes
- The graph shows you the total of selected traffic in that 5-minute period
- To get more detailed information on the individual flows in that period, nfsen lets you drill down using nfdump in the back end


NfSen structure

- Configuration file nfsen.conf
- NfDump files Netflow files containing collected flows stored in the directory:

/var/nfsen/profiles-data

- Note: It is possible for other programs to read
 NFDump files but don't store them for too long as they can fill up your drive
- Actual graphs stored in the directory:
 /var/nfsen/profiles-stat


NfSen Home Screen



Graphs Tab

Graphs of flows, packets and traffic based on interface with NetFlow activated

Note: What is seen under Traffic should closely match what your NMS shows for the same interface



Details Page

- Most interesting page
- Can view present flow information or stored flow information
- Can view detailed NetFlow information such as
 - AS Numbers (more useful if you have full routing table exported on your router)
 - Src hosts/ports, destination hosts and ports
 - Unidirectional or Bi-directional flows
 - Flows on specific interfaces
 - Protocols and TOS

Details Page (Contd.)




Profiles and Channels

- A channel is a type of traffic of interest
 - Total HTTP, HTTPS, SMTP traffic (etc)
 - Traffic to and from the Science department
- A profile is a collection of channels which can be shown together in a graph
 - v4 TCP, v6 TCP, v4 UDP, v6 UDP, Other
- You can create your own profiles and channels, and hence graphs.
- Use filters to define a channel
 - Filter out the flow data you are interested in from the data files that contain all the flows

Profiles and Channels (Contd.)

A profile is a collection of channels graphed together



Filters

- A filter is a collection of expressions
 - expr1, expr2 and expr3, expr4 or expr5, not expr6,
 (expr7), not (expr8)
- Each expression can specify things like
 - IP version: inet, ipv4, inet6, ipv6
 - Protocol: {proto} tcp, udp, icmp, gre, ...
 - IP Address:

```
[src|dst] ip 10.10.10.1
[src|dst] ip in <addr1> <addr2> <addr3>
```

- IP Network: [src|dst] net 172.16/16
- Port: [src|dst] port 80, [src|dst] port > 1024
- TCP Flags: flags S, flags S and not flags AFPRU
- **TOS**: tos 8

Filters (contd.)

- **Bytes**: bytes > 1024, bytes = 64
- Packets per second: pps > 10
- Bits per second: bps > 10m
- Bits per packet: bpp > 15
- Duration of flow: duration > 36000000
- **AS Number**: [src|dst] 23456
- All numbers can have scaling factors: k, m, g, t with 1024 as factor

Example filters

- proto tcp and (port 80 or port 443)
- proto tcp and (src ip 172.16.17.18 or dst ip 172.16.17.19)
- proto tcp and (net 172.16/16 and src port > 1024 and dst port 80) and bytes > 2048
- ipv6 and proto tcp and (port 80 or port 443)

Alerts and Stats

Alerts Page

- Can create alerts based on set thresholds eg, increase or decrease of traffic
- Emails can be sent once alarm is triggered

Stats page

- Can create graphs based on specific information
 - ASNs,
 - Host/Destination IPs/Ports
 - In/Out interfaces
 - Among others

Plugins

Several plugins available:


- PortTracker tracks the top 10 most active ports and displays a graph
- SURFmap displays country based traffic based on a Geo-Locator

More plugins available here http://sourceforge.net/projects/nfsen-plugins/

Plugin: Porttracker



Plugin: SURFmap



INNOG 6

When to use NfSen

- Can be used for:
 - Forensic work: which hosts were active at a specific time
 - Viewing src/dst AS traffic, src/dst port/IP traffic among many other options
 - Identifying most active IPs or Protocols
- It is a tool to complement your NMS so that you can have more detailed info regarding the traffic
- With this information, you can make an informed decision eg:
 - You have a high amount of SMTP traffic, some machines could be sending out spam
 - 80% of your traffic is to ASN X. Perhaps its wise to connect directly with that network and save costs


Bidirectional vs Unidirectional traffic as seen via NfSen

Unidirectional and Bidirectional


- Unidirectional shows flows from host A to B and then host B to host A
- Bidirectional shows flows between Host A and B combined
- Can be used with any of the other filters (src port, src host plus many more)
- List of filters can be found here:
 http://nfsen.sourceforge.net/#mozTocld652064

Bidirectional (Details tab)

You need to select either a *Singe Timeslot* or *Time Window*



Unidirectional (Details tab)



References

NfSen

http://nfsen.sourceforge.net

NfDump

http://nfdump.sourceforge.net/

