COMS30030
Image Processing and Computer Vision

Part II: Stereo and Motion

Andrew Calway
andrew@cs.bris.ac.uk

1

Andrew Calway
Professor of Computer Vision
www.cs.bris.ac.uk/~andrew
andrew@cs.bris.ac.uk
Computer Vision and Robotics





Vision-Based Simultaneous Localisation and Mapping (SLAM)

2

Stereo and Motion

- **Stereo**
  - Determining scene depth information from 2 (or more) images captured from different viewpoints
  - Geometry, correspondence matching and 3-D reconstruction
- **Motion**
  - Determining 2-D motion in video frames
  - Modelling, optical flow and motion estimation

3

Stereo Vision

- Stereo vision - 3-D from two images taken from different viewpoints.
- Objects appear in different positions in each viewpoint – **parallax**.
- Position of object in each image depends on its depth.
  - position difference (**disparity**) inversely proportional to depth
- If we know disparity & viewpoints
  - 3-D scene structure





Colour animated gif by **Nathaniel Domek**
https://en.wikipedia.org/wiki/Parallax#/media/File:Parallax.gif

4

Two-View Stereo Examples

5

Stereo Computer Vision



6

Three Problems of Stereo

- **Geometry** – determine relative position and orientation of the cameras
- **Correspondence** – determine matching points in the stereo views
- **Reconstruction** – determine 3D location in scene of matched points via triangulation

all interrelated

7

Stereo Vision – SOTA Examples

Two view

Group-wise Correlation Stereo Network, Guo *et al*, CVPR 2019

Multi-view

Depth from Gradients in Dense Light Fields for Object Reconstruction, Yucer *et al*, 3DV 2016

8

Stereo Geometry

- Need to understand geometric relationship between cameras to allow 3-D reconstruction from correspondences
- Simple two-view stereo - coplanar image planes – geometry defined by similar triangles



- General stereo – geometry depends on **position** and **orientation** of cameras
  - **epipolar geometry**



- But we also a need camera model …..

9

Pin Hole Camera Model



10

Perspective Projection Equations

- 3D point: $\mathbf{P} = (X, Y, Z)$ (on surface of object)
- Projects to 2D point: $\mathbf{p} = (x, y, f)$ (in image)
- Using similar triangles (pinhole model):

$$x = \frac{fX}{Z} \qquad y = \frac{fY}{Z}$$

$$\mathbf{p} = f\,\mathbf{P}/Z$$



11

Simple Two-View Stereo

- Coplanar image planes, COPs in X-Z plane
- T – **baseline**, distance between COPs
- Similar triangles:

$$\frac{T}{Z} = \frac{T - x_L + x_R}{Z - f}$$

- Rearrange for depth:

$$Z = \frac{fT}{x_L - x_R} = \frac{fT}{d}$$

Point P has depth Z



d - disparity

focal length f

12

General Two-View Stereo



13

Rotation Matrices



2-D clockwise rotation: 2x2 matrix

$$\mathbf{v}' = \begin{bmatrix} v'_x \\ v'_y \end{bmatrix} = \begin{bmatrix} \cos\theta & \sin\theta \\ -\sin\theta & \cos\theta \end{bmatrix} \begin{bmatrix} v_x \\ v_y \end{bmatrix} = R(\theta)\mathbf{v}$$

3-D rotation composed of rotations around X, Y and Z axes:

3x3 matrix: $R = R_X R_Y R_Z$

$$R_Y \mathbf{P} = \begin{bmatrix} \cos\theta_Y & 0 & \sin\theta_Y \\ 0 & 1 & 0 \\ -\sin\theta_Y & 0 & \cos\theta_Y \end{bmatrix} \begin{bmatrix} X \\ Y \\ Z \end{bmatrix}$$



Clockwise rotation about Y axis

14

2-D Coordinate Transformations



$\mathbf{v}' = R(-\theta)\mathbf{v}$

Vector representation in rotated coordinate system

15