


[Hiring Challenge Freshers](#) [DSA for Beginners](#) [DSA Tutorial](#) [Data Structures](#) [Algorithms](#) [Array](#) [Strings](#) [L](#)

Nth Fibonacci Number

[Read](#)[Discuss\(270+\)](#)[Courses](#)[Practice](#)[Video](#)

Given a number n , print n -th Fibonacci Number.

The Fibonacci numbers are the numbers in the following integer sequence: 0, 1, 1, 2, 3, 5, 8, 13, 21, 34, 55, 89, 144,



Examples:



We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !

Input : $n = 1$

Output : 1

Input : $n = 9$

Output : 34

Input : $n = 10$

Output : 55

Recommended Problem

Nth Fibonacci Number

[Solve Problem](#)

[Dynamic Programming](#) [Mathematical](#) [+2 more](#)

[Amazon](#) [Microsoft](#) [+6 more](#)

Submission count: 2.7L

Iterative Approach to Find and Print Nth Fibonacci Numbers:

In mathematical terms, the sequence F_n of Fibonacci numbers is defined by the recurrence relation: $F_n = F_{n-1} + F_{n-2}$ with seed values and $F_0 = 0$ and $F_1 = 1$.

C++

```
// Fibonacci Series using Space Optimized Method
#include <bits/stdc++.h>
using namespace std;

int fib(int n)
{
    int a = 0, b = 1, c, i;
    if (n == 0)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
        a = b;
        b = c;
    }
    return b;
}

// Driver code
int main()
{
    int n = 9;

    cout << fib(n);
    return 0;
}

// This code is contributed by Code_Mech
```

C

```
// Fibonacci Series using Space Optimized Method
#include <stdio.h>
int fib(int n)
{
    int a = 0, b = 1, c, i;
    if (n == 0)
        return a;
    for (i = 2; i <= n; i++) {
        c = a + b;
        a = b;
        b = c;
    }
    return b;
}

int main()
{
    int n = 9;
    printf("%d", fib(n));
    getchar();
    return 0;
}
```

Java

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
public class fibonacci {
    static int fib(int n)
    {
        int a = 0, b = 1, c;
        if (n == 0)
            return a;
        for (int i = 2; i <= n; i++) {
            c = a + b;
            a = b;
            b = c;
        }
        return b;
    }

    public static void main(String args[])
    {
        int n = 9;
        System.out.println(fib(n));
    }
};

// This code is contributed by Mihir Joshi
```

Python3

```
# Function for nth fibonacci number - Space Optimisation
# Taking 1st two fibonacci numbers as 0 and 1
```

```
def fibonacci(n):
    a = 0
    b = 1
    if n < 0:
        print("Incorrect input")
    elif n == 0:
        return a
    elif n == 1:
        return b
    else:
        for i in range(2, n+1):
            c = a + b
            a = b
            b = c
        return b
```

```
print(fibonacci(9))
```

This code is contributed by Saket Modi

C#

```
// C# program for Fibonacci Series
// using Space Optimized Method
using System;

namespace Fib {
public class GFG {
    static int Fib(int n)
    {
        int a = 0, b = 1, c = 0;

        // To return the first Fibonacci number
        if (n == 0)
            return a;

        for (int i = 2; i <= n; i++) {
            c = a + b;
            a = b;
            b = c;
        }

        return b;
    }

    // Driver function
    public static void Main(string[] args)
    {
        int n = 9;
        Console.Write("{0} ", Fib(n));
    }
}

// This code is contributed by Sam007.
```

Javascript

```
function fib(n)
{
    let a = 0, b = 1, c, i;
    if( n == 0)
        return a;
    for(i = 2; i <= n; i++)
    {
        c = a + b;
        a = b;
        b = c;
    }
    return b;
}

// Driver code

let n = 9;

document.write(fib(n));

// This code is contributed by Mayank Tyagi
```

PHP

```
<?php
// PHP program for Fibonacci Series
// using Space Optimized Method

function fib( $n)
{
    $a = 0;
    $b = 1;
    $c;
    $i;
    if( $n == 0)
        return $a;
    for($i = 2; $i <= $n; $i++)
    {
        $c = $a + $b;
        $a = $b;
        $b = $c;
    }
    return $b;
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
echo fib($n);

// This code is contributed by anuj_67.
?>
```

Learn [Data Structures & Algorithms](#) with GeeksforGeeks

Output

34

Time Complexity: $O(n)$

Auxiliary Space: $O(1)$

Recursion Approach to Find and Print Nth Fibonacci Numbers:

In mathematical terms, the sequence F_n of Fibonacci numbers is defined by the recurrence relation: $F_n = F_{n-1} + F_{n-2}$ with seed values and $F_0 = 0$ and $F_1 = 1$.

The Nth Fibonacci Number can be found using the recurrence relation shown above:

- if $n = 0$, then return 0.
- If $n = 1$, then it should return 1.
- For $n > 1$, it should return $F_{n-1} + F_{n-2}$

Below is the implementation of the above approach:



We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
#include <bits/stdc++.h>
using namespace std;

int fib(int n)
{
    if (n <= 1)
        return n;
    return fib(n - 1) + fib(n - 2);
}

int main()
{
    int n = 9;
    cout << n << "th Fibonacci Number: " << fib(n);
    return 0;
}

// This code is contributed
// by Akanksha Rai
```

C

```
// Fibonacci Series using Recursion
#include <stdio.h>
int fib(int n)
{
    if (n <= 1)
        return n;
    return fib(n - 1) + fib(n - 2);
}

int main()
{
    int n = 9;
    printf("%dth Fibonacci Number: %d", n, fib(n));
    return 0;
}
```

Java

```
// Fibonacci Series using Recursion
import java.io.*;
class fibonacci {
```



```

        return n;
    return fib(n - 1) + fib(n - 2);
}

public static void main(String args[])
{
    int n = 9;
    System.out.println(
        n + "th Fibonacci Number: " + fib(n));
}
}
/* This code is contributed by Rajat Mishra */

```

Python3

```

# Fibonacci series using recursion
def fibonacci(n):
    if n <= 1:
        return n
    return fibonacci(n-1) + fibonacci(n-2)

if __name__ == "__main__":
    n = 9
    print(n, "th Fibonacci Number: ")
    print(fibonacci(n))

# This code is contributed by Manan Tyagi.

```

C#

```

// C# program for Fibonacci Series
// using Recursion
using System;

public class GFG {
    public static int Fib(int n)
    {
        if (n <= 1) {
            return n;
        }
        else {
            return Fib(n - 1) + Fib(n - 2);
        }
    }
}

```

```
// driver code
public static void Main(string[] args)
{
    int n = 9;
    Console.Write(n + "th Fibonacci Number: " + Fib(n));
}

// This code is contributed by Sam007
```

Javascript

```
// Javascript program for Fibonacci Series
// using Recursion

function Fib(n) {
    if (n <= 1) {
        return n;
    } else {
        return Fib(n - 1) + Fib(n - 2);
    }
}

// driver code
let n = 9;
console.log(n + "th Fibonacci Number: " + Fib(n));
```

PHP

```
<?php
// PHP program for Fibonacci Series
// using Recursion

function Fib($n)
{
    if ($n <= 1) {
        return $n;
    }
    else {
        return Fib($n - 1) + Fib($n - 2);
    }
}
```

```
// This code is contributed by Sam007
?>
```

Learn [Data Structures & Algorithms](#) with GeeksforGeeks

Output


34

Time Complexity: Exponential, as every function calls two other functions.


Auxiliary space complexity: $O(n)$, as the maximum depth of the recursion tree is n .

Dynamic Programming Approach to Find and Print Nth Fibonacci Numbers:

Consider the Recursion Tree for the 5th Fibonacci Number from the above approach:



If you see, the same method call is being done multiple times for the same value. This can be optimized with the help of Dynamic Programming. We can



Dynamic Programming Approach to Find and Print Nth Fibonacci Numbers:

Below is the implementation of the above approach:

C++

```
// C++ program for Fibonacci Series
// using Dynamic Programming
#include <bits/stdc++.h>
using namespace std;

class GFG {

public:
    int fib(int n)
    {

        // Declare an array to store
        // Fibonacci numbers.
        // 1 extra to handle
        // case, n = 0
        int f[n + 2];
        int i;

        // 0th and 1st number of the
        // series are 0 and 1
        f[0] = 0;
        f[1] = 1;
```

```

        // in the series and store it
        f[i] = f[i - 1] + f[i - 2];
    }
    return f[n];
}
};

// Driver code
int main()
{
    GFG g;
    int n = 9;

    cout << g.fib(n);
    return 0;
}

// This code is contributed by SoumikMondal

```

C

```

// Fibonacci Series using Dynamic Programming
#include <stdio.h>

int fib(int n)
{
    /* Declare an array to store Fibonacci numbers. */
    int f[n + 2]; // 1 extra to handle case, n = 0
    int i;

    /* 0th and 1st number of the series are 0 and 1*/
    f[0] = 0;
    f[1] = 1;

    for (i = 2; i <= n; i++) {
        /* Add the previous 2 numbers in the series
        and store it */
        f[i] = f[i - 1] + f[i - 2];
    }

    return f[n];
}

int main()
{

```

```

    return 0;
}

```

Java

```

// Fibonacci Series using Dynamic Programming
public class fibonacci {
    static int fib(int n)
    {
        /* Declare an array to store Fibonacci numbers. */
        int f[]
            = new int[n
                + 2]; // 1 extra to handle case, n = 0

        int i;

        /* 0th and 1st number of the series are 0 and 1*/
        f[0] = 0;
        f[1] = 1;

        for (i = 2; i <= n; i++) {
            /* Add the previous 2 numbers in the series
            and store it */
            f[i] = f[i - 1] + f[i - 2];
        }

        return f[n];
    }

    public static void main(String args[])
    {
        int n = 9;
        System.out.println(fib(n));
    }
};
/* This code is contributed by Rajat Mishra */

```

Python3

```

# Fibonacci Series using Dynamic Programming
def fibonacci(n):

    # Taking 1st two fibonacci numbers as 0 and 1
    f = [0, 1]

```

```
return f[n]
```

```
print(fibonacci(9))
```

C#

```
// C# program for Fibonacci Series
// using Dynamic Programming
using System;
class fibonacci {

    static int fib(int n)
    {

        // Declare an array to
        // store Fibonacci numbers.
        // 1 extra to handle
        // case, n = 0
        int[] f = new int[n + 2];
        int i;

        /* 0th and 1st number of the
        series are 0 and 1 */
        f[0] = 0;
        f[1] = 1;

        for (i = 2; i <= n; i++) {
            /* Add the previous 2 numbers
            in the series and store it */
            f[i] = f[i - 1] + f[i - 2];
        }

        return f[n];
    }

    // Driver Code
    public static void Main()
    {
        int n = 9;
        Console.WriteLine(fib(n));
    }
}

// This code is contributed by anuj_67.
```

Javascript

```
// Fibonacci Series using Dynamic Programming

function fib(n)
{
    /* Declare an array to store Fibonacci numbers. */
    let f = new Array(n+2); // 1 extra to handle case, n = 0
    let i;
    /* 0th and 1st number of the series are 0 and 1*/
    f[0] = 0;
    f[1] = 1;
    for (i = 2; i <= n; i++)
    {
        /* Add the previous 2 numbers in the series
        and store it */
        f[i] = f[i-1] + f[i-2];
    }
    return f[n];
}
let n=9;
document.write(fib(n));

// This code is contributed by avanitrachhadiya2155
```

PHP

```
<?php
//Fibonacci Series using Dynamic
// Programming

function fib( $n)
{

    /* Declare an array to store
    Fibonacci numbers. */

    // 1 extra to handle case,
    // n = 0
    $f = array();
    $i;
```



```
$f[0] = 0;
$f[1] = 1;

for ($i = 2; $i <= $n; $i++)
{
    /* Add the previous 2
    numbers in the series
    and store it */
    $f[$i] = $f[$i-1] + $f[$i-2];
}

return $f[$n];
}

$n = 9;
echo fib($n);

// This code is contributed by
// anuj_67.
?>
```

Learn [Data Structures & Algorithms](#) with GeeksforGeeks

Output

34

Time complexity: $O(n)$ for given n

Auxiliary space: $O(n)$

Nth Power of Matrix Approach to Find and Print Nth Fibonacci Numbers

This approach relies on the fact that if we n times multiply the matrix $M = \begin{Bmatrix} 1 & 1 \\ 1 & 0 \end{Bmatrix}$ to itself (in other words calculate $\text{power}(M, n)$), then we get

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

the $(n+1)$ th Fibonacci number as the element at row and column $(0, 0)$ in the resultant matrix.

- If n is even then $k = n/2$:
 - Therefore Nth Fibonacci Number = $F(n) = [2 * F(k-1) + F(k)] * F(k)$
- If n is odd then $k = (n + 1)/2$:
 - Therefore Nth Fibonacci Number = $F(n) = F(k) * F(k) + F(k-1) * F(k-1)$

How does this formula work?

The formula can be derived from the matrix equation.

$$\begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^n = \begin{bmatrix} F_{n+1} & F_n \\ F_n & F_{n-1} \end{bmatrix}$$

Taking determinant on both sides, we get $(-1)^n = F_{n+1}F_{n-1} - F_n^2$

Moreover, since $A^n A^m = A^{n+m}$ for any square matrix A , the following identities can be derived (they are obtained from two different coefficients of the matrix product)

$$F_m F_n + F_{m-1} F_{n-1} = F_{m+n-1} \quad \text{—————(1)}$$

By putting $n = n+1$ in equation(1),

$$F_m F_{n+1} + F_{m-1} F_n = F_{m+n} \quad \text{—————(2)}$$

Putting $m = n$ in equation(1).

$$F_{2n-1} = F_n^2 + F_{n-1}^2$$

Putting $m = n$ in equation(2)

$$F_{2n} = (F_{n-1} + F_{n+1})F_n = (2F_{n-1} + F_n)F_n \quad \text{—————}$$

(By putting $F_{n+1} = F_n + F_{n-1}$)

To get the formula to be proved, we simply need to do the following

- If n is even, we can put $k = n/2$

- If n is odd, we can put $k = (n+1)/2$

Below is the implementation of the above approach

C++

```
// Fibonacci Series using Optimized Method
#include <bits/stdc++.h>
using namespace std;

void multiply(int F[2][2], int M[2][2]);
void power(int F[2][2], int n);

// Function that returns nth Fibonacci number
int fib(int n)
{
    int F[2][2] = { { 1, 1 }, { 1, 0 } };
    if (n == 0)
        return 0;
    power(F, n - 1);

    return F[0][0];
}

// Optimized version of power() in method 4
void power(int F[2][2], int n)
{
    if (n == 0 || n == 1)
        return;
    int M[2][2] = { { 1, 1 }, { 1, 0 } };

    power(F, n / 2);
    multiply(F, F);

    if (n % 2 != 0)
        multiply(F, M);
}

void multiply(int F[2][2], int M[2][2])
{
    int x = F[0][0] * M[0][0] + F[0][1] * M[1][0];
    int y = F[0][0] * M[0][1] + F[0][1] * M[1][1];
    int z = F[1][0] * M[0][0] + F[1][1] * M[1][0];
    int w = F[1][0] * M[0][1] + F[1][1] * M[1][1];
}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

        F[0][0] = x;
        F[0][1] = y;
        F[1][0] = z;
        F[1][1] = w;
    }

// Driver code
int main()
{
    int n = 9;

    cout << fib(9);
    getchar();

    return 0;
}

// This code is contributed by Nidhi_biet

```

C

```

#include <stdio.h>

void multiply(int F[2][2], int M[2][2]);

void power(int F[2][2], int n);

/* function that returns nth Fibonacci number */
int fib(int n)
{
    int F[2][2] = { { 1, 1 }, { 1, 0 } };
    if (n == 0)
        return 0;
    power(F, n - 1);
    return F[0][0];
}

/* Optimized version of power() in method 4 */
void power(int F[2][2], int n)
{
    if (n == 0 || n == 1)
        return;
    int M[2][2] = { { 1, 1 }, { 1, 0 } };

    power(F, n / 2);

```

```

        multiply(F, M);
    }

    void multiply(int F[2][2], int M[2][2])
    {
        int x = F[0][0] * M[0][0] + F[0][1] * M[1][0];
        int y = F[0][0] * M[0][1] + F[0][1] * M[1][1];
        int z = F[1][0] * M[0][0] + F[1][1] * M[1][0];
        int w = F[1][0] * M[0][1] + F[1][1] * M[1][1];

        F[0][0] = x;
        F[0][1] = y;
        F[1][0] = z;
        F[1][1] = w;
    }

    /* Driver program to test above function */
    int main()
    {
        int n = 9;
        printf("%d", fib(9));
        getchar();
        return 0;
    }

```

Java

```

// Fibonacci Series using Optimized Method
public class fibonacci {
    /* function that returns nth Fibonacci number */
    static int fib(int n)
    {
        int F[][] = new int[][] { { 1, 1 }, { 1, 0 } };
        if (n == 0)
            return 0;
        power(F, n - 1);

        return F[0][0];
    }

    static void multiply(int F[], int M[])
    {
        int x = F[0][0] * M[0][0] + F[0][1] * M[1][0];
        int y = F[0][0] * M[0][1] + F[0][1] * M[1][1];
        int z = F[1][0] * M[0][0] + F[1][1] * M[1][0];
    }
}

```

```

        F[0][1] = y;
        F[1][0] = z;
        F[1][1] = w;
    }

    /* Optimized version of power() in method 4 */
    static void power(int F[][], int n)
    {
        if (n == 0 || n == 1)
            return;
        int M[][] = new int[][] { { 1, 1 }, { 1, 0 } };

        power(F, n / 2);
        multiply(F, F);

        if (n % 2 != 0)
            multiply(F, M);
    }

    /* Driver program to test above function */
    public static void main(String args[])
    {
        int n = 9;
        System.out.println(fib(n));
    }
};
/* This code is contributed by Rajat Mishra */

```

Python3

```

# Fibonacci Series using
# Optimized Method

# function that returns nth
# Fibonacci number

```

```

def fib(n):

    F = [[1, 1],
          [1, 0]]
    if (n == 0):
        return 0
    power(F, n - 1)

```

```
def multiply(F, M):

    x = (F[0][0] * M[0][0] +
          F[0][1] * M[1][0])
    y = (F[0][0] * M[0][1] +
          F[0][1] * M[1][1])
    z = (F[1][0] * M[0][0] +
          F[1][1] * M[1][0])
    w = (F[1][0] * M[0][1] +
          F[1][1] * M[1][1])

    F[0][0] = x
    F[0][1] = y
    F[1][0] = z
    F[1][1] = w
```

```
# Optimized version of
# power() in method 4
```

```
def power(F, n):

    if(n == 0 or n == 1):
        return
    M = [[1, 1],
          [1, 0]]

    power(F, n // 2)
    multiply(F, F)

    if (n % 2 != 0):
        multiply(F, M)
```

```
# Driver Code
if __name__ == "__main__":
    n = 9
    print(fib(n))
```

```
# This code is contributed
# by ChitraNayal
```

C#

```
// Fibonacci Series using
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```

class GFG {
    /* function that returns
    nth Fibonacci number */
    static int fib(int n)
    {
        int[, ] F = new int[, ] { { 1, 1 }, { 1, 0 } };
        if (n == 0)
            return 0;
        power(F, n - 1);

        return F[0, 0];
    }

    static void multiply(int[, ] F, int[, ] M)
    {
        int x = F[0, 0] * M[0, 0] + F[0, 1] * M[1, 0];
        int y = F[0, 0] * M[0, 1] + F[0, 1] * M[1, 1];
        int z = F[1, 0] * M[0, 0] + F[1, 1] * M[1, 0];
        int w = F[1, 0] * M[0, 1] + F[1, 1] * M[1, 1];

        F[0, 0] = x;
        F[0, 1] = y;
        F[1, 0] = z;
        F[1, 1] = w;
    }

    /* Optimized version of
    power() in method 4 */
    static void power(int[, ] F, int n)
    {
        if (n == 0 || n == 1)
            return;
        int[, ] M = new int[, ] { { 1, 1 }, { 1, 0 } };

        power(F, n / 2);
        multiply(F, F);

        if (n % 2 != 0)
            multiply(F, M);
    }

    // Driver Code
    public static void Main()
    {
        int n = 9;
        Console.Write(fib(n));
    }
}

```



```
// This code is contributed  
// by ChitraNayal
```

Javascript

```
// Fibonacci Series using Optimized Method  
  
// Function that returns nth Fibonacci number  
function fib(n)  
{  
    var F = [ [ 1, 1 ], [ 1, 0 ] ];  
    if (n == 0)  
        return 0;  
  
    power(F, n - 1);  
  
    return F[0][0];  
}  
  
function multiply(F, M)  
{  
    var x = F[0][0] * M[0][0] + F[0][1] * M[1][0];  
    var y = F[0][0] * M[0][1] + F[0][1] * M[1][1];  
    var z = F[1][0] * M[0][0] + F[1][1] * M[1][0];  
    var w = F[1][0] * M[0][1] + F[1][1] * M[1][1];  
  
    F[0][0] = x;  
    F[0][1] = y;  
    F[1][0] = z;  
    F[1][1] = w;  
}  
  
// Optimized version of power() in method 4 */  
function power(F, n)  
{  
    if (n == 0 || n == 1)  
        return;  
  
    var M = [ [ 1, 1 ], [ 1, 0 ] ];  
  
    power(F, n / 2);  
    multiply(F, M);  
  
    if (n % 2 != 0)
```

```
// Driver code
var n = 9;

document.write(fib(n));

// This code is contributed by gauravrajput1
```

Learn [Data Structures & Algorithms](#) with GeeksforGeeks

Output

34

Time Complexity: $O(\log n)$

Auxiliary Space: $O(\log n)$ if we consider the function call stack size, otherwise $O(1)$.

Related Articles:

[Large Fibonacci Numbers in Java](#)

Feeling lost in the world of random DSA topics, wasting time without progress? It's time for a change! Join our DSA course, where we'll guide you on an exciting journey to master DSA efficiently and on schedule.

Ready to dive in? Explore our Free Demo Content and join our DSA course, trusted by over 100,000 geeks!

- [DSA in C++](#)
- [DSA in Java](#)
- [DSA in Python](#)
- [DSA in JavaScript](#)

Similar Reads



Check if a M-th fibonacci number divides N-th fibonacci number



Check if sum of Fibonacci elements in an Array is a Fibonacci number or not



C/C++ Program for nth multiple of a number in Fibonacci Series



Program to find last two digits of Nth Fibonacci number



Find nth Fibonacci number using Golden ratio



Nth XOR Fibonacci number



Nth Fibonacci number using Pell's equation



Program to find Nth odd Fibonacci Number



Find Nth Fibonacci Number using Binet's Formula



GFact | Finding nth Fibonacci Number using Golden Ratio

Related Tutorials



Mathematical and Geometric Algorithms - Data Structure and Algorithm Tutorials



Learn Data Structures with Javascript | DSA Tutorial



Introduction to Max-Heap - Data Structure and Algorithm Tutorials



Introduction to Set - Data Structure and Algorithm Tutorials



Introduction to Map - Data Structure and Algorithm Tutorials

[Previous](#)

How to check if a given number is Fibonacci number?

[Next](#)

C++ Program For Fibonacci Numbers

Article Contributed By :

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Vote for difficulty

Current difficulty : [Medium](#)

[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)

Improved By : 29AjayKumar, Rajput-Ji, Mithun Kumar, vt_m, ukasp, jit_t, ankthon, GauravRajput1, Akanksha_Rai, RishabhPrabhu, SoumikMondal, humblezero, princiraj1992, Code_Mech, LokeshMohanty, srinam, nidhi_biet, shivanisinghss2110, divyeshrabadiya07, amit143katiyar, 100rahulsingh100, mayankyagi1709, sujitmeshram, avanitrachhadiya2155, arorakashish0911, rutuja2229, prasun_parate, bhavneet2000, surbhityagi15, rohit5swd, rdtank, mukesh07, sweetty, dp0p, anikaseth98, cs19b080, gurjotssb2001, moontyagi786, bhawna1997, amartyaghoshgfg, guptaanushree821, rkbhola5, animeshdey, brian Carrie765, drea, prasad264, harendrakumar123, anshitbansal, polymatir3j, purisaurabh2885, himanshug9119, anshu_1230, factworx4i2, vikramshirsath177, kartikmoyade0901, rohityadavcdece19, singhchfb3w, rvd31305, harshjainmat20

Article Tags : [Amazon](#) , [Bloomberg](#) , [Fibonacci](#) , [MakeMyTrip](#) , [MAQ Software](#) , [matrix-exponentiation](#) , [Modular Arithmetic](#) , [series](#) , [Snapdeal](#) , [DSA](#) , [Dynamic Programming](#) , [Mathematical](#)

Practice Tags : [Amazon](#), [Bloomberg](#), [MakeMyTrip](#), [MAQ Software](#), [Snapdeal](#), [Dynamic Programming](#), [Fibonacci](#), [Mathematical](#), [Modular Arithmetic](#), [series](#)

[Improve Article](#)[Report Issue](#)



A-143, 9th Floor, Sovereign Corporate Tower, Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org



Company

[About Us](#)
[Legal](#)
[Terms & Conditions](#)
[Careers](#)
[In Media](#)
[Contact Us](#)
[Advertise with us](#)
[GFG Corporate Solution](#)
[Placement Training Program](#)
[Apply for Mentor](#)

Languages

[Python](#)
[Java](#)
[C++](#)
[PHP](#)
[GoLang](#)
[SQL](#)
[R Language](#)
[Android Tutorial](#)

Explore

[Job-A-Thon Hiring Challenge](#)
[Hack-A-Thon](#)
[GfG Weekly Contest](#)
[Offline Classes \(Delhi/NCR\)](#)
[DSA in JAVA/C++](#)
[Master System Design](#)
[Master CP](#)
[GeeksforGeeks Videos](#)

DSA Concepts

[Data Structures](#)
[Arrays](#)
[Strings](#)
[Linked List](#)
[Algorithms](#)
[Searching](#)
[Sorting](#)
[Mathematical](#)
[Dynamic Programming](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

DSA Roadmaps

DSA for Beginners
Basic DSA Coding Problems
DSA Roadmap by Sandeep Jain
DSA with JavaScript
Top 100 DSA Interview Problems
All Cheat Sheets

Computer Science

GATE CS Notes
Operating Systems
Computer Network
Database Management System
Software Engineering
Digital Logic Design
Engineering Maths

Data Science & ML

Data Science With Python
Data Science For Beginner
Machine Learning Tutorial
Maths For Machine Learning
Pandas Tutorial
NumPy Tutorial
NLP Tutorial
Deep Learning Tutorial

Competitive Programming

Top DSA for CP
Top 50 Tree Problems

Web Development

HTML
CSS
JavaScript
Bootstrap
ReactJS
AngularJS
NodeJS
Express.js
Lodash

Python

Python Programming Examples
Django Tutorial
Python Projects
Python Tkinter
OpenCV Python Tutorial
Python Interview Question

DevOps

Git
AWS
Docker
Kubernetes
Azure
GCP

System Design

What is System Design
Monolithic and Distributed SD

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[Top 50 Array Problems](#)[Top 50 String Problems](#)[Top 50 DP Problems](#)[Top 15 Websites for CP](#)[Databases in SD](#)[High Level Design or HLD](#)[Low Level Design or LLD](#)[Crack System Design Round](#)[System Design Interview Questions](#)

Interview Corner

[Company Wise Preparation](#)[Preparation for SDE](#)[Experienced Interviews](#)[Internship Interviews](#)[Competitive Programming](#)[Aptitude Preparation](#)

Commerce

[Accountancy](#)[Business Studies](#)[Economics](#)[Human Resource Management \(HRM\)](#)[Management](#)[Income Tax](#)[Finance](#)[Statistics for Economics](#)

SSC/ BANKING

[SSC CGL Syllabus](#)[SBI PO Syllabus](#)[SBI Clerk Syllabus](#)[IBPS PO Syllabus](#)[IBPS Clerk Syllabus](#)[Aptitude Questions](#)[SSC CGL Practice Papers](#)

GfG School

[CBSE Notes for Class 8](#)[CBSE Notes for Class 9](#)[CBSE Notes for Class 10](#)[CBSE Notes for Class 11](#)[CBSE Notes for Class 12](#)[English Grammar](#)

UPSC

[Polity Notes](#)[Geography Notes](#)[History Notes](#)[Science and Technology Notes](#)[Economics Notes](#)[Important Topics in Ethics](#)[UPSC Previous Year Papers](#)

Write & Earn

[Write an Article](#)[Improve an Article](#)[Pick Topics to Write](#)[Share your Experiences](#)[Internships](#)