



# K means Clustering – Introduction

[Read](#)[Discuss](#)[Courses](#)[Practice](#)[Video](#)

K-Means Clustering is an Unsupervised Machine Learning algorithm, which groups the unlabeled dataset into different clusters.

## K means Clustering

[Unsupervised Machine Learning](#) is the process of teaching a computer to use unlabeled, unclassified data and enabling the algorithm to operate on that data without supervision. Without any previous data training, the machine's job in this case is to organize unsorted data according to parallels, patterns, and variations.

The goal of [clustering](#) is to divide the population or set of data points into a number of groups so that the data points within each group are more comparable to one another and different from the data points within the other groups. It is essentially a grouping of things based on how similar and different they are to one another.

We are given a data set of items, with certain features, and values for these features (like a vector). The task is to categorize those items into groups. To achieve this, we will use the K-means algorithm; an unsupervised learning algorithm. 'K' in the name of the algorithm represents the number of groups/clusters we want to classify our items into.





(It will help if you think of items as points in an  $n$ -dimensional space). The algorithm will categorize the items into  $k$  groups or clusters of similarity. To calculate that similarity, we will use the Euclidean distance as a measurement.

The algorithm works as follows:

1. First, we randomly initialize  $k$  points, called means or cluster centroids.
2. We categorize each item to its closest mean and we update the mean's coordinates, which are the averages of the items categorized in that cluster so far.
3. We repeat the process for a given number of iterations and at the end, we have our clusters.

The “points” mentioned above are called means because they are the mean values of the items categorized in them. To initialize these means, we have a lot of options. An intuitive method is to initialize the means at random items in the data set. Another method is to initialize the means at random values between the boundaries of the data set (if for a feature  $x$ , the items have values in  $[0,3]$ , we will initialize the means with values for  $x$  at  $[0,3]$ ).

Google Ads

The above algorithm in pseudocode is as follows:

```
Initialize k means with random values
```

```
--> For a given number of iterations:
```

```
--> Iterate through items:
```

```
--> Find the mean closest to the item by calculating  
the euclidean distance of the item with each of the means
```

```
--> Assign item to mean
```

```
--> Update mean by shifting it to the average of the items in  
that cluster
```

## Import the necessary Libraries:

We are importing Numpy for statistical computations, Matplotlib to plot the graph, and make\_blobs from sklearn.datasets.

---

## Python3

```
import numpy as np  
import matplotlib.pyplot as plt  
from sklearn.datasets import make_blobs
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Create the custom dataset with `make_blobs` and plot it


---

## Python3

```
X,y = make_blobs(n_samples = 500,n_features = 2,centers = 3,random_state = 23)

fig = plt.figure(0)
plt.grid(True)
plt.scatter(X[:,0],X[:,1])
plt.show()
```

Output:



Initialize the random centroids

---

## Python3

```
k = 3

clusters = {}
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
center = 2*(2*np.random.random((X.shape[1],))-1)
points = []
cluster = {
    'center' : center,
    'points' : []
}

clusters[idx] = cluster

clusters
```

### Output:

```
{0: {'center': array([0.06919154, 1.78785042]), 'points': []},
 1: {'center': array([ 1.06183904, -0.87041662]), 'points': []},
 2: {'center': array([-1.11581855,  0.74488834]), 'points': []}}
```


Plot the random initialize center with data points

---

## Python3

```
plt.scatter(X[:,0],X[:,1])
plt.grid(True)
for i in clusters:
    center = clusters[i]['center']
    plt.scatter(center[0],center[1],marker = '*',c = 'red')
plt.show()
```

### Output:



Define euclidean distance

---

## Python3

```
def distance(p1,p2):
    return np.sqrt(np.sum((p1-p2)**2))
```

Create the function to Assign and Update the cluster center

---

## Python3

```
#Implementing E step
def assign_clusters(X, clusters):
    for idx in range(X.shape[0]):
        dist = []

        curr_x = X[idx]

        for i in range(k):
            dis = distance(curr_x, clusters[i]['center'])
            dist.append(dis)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
#Implementing the M-Step
def update_clusters(X, clusters):
    for i in range(k):
        points = np.array(clusters[i]['points'])
        if points.shape[0] > 0:
            new_center = points.mean(axis = 0)
            clusters[i]['center'] = new_center

        clusters[i]['points'] = []
    return clusters
```

---

Create the function to Predict the cluster for the datapoints

## Python3

```
def pred_cluster(X, clusters):
    pred = []
    for i in range(X.shape[0]):
        dist = []
        for j in range(k):
            dist.append(distance(X[i],clusters[j]['center']))
        pred.append(np.argmin(dist))
    return pred
```

---

Assign, Update, and predict the cluster center

## Python3

```
clusters = assign_clusters(X,clusters)
clusters = update_clusters(X,clusters)
pred = pred_cluster(X,clusters)
```

---

Plot the data points with their predicted cluster center


## Python3

```
plt.scatter(X[:,0],X[:,1],c = pred)
```

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
plt.scatter(center[0],center[1],marker = '^',c = 'red')  
plt.show()
```

Output:



Example 2:

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).



## Python3

```
import pandas as pd
import numpy as np
import seaborn as sns
import matplotlib.pyplot as plt
import matplotlib.cm as cm
from sklearn.datasets import load_iris
from sklearn.cluster import KMeans
```

### Load the Dataset

---

## Python3

```
X, y = load_iris(return_X_y=True)
```

### Elbow Method

Finding the ideal number of groups to divide the data into is a basic stage in any unsupervised algorithm. One of the most common techniques for figuring out this ideal value of k is the elbow approach.

---

## Python3

```
#Find optimum number of cluster
sse = [] #SUM OF SQUARED ERROR
for k in range(1,11):
    km = KMeans(n_clusters=k, random_state=2)
    km.fit(X)
    sse.append(km.inertia_)
```

### Plot the Elbow graph to find the optimum number of cluster


---

## Python3

```
g.set(xlabel = "Number of cluster (k)",  
      ylabel = "Sum Squared Error",  
      title = 'Elbow Method')
```

```
plt.show()
```

Output:



From the above graph, we can observe that at  $k=2$  and  $k=3$  elbow-like situation. So, we are considering  $K=3$

Build the Kmeans clustering model

---

## Python3

```
kmeans = KMeans(n_clusters = 3, random_state = 2)  
kmeans.fit(X)
```

```
KMeans
```

```
KMeans(n_clusters=3, random_state=2)
```

Find the cluster center

---

## Python3

```
kmeans.cluster_centers_
```

Output:

```
array([[5.006      , 3.428      , 1.462      , 0.246      ],
       [5.9016129 , 2.7483871 , 4.39354839, 1.43387097],
       [6.85      , 3.07368421, 5.74210526, 2.07105263]])
```

Predict the cluster group:

---

## Python3

```
pred = kmeans.fit_predict(X)
pred
```

Output:

```
array([0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0,
       0, 0, 0, 0, 0, 0, 1, 1, 2, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 2, 1, 1, 1, 1, 1, 1, 1, 1, 1,
       1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 2, 1, 2, 2, 2, 2, 1, 2, 2, 2,
       2, 2, 2, 1, 1, 2, 2, 2, 2, 1, 2, 1, 2, 1, 2, 2, 1, 1, 2, 2, 2, 2,
       2, 1, 2, 2, 2, 2, 1, 2, 2, 2, 1, 2, 2, 2, 1, 2, 2, 1],
      dtype=int32)
```


Plot the cluster center with data points

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

```
plt.figure(figsize=(12,5))
plt.subplot(1,2,1)
plt.scatter(X[:,0],X[:,1],c = pred, cmap=cm.Accent)
plt.grid(True)
for center in kmeans.cluster_centers_:
    center = center[:2]
    plt.scatter(center[0],center[1],marker = '^',c = 'red')
plt.xlabel("petal length (cm)")
plt.ylabel("petal width (cm)")

plt.subplot(1,2,2)
plt.scatter(X[:,2],X[:,3],c = pred, cmap=cm.Accent)
plt.grid(True)
for center in kmeans.cluster_centers_:
    center = center[2:4]
    plt.scatter(center[0],center[1],marker = '^',c = 'red')
plt.xlabel("sepal length (cm)")
plt.ylabel("sepal width (cm)")
plt.show()
```

Output:




Whether you're preparing for your first job interview or aiming to upskill in this ever-evolving tech landscape, [GeeksforGeeks Courses](https://www.geeksforgeeks.org/courses/) are your key to success. We provide top-quality content at affordable prices, all geared towards

already empowered, and we're here to do the same for you. Don't miss out - [check it out now!](#)


Last Updated : 25 Aug, 2023

49


## Similar Reads



Analysis of test data using K-Means Clustering in Python




ML | Determine the optimal value of K in K-Means Clustering



ML | Mini Batch K-means clustering algorithm



Image compression using K-means clustering



K-Means Clustering in R Programming



Difference between K means and Hierarchical Clustering



Image Segmentation using K Means Clustering



K- means clustering with SciPy



K means clustering using Weka



Clustering Text Documents using K-Means in Scikit Learn

## Related Tutorials



OpenAI Python API - Complete Guide



Computer Vision Tutorial



Pandas AI: The Generative AI Python Library



Top Computer Vision Projects (2023)



Python for Kids - Fun Tutorial to Learn Python Programming

[Previous](#)[Next](#)[Music Recommendation System Using Machine Learning](#)[Image Segmentation using K Means Clustering](#)

Article Contributed By :



GeeksforGeeks

### Vote for difficulty

Current difficulty : [Medium](#)[Easy](#)[Normal](#)[Medium](#)[Hard](#)[Expert](#)Improved By : [AlindGupta](#), [utkarshanand221](#), [marcosarcticseal](#), [harshmaster07705](#),  
[pawan\\_kumar\\_gunjan](#), [laxmiraghavyb0c](#)Article Tags : [Machine Learning](#) , [Python](#)Practice Tags : [Machine Learning](#), [python](#)[Improve Article](#)[Report Issue](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

201305

[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

## Company

[About Us](#)  
[Legal](#)  
[Terms & Conditions](#)  
[Careers](#)  
[In Media](#)  
[Contact Us](#)  
[Advertise with us](#)  
[GFG Corporate Solution](#)  
[Placement Training Program](#)  
[Apply for Mentor](#)

## Languages

[Python](#)  
[Java](#)  
[C++](#)  
[PHP](#)  
[GoLang](#)  
[SQL](#)  
[R Language](#)  
[Android Tutorial](#)

## DSA Roadmaps

[DSA for Beginners](#)

## Explore

[Job-A-Thon Hiring Challenge](#)  
[Hack-A-Thon](#)  
[GfG Weekly Contest](#)  
[Offline Classes \(Delhi/NCR\)](#)  
[DSA in JAVA/C++](#)  
[Master System Design](#)  
[Master CP](#)  
[GeeksforGeeks Videos](#)

## DSA Concepts

[Data Structures](#)  
[Arrays](#)  
[Strings](#)  
[Linked List](#)  
[Algorithms](#)  
[Searching](#)  
[Sorting](#)  
[Mathematical](#)  
[Dynamic Programming](#)

## Web Development

[HTML](#)

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

[DSA Roadmap by Sandeep Jain](#)[DSA with JavaScript](#)[Top 100 DSA Interview Problems](#)[All Cheat Sheets](#)[JavaScript](#)[Bootstrap](#)[ReactJS](#)[AngularJS](#)[NodeJS](#)[Express.js](#)[Lodash](#)

## Computer Science

[GATE CS Notes](#)[Operating Systems](#)[Computer Network](#)[Database Management System](#)[Software Engineering](#)[Digital Logic Design](#)[Engineering Maths](#)

## Python

[Python Programming Examples](#)[Django Tutorial](#)[Python Projects](#)[Python Tkinter](#)[OpenCV Python Tutorial](#)[Python Interview Question](#)

## Data Science & ML

[Data Science With Python](#)[Data Science For Beginner](#)[Machine Learning Tutorial](#)[Maths For Machine Learning](#)[Pandas Tutorial](#)[NumPy Tutorial](#)[NLP Tutorial](#)[Deep Learning Tutorial](#)

## DevOps

[Git](#)[AWS](#)[Docker](#)[Kubernetes](#)[Azure](#)[GCP](#)

## Competitive Programming

[Top DSA for CP](#)[Top 50 Tree Problems](#)[Top 50 Graph Problems](#)[Top 50 Array Problems](#)[Top 50 String Problems](#)

## System Design

[What is System Design](#)[Monolithic and Distributed SD](#)[Scalability in SD](#)[Databases in SD](#)[High Level Design or HLD](#)



## Interview Corner

Company Wise Preparation

Preparation for SDE

Experienced Interviews

Internship Interviews

Competitive Programming

Aptitude Preparation

## Commerce

Accountancy

Business Studies

Economics

Human Resource Management (HRM)

Management

Income Tax

Finance

Statistics for Economics

## SSC/ BANKING

SSC CGL Syllabus

SBI PO Syllabus

SBI Clerk Syllabus

IBPS PO Syllabus

IBPS Clerk Syllabus

Aptitude Questions

SSC CGL Practice Papers

## GfG School

CBSE Notes for Class 8

CBSE Notes for Class 9

CBSE Notes for Class 10

CBSE Notes for Class 11

CBSE Notes for Class 12

English Grammar

## UPSC

Polity Notes

Geography Notes

History Notes

Science and Technology Notes

Economics Notes

Important Topics in Ethics

UPSC Previous Year Papers

## Write & Earn

Write an Article

Improve an Article

Pick Topics to Write

Share your Experiences

Internships

@GeeksforGeeks, Sanchhaya Education Private Limited, All rights reserved