

08 - Superlative Streams

CS 2043: Unix Tools and Scripting, Spring 2016 [1]

Stephen McDowell

February 12th, 2016

Cornell University

Table of contents

1. Cutting and Pasting
2. Splitting and Joining
3. The Stream Editor (`sed`)

Some Logistics

- HW1 due today at 5pm

Some Logistics

- HW1 due today at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- **On my usage of >, which will now become ~>**

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `~>`
- **Repository confusion:**

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `~>`
- Repository confusion:
 - *do NOT fork the `<usr>-assignments` repositories!!!!!!*

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `~>`
- Repository confusion:
 - *do **NOT** fork the <usr>-assignments repositories!!!!!!*
 - getting lectures easily: **clone** the **lecture-slides** repo, **pull** as needed

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `~>`
- Repository confusion:
 - *do **NOT** fork the <usr>-assignments repositories!!!!!!*
 - getting lectures easily: `clone` the `lecture-slides` repo, `pull` as needed
 - ***only fork** the **lecture-demos** repo*

Some Logistics

- HW1 due **today** at 5pm
- OH Today: only 2pm - 3pm...thanks (again) Joe!
- On my usage of `>`, which will now become `~>`
- Repository confusion:
 - *do **NOT** fork the <usr>-assignments repositories!!!!!!*
 - getting lectures easily: `clone` the `lecture-slides` repo, `pull` as needed
 - *only fork the lecture-demos repo*
 - *this allows you to put your demo work online, get more practice with **git***

Cutting and Pasting

Chopping up Input

Cut

`cut <options> [file]`

- *must* specify a list of bytes, characters, or fields
 - `file` is optional this time, uses `STDIN` if unspecified
- `-b`: extracts using range of *bytes*
- `-c`: extracts using a range of *characters*
- `-f`: extracts a range of *fields* separated by a delimiter

N	N th byte, character or field, counted from 1
N-	from N th byte, character or field, to end of line
N-M	from N th to M th (included) byte, character or field
-M	from first to M th (included) byte, character or field

- `-d`: specify the delimiter (`TAB` by default)
- `-s`: suppress line if `delimiter` not found

Cut Examples

employees.csv

```
Alice,female,607-123-4567,11 Sunny Place,Ithaca,NY,14850
Bob,male,607-765-4321,1892 Rim Trail,Ithaca,NY,14850
Andy,n/a,607-706-6007,1 To Rule Them All,Ithaca,NY,14850
Bad employee data without proper delimiter
```

Examples

- Get names, ignore improper lines
~> `cut -d , -f 1 -s employees.csv`
- Get names and phone numbers, ignore improper lines
~> `cut -d , -f 1,3 -s employees.csv`
- Get address (4th col and after), ignore improper lines
~> `cut -d , -f 4- -s employees.csv`
- Get 11th character of every line
~> `cut -c 11 employees.csv`

Paste

```
paste [options] [file1] [file2] ...
```

- No **options** or **files** necessary...
...but relatively useless program without them.
- **-d**: specify the delimiter (**TAB** by default)
- **-s**: concatenates serially instead of side-by-side
- No options and one **file** specified: just like **cat**
 - Use with **-s** to join all lines of file!

Paste Examples I

names.txt

Alice

Bob

Andy

phones.txt

607-123-4567

607-765-4321

607-706-6007

```
~> paste -d , names.txt phones.txt > result.txt
```

result.txt

Alice,607-123-4567

Bob,607-765-4321

Andy,607-706-6007

Paste Examples II

names.txt

Alice

Bob

Andy

phones.txt

607-123-4567

607-765-4321

607-706-6007

```
~> paste -d , -s names.txt phones.txt > result.txt
```

result.txt

Alice,Bob,Andy

607-123-4567,607-765-4321,607-706-6007

Paste Examples III

employees.csv

```
Alice,female,607-123-4567,11 Sunny Place,Ithaca,NY,14850
Bob,male,607-765-4321,1892 Rim Trail,Ithaca,NY,14850
Andy,n/a,607-706-6007,1 To Rule Them All,Ithaca,NY,14850
Bad employee data without proper delimiter
```

```
~> paste -d " " -s employees.csv | \
      cut -d , -f 1- --output-delimiter=" " | \
      tr -d "[:space:]"
```

output (all on one line...)

```
Alicefemale607-123-456711SunnyPlaceIthacaNY14850Bobmale6
07-765-43211892RimTrailIthacaNY14850Andyn/a607-706-60071
ToRuleThemAllIthacaNY14850Bademployeedatawithoutproperde
limiter
```

Splitting and Joining

Split

```
split [options] [input] [prefix]
```

- **-l**: how many lines in each file
 - default is 1000
- **-b**: how many bytes in each file
- **prefix**: name prefix of each file produced
- **-d**: use numeric suffixes instead of lexicographic
 - not available on OSX

- Extremely useful for managing large streams of data

Split

```
split [options] [input] [prefix]
```

- **-l**: how many lines in each file
 - default is 1000
- **-b**: how many bytes in each file
- **prefix**: name prefix of each file produced
- **-d**: use numeric suffixes instead of lexographic
 - not available on OSX

- Extremely useful for managing large streams of data
- Remember that annoying *dungeon* folder?

Splitting Files

Split

`split [options] [input] [prefix]`

- `-l`: how many lines in each file
 - default is 1000
- `-b`: how many bytes in each file
- `prefix`: name prefix of each file produced
- `-d`: use numeric suffixes instead of lexographic
 - not available on OSX

- Extremely useful for managing large streams of data
- Remember that annoying *dungeon* folder?
 - `split -l 5` is what we did

Joining Files

Join lines that contain the same keys between two different files.

Join

```
join [options] file1 file2
```

- Join two files at a time, no more, no less.
- Default: files are assumed to be delimited by *whitespace*.
- **-t <char>**: specify alternative *single-character* delimiter.
- **-1 field_number**: join by the n^{th} field of **file1**
- **-2 field_number**: join by the n^{th} field of **file2**
 - field numbers start at 1, like **cut** and **paste**
- **-a f_num**: displays unpaired lines of file **f_num**.

Join Examples I

ages.txt

Alice 44

Bob 30

Candy 12

salaries.txt

Bob 300,000

Candy 120,000

```
~> join ages.txt salaries.txt > results.txt
```

results.txt

Bob 30 300,000

Candy 12 120,000

Join Examples II

ages.txt

Alice 44

Bob 30

Candy 12

salaries.txt

Bob 300,000

Candy 120,000

```
~> join -a1 ages.txt salaries.txt > results.txt
```

results.txt

Alice 44

Bob 30 300,000

Candy 12 120,000

The Stream Editor (`sed`)

Introducing...

Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
 - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
 - Replace anything that matches `<regex>` with `<text>`.
 - `sed` goes line by line searching for the regular expression.
-
- We will only cover the *basics*, as `sed` is an entire programming language.

Introducing...

Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
- We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
 - Replace anything that matches `<regex>` with `<text>`.
- `sed` goes line by line searching for the regular expression.
- We will only cover the *basics*, as `sed` is an entire programming language.
 - As in there are entire books on it...

Introducing...

Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
- We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
 - Replace anything that matches `<regex>` with `<text>`.
- `sed` goes line by line searching for the regular expression.
- We will only cover the *basics*, as `sed` is an entire programming language.
 - As in there are entire books on it...
- What is the difference between `sed` and `tr`?

Introducing...

Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
 - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
 - Replace anything that matches `<regex>` with `<text>`.
 - `sed` goes line by line searching for the regular expression.
-
- We will only cover the *basics*, as `sed` is an entire programming language.
 - As in there are entire books on it...
 - What is the difference between `sed` and `tr`?
 - `sed` can match regular expressions!

Introducing...

Stream Editor

`sed [options] [script] [file]`

- Stream editor for filtering and transforming text.
 - We will focus on `sed`'s '`s/<regex>/<text>`' `[file]`.
 - Replace anything that matches `<regex>` with `<text>`.
 - `sed` goes line by line searching for the regular expression.
-
- We will only cover the *basics*, as `sed` is an entire programming language.
 - As in there are entire books on it...
 - What is the difference between `sed` and `tr`?
 - `sed` can match regular expressions!
 - `sed` also does a lot more.

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with `sed`
 - don't have to escape every double-quote (")

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**
 - don't have to escape every double-quote (")
- What happens if we do not have the **g**?

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**
 - don't have to escape every double-quote (")
- What happens if we do not have the **g**?
 - Without the **g**, it will only do one substitution per line.

A Basic Example

```
sed 's/not guilty/guilty/g' filename
```

- Replaces *not guilty* with *guilty* everywhere in the file.
- CAUTION: You should be in the habit of using *single-quotes* for strings with **sed**
 - don't have to escape every double-quote (")
- What happens if we do not have the **g**?
 - Without the **g**, it will only do one substitution per line.
 - There are definitely cases where you would want that!

Deletion

- Just like with `tr` we can do deletion with `sed`.

Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all lines that contain `regex`.

Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all **lines** that contain `regex`.
- **Example:**

Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all lines that contain `regex`.
- Example:
 - `sed '/[Dd]avid/d' file1 > file2`

Deletion

- Just like with `tr` we can do deletion with `sed`.
- `sed '/regex/d'` - deletes all **lines** that contain **regex**.
- Example:
 - `sed '/[Dd]avid/d' file1 > file2`
 - Deletes all lines in **file1** that contain either *David* or *david*, and saves the result into **file2**.

- The power of `sed` is that it treats everything between the first pair of `/`'s as a regular expression.

Regular Expressions

- The power of `sed` is that it treats everything between the first pair of `/`'s as a regular expression.
- What does this do?

Regular Expressions

- The power of `sed` is that it treats everything between the first pair of `/`'s as a regular expression.
- What does this do?

```
~> sed 's/[[:alpha:]]\{1,3\}[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

Regular Expressions

- The power of `sed` is that it treats everything between the first pair of `/`'s as a regular expression.
- What does this do?

```
~> sed 's/[[:alpha:]]\{1,3\}[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

- Print a file with all `netID@cornell.edu` emails removed!

Regular Expressions

- The power of `sed` is that it treats everything between the first pair of `/`'s as a regular expression.
- What does this do?

```
~> sed 's/[[:alpha:]]\{1,3\}[[:digit:]]*@cornell\.edu/REMOVED/g' file
```

- Print a file with all `netID@cornell.edu` emails removed!
- Use `-r` (`-E` on OSX) to use *extended* regular expressions.

Saving Strings

- What does this do?

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\), \([A-Z][A-Za-z]*\)/\2 \1/' file
```

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \1 \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\), \([A-Z][A-Za-z]*\)/\2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside **()** tells the editor to *save* whatever string matches the expression.

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\), \([A-Z][A-Za-z]*\)/\2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside **()** tells the editor to *save* whatever string matches the expression.
- Since **()** are special characters, we escape them e.g. with **\(\)**.

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1**, **e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside () tells the editor to *save* whatever string matches the expression.
- Since () are special characters, we escape them e.g. with `\(\)`.
- We access the saved strings as `\1` and `\2`.

Saving Strings

- What does this do?

```
~> sed 's/^\([A-Z][A-Za-z]*\) , \([A-Z][A-Za-z]*\) / \2 \1/' file
```

- Searches for an expression at the beginning of the line of the form **e1, e2** where **e1** and **e2** are "words" starting with capital letters.
- Placing an expression inside **()** tells the editor to *save* whatever string matches the expression.
- Since **()** are special characters, we escape them e.g. with **\(\)**.
- We access the saved strings as **\1** and **\2**.
- This script for example could convert a database file from **Lastname, Firstname** - to - **Firstname, Lastname**

[1] B. Abrahao, H. Abu-Libdeh, N. Savva, D. Slater, and others over the years.

Previous cornell cs 2043 course slides.