

Logic.CommandType

Class DisplayCommandType

java.lang.Object
Logic.CommandType.DisplayCommandType

All Implemented Interfaces:

Logic.CommandType.CommandType

```
public class DisplayCommandType
extends java.lang.Object
implements Logic.CommandType.CommandType
```

This is a class that can be instantiated to represent a display command. It can support all types of add commands (all tasks, specific projects) Each type of add command has a dedicated constructor.

Author:
abdulla contractor and amit gamane

Constructor Summary

Constructors

Constructor and Description

- [DisplayCommandType\(\)](#)
- [DisplayCommandType\(java.lang.String _modifiers\)](#)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type Method and Description

- | | |
|------------------|--------------------------------|
| java.lang.String | getModifiers() |
| java.lang.String | getType() |

Methods inherited from class java.lang.Object

`equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructor Detail

DisplayCommandType

```
public DisplayCommandType()
```

DisplayCommandType

```
public DisplayCommandType(java.lang.String _modifiers)
```

Method Detail

getType

```
public java.lang.String getType()
```

Specified by:

getType in interface Logic.CommandType.CommandType

getModifiers

public java.lang.String getModifiers()