

Logic.CommandType

Class DeleteCommandType

java.lang.Object
Logic.CommandType.DeleteCommandType

All Implemented Interfaces:

Logic.CommandType.CommandType

```
public class DeleteCommandType
extends java.lang.Object
implements Logic.CommandType.CommandType
```

This is a class that can be instantiated to represent a display command. It can support all types of add commands (all tasks, specific projects) Each type of add command has a dedicated constructor.

Author:

abdulla contractor and amit gamane

Constructor Summary

Constructors

Constructor and Description

DeleteCommandType(java.lang.String _taskDescription)

DeleteCommandType(java.lang.String _taskDescription, java.lang.String _projectName)

Method Summary

All Methods Instance Methods Concrete Methods

Modifier and Type	Method and Description
java.lang.String	getProjectName ()
java.lang.String	getTaskDescription ()
java.lang.String	getType ()

Methods inherited from class java.lang.Object

equals, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructor Detail

DeleteCommandType

```
public DeleteCommandType(java.lang.String _taskDescription)
```

DeleteCommandType

```
public DeleteCommandType(java.lang.String _taskDescription,
                           java.lang.String _projectName)
```

Method Detail

getType

```
public java.lang.String getType()
```

Specified by:
getType in interface `Logic.CommandType.CommandType`

getProjectName

```
public java.lang.String getProjectName()
```

getTaskDescription

```
public java.lang.String getTaskDescription()
```