

M4350 Series - Important specifications

M4350 series is a fully managed switch mainly used for high performance audio/video over IP applications.

Comparison with M4250:

M4350 series supports 25G and 100 G uplinks along with redundant power supply.

Specifically designed for greater scalability whereas 4250 is mostly limited to 1and 10G uplinks

M4350 supports redundant power supplies in certain models and provides with hitless switchover whereas M4250 doesn't have redundant power support and doesn't promise same level of seamless failover.

Most advanced features(I2,I3 and AV features) are available without extra licenses.

Like M4250, M4350 also has different flavors ,details of which is shown below.

Abbreviations:

X - 10 G ports

F - 10G fiber ports

M - Multi gigabit ports - supports multiple speeds 100 Mbps/1g/2.5g/5g/10g automatically negotiated based on peer connection.

V - Very high power POE(POE++) which can supply upto 90W per port

C- Combo ports - (Copper plus fiber)

Combo ports = **flexible physical interface** (copper or fiber)

Port that can support both copper and fiber interfaces but only one at the same time.

*star - Indicates POE support

** star star - Indicates POE ++ support

M4350 Product Series	Number of Ports	POE sup port	Broadcom Chipset	RAM Detail s (DDR 4 SDRA M)	PHASE	
----------------------------	--------------------	--------------------	---------------------	---	-------	--

M4350-8X8F	8 × 10G (or multi-gig / copper) and 8 × SFP+ (fiber) ports	No POE support	56174 - Hurricane 3 MG variantn	2 GB	Phase 1 / 1.5	
M4350-12X12F	12 × 10G / multi-gig and 12 × SFP+ fiber ports	No POE support	56172 - Hurricane 3 MG variant	2 GB		
M4350-44M4X4V **	44 - Multi Gigabit ports 4 - 10 G ports 4 × “V” (PoE / high power)	POE ++ support	56170 - Hurricane 3 MG	2 GB		
M4350-24F4V	24-SFP / fiber and 4- “V” (PoE / powered)	No POE support		2 GB		
M4350-24X4V*	24 *10 G ports and 4 POE++ each upto 90W	POE +		2 GB		
M4350-4XF*	24 * 1G ports and 4 *SFP+ 10 G uplinks	POE +	56160 - Hurricane 3	2 GB		
M4350-48G4F*	48 * 1G ports and 4 * SFP 10 G uplinks	POE +	56172 - Hurricane 3 MG variant	2 GB		
M4350-24X8F8V**	24* 10 G ports and 8* 25G SFP28 fiber ports	POE ++	56370 - Trident3 - X3	4GB	Phase 2	

	and 8V Multi-gigabit POE++					
M4350-36X4V**	36* 10G ports and 4*Multi gigabit POE++ copper ports	POE ++		4 GB		
M4350-32F8V	32 * SFP fiber ports (10G/25G) and 8 * multi gigabit POE++ copper port	No POE		4 GB		
M4350-16V4C	16 * POE ++ multi gigabit port and 4 Combo ports	No POE	56471 - Trident 3 - X4 variant	4 GB		
M4350-40X4C**	40 * 10g ports and 4 Combo ports	POE ++	56472 - Trident 3 - X4 variant	4 GB		
M4350-24F4X	24 * Fiber ports and 4 *10g fiber uplink ports	No POE	56172 - Hurricane 3 MG variant	4 GB	Phase3	
M4350-8M2V**	8* Multi gigabit and 2 * POE++ ports	POE ++	56172 - Hurricane 3 MG variant	4 GB		

M4350-24M4X4 V**	24 * Multigigabit ports and 4 *10 G ports and 4 * POE** ports	POE ++	56172 - Hurricane 3 MG variant	4 GB		
M4350-40F4C	40 * 10 G SFP ports and 4 Combo ports	No POE	56472 - Trident 3 X4 variant	4 GB		
M4350-16M4V*	16 * multi gigabit ports and 4 * POE ++ ports	POE ++	56172 - Hurricane 3 MG variant	2 GB	Phase 4	
M4350-16C	16 combo ports	No POE	56471 - Trident 3 X4 variant	4 GB		

NOTE:

All the modes of 4350 either have Hurricane 3 , Hurricane 3 MG chipset/variant or Trident 3 -x3 and x4.

BCM56170 is the standard Hurricane 3 MG chipset ,variation in last digit indicates a variant in the same chipset.

BCM56160 - Standard Hurricane 3 chipset

BCM56370 - Trident 3 -X3

BCM56470-Trident 3 X4