

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ \begin{array}{l} C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \end{array} \right\}$
5a	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
6	$\left\{ \begin{array}{l} C = A_0 B_0^T + B_0 A_0^T + \widehat{C} \end{array} \right\}$
8	$C := a_1 b_1^T + b_1 a_1^T + C$
7	$\left\{ \begin{array}{l} C = A_0 B_0^T + B_0 A_0^T + a_1 b_1^T + b_1 a_1^T + \widehat{C} \end{array} \right\}$
5b	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
2	$\left\{ \begin{array}{l} C = A_L B_L^T + B_L A_L^T + \widehat{C} \end{array} \right\}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	{ }
4	where
2	{ }
3	while do
2,3	{ \wedge }
5a	where
6	{ }
8	
7	{ }
5b	
2	{ }
	endwhile
2,3	{ $\wedge \neg($) }
1b	{ }

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	{ $C = \hat{C}$ }
4	where
2	{ }
3	while do
2,3	{ \wedge }
5a	where
6	{ }
8	
7	{ }
5b	
2	{ }
	endwhile
2,3	{ $\wedge \neg($) }
1b	{ $[C] = \text{syr2k_ln}(A, B, \hat{C})$ }

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	where
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while do
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge$
5a	where
6	$\{$
8	
7	$\{$
5b	
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg($
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	where
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A)\}$
5a	where
6	$\{$
8	
7	$\{$
5b	
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \right\}$
5a	where
6	$\{$
8	
7	$\{$
5b	
2	$\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \right\}$
5a	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
6	$\{$
8	
7	$\{$
5b	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
2	$\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \right\}$
5a	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
6	$\{ \textcolor{red}{C} = A_0 B_0^T + B_0 A_0^T + \widehat{C} \}$
8	
7	$\{$
5b	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
2	$\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}\}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}\}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \right\}$
5a	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
6	$\{ C = A_0 B_0^T + B_0 A_0^T + \widehat{C} \}$
8	
7	$\{ \textcolor{red}{C} = A_0 B_0^T + B_0 A_0^T + a_1 b_1^T + b_1 a_1^T + \widehat{C} \}$
5b	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
2	$\{ C = A_L B_L^T + B_L A_L^T + \widehat{C} \}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))\}$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})\}$

Step	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
1a	$\{C = \widehat{C}$
4	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}$
3	while $n(A_L) < n(A)$ do
2,3	$\left\{ \begin{array}{l} C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge n(A_L) < n(A) \end{array} \right\}$
5a	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
6	$\{C = A_0 B_0^T + B_0 A_0^T + \widehat{C}$
8	$C := a_1 b_1^T + b_1 a_1^T + C$
7	$\{C = A_0 B_0^T + B_0 A_0^T + a_1 b_1^T + b_1 a_1^T + \widehat{C}$
5b	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
2	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C}$
	endwhile
2,3	$\{C = A_L B_L^T + B_L A_L^T + \widehat{C} \wedge \neg(n(A_L) < n(A))$
1b	$\{[C] = \text{syr2k_ln}(A, B, \widehat{C})$

	Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
	$A \rightarrow \left(A_L \middle A_R \right), B \rightarrow \left(B_L \middle B_R \right)$ where A_L has 0 columns, B_L has 0 columns
	while $n(A_L) < n(A)$ do
	$\left(A_L \middle A_R \right) \rightarrow \left(A_0 \middle a_1 \ A_2 \right), \left(B_L \middle B_R \right) \rightarrow \left(B_0 \middle b_1 \ B_2 \right)$ where a_1 has 1 column, b_1 has 1 column
	$C := a_1 b_1^T + b_1 a_1^T + C$
	$\left(A_L \middle A_R \right) \leftarrow \left(A_0 \ a_1 \middle A_2 \right), \left(B_L \middle B_R \right) \leftarrow \left(B_0 \ b_1 \middle B_2 \right)$
	endwhile

Algorithm: $[C] := \text{SYR2K_LN_UNB_VAR9}(A, B, C)$
$A \rightarrow \left(A_L \left A_R \right. \right), B \rightarrow \left(B_L \left B_R \right. \right)$ where A_L has 0 columns, B_L has 0 columns while $n(A_L) < n(A)$ do $\left(A_L \left A_R \right. \right) \rightarrow \left(A_0 \left a_1 \ A_2 \right. \right), \left(B_L \left B_R \right. \right) \rightarrow \left(B_0 \left b_1 \ B_2 \right. \right)$ where a_1 has 1 column, b_1 has 1 column $C := a_1 b_1^T + b_1 a_1^T + C$ $\left(A_L \left A_R \right. \right) \leftarrow \left(A_0 \ a_1 \left A_2 \right. \right), \left(B_L \left B_R \right. \right) \leftarrow \left(B_0 \ b_1 \left B_2 \right. \right)$ endwhile