


SYSTEMS AND SOFTWARE REQUIREMENTS SPECIFICATION (SSRS) FOR
sQuire Collaborative IDE



Version 1.3
April 11, 2016

Prepared for:
CS383-01

Prepared by:
Domn Werner (wern0096) | Robert Carlson (carl7595)
Brian Cartwright (cart1189) | Max Welch (welc2150)
Matthew Daniel (dani2918) | Brandon Ratcliff (ratc8795)
Joel Doumit (doum6708) | Eric Gentile-Quant (gent7104)
Team 4 - It Compiled Yesterday (ICY)
University of Idaho
Moscow, ID 83844-1010

sQuire SSRS

RECORD OF CHANGES

[illegible]

*A - ADDED M - MODIFIED D - DELETED

SQUIRE SSRS TABLE OF CONTENTS

Section	Page
1 REQUIREMENTS	1
1.1 INTRODUCTION	1
1.1.1 IDENTIFICATION	1
1.1.2 PURPOSE	1
1.1.3 SCOPE	1
1.1.4 DEFINITIONS, ACRONYMS, AND ABBREVIATIONS	1
1.1.5 OVERALL DESCRIPTION	3
1.1.6 PRODUCT PERSPECTIVE	3
1.2 SYSTEM LEVEL (NON-FUNCTIONAL REQUIREMENTS)	4
1.2.1 Site dependencies	4
1.3 Safety, security and privacy requirements	4
1.3.1 Performance requirements	5
1.3.2 System and software quality	5
1.3.3 Packaging and delivery requirements	5
1.3.4 Personnel-related requirements	5
1.3.5 Training-related requirements	5
1.4 FUNCTIONAL REQUIREMENTS	5
1.4.1 Project Browsing	5
1.4.2 Authentication	6
1.4.3 Communication	7
1.4.4 File Management	7
1.4.5 File Editing	7
1.4.6 Project Management	8
1.4.7 Project User Management	9
1.4.8 User Preferences	9
2 DESIGN	10
2.1 USE CASE DESCRIPTIONS	10
2.1.1 Authentication Feature 1: Sign Up Use Case Description	10
2.1.2 Authentication Feature 2: Log In Use Case Description	11
2.1.3 Authentication Feature 3: Log Out Use Case Description	12
2.1.4 Authentication Feature 4: Change Password Use Case Description	13
2.1.5 Authentication Feature 5: Change Email Use Case Description	14
2.1.6 Authentication Feature 6: Change Username Use Case Description	15
2.1.7 Project Browsing Feature 1: Project Browsing Use Case Description	16
2.1.8 Project Browsing Feature 2: Project Creation Use Case Description	17
2.1.9 Project Browsing Feature 3: Project Commenting Use Case Description	18
2.1.10 Project Browsing Feature 4: Project Voting Use Case Description	19
2.1.11 Communication Feature 1: Read Project Chat Use Case Description	20
2.1.12 Communication Feature 2: Write to Project Chat Use Case Description	21
2.1.13 Communication Feature 3: Message User by Name Use Case Description	22
2.1.14 Communication Feature 4: Comment on Project Use Case Description	23

2.1.15	Communication Feature 5: Close chat Use Case Description	24
2.1.16	Project Management Feature 1: Use Case Description 1: Compile and execute project (dani2918)	25
2.1.17	Project Management Feature 2: Create project Use Case Description (dani2918) . . .	26
2.1.18	Project Management Feature 3: Delete Project Use Case Description (dani2918) . . .	27
2.1.19	Project Management Feature 4: Request to Join Project Use Case Description (dani2918)	28
2.1.20	Project Management Feature 5: Manage Request to Join Project Use Case Description (dani2918)	29
2.1.21	Project Management Feature 6: Leave Project Use Case Description (dani2918) . . .	30
2.1.22	Project Management Feature 7: Invite to Project Use Case Description (dani2918) . .	31
2.1.23	Project Management Feature 8: Respond to Project Invite Use Case Diagram (dani2918)	32
2.1.24	File Editing Feature 1: View Line Numbers	33
2.1.25	File Editing Feature 2: View References	34
2.1.26	File Editing Feature 3: View Dates	35
2.1.27	File Editing Feature 4: View Authors	36
2.1.28	File Editing Feature 5: Format Document	37
2.1.29	File Editing Feature 6: Find/Replace	38
2.1.30	File Editing Feature 7: Comment Section	39
2.1.31	File Editing Feature 8: Display Typing User	40
2.1.32	File Editing Feature 9: Display Syntax Errors	41
2.1.33	File Editing Feature 10: Display Syntax Highlighting	42
2.1.34	File Management Feature 1: Open File Use Case Description	43
2.1.35	File Management Feature 2: Close File Use Case Description	44
2.1.36	File Management Feature 3: Save File Use Case Description	45
2.1.37	File Management Feature 4: Add File Use Case Description	46
2.1.38	Project User Management Feature 1: Add User to Project Use Case Description . . .	47
2.1.39	Project User Management Feature 2: Kick User Use Case Description	48
2.1.40	Project User Management Feature 3: Set User Permissions Use Case Description . . .	49
2.2	USE CASE DIAGRAMS	50
2.2.1	Use Case Diagram 1: Authentication	50
2.2.2	Use Case Diagram 2: Project Browsing	51
2.2.3	Use Case Diagram 4: User Preferences	52
2.2.4	User Preferences Feature 1: Use Case Diagram 1	53
2.2.5	User Preferences Feature 2: Use Case Diagram 2	54
2.2.6	Use Case Diagram 5: Project Management (dani2918)	55
2.2.7	Use Case Diagram 6: File Editing	56
2.2.8	Use Case Diagram 7: File Management	57
2.2.9	Use Case Diagram 8: Project User Management	58
2.2.10	Use Case Diagram 3: Communication	59
2.3	CLASS DIAGRAMS	60
2.3.1	Class Diagram 1: File Management	60
2.3.2	Class Diagram Description 1: File Management Description	61
2.3.3	Class Diagram 2: File Editing	62
2.3.4	Class Diagram Description 2: File Editing Description	63
2.3.5	Class Diagram 3: Authentication	65
2.3.6	Class Diagram Description 3: Authentication Description	66
2.3.7	Class Diagram 4: User Preferences	67
2.3.8	Class Diagram Description 4: User Preferences Description	68
2.3.9	Class Diagram 5: Communication	69
2.3.10	Class Diagram Description 5: Communication Description	70

2.3.11	Class Diagram 6: Project Browsing	71
2.3.12	Class Diagram Description 6: Project Browsing	72
2.3.13	Class Diagram 7: Project User Management	73
2.3.14	Class Diagram Description 7: Project User Management Description	74
2.3.15	Class Diagram 8: Project Management	75
2.4	SEQUENCE DIAGRAMS	77
2.4.1	Authentication Feature 1: Sign Up Sequence Diagram	77
2.4.2	Authentication Feature 2: Log In Sequence Diagram	78
2.4.3	Authentication Feature 3: Log Out Sequence Diagram	79
2.4.4	Authentication Feature 4: Change Password Sequence Diagram	80
2.4.5	Authentication Feature 5: Change Email Sequence Diagram	81
2.4.6	Authentication Feature 6: Change Username Sequence Diagram	82
2.4.7	Project Browsing Feature 2: Project Creation Sequence Diagram	83
2.4.8	Project Browsing Feature 3: Project Commenting Sequence Diagram	84
2.4.9	Project Browsing Feature 4: Project Voting Sequence Diagram	85
2.4.10	Communication Feature 1: Read Project Chat Sequence Diagram	86
2.4.11	Communication Feature 2: Write to Project Chat Sequence Diagram	87
2.4.12	Communication Feature 4: Comment on Project Sequence Diagram	88
2.4.13	Communication Feature 5: Close chat Sequence Diagram	89
2.4.14	Project Management Feature 3: Delete Project Sequence Diagram (dani2918)	90
2.4.15	Project Management Feature 4/5: Request/Manage Request to Join Project Sequence Diagram (dani2918)	91
2.4.16	Project Management Feature 6: Leave Project Sequence Diagram (dani2918)	92
2.4.17	Project Management Feature 7/8: Invite/Respond to Project Invite Sequence Diagram (dani2918)	93
2.4.18	File Editing Feature 1: View Line Numbers Sequence Diagram	94
2.4.19	File Editing Feature 2: View References Sequence Diagram	95
2.4.20	File Editing Feature 3: View Dates Sequence Diagram	96
2.4.21	File Editing Feature 4: View Author Sequence Diagram	97
2.4.22	File Editing Feature 6: Find Sequence Diagram	98
2.4.23	File Editing Feature 7: Comment Section Sequence Diagram	99
2.4.24	File Editing Feature 8: Display Typing User Sequence Diagram	100
2.4.25	File Editing Feature 9: Display Syntax Errors Sequence Diagram	101
2.4.26	File Editing Feature 10: Display Syntax Highlighting Sequence Diagram	102
2.4.27	File Management Feature 1: Open File Sequence Diagram	103
2.4.28	File Management Feature 2: Close File Sequence Diagram	104
2.4.29	File Management Feature 3: Save File Sequence Diagram	105
2.4.30	File Management Feature 4: Add File Sequence Diagram	106
2.4.31	Project User Management Feature 1: Add User Sequence Diagram	107
2.4.32	Project User Management Feature 2: Kick User Sequence Diagram	108
2.4.33	Project User Management Feature 3: Set User Permissions Sequence Diagram	109
2.4.34	Project Management Feature 2: Create project Sequence Diagram (dani2918)	110
2.4.35	Project Management Feature 1: Sequence Diagram 1: Compile and execute project (dani2918)	111
2.4.36	Project Browsing Feature 1: Project Browsing Sequence Diagram	112
2.4.37	Communication Feature 3: Message User by Name Sequence Diagram	113
2.5	USER INTERFACE DIAGRAMS	114
2.5.1	UI Window Flowchart	114

3	IMPLEMENTATION	115
3.1	User Interface	115
3.1.1	JavaFX Framework	115
3.2	Server	117
3.2.1	MobWrite	117
3.2.2	Chat	118
3.2.3	Database	119
3.2.4	Request Handler	120
3.3	Client	121
3.3.1	CodeArea	121
3.3.2	Response Handler	122
3.4	Deployment	123
3.4.1	GitHub Repository	123
3.4.2	Dependencies	124
3.4.3	IDE and Plugins	125
4	Testing	126
4.1	Introduction	126
4.2	Logic Testing	127
4.2.1	Test Classes	127
4.2.2	Results	128
4.3	GUI Testing	129
4.3.1	Test Classes	129
4.3.2	Results	130
4.4	Back-end Testing	132
4.4.1	Test Classes	132
4.4.2	Results	133
4.5	Coverage Testing (wern0096)	133
4.5.1	Methodology	133
4.5.2	Results	133
4.6	Software Risk Issues (wern0096)	136
4.6.1	High Risk	136
4.6.2	Medium Risk	136
4.6.3	Low Risk	137
5	METRICS	138

1 REQUIREMENTS

1.1 INTRODUCTION

The sQuire Collaborative IDE is a collaborative IDE software project for CS383-01. The intended audience for this project is Java programmers looking for a more social collaborative experience. A large focus of the program is also to help programmers connect with others who may be interested in their projects.

1.1.1 IDENTIFICATION

The software system being considered for development is referred to as sQuire. The customer providing specifications for the system is Dr. Jeffery and the CS383-01 class. The ultimate customer, or end-user, of the system will be Java programmers. This is a new project effort, so the version under development is version 1.0.

1.1.2 PURPOSE

The purpose of the system under development is to provide Java programmers with a more social collaborative experience. Instead of individual methods of source control, sQuire will provide an environment where programmers can work together in the same environment and instantly see the effect of others' code. While the system will be used by Java programmers, this document is intended to be read and understood by UI CS software designers and coders. The document will also be vetted or approved by Team 4.

1.1.3 SCOPE

This project is sponsored by the CS383-01 class and is being worked on by Team ICY (4) from scratch. The goal is to have a working prototype by the end of the Spring 2016 semester. We plan to operate individually for the most part by programming from our own machines at home for about 10 hours per week. We also plan on using a Windows Server running in a VM at Domn Werner's house.

1.1.4 DEFINITIONS, ACRONYMS, AND ABBREVIATIONS

Term or Acronym	Definition
Alpha test	Limited release(s) to selected, outside testers
Beta test	Limited release(s) to cooperating customers wanting early access to developing systems
Final test	aka, Acceptance test, release of full functionality to customer for approval
DFD	Data Flow Diagram
SDD	Software Design Document, aka SDS, Software Design Specification
SRS	Software Requirements Specification
SSRS	System and Software Requirements Specification
IDE	Integrated Development Environment

--	--

1.1.5 OVERALL DESCRIPTION

The sQuire project is an answer to the lack of real-time collaborative programming experiences. By bringing programmers together in a more social environment, this program aims to improve collaboration between programmers in a much more fast paced and agile methodology. Furthermore, for programmers who seek others to help with their projects, sQuire aims to provide a simple social platform for engaging with other programmers and start working on a project together.

1.1.6 PRODUCT PERSPECTIVE

This program will be a standalone executable, connecting to a central project server.

1.2 SYSTEM LEVEL (NON-FUNCTIONAL REQUIREMENTS)

1.2.1 Site dependencies

1. Central SQL Server
2. Host-side Project Server
3. Collaborator-side Client

The Central server stores user credentials, project descriptions, and user profile and achievement data.
Requirements for Central SQL Server

1. Host with high uptime percentage
2. SQL capable
3. E-mail capable for password resets
4. Fast enough connection to prevent login timeout, even while handling multiple requests
5. Prefer host with multiple backups

The Host-side server stores the project files, project access list, hosts the editing environment, runs chat channels, and serves files to collaborators for compiling.

Requirements for Host-side Server

1. Java Capable (<http://java.com/en/download/help/sysreq.xml>)
2. SQL Capable (WAMP/LAMP)
3. 4 GB RAM
4. Hard drive space for server + project files

The client side application connects to the host server, renders GUI elements, stores connection profiles, stores server files, and compiles the project.

Requirements for Collaborator-side Client

1. Java Capable (<http://java.com/en/download/help/sysreq.xml>)
2. Compatible Java version installed
3. 2 GB RAM
4. Hard drive space for project files

1.3 Safety, security and privacy requirements

The collaborative nature of sQuire includes several concerns for security and privacy. The program will include in the license agreement the following stipulations:

1. sQuire is a free development environment, and may be used for commercial purposes
2. No guarantee of code confidentiality is implied by use of sQuire
3. Clients assume the risk of downloading, compiling, and running project files
4. Email addresses are visible as part of a user profile

5. Host assume the risk of allowing peers to connect to their server

However, the program will provide the following minimum features to address security and privacy concerns:

1. All SQL servers will include input sanitization and appropriate anti-injection safeguards
2. Project hosts may turn off guest access to their project
3. Uploads for assets will be limited to folders within the project directory
4. Visibility to host file structure will be limited to project folders only

1.3.1 Performance requirements

1. Up to 33 concurrent connections will be supported
2. Edits will be visible to all connected collaborators within 10 seconds
3. Login and server connections will report success or failure within 45 seconds

1.3.2 System and software quality

Adaptability

1. The program will allow selection of different compiling programs and command line arguments.
2. The program will allow importing of files of key words to allow other development languages to be used.

1.3.3 Packaging and delivery requirements

The executable system and all associated documentation (i.e., SSRS, SDD, code listing, test plan (data and results), and user manual) will be delivered to the customer on CD's and/or via email, as specified by the customer at time of delivery. Although document "drops" will occur throughout the system development process, the final, edited version of the above documents will accompany the final, accepted version of the executable system.

1.3.4 Personnel-related requirements

The system under development has no special personnel-related characteristics.

1.3.5 Training-related requirements

No training materials or expectations are tied to this project other than the limited help screens built into the software and the accompanying user manual.

1.4 FUNCTIONAL REQUIREMENTS

1.4.1 Project Browsing

These requirements involve the ability for users to find and learn about projects that they may wish to contribute to. Users shall be able to:

1. See a list of open projects.
 Use Case Description: 2.1.7
 Sequence Diagram: 2.4.36
2. Filter or search projects.
 Use Case Description: ??
 Sequence Diagram: ??
3. View more information about a specific project.
 Use Case Description: ??
 Sequence Diagram: ??
4. Upvote and downvote projects.
 Use Case Description: ??
 Sequence Diagram: ??
5. Comment on projects and interact with its contributors.
 Use Case Description: ??
 Sequence Diagram: ??
6. Request to join a specific project.
 Use Case Description: ??
 Sequence Diagram: ??

1.4.2 Authentication

These requirements involve the ability for users to have individual accounts and the security that comes from that. Users shall be able to:

Use case diagram: 2.2.1

1. Sign up for a sQuire user account.
 Use Case Description: 2.1.1
 Sequence Diagram: 2.4.1
2. Log in to the program using their user account.
 Use Case Description: 2.1.2
 Sequence Diagram: 2.4.2
3. Log out of the program using their user account.
 Use Case Description: 2.1.3
 Sequence Diagram: 2.4.3
4. Change their password.
 Use Case Description: 2.1.4
 Sequence Diagram: 2.4.4

5. Change their email.
 Use Case Description: 2.1.5
 Sequence Diagram: 2.4.5
6. Change their username.
 Use Case Description: 2.1.6
 Sequence Diagram: 2.4.6

1.4.3 Communication

These requirements involve the ability for users to be able to communicate with other users. Users shall be able to:

1. Open and close project chat.
2. Write to project chat.
3. Read from project chat.
4. Message a user by their name.
5. Leave a comment in a file.

1.4.4 File Management

These requirements involve the ability for users to manage the files that compose a project. Users shall be able to:

1. Open one or more files.
2. Close one or more files.
3. Delete one or more files.
4. Download one or more files.
5. Add a new file to the project.
6. Add an existing file to the project.
7. Save one or more files.

1.4.5 File Editing

These requirements involve the collaborative editor part of sQuire. Users shall be able to:

1. Enable or disable line numbers.
 Use Case Description: **S3.3.53**
 Sequence Diagram: **S3.3.54**
2. Enable or disable viewing reference counts above each line.
 Use Case Description: **S3.3.55**
 Sequence Diagram: **S3.3.56**

3. Enable or disable viewing date of last edit above each line.
Use Case Description: **S3.3.57**
Sequence Diagram: **S3.3.58**
4. Enable or disable view author of each line.
Use Case Description: **S3.3.59**
Sequence Diagram: **S3.3.60**
5. Comment/Uncomment a selected section code.
Use Case Description: **S3.3.64**
Sequence Diagram: **S3.3.65**
6. Format the document to adhere to code style.
Use Case Description: **S3.3.61**
7. Find/Replace specified text.
Use Case Description: **S3.3.62**
Sequence Diagram: **S3.3.63**
8. View text highlighted by other users.
9. Type text and have the system apply syntax coloring for Java files and display errors.
Use Case Description: **S3.3.68**
Use Case Description: **S3.3.70**
Sequence Diagram: **S3.3.69**
Sequence Diagram: **S3.3.71**
10. View other users' carets as they type.
Use Case Description: **S3.3.66**
Sequence Diagram: **S3.3.67**

1.4.6 Project Management

These requirements involve the management of entire projects. Users shall be able to:

1. Compile a project.
Use Case Description: 2.1.16
Sequence Diagram: 2.4.35
2. Execute a compiled project.
Use Case Description: 2.1.16
Sequence Diagram: 2.4.35
3. Create a new project.
Use Case Description: 2.1.17
Sequence Diagram: 2.4.34

4. Delete a project.
 Use Case Description: 2.1.18
 Sequence Diagram: 2.4.14
5. Invite a user to a project.
 Use Case Description: 2.1.22
 Sequence Diagram: 2.4.17
6. Join a project.
 Use Case Description: 2.1.19
 Sequence Diagram: 2.4.15
7. Leave a project.
 Use Case Description: 2.1.21
 Sequence Diagram: 2.4.16

1.4.7 Project User Management

These requirements involve project admins managing their Users. Admins shall be able to:

1. Add users to a project.
 Use Case Description: **S3.3.49**
 Sequence Diagram: **S3.3.50**
2. Remove users from a project.
 Use Case Description: **S3.3.51**
 Sequence Diagram: **S3.3.52**
3. Change user permissions to a project.
 Use Case Description: **S3.3.53**
 Sequence Diagram: **S3.3.54**

1.4.8 User Preferences

These requirements involve managing user preferences. Users shall be able to:

1. Update their username.
2. Update their password.
3. Update their email address.
4. Update their biography.
5. Update their display name.
6. Enable receiving email updates.
7. Enable receiving messages from any user.
8. Display their email address to selected groups.
9. Change program colors.

2 DESIGN

2.1 USE CASE DESCRIPTIONS

2.1.1 Authentication Feature 1: Sign Up Use Case Description

Actors: User

Summary: The user signs up and creates an account using their email address and creates username and password in order to access the program.

Purpose: To register and create an account in the program

Preconditions: None

Steps:

1. User clicks Register button.
2. System prompts the user to enter email and password.
3. User enters email and password and clicks Submit button.
4. System sends confirmation email.
5. User verifies email by clicking a link.
6. System adds verified user to database.

Alternative 1: User already has an account.

Alternative 2: User doesn't confirm email. Delete request after timeout period.

Relevant Classes:

- **User** in **S3.4.5**
 - **Email** in **S3.4.5**
 - **Validator** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.2 Authentication Feature 2: Log In Use Case Description

Actors: User

Summary: A registered logs in to the program in order to access its features.

Purpose: Allow registered users access to the program.

Preconditions: User must already have a registered account.

Steps:

1. Users clicks Log In button.
2. System prompts the user for their username and password.
3. User enters their login information.
4. System verifies the login information and grants user access to their account.

Alternatives:

1. User enters incorrect information. System prompts for credentials again.
2. User has not clicked email confirmation. System resends email and tells user.
3. User makes 5 incorrect login attempts. System prevents more login attempts for 5 minutes.

Relevant Classes:

- **User** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.3 Authentication Feature 3: Log Out Use Case Description

Actors: User

Summary: A user logs out of the program.

Purpose: Allows logged in users to log out in order to protect their account.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks log out button.
2. System logs user out.
3. Browser cookies are updated to reflect user being logged out.

Relevant Classes:

- **User** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.4 Authentication Feature 4: Change Password Use Case Description

Actors: User

Summary: A user changes their password while logged in.

Purpose: Allows logged in users to change their passwords.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks Change Password button.
2. System prompts user to enter their password twice.
3. User enters their password twice.
4. System hashes both passwords.

Alternatives:

1. If passwords match, System updates user password and sends email to registered email account.
2. If passwords don't match, system notifies user.

Related Use Cases:

1. Change Email
2. Change Username

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **Validator** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.5 Authentication Feature 5: Change Email Use Case Description

Actors: User

Summary: A user changes their email while logged in.

Purpose: Allows logged in users to change their email.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. User clicks Change Email button.
2. System prompts user to enter their email.
3. User enters their email.
4. System sends a confirmation link to the email entered.

Alternatives:

1. If User clicks confirmation link, System updates the user's email and sends an email to the new email stating so.
2. If user doesn't click confirmation link in an hour, the link becomes invalid.

Related Use Cases:

1. Change Password
2. Change Username

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **Validator** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.6 Authentication Feature 6: Change Username Use Case Description

Actors: User

Summary: A user changes their username while logged in.

Purpose: Allows logged in users to change their username.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks Change Username button.
2. System prompts user to enter a new username.
3. User enters a username and clicks Change Username.

Alternatives:

1. If username doesn't exist, System changes the user's username and notifies the user in the UI and through an email.
2. If username exists, System asks user to enter a different username.

Related Use Cases:

1. Change Password
2. Change Email

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

2.1.7 Project Browsing Feature 1: Project Browsing Use Case Description

Actors: User

Summary: User looks through posted project ideas to find projects to work on and/or discuss.

Purpose: To find and view projects relevant to the user's search parameters

Preconditions: User is signed in

Steps:

1. Actor selects Browse Project Ideas button
2. Actor refines search by selecting from list of project categories as desired
3. Actor enters terms into search field as desired and views a list of top projects
4. Actor selects desired project
5. System displays detailed project information

Alternative 1: None

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

2.1.8 Project Browsing Feature 2: Project Creation Use Case Description

Actors: User

Summary: User will create a project.

Purpose: To allow users to create projects and make them accessible to other users

Preconditions: User is signed in

Steps:

1. User selects Create Project button
2. User will enter the information on the project, including its name, goals, and identifying tags.
3. If project name does not match any existing project, the system will create a project with the specified parameters and set user as an admin for the project.

Alternative 1: Project name matches the name of an existing project and will ask the user to rename it.

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

2.1.9 Project Browsing Feature 3: Project Commenting Use Case Description

Actors: User

Summary: Provide detailed feedback on project ideas

Purpose: To allow users to write longform feedback on projects as necessary.

Preconditions: User is signed in

Steps:

1. User selects Comment button
2. User types feedback into field
3. User clicks Submit button
4. System shows confirmation that feedback was received

Alternative 1: If the project requires comments to be made by project members only and the user is not a project member, the user will be shown an error message.

Relevant Classes:

- User in S3.4.5
 - Project in S3.4.5
-

2.1.10 Project Browsing Feature 4: Project Voting Use Case Description

Actors: User

Summary: Support promising project ideas or offer criticism to unfavorable ones

Purpose: Allow for feedback and help users search for well received projects

Preconditions: User is signed in

Steps:

1. User selects Browse Project Ideas button
2. User refines search by selecting from list of project categories as desired
3. User enters terms into search field as desired and views a list of top projects
4. User selects desired project
5. System displays detailed project information
6. User selects Up Vote or Down Vote button
7. Project receives the vote and updates its total score

Alternative 1: None

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

2.1.11 Communication Feature 1: Read Project Chat Use Case Description

Actors: User

Summary: Open a window to view the conversation in a project

Purpose: Allow users to communicate quickly without permanently taking up screen space in a project

Preconditions: User is signed in and viewing a project

Steps:

1. User selects the "Open Chat" button
2. System opens the chat window, and notifies the other users in the project of the new arrival
3. System displays any messages from other users in the project in that window until it is closed/left.

Alternative 1: None

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

2.1.12 Communication Feature 2: Write to Project Chat Use Case Description

Actors: at least one User

Summary: Contribute to the conversation in a project

Purpose: Allow users to communicate quickly without permanently taking up screen space in a project

Preconditions: User is signed in and has joined the project chat

Steps:

1. User types a message in the project chat window and presses Send
2. System sends that message to the project server, which delivers it to the other users in the project chat
3. Other users may read and/or respond to the message at their leisure

Alternative 1: None

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

2.1.13 Communication Feature 3: Message User by Name Use Case Description

Actors: User

Summary: Start talking an individual user

Purpose: Allow users to communicate outside of a project, or in private

Preconditions: At least one of the users are signed in

Steps:

1. User selects "Send PM" from the chat menu and types or selects the other user's ID
2. System checks to see if the user exists and is online, and if so creates a chat channel for the two users
3. Both users then use the chat as normal

Alternative 1: If the second user exists but is offline, the first user is notified and the second user gets the message from the server the next time they're online.

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

2.1.14 Communication Feature 4: Comment on Project Use Case Description

Actors: User, sometimes also a Project Admin

Summary: Communicate more important info about a project

Purpose: Allow users to record and semi-permanently attach messages to be displayed alongside a project

Preconditions: User is signed in and has joined the project

Steps:

1. In a section of the window separate from temporary chat, the user writes a comment and presses Post.
2. System sends that message to the project server, which attaches it to the project. The message is then displayed with previous comments in the post.
3. Other users may read and/or respond to the message at their leisure

Alternative 1: A project administrator may remove the post.

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

2.1.15 Communication Feature 4: Comment on Project Use Case Description

Actors: User or Admin

Summary: Clean up when a user leaves a project chat

Purpose: Close the window and remove the user from the list of active users in the project chat so they don't receive more messages

Preconditions: User is signed in and has joined the project chat

Steps:

1. User clicks "close" on the project chat window
2. System minimizes the window, and removes the user from the list of active users in the project chat

Alternatives: Step one is skipped if one of the following happen:

1. The user closes the entire project or program windows
2. The user is idle for too long
3. An administrator removes them from the project or project chat

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

2.1.16 Project Management Feature 1: Compile and Execute Project Use Case Description (dani2918)

Actors: User

Goals: Compile and execute active project

Pre-conditions: Actor is logged in, navigated to desired project.

Summary: User compiles a project and the project executes.

Related use cases:

Steps:

1. User clicks “Compile”
2. System displays results of compilation
3. System executes compiled project.

Alternatives: Compilation fails.

Post-conditions: None.

2.1.17 Project Management Feature 2: Create project Use Case Description(dani2918)

Actors: User

Goals: Create a new project.

Pre-conditions: Actor is logged in.

Summary: User creates a new project with a description and includes any desired files.

Related use cases: Import file

Steps:

1. User clicks "New Project."
2. User gives project a title.
3. User adds an applicable description.
4. User imports any files by clicking "Import."
5. User clicks "Create".
6. System imports files and instantiates project.

Alternatives: None.

Post-conditions: None.

2.1.18 Project Management Feature 3: Delete Project Use Case Description (dani2918)

2.1.17

Actors: Project Administrator, sQuire Administrator.

Goals: Remove project from sQuire sever.

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor chooses to delete or remove an irrelevant or inappropriate project.

Related use cases: Create project

Steps:

1. Actor clicks “Delete” icon on active project.
2. Delete dialog opens.
3. Actor presses “Delete”.
4. Confirmation window is displayed.
5. Actor confirms or disregards deletion.
6. System notifies collaborators that project was deleted.

Alternatives: Actor clicks “Cancel.”

Post-conditions: None.

2.1.19 Project Management Feature 4: Request to Join Project Use Case Description (dani2918)

Actors: User

Goals: Join an existing project.

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor sends a request to join as a collaborator on a project

Related use cases: Manage request to join project

Steps:

1. Actor clicks “Join project.”
2. Notification is sent to project administrator for review.

Alternatives: None.

Post-conditions: None.

2.1.20 Project Management Feature 5: Manage Request to Join Project Use Case Description (dani2918)

Actors: Project Administrator

Goals: Approve .

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor approves/rejects a user who has requested to join as a collaborator on a project.

Related use cases: Request to join project

Steps:

1. Actor clicks “Review join requests.”
2. Actor reviews information about potential collaborator.
3. Actor clicks “Approve User” to approve a collaborator or “Reject user” to reject a collaborator.
4. System notifies user that they have been approved/rejected.

Alternatives: None.

Post-conditions: None.

2.1.21 Project Management Feature 6: Leave Project Use Case Description (dani2918)

Actors: User

Goals: Remove actor as a collaborator from project.

Pre-conditions: logged in, viewing desired project, collaborator on desired project, not project owner.

Summary: A member of a project leaves said project, leaving the project intact.

Related use cases: Delete project

Steps:

1. User clicks "Leave Project".
2. System prompts user to confirm decision.
3. User clicks "Confirm".
4. User is removed from project member list.

Alternatives: User clicks "Cancel" at step 4.

Post-conditions: None.

2.1.22 Project Management Feature 7: Invite to Project Use Case Description (dani2918)

Actors: Project Administrator, Authorized Project Collaborator (User).

Goals: Invite user(s) to collaborate on project

Pre-conditions: Actor is viewing project which he or she created, is logged in

Summary: A project administrator requests help from a user on a project. The sQuire system facilitates the invitation process

Related use cases: Respond to project invite

Steps:

1. Actor clicks "Invite User."
2. Actor enters the username(s) of the user(s) to be invited to the project.
3. Actor enters any message to the user(s) in a text box.
4. Actor clicks "Send invite."
5. System sends notification of invite to user(s).

Alternatives: Actor clicks "Cancel." **Post-conditions:** None.

2.1.23 Project Management Feature 8: Respond to Project Invite Use Case Diagram (dani2918)

Actors: User

Goals: Actor responds to an invitation to a project.

Pre-conditions: Actor is signed in, viewing invitation.

Summary: Actor receives notification that he or she has been invited to a project and either accepts the invitation or declines it.

Related use cases: Invite to project

Steps:

1. Actor clicks "Respond to Invitation."
2. Actor clicks "Accept" or "Reject."
3. Actor types any message to invitation-sender in text box.
4. Actor clicks "Confirm."

Alternatives: Actor clicks "Cancel."

Post-conditions: Actor becomes collaborator on project if invitation was accepted.

2.1.24 File Editing Feature 1: View Line Numbers Use Case Description

Name: View Line Numbers

Category: File Editing

Actor: User

Summary: Allows the user to view line numbers to the left of the document.

Purpose: Makes it easier to communicate position in code. It is also a useful metric to have.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Line Numbers* option.
4. System displays line numbers to the left of the document.

Relevant Classes:

1. **TextOperation**
-

2.1.25 File Editing Feature 2: View References Use Case Description

Name: View References

Category: File Editing

Actor: User

Summary: Allows the user to view the number of references to a given function.

Purpose: It is useful to know the number of references to a given function for optimization and debugging purposes.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A **code** file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View References* option.
4. System displays the number of references above each method declaration.

Relevant Classes:

1. **ColabFile**
 2. **LineHistory**
 3. **Project**
-

2.1.26 File Editing Feature 3: View Dates Use Case Description

Name: View Dates

Category: File Editing

Actor: User

Summary: Allows the user to view the last date that each line of a document was edited.

Purpose: This provides a useful metric for how up-to-date parts of the document are.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Dates* option.
4. System displays the last date that each line of a document was edited.

Relevant Classes:

1. **LineHistory**
 2. **FileLineHistory**
-

2.1.27 File Editing Feature 4: View Authors Use Case Description

Name: View Authors

Category: File Editing

Actor: User

Summary: Allows the user to view the last author that edited each of line of the document.

Purpose: This is an accountability tool allowing other users to identify who is responsible for a change to a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Authors* option.
4. System displays the name of the last editor of each line of the document.

Relevant Classes:

1. **FileLineHistory**
 2. **LineHistory**
-

2.1.28 File Editing Feature 5: Format Document Use Case Description

Name: Format Document

Category: File Editing

Actor: User

Summary: Allows the user to format the document to a specified format

Purpose: An easy tool for making sweeping changes to a large part of a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.
5. The document has formatting options set.

Steps:

1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Format Document* option.
4. System formats the current document to the formatting settings currently set.

Alternatives:

1. If no formatting settings are currently set, display a dialog box after step 3 and give the option for the user to do so now.

Relevant Classes:

1. **TextOperation**
-

2.1.29 File Editing Feature 6: Find/Replace Use Case Description

Name: Find/Replace

Category: File Editing

Actor: User

Summary: Allows the user to find and/or replace phrases.

Purpose: This is a powerful tool that allows a user to make safer, quicker, and more efficient changes to a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.

Steps:

1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Find/Replace* option.
4. System displays a small form in an unobtrusive location.
5. User enter the phrase to find and selects find.
6. System highlights and focuses on the first occurrence of the phrase and all highlights all other occurrences.

Alternatives:

1. User selects option to replace in step 5 and enters a phrase with which to replace the found occurrences of the searched phrase. The system replaces each occurrence.

Relevant Classes:

1. **Project**
-

2.1.30 File Editing Feature 7: Comment Section Use Case Description

Name: Comment Section

Category: File Editing

Actor: User

Summary: Allows the user to comment out a part of a document.

Purpose: A useful and quick way to disable a large part of a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. A file is open.
4. User has read/write permission.
5. Current open document supports commenting.

Steps:

1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Comment Section* option.
4. System comments the selected area.

Alternatives:

1. If document does not support commenting, display a dialog box telling the user.

Relevant Classes:

1. **TextOperation**
-

2.1.31 File Editing Feature 8: Display Typing User Use Case Description

Name: Display Typing User

Category: File Editing

Actors:

1. User
2. Other Users

Summary: As the user types, the system displays their name, their typing, and their caret, in a different color, to other users.

Purpose: Differentiate who is typing what.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.
5. Other users have the same document open.

Steps:

1. User begins typing.
2. System displays the user's typing, the user's name, and the user's caret, in a different color, to Other Users.
3. Other Users see User typing, his username, and his caret, in a different color.

Relevant Classes:

1. **ColabFile**
 2. **Cursor**
 3. **Project**
-

2.1.32 File Editing Feature 9: Display Syntax Errors Use Case Description

Name: Display Syntax Errors

Category: File Editing

Actor: User

Summary: As the user types code, the editor will underline syntax errors with a red line.

Purpose: Aids the user is writing correct code.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A supported code file is open.

Steps:

1. User begins typing.
2. System displays any syntax errors as a red underline under the incorrect section.

Relevant Classes:

1. **ColabFile**
 2. **Project**
-

2.1.33 File Editing Feature 10: Display Syntax Highlighting Use Case Description

Name: Display Syntax Highlighting

Category: File Editing

Actor: User

Summary: As the user types code, the editor will change font color for different code structures and keywords.

Purpose: Aids the user is writing code and identifying key code parts.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A supported code file is open.

Steps:

1. User begins typing.
2. System automatically colors special code structures and keywords.

Relevant Classes:

1. **Project**
-

2.1.34 File Management Feature 1: Open File Use Case Description

Actors: User

Summary: The user selects a file to open based on a filename, which is then opened by the software.

Purpose: To open a file in the program.

Preconditions: The desired file must already exist.

Steps:

1. User clicks Open File button.
2. System prompts the user to select file to open from a list of existing files.
3. User selects desired file and clicks Submit button.
4. System opens selected file and displays it.

Alternative 1: The User decides they don't want to open a file and presses Cancel at step 3.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

2.1.35 File Management Feature 2: Close File Use Case Description

Actors: User

Summary: The user chooses to close the file they are working on.

Purpose: To close a file in the program.

Preconditions: The desired file must already exist, and be already opened by the User.

Steps:

1. User clicks Close File button.
2. System closes the file and updates the Controller's status on the file being open.

Alternative 1: The file cannot be closed for some reason.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

2.1.36 File Management Feature 3: Save File Use Case Description

Actors: User

Summary: The user chooses to save the file they are currently working on.

Purpose: To save a file in the program.

Preconditions: The desired file must already exist, and be opened by the user.

Steps:

1. User clicks Save File button.
2. System prompts the user to choose a name to save the file under.
3. User selects desired name and clicks Submit button.
4. System saves selected file and allows the user to keep working.

Alternative 1: The User decides they don't want to save the file and presses Cancel at step 3.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

2.1.37 File Management Feature 4: Add File Use Case Description

Actors: User

Summary: The user chooses to add a file to the directory.

Purpose: To add a file to a directory.

Preconditions: The desired file must already exist.

Steps:

1. User clicks Add File button.
2. System prompts the user to choose a file to add to a directory..
3. User selects desired file and clicks Submit button.
4. System prompts the user to choose a directory to add the file to.
5. User selects directory to add the file to and click Submit button.
6. System adds the file to the selected directory and lets the user return to their work.

Alternative 1: The User decides they don't want to add the file and presses Cancel at step 3.

Alternative 2: The User decides, after they chose a file, not to add it to a directory and clicks Cancel at step 5.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

2.1.38 Project User Management Feature 1: Add User to Project Use Case Description

Actors: User

Goals: Add a user to project

Pre-conditions: User has admin rights to project.

Summary: User adds a user to a project

Related use cases: Kick User

Steps:

1. User clicks add user button.
2. System prompts user to enter the username of the user they wish to invite.
3. User enters username.
4. System adds the specified user to the project, and notifies them.

Alternatives:

1. User enters an invalid username, in which case an error is reported

Post-conditions: None.

Relevant Classes:

- User
 - Project
 - UserManager
 - Permissions
 - Email
-

2.1.39 Project User Management Feature 2: Kick User Use Case Description

Actors: User

Goals: Kick a user from project.

Pre-conditions: User is an admin, and the user they wish to kick is a member of the project.

Summary: User removes a selected user from the Project

Related use cases: Add User

Steps:

1. User clicks Kick User button.
2. System displays list of Members of the project.
3. User selects one or more other users from the list and presses Remove.
4. System prompts User for verification.
5. User presses Confirm.
6. System removes the selected users from the project.

Alternatives: None.

Post-conditions: None.

- User
 - Project
 - UserManager
 - Permissions
-

2.1.40 Project User Management Feature 3: Set User Permissions Use Case Description

Actors: User

Goals: Modify a user's permissions.

Pre-conditions: User has admin permissions, and the user whose permissions they wish to change is a member of the project

Summary: User modifies another User's permissions to the project.

Related use cases: None.

Steps:

1. User clicks Permissions Management button.
2. System displays permissions management window.
3. User selects the user whose permissions they want to edit.
4. System displays a list of toggles for the user's permissions.
5. User makes changes to the user's permissions.
6. System modifies the target User's permissions.


Alternatives: None.

Post-conditions: None.


- User
 - Project
 - UserManager
 - Permissions
-

2.2 USE CASE DIAGRAMS


2.2.1 Use Case Diagram 1: Authentication




2.2.2 Use Case Diagram 2: Project Browsing



2.2.3 Use Case Diagram 4: User Preferences




2.2.4 User Preferences Feature 1: Use Case Diagram 1




Author: Robert Carlson (carl7595)
Reviewed by: Team ICY

2.2.5 User Preferences Feature 2: Use Case Diagram 2



Author: Robert Carlson (carl7595)
Reviewed by: Team ICY


2.2.6 Use Case Diagram 5: Project Management




Use case descriptions were roughly based upon cases from HW2, Team 4. sass8427 worked on the original use cases in this section.

Traceability: Relevant classes are found in **Project Management** section and include *User* and *Project*. For the *User* class, methods and fields from all class diagrams will be used.


2.2.7 Use Case Diagram 6: File Editing




2.2.8 Use Case Diagram 7: File Management



2.2.9 Use Case Diagram 8: Project User Management




2.2.10 Use Case Diagram 3: Communication



2.3 CLASS DIAGRAMS

2.3.1 Class Diagram 1: File Management



2.3.2 Class Diagram Description 1: File Management Description


Interfaces:

- The *Observer* interface requires its implementers to implement a method with the following signature: **void Observe(T)**. The purpose of this method is for classes to implement ways in which to observe other classes. We foresee the **FileController** class implementing this interface in order to observe changes in **CollabFile** objects.
- The *Runnable* interface requires its implementers to implement a method with the following signature: **void Run(Task)** where **Task** is a method that can be run in a separate thread. The **FileController** class will implement this interface in order to execute its IO operations in a separate thread. This will keep the UI thread free and our program responsive.
- The *Serializable* interface requires its implementers to implement the **void Serialize<T>()** method and serializes objects of type **T**. It also requires the implementation of the **T Deserialize<T>()** method which will operate on a serialized string object and return an instantiated object of type **T**.
- The *Observable* interface requires its implementers to have a list of observers and a method to notify its observers of changes to itself. The purpose of this implementation is to communicate with the **FileController** object and notify it when a **CollabFile** changes.
- The *Downloadable* interface requires its implementers to implement a method with the following signature: **int Download()**. The purpose of this method is for classes to implement ways in which their objects can be downloaded. The **int** return type will be used as a status code. We foresee this interface being used with the **Project** and **CollabFile** classes, as the diagram shows, allowing users to download files or projects with the **Download()** method.

Classes:

- The **FileController** class will manage the **CollabFile** objects in the **Project** class. It will do so by storing a list of files and a dictionary of its methods that can be run in a separate thread. Its methods all deal with managing files. It will implement the *Observer* and *Runnable* interfaces. Refer to the interfaces list above to see the details of such implementations.
- The **Project** class represents the entire project that users work on. This includes users, files, permissions, etc. For the sake of simplicity, this diagram only lists properties and methods relating to file editing. Objects of type **Project** will have a **FileController** and a root **CollabFile** as per a file-tree structure. The **Project** class must also implement the *Downloadable* interface in order to specify how projects are downloaded. Refer to the interfaces list above to see the details of this implementation.
- the **CollabFile** class represents a file in a **Project**. It extends the **File** class for the purposes of allowing collaborative editing, among other project functions. It implements the *Serializable* interface to allow its information to be transported over the internet in the best possible format. This requires the implementation of the **void Serialize<T>()** and **T Deserialize<SerializedString>()** methods which will handle serialization and deserialization. This class also implements the *Observable* interface which will specify how it communicates with the **FileController** class in order to notify of relevant changes to **CollabFile** objects. This requires the implementation of a list of observers and a method to notify observers. Lastly, it implements the *Downloadable* interface which will specify how **CollabFile** objects are to be downloaded. Refer to the interfaces list above for more details of such implementations.

2.3.3 Class Diagram 2: File Editing



2.3.4 Class Diagram Description 2: File Editing Description

Editor:

- The *CollabFile* class is a class used in many of the other class diagrams in this project. It is the general class containing all the methods and variables for managing a file. It contains a **FileLineHistory** object. CollabFile has a list of **Cursor** objects, one for every user editing the file..
- The *User* class is a class used in many of the class diagrams. It represents a single user of the sQuire program.
- The *TimeStamp* class is used in several other places. It represents a date and time.
- The *FileLineHistory* class is a class that keeps track of who last edited every line in the file. This will be used to display the changes inside the editor. It does this by having an array (one element per line in the file) of **LineHistory** objects.
- The *LineHistory* class contains the information used by the **FileLineHistory** class. It contains a **User** the last one to edit a particular line and a **Timestamp** (when the line was last edited). More fields can easily be added to this if it turns out there is more information we'd like to keep track of on a line-by-line basis.
- The *EditorWidget* class is something that we will (hopefully) not write ourselves. It will be the editor widget we use for providing the code editor. Preliminary research found **RSyntaxTextArea** (<https://github.com/bobbylight/RSyntaxTextArea>). This looks like a good fit because it has syntax highlighting, auto completion, code analysis, and of course, support from java. It also has a simple plugin architecture, so it looks like it would be easy to extend to our needs. More research needs to be done to figure out the exact class structure for this.
- The *Cursor* class is made up of a **User** and a position within a file- everything that is needed to display a users cursor inside the editor.

OperationalTransform:


I organized this one into a separate package because that's how I'm pretty sure we'll write it. The OperationalTransform algorithm is a collaborative editing algorithm used to allow multiple people to edit the same document at the same time, and keep the documents in sync. Ideally, we would use a pre-built library for this, as the algorithm is quite complex and there are lots of special cases, but I was unable to find one written in Java. Our best bet will probably be to port an existing library in another language. The clearest, best documented implementation I found was OT.js (<https://github.com/Operational-Transformation/ot.js/>). The following classes are the main data structures implemented by this version of Operational Transformation.

- The *TextOperation* class represents a sequence of **Operation** objects, or changes. The TextOperation can then be applied to a string, or transformed with another TextOperation (from another client) in order account for changes that occurred simultaneously. See the Operational Transformation algorithm for more details.
- The *Operation* class represents a specific operation. This contains an **OperationType**, a integer front, which specifies the number of characters before the change, a string s, which contains the actual character changed (ex, inserted or deleted). And then an integer back, which contains the number of characters until the end of the document.
- The *OperationType* Enum is used to specify what type of operation a **Operation** is. Type can be either an INSERT, when character(s) are inserted to a document, DELETE, when character(s) are deleted from a document, or RETAIN, used to shift other operations.

- the *Server* class is a class that will be running on the server to sync changes between clients. It's job is to listen for **TextOperations** from all connected clients, and when it receives one, broadcast that change to all connected clients.

2.3.5 Class Diagram 3: Authentication

Authentication




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

2.3.6 Class Diagram Description 3: Authentication Description

Classes:

- The **User** class represents the main user of the entire program. It details the basic information of each individual user, and allows each user the ability to create an account, to log into an existing account, and once logged in, to log out of the user account. It also allows a user to change his/her password, which involves the other classes.
- The **Email** class allows the program to send emails to Users who have signed up, or are signing up. It stores User information as a series of strings to be used by the **send()** function, which sends validation codes to Users' email addresses.
- The **Validator** class will run validation functions when called to do so by the User. Upon a User indicating they would like to change/have forgotten their password, it generates a validation code for that particular User, which it then stores in a dictionary. This validation code is sent to Users by means of the **send()** function denoted earlier.

2.3.7 Class Diagram 4: User Preferences




2.3.8 Class Diagram Description 4: User Preferences Description

Classes:

- **User:** Represents the human user of the program. It will hold the user's profile information so that it can be validated later.
- **Preferences:** Holds all the user's account preferences. This includes profile picture, chat font, chat color, ect.
- **ModifyPref:** Allows the user to modify his or her's preferences.
- **Authentication:** Authenticates the user's username and password to allow access to make changes on their account.

2.3.9 Class Diagram 5: Communication




Authored By: Max Welch
Peer Reviewed By: Team I.C.Y.

2.3.10 Class Diagram Description 5: Communication Description

Classes:

- **TextChat:** The master class to manage the messages, users, and display of the system.
- **ChatDisplay:** Displays relevant information including most recent 20 messages and active users
- **User:** Users interacting with the chat system.
- **Message:** Messages sent by users to TextChat, contain a string, timestamp, and sender/receiver data.
- **Timestamp:** Recorded time of when message was sent.

2.3.11 Class Diagram 6: Project Browsing



2.3.12 Class Diagram Description 6: Project Browsing

Enums:

- The *Rating* enum produces a value based upon the user's desired rating of another user or a project.


Interfaces:

- The *Receives Feedback* interface requires its implementers to implement two methods: **int VoteOnUser(User)**, which returns a value based on a user's rating, and **string Comment(User)**, which leaves feedback in the form of a comment.

Classes:

- The **User** class will be the class, shared across many of the class diagrams, that stores information about a user. The User class will have not only the methods and fields shown in this diagram, but a concatenation of the ones shown here and all other methods and fields from the other diagrams. Here, the User class implements the *ReceivesFeedback* interface so that other users may leave comments/reviews of a User object, and so that they may receive an accompanying rating from one to five stars. In relation to browsing projects, a User is the agent who searches a ProjectBrowser object and works on a Project object.
- The **Project** class will also have the methods and fields of other class diagrams, similar to the User class above. Here, the Project class implements the *ReceivesFeedback* interface so that users may leave comments/reviews on projects, as well as vote up or down on projects that they come across. Projects are displayed in the ProjectBrowser class and worked on by users.
- The **ProjectBrowser** class contains a search-able list of zero or more projects tailored to a user's search. Users browse the list in order to find projects of interest.

2.3.13 Class Diagram 7: Project User Management




2.3.14 Class Diagram Description 7: Project User Management Description

Classes:

- The **User** class contains the profiles of everyone who uses sQuire, and identifies anyone who tries to access a board.
- The **Project** class contains all of the information pertinent to an individual project, including one UserManager, which the client uses to control what kind of access each user has to that specific project.
- The **UserManager** class is referenced to check if a user has permission to read, modify, or run a project, or invite, ban, or change the permissions of another user. It does this by updating and checking against a HashMap of Permissions indexed by User. It records the User profile of the project creator to prevent the creator being demoted by another admin. It also contains a set of Permissions to use by default, before users are manually added to the project. The functions AddUser, KickUser, and SetPerms all modify the permissions HashMap after checking against it to make sure the active user has the authority to change the permissions of the target user.
- The **HashMap** class, in this case, functions as a permissions lookup table. It's indexed by User, and for each User in it there's one set of Permissions that it returns.
- The **Permissions** class is a set of bools that store whether each User has permission (within the instance's parent project) to read, write, execute the project, invite users, and/or modify the permissions of other users regarding the project.

2.3.15 Class Diagram 8: Project Management




Classes:

- The **User** class contains the profiles of everyone who uses sQuire, and identifies anyone who tries to access a board.
- The **Project** class contains all of the information pertinent to an individual project, including one **UserManager**, which the client uses to control what kind of access each user has to that specific project.
- The **UserManager** class is referenced to check if a user has permission to read, modify, or run a project, or invite, ban, or change the permissions of another user. It does this by updating and checking against a `HashMap` of `Permissions` indexed by `User`. It records the `User` profile of the project creator to prevent the creator being demoted by another admin. It also contains a set of `Permissions` to use by default, before users are manually added to the project. The functions `AddUser`, `KickUser`, and `SetPerms` all modify the permissions `HashMap` after checking against it to make sure the active user has the authority to change the permissions of the target user.


- The **HashMap** class, in this case, functions as a permissions lookup table. It's indexed by User, and for each User in it there's one set of Permissions that it returns.
- The **Permissions** class is a set of bools that store whether each User has permission (within the instance's parent project) to read, write, execute the project, invite users, and/or modify the permissions of other users regarding the project.

2.4 SEQUENCE DIAGRAMS

2.4.1 Authentication Feature 1: Sign Up Sequence Diagram




2.4.2 Authentication Feature 2: Log In Sequence Diagram




Author: Domn Werner
Reviewed by: Entire Group

2.4.3 Authentication Feature 3: Log Out Sequence Diagram




Author: Domn Werner
Reviewed by: Entire Group

2.4.4 Authentication Feature 4: Change Password Sequence Diagram




2.4.5 Authentication Feature 5: Change Email Sequence Diagram




Author: Domn Werner
Reviewed by: Entire Group

2.4.6 Authentication Feature 6: Change Username Sequence Diagram




Author: Domn Werner
Reviewed by: Entire Group


2.4.7 Project Browsing Feature 2: Project Creation Sequence Diagram




2.4.8 Project Browsing Feature 3: Project Commenting Sequence Diagram




2.4.9 Project Browsing Feature 4: Project Voting Sequence Diagram




2.4.10 Communication Feature 1: Read Project Chat Sequence Diagram




2.4.11 Feature 2: Write to Project Chat Sequence Diagram




2.4.12 Feature 4: Comment on Project Sequence Diagram




2.4.13 Feature 5: Close chat Sequence Diagram



2.4.14 Project Management Feature 3: Delete Project Sequence Diagram (dani2918)




2.4.15 Project Management Feature 4/5: Request/Manage Request to Join Project Sequence Diagram (dani2918)




Authored by: Matthew Daniel
Reviewed by: Entire Group

2.4.16 Project Management Feature 6: Leave Project Sequence Diagram (dani2918)




Authored by: Matthew Daniel
Reviewed by: Entire Group


2.4.17 Project Management Feature 7/8: Invite/Respond to Project Invite Sequence Diagram (dani2918)




2.4.18 File Editing Feature 1: View Line Numbers Sequence Diagram




2.4.19 File Editing Feature 2: View References Sequence Diagram




2.4.20 File Editing Feature 3: View Dates Sequence Diagram




2.4.21 File Editing Feature 4: View Author Sequence Diagram




2.4.22 File Editing Feature 6: Find Sequence Diagram




2.4.23 File Editing Feature 7: Comment Section Sequence Diagram



2.4.24 File Editing Feature 8: Display Typing User Sequence Diagram




2.4.25 File Editing Feature 9: Display Syntax Errors Sequence Diagram




Author: Eric Gentile-Quant
Reviewed by: Everyone

2.4.26 File Editing Feature 10: Display Syntax Highlighting Sequence Diagram




2.4.27 File Management Feature 1: Open File Sequence Diagram




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

2.4.28 File Management Feature 2: Close File Sequence Diagram




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

2.4.29 File Management Feature 3: Save File Sequence Diagram




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

2.4.30 File Management Feature 4: Add File Sequence Diagram




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

2.4.31 Project User Management Feature 1: Add User Sequence Diagram




2.4.32 Project User Management Feature 2: Kick User Sequence Diagram




Author: Brandon Ratcliff
Reviewed by: Entire Group

2.4.33 Project User Management Feature 3: Set User Permissions Sequence Diagram




Author: Brandon Ratcliff
Reviewed by: Entire Group

2.4.34 Project Management Feature 2: Create project Sequence Diagram(dani2918)




2.4.35 Project Management Feature 1: Compile and Execute Project Sequence Diagram (dani2918)




Authored by: Matthew Daniel
Reviewed by: Entire Group

2.4.36 Project Browsing Feature 1: Project Browsing Sequence Diagram




2.4.37 Feature 3: Message User by Name Sequence Diagram



2.5 USER INTERFACE DIAGRAMS

2.5.1 UI Window Flowchart



3 IMPLEMENTATION

Code organization overview. Description of major components/folders (client, server, ..., but maybe a level or two more detailed). Description of how it is built. Which IDE(s)? Number of targets in IDE. What does it look like to run outside an IDE? What does a client binary distribution look like, and how portable is it? What about a server (or client/server) binary distribution, and how portable is it?


3.1 User Interface

3.1.1 JavaFX Framework

We used the JavaFX framework for the implementation of our user interface. It comes by default as part of the current JDKs. There are two major parts to the JavaFX framework: FXML resource files and their respective controllers.

The FXML files are XML files dictating the static structure of each user-interface “scene” - the current content being show in a window of the program. Each FXML file is associated with a controller class that has the FXML file’s items, the UI elements, injected into it via Java annotations. The controller class is then able to handle any events that take place on the user interface.

Our project’s FXML files can be located in the `src/main/resources` directory:



3.2 Server

3.2.1 MobWrite

3.2.2 Chat

3.2.3 Database

3.2.4 Request Handler

3.3 Client

3.3.1 CodeArea

3.3.2 Response Handler

3.4 Deployment

3.4.1 GitHub Repository

3.4.2 Dependencies

3.4.3 IDE and Plugins

4 TESTING

Stuff that Jeffery wants in bold and then followed by my comments:

- **Test plans, tests actually run, test results, test coverage.** I'll just copy our test plan document that we turned in for homework in. I think it needs some more stuff added to it though so add it here from now on and not there. Basically, we need to write tests for our major pieces of functionality. I think we should just focus on the logic instead of the UI here.
- **Write textual descriptions of test cases for everything that's not junit-integrated.** I think we only need to this for ORMTest so far.

4.1 Introduction

The purpose of this test plan is to provide a outline and provide reference for developers testing the complete sQuire program. This document is currently a standalone, but will be integrated with the SSRS document before the final submission. This document covers sQuire's logic tests, GUI tests, back-end tests, coverage tests, and any additional testing methods deemed necessary to ascertain that the complete sQuire software program adheres to our group's acceptable quality standard.

4.2 Logic Testing

The purpose of this section of tests is to list and describe logic tests in the sQuire program and the required output deemed as a “pass”. These include algorithmic functions, arithmetic functions, validator functions, and other pieces of functionality that can easily be decoupled from the main project and/or reused as part of different projects.

4.2.1 Test Classes

Table 1: PasswordHashTest (wern0096)

Function Name	Description	Pass Criteria
createHash()	Verifies that the hashing algorithm does not create colliding hashes.	A false assertion that all hashes created inside this function are different.
validatePasswor()	Verifies that the PasswordHash.validatePassword() function correctly authenticates a user based on their hashes password.	A true assertion that the a valid password and hash were validated. A false assertion that an invalid password and hash were validated.

Table 2: EditorControllerTest (dani2918)

Function Name	Description	Pass Criteria
testSetupMobWrite()	Verifies that we can set up mobwrite components with various names.	Successful creation of mobwrite components with various names constitutes a success.

Table 3: NewProjectControllerTest (dani2918)

Function Name	Description	Pass Criteria
testInitProjectFields()	Verifies that projects with various names and descriptions (in the form of strings due to the controller class's use of strings from TextFields) are properly created.	Successful creation of project directory inside a test directory constitutes a passing test.
testCopyMainFile()	Verifies that the initial dummy Main "Hello World" class is successfully copied into a directory.	Existence of the file at the specified location constitutes a passing test.

4.2.2 Results

PasswordHashTest (wern0096)

PasswordHashTest: 2 total, 2 passed5.83 s

[Collapse](#) | [Expand](#)

PasswordHashTest.validatePassword	passed	907 ms
PasswordHashTest.createHash	passed	4.92 s

Generated by IntelliJ IDEA on 4/25/16 9:29 PM

This passed test indicates that we our hashing algorithm successfully validates a user's entered password with their hashed password, and properly creates non-colliding hashes. It also shows us that the createHash method takes 5 seconds to run, indicating a possible place for better optimization.

Table 4: EditorControllerTest (dani2918)

Function Name	Result	Description
testSetupMobWrite()	FAILURE	Attempting to create a new CodeArea, which the setupMobWrite function requires as a parameter, was not working in the test class. Further investigation will be required to determine whether the function works properly.

Table 5: NewProjectControllerTest (dani2918)

Function Name	Result	Description
testInitProjectFields()	FAILURE	The test fails when attempting to create a project based upon the empty string as a title. We will have to implement logic to ensure that a user enters a project title in the appropriate field. This is the only case of those tested which caused a failure.
testCopyMainFile()	PASS	The copied file existed with multiple attempts.

4.3 GUI Testing

This section governs our GUI unit tests and the required output deemed as a “pass”. Since we are using the JavaFX framework, every test case requires an initialization step of loading the .fxml file for the GUI scene to be tested. Once it is loaded we perform tests on individual parts of the scene using the TestFX libraries that integrate with JUnit.

4.3.1 Test Classes

Table 6: HomeTest (wern0096)

Function Name	Description	Pass Criteria
verifyUiElementsLoaded()	Checks that every UI element loaded properly.	No exceptions thrown by the verifyThat() function calls.

Table 7: EditorTest (wern0096)

Function Name	Description	Pass Criteria
verifyUiElementsLoaded()	Checks that every UI element loaded properly.	No exceptions thrown by the verifyThat() function calls.

Table 8: NewProjectTest (dani2918)

Function Name	Description	Pass Criteria
verifyUiElementsLoaded()	Checks that every UI element loaded properly.	No exceptions thrown by the verifyThat() function calls.

4.3.2 Results

HomeTest

HomeTest: 1 total, 1 passed515 ms

[Collapse](#) | [Expand](#)

HomeTest.verifyUiElementsLoaded

passed515 ms

Apr 25, 2016 8:54:15 PM javafx.fxml.FXMLLoader\$ValueElement processValue
WARNING: Loading FXML document with JavaFX API of version 8.0.65 by JavaFX runtime of version 8.0.20

Generated by IntelliJ IDEA on 4/25/16 8:54 PM

This passed test indicates that all UI elements are loading properly. It does create a warning message about a mismatch of the JavaFX API and the runtime, however, and we will remedy that next sprint.

EditorTest

EditorTest: 1 total, 1 error296 ms

[Collapse](#) | [Expand](#)

EditorTest.verifyUiElementsLoaded

error296 ms

Generated by IntelliJ IDEA on 4/25/16 8:56 PM

This test currently fails due to it requiring initialization with data from another class. This will be better tested with an automation script, but it is still useful to know what data it requires to successfully initialize. Here is the following exception it throws:




Table 9: NewProjectTest (dani2918)

Function Name	Description	Pass Criteria
verifyUiElementsLoaded()	PASS	No exceptions were thrown after loading all elements from the FXML file.

4.4 Back-end Testing

This section governs any tests aimed at our database(s) or server(s) and the required output deemed as a “pass”.

One of the major libraries we use on the server (MobWrite) contains a full test suite written in JUnit, however, since we use the library as-is, without any modifications, we do not integrate these tests with our test suite. Instead, we just test to see if the client can successfully connect to the server, as that should be the only variable.

4.4.1 Test Classes

Table 10: MobWriteServerTest (ratc8795)

Function Name	Description	Pass Criteria
connectToServer()	Checks to see if the server can be connected to.	No exceptions thrown by the Connection.connect() function.

Table 11: MobWriteClientTest (ratc8795)

Function Name	Description	Pass Criteria
testComputeSyncInterval()	Tests that the sync interval is calculated correctly.	The sync interval is calculated correctly under a variety of conditions.
testUniqueId()	Tests that unique IDs are created correctly.	The ID generated is 8 characters long, and two separate IDs are unique.

Table 12: SessionTest (ratc8795)

Function Name	Description	Pass Criteria
isExpired()	Check that the isExpired function works correctly.	A not-expired session returns false, and a expired session returns true.
logout()	Check that logout function works correctly.	Once the logout function is called on the session, the session no longer exists.
activeSession()	Check the activeSession function returns an active session given a token.	The correct session is returned for a given token, a not active session won't be returned, and a non existant token won't return a session.

Table 13: ChatServerTest (gent7104)

Function Name	Description	Pass Criteria
VerifyConnection()	Verify that the a connection has been made	No exception is thrown when testconnection() is called.

Table 14: ChatClientTest (gent7104)

Function Name	Description	Pass Criteria
VerifySocektConnection()	Verify that the client was able to connect with the specified host and and port number	No exception is thrown when connecting to the socket.

4.4.2 Results

Table 15: ProjectDatabaseTest (cart1189)

Function Name	Description	Pass Criteria
testAddProject()	Checks the ability to create and save new Project objects to their database table.	No exceptions thrown during Project initialization or database save(). The new Project entry is in the table during the test.
testRemoveProject()	Checks the ability to remove Project object entries from their database table.	No exceptions thrown during Project initialization or database save(). The Project in question is removed from the table by the the end of the test.
testGetSetTextFields()	Checks ability to set each string field of a Project database entry, and retrieve those fields from the database.	No exceptions thrown by the test. Each retrieved value matches the value it was set to.
testLoadFile()	Checks ability to upload and download raw files into the ProjectFile table	No exceptions thrown by the test. Retrieved copy of uploaded file matches the original version.

Table 16: MobWriteServerTest (ratc8795)

Function Name	Result	Description
connetToServer()	PASS	

4.5 Coverage Testing (wern0096)

4.5.1 Methodology

The coverage test of sQuire was performed by running the program with the coverage testing option enabled in IntelliJ IDEA and a developer manually navigating through all of the functionality in the program.

4.5.2 Results

The following report was then generated, showing usability per package:

Table 17: MobWriteClientTest (ratc8795)

Function Name	Result	Description
testComputeSyncInterval()	PASS	
testUniqueID()	PASS	

Table 18: SessionTest (ratc8795)

Function Name	Result	Description
isExpired()	PASS	
logout()	PASS	
activeSession()	PASS	

[all classes]

Overall Coverage Summary

Package	Class, %	Method, %	Line, %
all classes	58.2% (32/ 55)	44% (147/ 334)	34.9% (942/ 2699)

Coverage Breakdown

Package ▼	Class, %	Method, %	Line, %
squire.controllers	90.9% (10/ 11)	87.7% (57/ 65)	83.1% (375/ 451)
squire.chatserver	0% (0/ 3)	0% (0/ 9)	0% (0/ 136)
squire.Users.query.assoc	0% (0/ 4)	0% (0/ 16)	0% (0/ 24)
squire.Users.query	25% (1/ 4)	16.7% (2/ 12)	20% (4/ 20)
squire.Users	100% (9/ 9)	45.5% (30/ 66)	40.4% (61/ 151)
squire.Projects	66.7% (2/ 3)	32.1% (9/ 28)	25% (18/ 72)
squire	66.7% (2/ 3)	51.6% (16/ 31)	56.3% (49/ 87)
google.mobwrite	44.4% (8/ 18)	30.8% (33/ 107)	24.7% (435/ 1758)

generated on 2016-04-25 21:15

As indicated, most of the squire.controllers package was hit by our coverage test, indicating very little extraneous UI code. The chat server was not tested with this run, and the rest of the packages had about half of their functionalities hit, due to being heavily in development at the moment. As an example of the granularity of this report, let's examine the squire.controllers package to see what code didn't run during this test:

Table 19: UserTest (ratc8795)

Function Name	Result	Description
getSetUsername()	PASS	
setCheckPassword()	PASS	
authenticate()	PASS	
userQuery()	PASS	

[\[all classes \]](#) [\[squire.controllers \]](#)

Coverage Summary for Package: squire.controllers

Package	Class, %	Method, %	Line, %
squire.controllers	90.9% (10/ 11)	87.7% (57/ 65)	83.1% (375/ 451)

Class ▼	Class, %	Method, %	Line, %
SettingsDialogController	100% (1/ 1)	100% (5/ 5)	100% (17/ 17)
RegisterDialogController	100% (1/ 1)	100% (5/ 5)	100% (15/ 15)
ProjectBrowsingController	100% (1/ 1)	100% (2/ 2)	83.3% (10/ 12)
PreferencesDialogController	100% (1/ 1)	100% (4/ 4)	100% (10/ 10)
NewProjectController3	100% (1/ 1)	100% (10/ 10)	92% (80/ 87)
LogInDialogController	100% (1/ 1)	80% (4/ 5)	67.9% (19/ 28)
HomeController	100% (1/ 1)	88.9% (8/ 9)	75% (75/ 100)
EditorController	75% (3/ 4)	76% (19/ 25)	81.9% (149/ 182)

generated on 2016-04-25 21:

Delving further, let's see what code in the EditorController didn't run:

[\[all classes \]](#) [\[squire.controllers \]](#)

Coverage Summary for Class: EditorController (squire.controllers)

Class	Method, %	Line, %
EditorController	100% (14/ 14)	93.8% (121/ 129)
EditorController\$1	100% (2/ 2)	100% (17/ 17)
EditorController\$TextFieldTreeCellImpl	42.9% (3/ 7)	36.7% (11/ 30)
EditorController\$TextFieldTreeCellImpl\$1	0% (0/ 2)	0% (0/ 6)
total	76% (19/ 25)	81.9% (149/ 182)

Lastly, we can get very granular and see exactly which lines of code didn't run. Here's an example of the `updateItem()` function's code and how the IntelliJ Coverage Report displays code that was hit with a green outline and code that wasn't hit with a red outline:

```

@Override
public void updateItem(String item, boolean empty)
{
    super.updateItem(item, empty);

    if (empty)
    {
        setText(null);
        setGraphic(null);
    }
    else
    {
        if (isEditing())
        {
            if (textField != null)
            {
                textField.setText(getString());
            }
            setText(null);
            setGraphic(textField);
        }
        else
        {
            setText(getString());
            setGraphic(getTreeItem().getGraphic());
        }
    }
}
}

```

4.6 Software Risk Issues (wern0096)

4.6.1 High Risk

The following items are deemed high risk to the security of users and to the usability and quality of the sQuire software:

- **MobWrite Server and Client** Our collaborative editing relies on Google's MobWrite software library. We are rating it high risk because it is the core of the collaborative editing functionality, and it is also a third-party tool with a high impact on the functionality of our product. This module also incorporates the diff-match-patch algorithm running on clients' machines that talks to our Azure server that broadcasts text changes from one client to the rest of the clients. Since it will be sending code over the internet to and from the server, the security implications for all machines involved are very serious. As such, we plan to have extensive testing and review of code using this module.
- **Chat Client** Our chat client is simply a Java application running indefinitely in the same Azure server as the MobWrite server. Nevertheless, it is broadcasting possibly confidential data through the internet and should have the proper encryption and security reviews as the rest of the high risk items.
- **JavaFX** The JavaFX framework is also core to our program. Since it has been used to build most of the user interface, it will require great usability and coverage testing to make sure that it is friendly and intuitive to our users. The breakdown of the user interface would essentially render the rest of the program useless. Thus, it receives a high risk rating.
- **Database Credentials** The project uses a SQLite database for storing of user credentials and project information. We rate the security of user and project credentials in the database as high risk. In order to protect the confidentiality of user credentials and integrity of user projects, we will have to adhere to database security best practices such as salting and hashing stored credentials, encrypting traffic over the internet, and ensuring SQL-injection attacks are mitigated.

4.6.2 Medium Risk

The following items are deemed medium risk to the security of users and to the usability and quality of the sQuire software:

- **Database Storage and Ebean ORM** The non-confidential data stored in the database is rated as medium risk. This is because project data is also stored locally, and breakdown of the database storage functionality would not severely reduce core functionality of the sQuire software. However, it would still significantly hinder collaborative functionality. To address this, we plan on extensively testing database commands with unit tests and code reviews.
- **Code Compilation** Whenever code compilation is involved, security becomes a concern. However, there is not code being executed remotely, so the security risks become much smaller, thus earning this module a medium rating. Compilation in sQuire will rely on the user reviewing their code for malicious intent before executing. We plan on implementing tools for the user to easily track changes to the code in order to aid in the review process if we have time. Also, we will have unit tests making sure that the user is properly notified of code errors and their location(s).
- **Testing Modules** We are putting testing modules themselves as a medium risk item because of the sheer complexity of testing the user interface with JavaFX and TestFX, another open source framework. Since the user interface is rated as a high-risk item, we believe that properly testing it is at least a medium risk item to the proper functionality of our program. We didn't rate it as high-risk, because there are many ways of testing the user interface that are less complex but take more time.

4.6.3 Low Risk

The following items are deemed low risk to the security of users and to the usability and quality of the sQuire software:

- **Editor Features** This module features some complicated code that will come from third-party open sources such as search/replace, syntax highlighting, and auto-complete. However, failure of this module does not severely endanger users' security or the core functionality of the software. As such, it earns a low risk rating. This module will require extensive unit testing, however.
- **Local File Structure** The local file structure stores user's projects locally in the form of a folder for each project. We rate this module as a low risk module because even if the local files were corrupted or deleted, the user's projects/files can still be restored from the database, and the program has code to handle such a case. Nevertheless, we plan to have various unit tests documenting valid/invalid file structures that we can then create code to handle such cases.
- **Program Settings** This module involves settable user preferences that should persist between runs of sQuire. We plan to have the user's settings be saved locally as well as on the database, so that upon login, sQuire will update to conform to the user's preferences. Since there is redundancy to this module and its breakdown does not constitute a large hit to the functionality of sQuire, we deem it low risk.

5 METRICS

Metrics that Jeffery wants are in bold and then followed by my ideas on how to get them:

- **How “big” our projects are.** Ex: lines of code, complexity, packages, classes. Use IntelliJ for that.
- **How much of our functionality is implemented.** Will probably have to be done by hand. Maybe make a table of use-case/functional requirement and whether it was implemented or not and a justification.
- **How much of our code is tested and how tested is the code.** Get a ratio of unit test classes vs actual classes? How much functions have a unit test associated with them? Do we have uncovered cases?
- **Who did the work?** Use GitHub for that? Add any extra info manually.
- **Problem Areas.** What was hard to implement and why?