

**SYSTEMS AND SOFTWARE REQUIREMENTS SPECIFICATION (SSRS) FOR
sQuire Collaborative IDE**

Picture here.

**Version 1.0
February 09, 2016**

**Prepared for:
CS383-01**

**Prepared by:
Domn Werner (wern0096) | Robert Carlson (carl7595) | Brian Cartwright (cart1189)
Max Welch (welc2150) | Matthew Daniel (dani2918) | Brandon Ratcliff (ratc8795)
Joel Doumit (doum6708) | Eric Gentile-Quant (gent7104)
Team 4 - It Compiled Yesterday (ICY)
University of Idaho
Moscow, ID 83844-1010**

RECORD OF CHANGES

[illegible]

***A** - ADDED **M** - MODIFIED **D** - DELETED

SQUIRE SSRS TABLE OF CONTENTS

Section	Page
1 Introduction	1
1.1 IDENTIFICATION	1
1.2 PURPOSE	1
1.3 SCOPE	1
1.4 DEFINITIONS, ACRONYMS, AND ABBREVIATIONS	1
1.5 REFERENCES	2
1.6 OVERVIEW AND RESTRICTIONS	2
2 OVERALL DESCRIPTION	3
2.1 PRODUCT PERSPECTIVE	3
2.2 PRODUCT FUNCTIONS	3
2.3 USER CHARACTERISTICS	3
2.4 CONSTRAINTS	3
2.5 ASSUMPTIONS AND DEPENDENCIES	3
2.6 SYSTEM LEVEL (NON-FUNCTIONAL) REQUIREMENTS	4
2.6.1 Site dependencies	4
2.6.2 Safety, security and privacy requirements	5
2.6.3 Performance requirements	5
2.6.4 System and software quality	5
2.6.5 Packaging and delivery requirements	6
2.6.6 Personnel-related requirements	6
2.6.7 Training-related requirements	6
2.6.8 Logistics-related requirements	6
2.6.9 Other requirements	6
2.6.10 Precedence and criticality of requirements	6
3 SPECIFIC REQUIREMENTS	8
3.1 Functional Requirements	8
3.1.1 Project Browsing	8
3.1.2 Authentication	8
3.1.3 Communication	9
3.1.4 File Management	9
3.1.5 File Editing	9
3.1.6 Project Management	10
3.1.7 Project User Management	10
3.1.8 User Preferences	10
3.2 EXTERNAL INTERFACE REQUIREMENTS	11
3.2.1 Hardware Interfaces	11
3.2.2 Software Interfaces	11
3.2.3 User Interfaces	11
3.2.4 Other Communication Interfaces	11
3.3 SYSTEM FEATURES	1

3.3.1	Use Case Diagram 1: Authentication	1
3.3.2	Authentication Feature 1: Sign Up Use Case Description	2
3.3.3	Authentication Feature 1: Sign Up Sequence Diagram	3
3.3.4	Authentication Feature 2: Log In Use Case Description	4
3.3.5	Authentication Feature 2: Log In Sequence Diagram	5
3.3.6	Authentication Feature 3: Log Out Use Case Description	6
3.3.7	Authentication Feature 3: Log Out Sequence Diagram	7
3.3.8	Authentication Feature 4: Change Password Use Case Description	8
3.3.9	Authentication Feature 4: Change Password Sequence Diagram	9
3.3.10	Authentication Feature 5: Change Email Use Case Description	10
3.3.11	Authentication Feature 5: Change Email Sequence Diagram	11
3.3.12	Authentication Feature 6: Change Username Use Case Description	12
3.3.13	Authentication Feature 6: Change Username Sequence Diagram	13
3.3.14	Use Case Diagram 2: Project Browsing	14
3.3.15	Project Browsing Feature 1: Project Browsing Use Case Description	15
3.3.16	Project Browsing Feature 1: Project Browsing Sequence Diagram	16
3.3.17	Project Browsing Feature 2: Project Creation Use Case Description	17
3.3.18	Project Browsing Feature 2: Project Creation Sequence Diagram	18
3.3.19	Project Browsing Feature 3: Project Commenting Use Case Description	19
3.3.20	Project Browsing Feature 3: Project Commenting Sequence Diagram	20
3.3.21	Project Browsing Feature 4: Project Voting Use Case Description	21
3.3.22	Project Browsing Feature 4: Project Voting Sequence Diagram	22
3.3.23	Use Case Diagram 3: Communication	23
3.3.24	Communication Feature 1: Read Project Chat Use Case Description	24
3.3.25	Communication Feature 2: Write to Project Chat Use Case Description	25
3.3.26	Communication Feature 3: Message User by Name Use Case Description	26
3.3.27	Communication Feature 4: Comment on Project Use Case Description	27
3.3.28	Communication Feature 5: Close chat Use Case Description	28
3.3.29	Project Browsing Feature 2: Use Case Description 2	29
3.3.30	Use Case Diagram 4: User Preferences	30
3.3.31	User Preferences Feature 1: Use Case Description 1	31
3.3.32	User Preferences Feature 2: Use Case Description 2	32
3.3.33	Use Case Diagram 5: Project Management (dani2918)	33
3.3.34	Project Management Feature 1: Use Case Description 1: Compile and execute project (dani2918)	34
3.3.35	Project Management Feature 1: Sequence Diagram 1: Compile and execute project (dani2918)	35
3.3.36	Project Management Feature 2: Create project Use Case Description (dani2918) . . .	36
3.3.37	Project Management Feature 2: Create project Sequence Diagram (dani2918)	36
3.3.38	Project Management Feature 3: Delete Project Use Case Description (dani2918) . . .	37
3.3.39	Project Management Feature 3: Delete Project Sequence Diagram (dani2918)	37
3.3.40	Project Management Feature 4: Request to Join Project Use Case Description (dani2918)	38
3.3.41	Project Management Feature 5: Manage Request to Join Project Use Case Description (dani2918)	39
3.3.42	Project Management Feature 4/5: Request/Manage Request to Join Project Sequence Diagram (dani2918)	39
3.3.43	Project Management Feature 6: Leave Project Use Case Description (dani2918) . . .	40
3.3.44	Project Management Feature 6: Leave Project Sequence Diagram (dani2918)	40
3.3.45	Project Management Feature 7: Invite to Project Use Case Description (dani2918) . .	41
3.3.46	Project Management Feature 8: Respond to Project Invite Use Case Diagram (dani2918)	42

3.3.47	Project Management Feature 7/8: Invite/Respond to Project Invite Sequence Diagram (dani2918)	43
3.3.48	Use Case Diagram 6: File Editing	44
3.3.49	File Editing Feature 1: View Line Numbers	45
3.3.50	File Editing Feature 1: View Line Numbers Sequence Diagram	46
3.3.51	File Editing Feature 2: View References	47
3.3.52	File Editing Feature 2: View References Sequence Diagram	48
3.3.53	File Editing Feature 3: View Dates	49
3.3.54	File Editing Feature 3: View Dates Sequence Diagram	50
3.3.55	File Editing Feature 4: View Authors	51
3.3.56	File Editing Feature 4: View Author Sequence Diagram	52
3.3.57	File Editing Feature 5: Format Document	53
3.3.58	File Editing Feature 6: Find/Replace	54
3.3.59	File Editing Feature 6: Find Sequence Diagram	55
3.3.60	File Editing Feature 7: Comment Section	56
3.3.61	File Editing Feature 7: Comment Section Sequence Diagram	57
3.3.62	File Editing Feature 8: Display Typing User	58
3.3.63	File Editing Feature 8: Display Typing User Sequence Diagram	59
3.3.64	File Editing Feature 9: Display Syntax Errors	60
3.3.65	File Editing Feature 9: Display Syntax Errors Sequence Diagram	61
3.3.66	File Editing Feature 10: Display Syntax Highlighting	62
3.3.67	File Editing Feature 10: Display Syntax Highlighting Sequence Diagram	63
3.3.68	Use Case Diagram 7: File Management	64
3.3.69	File Management Feature 1: Open File Use Case Description	65
3.3.70	File Management Feature 1: Open File Sequence Diagram	67
3.3.71	File Management Feature 2: Close File Use Case Description	68
3.3.72	File Management Feature 2: Close File Sequence Diagram	69
3.3.73	File Management Feature 3: Save File Use Case Description	70
3.3.74	File Management Feature 3: Save File Sequence Diagram	71
3.3.75	File Management Feature 4: Add File Use Case Description	72
3.3.76	File Management Feature 4: Add File Sequence Diagram	73
3.3.77	Use Case Diagram 8: Project User Management	74
3.3.78	Project User Management Feature 1: Add User to Project Use Case Description	75
3.3.79	Project User Management Feature 1: Add User Sequence Diagram	76
3.3.80	Project User Management Feature 2: Kick User Use Case Description	77
3.3.81	Project User Management Feature 2: Kick User Sequence Diagram	78
3.3.82	Project User Management Feature 3: Set User Permissions Use Case Description	79
3.3.83	Project User Management Feature 3: Set User Permissions Sequence Diagram	80
3.4	Class Diagrams	82
3.4.1	Class Diagram 1: File Management	82
3.4.2	Class Diagram Description 1: File Management Description	83
3.4.3	Class Diagram 2: File Editing	84
3.4.4	Class Diagram Description 2: File Editing Description	85
3.4.5	Class Diagram 3: Authentication	87
3.4.6	Class Diagram Description 3: Authentication Description	88
3.4.7	Class Diagram 4: User Preferences	89
3.4.8	Class Diagram Description 4: User Preferences Description	90
3.4.9	Class Diagram 5: Communication	91
3.4.10	Class Diagram Description 5: Communication Description	92
3.4.11	Class Diagram 6: Project Browsing	93

3.4.12	Class Diagram Description 6: Project Browsing	94
3.4.13	Class Diagram 7: Project User Management	95
3.4.14	Class Diagram Description 7: Project User Management Description	96
3.4.15	Class Diagram 8: Project Management	97
	97
4	REQUIREMENTS TRACEABILITY	1
5	APPENDIX A. [insert name here]	1
6	APPENDIX B. [insert name here]	1

1 Introduction

The sQuire Collaborative IDE is a collaborative IDE software project for CS383-01. The intended audience for this project is Java programmers looking for a more social collaborative experience. A large focus of the program is also to help programmers connect with others who may be interested in their projects.

1.1 IDENTIFICATION

The software system being considered for development is referred to as sQuire. The customer providing specifications for the system is Dr. Jeffery and the CS383-01 class. The ultimate customer, or end-user, of the system will be Java programmers. This is a new project effort, so the version under development is version 1.0.

1.2 PURPOSE

The purpose of the system under development is to provide Java programmers with a more social collaborative experience. Instead of individual methods of source control, sQuire will provide an environment where programmers can work together in the same environment and instantly see the effect of others' code. While the system will be used by Java programmers, this document is intended to be read and understood by UI CS software designers and coders. The document will also be vetted or approved by Team 4.

1.3 SCOPE

This paragraph shall briefly summarize the history of system development, operation, and maintenance; identify the project sponsor, acquirer, user, developer, and support agencies; identify current and planned operating sites; and list other relevant documents.

[insert your text here]

1.4 DEFINITIONS, ACRONYMS, AND ABBREVIATIONS

This section shall list and define all special terms, acronyms and abbreviations used throughout this document. A tabular form is preferable, but not mandatory.

Term or Acronym	Definition
Alpha test	Limited release(s) to selected, outside testers
Beta test	Limited release(s) to cooperating customers wanting early access to developing systems
Final test	aka, Acceptance test, release of full functionality to customer for approval
DFD	Data Flow Diagram
SDD	Software Design Document, aka SDS, Software Design Specification
SRS	Software Requirements Specification
SSRS	System and Software Requirements Specification
IDE	Integrated Development Environment

1.5 REFERENCES

This section shall list full bibliographic citations of all documents referenced in this report. This section shall also identify the source for all materials not available in printed form (e.g., web-based information) and list the complete URL along with owner, author, posting date, and date last visited.

[insert your citations here]

1.6 OVERVIEW AND RESTRICTIONS

This paragraph shall describe the organization of this document and shall describe any security or privacy considerations associated with its use.

This document is for limited release only to UI CS personnel working on the project and [state others who will receive the document].

Section 2 of this document describes the system under development from a holistic point of view. Functions, characteristics, constraints, assumptions, dependencies, and overall requirements are defined from the system-level perspective.

Section 3 of this document describes the specific requirements of the system being developed. Interfaces, features, and specific requirements are enumerated and described to a degree sufficient for a knowledgeable designer or coder to begin crafting an architectural solution to the proposed system.

Section 4 provides the requirements traceability information for the project. Each feature of the system is indexed by the SSRS requirement number and linked to its SDD and test references.

Sections 5 and up are appendices including original information and communications used to create this document.

2 OVERALL DESCRIPTION

The sQuire project is an answer to the lack of real-time collaborative programming experiences. By bringing programmers together in a more social environment, this program aims to improve collaboration between programmers in a much more fast paced and agile methodology. Furthermore, for programmers who seek others to help with their projects, sQuire aims to provide a simple social platform for engaging with other programmers and start working on a project together.

2.1 PRODUCT PERSPECTIVE

This program will either be a standalone executable with many linked DLLs or a web application that can run on most modern web-browsers with internet access.

2.2 PRODUCT FUNCTIONS

This subsection of the document should provide a summary of the major functions that the software will perform. For the sake of clarity, the functions should be organized in a way that makes the list of functions understandable to the customer or to anyone else reading the document for the first time. Textual or graphical methods can be used to show the different functions and their relationships. Such a diagram is not intended to show a design of a product, but simply shows the logical relationships among variables.

[insert your text here]

2.3 USER CHARACTERISTICS

This subsection of the document should describe those general characteristics of the intended users of the product including educational level, experience, and technical expertise. It should not be used to state specific requirements, but rather provide the reasons why certain specific requirements are later specified in Section 3 of this document.

[insert your text here]

2.4 CONSTRAINTS

This subsection of the document should provide a general description of any other items that will limit the developer's options. These include: a) Regulatory policies; b) Hardware limitations (e.g., signal timing requirements); c) Interfaces to other applications; d) Parallel operation; e) Audit functions; f) Control functions; g) Higher-order language requirements; h) Signal handshake protocols; i) Reliability requirements; j) Criticality of the application; k) Safety and security considerations.

[insert your text here]

2.5 ASSUMPTIONS AND DEPENDENCIES

This subsection of the document should list each of the factors that affect the requirements stated in the document. These factors are not design constraints on the system and/or software but are, rather, any changes to them that can affect the requirements in the document. For example, an assumption may be that a specific operating system will be available on the hardware designated for the software product. If, in fact, the operating system is not available, the document would then have to change accordingly.

[insert your text here]

2.6 SYSTEM LEVEL (NON-FUNCTIONAL) REQUIREMENTS

This subsection of the document should identify system level (whole, not functional) requirements that impact the construction, operation, packaging and delivery of the system and software.

2.6.1 Site dependencies

This paragraph shall specify site-dependent operational parameters and needs (such as parameters indicating operation-dependent targeting constants or data recording). The requirements shall include, as applicable, number of each type of equipment, type, size, capacity, and other required characteristics of processors, memory, input/output devices, auxiliary storage, communications/ network equipment, and other required equipment or software that must be used by, or incorporated into, the system. Examples include operating systems, database management systems, communications/network software, utility software, input and equipment simulators, test software, and manufacturing software. The correct nomenclature, version, and documentation references of each such device or software item shall be provided.

1. Central SQL Server
2. Host-side Project Server
3. Collaborator-side Client

The Central server stores user credentials, project descriptions, and user profile and achievement data.
Requirements for Central SQL Server

1. Host with high uptime percentage
2. SQL capable
3. E-mail capable for password resets
4. Fast enough connection to prevent login timeout, even while handling multiple requests
5. Prefer host with multiple backups

The Host-side server stores the project files, project access list, hosts the editing environment, runs chat channels, and serves files to collaborators for compiling.

Requirements for Host-side Server

1. Java Capable (<http://java.com/en/download/help/sysreq.xml>)
2. SQL Capable (WAMP/LAMP)
3. 4 GB RAM
4. Hard drive space for server + project files

The client side application connects to the host server, renders GUI elements, stores connection profiles, stores server files, and compiles the project.

Requirements for Collaborator-side Client

1. Java Capable (<http://java.com/en/download/help/sysreq.xml>)
2. Project specified Java installed
3. 2 GB RAM
4. Hard drive space for project files

2.6.2 Safety, security and privacy requirements

This paragraph shall specify the system requirements, if any, concerned with maintaining safety, security and privacy. These requirements shall include, as applicable, the safety, security and privacy environment in which the system must operate, the type and degree of security or privacy to be provided, and the criteria that must be met for safety/security/privacy certification and/or accreditation.

The collaborative nature of sQuire includes several concerns for security and privacy. The program will include in the license agreement the following stipulations:

1. sQuire is a free development environment, and may be used for commercial purposes
2. No guarantee of code confidentiality is implied by use of sQuire
3. Clients assume the risk of downloading, compiling, and running project files
4. Email addresses are visible as part of a user profile
5. Host assume the risk of allowing peers to connect to their server

However, the program will provide the following minimum features to address security and privacy concerns:

1. All SQL servers will include input sanitization and appropriate anti-injection safeguards
2. Project hosts may turn off guest access to their project
3. Uploads for assets will be limited to folders within the project directory
4. Visibility to host file structure will be limited to project folders only

2.6.3 Performance requirements

This paragraph should specify both the static and the dynamic numerical performance requirements placed on the software or on human interaction as a whole. Static numerical requirements may include the following: a) The number of terminals to be supported; b) The number of simultaneous users to be supported; c) Amount and type of information to be handled. Dynamic numerical requirements may include, for example, the numbers of transactions and tasks and the amount of data to be processed within certain time periods for both normal and peak workload conditions. All of these requirements should be stated in measurable terms. For example, "95% of the transactions shall be processed in less than 1msec."

1. Up to 33 concurrent connections will be supported
2. Edits will be visible to all connected collaborators within 10 seconds
3. Login and server connections will report success or failure within 45 seconds

2.6.4 System and software quality

This paragraph shall specify the requirements, if any, concerned with hardware and software quality factors identified in the contract. Examples include quantitative requirements regarding the system's functionality (the ability to perform all required functions), reliability (the ability to perform with correct, consistent results), maintainability (the ability to be easily corrected), availability (the ability to be accessed and operated when needed), flexibility (the ability to be easily adapted to changing requirements), portability (the ability to be easily modified for a new environment), reusability (the ability to be used in multiple applications), testability (the ability to be easily and thoroughly tested), usability (the ability to be easily learned and used), and other attributes.

Adaptability

1. The program will allow selection of different compiling programs and command line arguments.
2. The program will allow importing of files of key words to allow other development languages to be used.

2.6.5 Packaging and delivery requirements

This paragraph shall specify the requirements, if any, for packaging, labeling, handling and delivery of the system being developed to the customer.

The executable system and all associated documentation (i.e., SSRS, SDD, code listing, test plan (data and results), and user manual) will be delivered to the customer on CD's and/or via email, as specified by the customer at time of delivery. Although document "drops" will occur throughout the system development process, the final, edited version of the above documents will accompany the final, accepted version of the executable system.

2.6.6 Personnel-related requirements

This paragraph shall specify the system requirements, if any, included to accommodate the number, skill levels, duty cycles, training needs, or other information about the personnel who will use or support the system under development. These requirements shall include, as applicable, considerations for the capabilities and limitations of humans; foreseeable human errors under both normal and extreme conditions; and specific areas where the effects of human error would be particularly serious. Examples include requirements for color and duration of error messages, physical placement of critical indicators or keys, and use of auditory signals.

The system under development has no special personnel-related characteristics.

2.6.7 Training-related requirements

This paragraph shall specify the system requirements, if any, pertaining to training. Examples include training software, tutorials, or help information to be included in the system.

No training materials or expectations are tied to this project other than the limited help screens built into the software and the accompanying user manual.

2.6.8 Logistics-related requirements

This paragraph shall specify the system requirements, if any, concerned with logistics considerations. These considerations may include: system maintenance, software support, system transportation modes, supply-system requirements, impact on existing facilities, and impact on existing equipment.

[Insert a description of the minimum hardware requirements and OS and application software dependencies here]

2.6.9 Other requirements

This paragraph shall specify additional system level requirements, if any, not covered in the previous paragraphs.

[insert your text here]

2.6.10 Precedence and criticality of requirements

This paragraph shall specify, if applicable, the order of precedence, criticality, or assigned weights indicating the relative importance of the requirements in this specification. Examples include identifying those

requirements deemed critical to safety, to security, or to privacy for purposes of singling them out for special treatment. If all requirements have equal weight, this paragraph shall so state.

[insert your text here]

3 SPECIFIC REQUIREMENTS

3.1 Functional Requirements

3.1.1 Project Browsing

These requirements involve the ability for users to find and learn about projects that they may wish to contribute to. Users shall be able to:

1. See a list of open projects.
2. Filter or search projects.
3. View more information about a specific project.
4. Upvote and downvote projects.
5. Comment on projects and interact with its contributors.
6. Request to join a specific project.

3.1.2 Authentication

These requirements involve the ability for users to have individual accounts and the security that comes from that. Users shall be able to:

1. Sign up for a sQuire user account.
Use Case Description: **S3.3.2**
Sequence Diagram: **S3.3.3**
2. Log in to the program using their user account.
Use Case Description: **S3.3.4**
Sequence Diagram: **S3.3.5**
3. Log out of the program using their user account.
Use Case Description: **S3.3.6**
Sequence Diagram: **S3.3.7**
4. Change their password.
Use Case Description: **S3.3.8**
Sequence Diagram: **S3.3.9**
5. Change their email.
Use Case Description: **S3.3.10**
Sequence Diagram: **S3.3.11**
6. Change their username.
Use Case Description: **S3.3.12**
Sequence Diagram: **S3.3.13**

3.1.3 Communication

These requirements involve the ability for users to be able to communicate with other users. Users shall be able to:

1. Open and close project chat.
2. Write to project chat.
3. Read from project chat.
4. Message a user by their name.
5. Leave a comment in a file.

3.1.4 File Management

These requirements involve the ability for users to manage the files that compose a project. Users shall be able to:

1. Open one or more files.
2. Close one or more files.
3. Delete one or more files.
4. Download one or more files.
5. Add a new file to the project.
6. Add an existing file to the project.
7. Save one or more files.

3.1.5 File Editing

These requirements involve the collaborative editor part of sQuire. Users shall be able to:

1. Enable or disable line numbers.
2. Enable or disable viewing reference counts above each line.
3. Enable or disable viewing date of last edit above each line.
4. Enable or disable view author of each line.
5. Comment/Uncomment a selected section code.
6. Format the document to adhere to code style.
7. Find/Replace specified text.
8. View text highlighted by other users.
9. Type text and have the system apply syntax coloring for Java files and display errors.
10. View other users' carets as they type.

3.1.6 Project Management

These requirements involve the management of entire projects. Users shall be able to:

1. Compile a project. See use case description and sequence diagram **Project Management Feature 1: Compile and Execute Project**
2. Execute a compiled project. See use case description and sequence diagram **Project Management Feature 1: Compile and Execute Project Use Case Description**
3. Create a new project. See use case description and sequence diagram **Project Management Feature 2: Create project**
4. Delete a project. See use case description and sequence diagram **Project Management Feature 3: Delete project**
5. Invite a user to a project. See use case description and sequence diagram **Project Management Feature 7/8: Invite/Respond to Project Invite**
6. Join a project. See use case description and sequence diagram **Project Management Feature 4/5: Request/Manage Request to Join Project**
7. Leave a project. See use case description and sequence diagram **Project Management Feature 6: Leave Project**

3.1.7 Project User Management

These requirements involve project admins managing their Users. Admins shall be able to:

1. Add users to a project.
Use Case Description: **S3.3.49**
Sequence Diagram: **S3.3.50**
2. Remove users from a project.
Use Case Description: **S3.3.51**
Sequence Diagram: **S3.3.52**
3. Change user permissions to a project.
Use Case Description: **S3.3.53**
Sequence Diagram: **S3.3.54**

3.1.8 User Preferences

These requirements involve managing user preferences. Users shall be able to:

1. Update their username.
2. Update their password.
3. Update their email address.
4. Update their biography.
5. Update their display name.

6. Enable receiving email updates.
7. Enable receiving messages from any user.
8. Display their email address to selected groups.
9. Change program colors.

3.2 EXTERNAL INTERFACE REQUIREMENTS

This subsection should be a detailed description of all inputs into and outputs from the software system. It should complement the constraints and dependencies defined in earlier sections, but not repeat that information. Hardware, software, user, and other communication interfaces need to be specified. Use the four subsections listed below or the table on the next page, or some combination of both.

3.2.1 Hardware Interfaces

[insert your text here]

3.2.2 Software Interfaces

[insert your text here]

3.2.3 User Interfaces

[insert your text here]

3.2.4 Other Communication Interfaces

[insert your text here]

External Interface Requirements**Hardware Interfaces**

Name	Source/Destination	Description	Type/range	Dependencies

Software Interfaces

Name	Source/Destination	Description	Type/range	Dependencies

User Interfaces

Name	Source/Destination	Description	Type/range	Dependencies

Other Communication Interfaces


Name	Source/Destination	Description	Type/range	Dependencies

3.3 SYSTEM FEATURES

Functional requirements should define the fundamental actions (i.e., features) that must take place in the software in accepting and processing the inputs and in processing and generating the outputs. These requirements are given in the form of **Use Cases** where possible, denoting a concrete use (discrete user-performable task) of the system. Use case diagrams are followed by use case descriptions, followed by any non-task features. Non-task features are generally listed as “shall” statements starting with “The system shall...” These include: a) Validity checks on the inputs; b) Exact sequence of operations; c) Responses to abnormal situations, including error detection, handling and recovery; d) Parameter specification and usage; e) Relationship of outputs to inputs, including formulas for input to output conversion.

It may be appropriate to partition the functional requirements into sub functions or subprocesses, but that decomposition (here) does not imply that the software design will also be partitioned that way. You should repeat subsections 3.3.i for every specified feature defined for the system or software.

3.3.1 Use Case Diagram 1: Authentication



3.3.2 Authentication Feature 1: Sign Up Use Case Description

Actors: User

Summary: The user signs up and creates an account using their email address and creates username and password in order to access the program.

Purpose: To register and create an account in the program

Preconditions: None

Steps:

1. User clicks Register button.
2. System prompts the user to enter email and password.
3. User enters email and password and clicks Submit button.
4. System sends confirmation email.
5. User verifies email by clicking a link.
6. System adds verified user to database.


Alternative 1: User already has an account.

Alternative 2: User doesn't confirm email. Delete request after timeout period.

Relevant Classes:

- **User** in **S3.4.5**
 - **Email** in **S3.4.5**
 - **Validator** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.3 Authentication Feature 1: Sign Up Sequence Diagram



3.3.4 Authentication Feature 2: Log In Use Case Description

Actors: User

Summary: A registered logs in to the program in order to access its features.

Purpose: Allow registered users access to the program.

Preconditions: User must already have a registered account.

Steps:

1. Users clicks Log In button.
2. System prompts the user for their username and password.
3. User enters their login information.
4. System verifies the login information and grants user access to their account.


Alternatives:

1. User enters incorrect information. System prompts for credentials again.
2. User has not clicked email confirmation. System resends email and tells user.
3. User makes 5 incorrect login attempts. System prevents more login attempts for 5 minutes.

Relevant Classes:

- **User** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.5 Authentication Feature 2: Log In Sequence Diagram



Author: Domn Werner
Reviewed by: Entire Group

3.3.6 Authentication Feature 3: Log Out Use Case Description

Actors: User

Summary: A user logs out of the program.

Purpose: Allows logged in users to log out in order to protect their account.

Preconditions:


1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks log out button.
2. System logs user out.
3. Browser cookies are updated to reflect user being logged out.

Relevant Classes:

- **User** in **S3.4.5**
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.7 Authentication Feature 3: Log Out Sequence Diagram

Author: Domn Werner
Reviewed by: Entire Group

3.3.8 Authentication Feature 4: Change Password Use Case Description

Actors: User

Summary: A user changes their password while logged in.

Purpose: Allows logged in users to change their passwords.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks Change Password button.
2. System prompts user to enter their password twice.
3. User enters their password twice.
4. System hashes both passwords.

Alternatives:

1. If passwords match, System updates user password and sends email to registered email account.
2. If passwords don't match, system notifies user.


Related Use Cases:

1. Change Email
2. Change Username

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **Validator** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.9 Authentication Feature 4: Change Password Sequence Diagram



3.3.10 Authentication Feature 5: Change Email Use Case Description

Actors: User

Summary: A user changes their email while logged in.

Purpose: Allows logged in users to change their email.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. User clicks Change Email button.
2. System prompts user to enter their email.
3. User enters their email.
4. System sends a confirmation link to the email entered.

Alternatives:


1. If User clicks confirmation link, System updates the user's email and sends an email to the new email stating so.
2. If user doesn't click confirmation link in an hour, the link becomes invalid.

Related Use Cases:

1. Change Password
2. Change Username

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **Validator** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.11 Authentication Feature 5: Change Email Sequence Diagram

Author: Domn Werner
Reviewed by: Entire Group

3.3.12 Authentication Feature 6: Change Username Use Case Description

Actors: User

Summary: A user changes their username while logged in.

Purpose: Allows logged in users to change their username.

Preconditions:

1. User must have a registered account.
2. User must be logged in.

Steps:

1. Users clicks Change Username button.
2. System prompts user to enter a new username.
3. User enters a username and clicks Change Username.

Alternatives:


1. If username doesn't exist, System changes the user's username and notifies the user in the UI and through an email.
2. If username exists, System asks user to enter a different username.


Related Use Cases:

1. Change Password
2. Change Email

Relevant Classes:

- **User** in **S3.4.5**.
 - **Email** in **S3.4.5**.
 - **UserController** to be added.
 - **ServerController** to be added.
 - **Database** to be added.
-

3.3.13 Authentication Feature 6: Change Username Sequence Diagram

3.3.14 Use Case Diagram 2: Project Browsing

3.3.15 Project Browsing Feature 1: Project Browsing Use Case Description

Actors: User

Summary: User looks through posted project ideas to find projects to work on and/or discuss.

Purpose: To find and view projects relevant to the user's search parameters

Preconditions: User is signed in


Steps:

1. Actor selects Browse Project Ideas button
2. Actor refines search by selecting from list of project categories as desired
3. Actor enters terms into search field as desired and views a list of top projects
4. Actor selects desired project
5. System displays detailed project information

Alternative 1: None

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

3.3.16 Project Browsing Feature 1: Project Browsing Sequence Diagram

3.3.17 Project Browsing Feature 2: Project Creation Use Case Description

Actors: User

Summary: User will create a project.

Purpose: To allow users to create projects and make them accessible to other users

Preconditions: User is signed in


Steps:

1. User selects Create Project button
2. User will enter the information on the project, including its name, goals, and identifying tags.
3. If project name does not match any existing project, the system will create a project with the specified parameters and set user as an admin for the project.

Alternative 1: Project name matches the name of an existing project and will ask the user to rename it.

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

3.3.18 Project Browsing Feature 2: Project Creation Sequence Diagram

3.3.19 Project Browsing Feature 3: Project Commenting Use Case Description

Actors: User

Summary: Provide detailed feedback on project ideas

Purpose: To allow users to write longform feedback on projects as necessary.

Preconditions: User is signed in


Steps:

1. User selects Comment button
2. User types feedback into field
3. User clicks Submit button
4. System shows confirmation that feedback was received

Alternative 1: If the project requires comments to be made by project members only and the user is not a project member, the user will be shown an error message.

Relevant Classes:

- User in S3.4.5
 - Project in S3.4.5
-

3.3.20 Project Browsing Feature 3: Project Commenting Sequence Diagram

3.3.21 Project Browsing Feature 4: Project Voting Use Case Description

Actors: User

Summary: Support promising project ideas or offer criticism to unfavorable ones

Purpose: Allow for feedback and help users search for well received projects

Preconditions: User is signed in


Steps:


1. User selects Browse Project Ideas button
2. User refines search by selecting from list of project categories as desired
3. User enters terms into search field as desired and views a list of top projects
4. User selects desired project
5. System displays detailed project information
6. User selects Up Vote or Down Vote button
7. Project receives the vote and updates its total score

Alternative 1: None

Relevant Classes:

- User in S3.4.5
 - Project Browser in S3.4.5
 - Project in S3.4.5
-

3.3.22 Project Browsing Feature 4: Project Voting Sequence Diagram

3.3.23 Use Case Diagram 3: Communication

3.3.24 Communication Feature 1: Read Project Chat Use Case Description

Actors: User

Summary: Open a window to view the conversation in a project

Purpose: Allow users to communicate quickly without permanently taking up screen space in a project

Preconditions: User is signed in and viewing a project

Steps:

1. User selects the "Open Chat" button
2. System opens the chat window, and notifies the other users in the project of the new arrival
3. System displays any messages from other users in the project in that window until it is closed/left.

Alternative 1: None

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

3.3.25 Communication Feature 2: Write to Project Chat Use Case Description

Actors: at least one User

Summary: Contribute to the conversation in a project

Purpose: Allow users to communicate quickly without permanently taking up screen space in a project

Preconditions: User is signed in and has joined the project chat

Steps:

1. User types a message in the project chat window and presses Send
2. System sends that message to the project server, which delivers it to the other users in the project chat
3. Other users may read and/or respond to the message at their leisure

Alternative 1: None

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

3.3.26 Communication Feature 3: Message User by Name Use Case Description

Actors: User

Summary: Start talking an individual user

Purpose: Allow users to communicate outside of a project, or in private

Preconditions: At least one of the users are signed in

Steps:

1. User selects "Send PM" from the chat menu and types or selects the other user's ID
2. System checks to see if the user exists and is online, and if so creates a chat channel for the two users
3. Both users then use the chat as normal

Alternative 1: If the second user exists but is offline, the first user is notified and the second user gets the message from the server the next time they're online.

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

3.3.27 Communication Feature 4: Comment on Project Use Case Description

Actors: User, sometimes also a Project Admin

Summary: Communicate more important info about a project

Purpose: Allow users to record and semi-permanently attach messages to be displayed alongside a project

Preconditions: User is signed in and has joined the project

Steps:

1. In a section of the window separate from temporary chat, the user writes a comment and presses Post
2. System sends that message to the project server, which attaches it to the project. The message is then displayed with previous comments in the post.
3. Other users may read and/or respond to the message at their leisure

Alternative 1: A project administrator may remove the post.

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

3.3.28 Communication Feature 4: Comment on Project Use Case Description

Actors: User or Admin

Summary: Clean up when a user leaves a project chat

Purpose: Close the window and remove the user from the list of active users in the project chat so they don't receive more messages

Preconditions: User is signed in and has joined the project chat

Steps:

1. User clicks "close" on the project chat window
2. System minimizes the window, and removes the user from the list of active users in the project chat

Alternatives: Step one is skipped if one of the following happen:


1. The user closes the entire project or program windows
2. The user is idle for too long
3. An administrator removes them from the project or project chat

Relevant Classes:

- User
 - TextChat
 - ChatDisplay
 - Message
-

3.3.29 Project Browsing Feature 2: Use Case Description 2

*For each feature, you should either provide a Use Case Description **or** a Non-task feature description, whichever is more appropriate.*


3.3.30 Use Case Diagram 4: User Preferences

3.3.31 User Preferences Feature 1: Use Case Description 1

*For each feature, you should either provide a Use Case Description **or** a Non-task feature description, whichever is more appropriate.*

3.3.32 User Preferences Feature 2: Use Case Description 2

*For each feature, you should either provide a Use Case Description **or** a Non-task feature description, whichever is more appropriate.*

3.3.33 Use Case Diagram 5: Project Management

Use case descriptions were roughly based upon cases from HW2, Team 4. sass8427 worked on the original use cases in this section.

Traceability: Relevant classes are found in **Project Management** section and include *User* and *Project*. For the *User* class, methods and fields from all class diagrams will be used.

3.3.34 Project Management Feature 1: Compile and Execute Project Use Case Description (dani2918)

Actors: User

Goals: Compile and execute active project

Pre-conditions: Actor is logged in, navigated to desired project.

Summary: User compiles a project and the project executes.


Related use cases:

Steps:

1. User clicks “Compile”
2. System displays results of compilation
3. System executes compiled project.

Alternatives: Compilation fails.

Post-conditions: None.

3.3.35 Project Management Feature 1: Compile and Execute Project Sequence Diagram (dani2918)

3.3.36 Project Management Feature 2: Create project Use Case Description(dani2918)

Actors: User

Goals: Create a new project.

Pre-conditions: Actor is logged in.

Summary: User creates a new project with a description and includes any desired files.

Related use cases: Import file


Steps:

1. User clicks "New Project."
2. User gives project a title.
3. User adds an applicable description.
4. User imports any files by clicking "Import."
5. User clicks "Create".
6. System imports files and instantiates project.

Alternatives: None.

Post-conditions: None.

3.3.37 Project Management Feature 2: Create project Sequence Diagram(dani2918)



3.3.38 Project Management Feature 3: Delete Project Use Case Description (dani2918)

Actors: Project Administrator, sQuire Administrator.

Goals: Remove project from sQuire sever.

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor chooses to delete or remove an irrelevant or inappropriate project.

Related use cases: Create project


Steps:

1. Actor clicks “Delete” icon on active project.
2. Delete dialog opens.
3. Actor presses “Delete”.
4. Confirmation window is displayed.
5. Actor confirms or disregards deletion.
6. System notifies collaborators that project was deleted.

Alternatives: Actor clicks “Cancel.”

Post-conditions: None.

3.3.39 Project Management Feature 3: Delete Project Sequence Diagram (dani2918)



3.3.40 Project Management Feature 4: Request to Join Project Use Case Description (dani2918)

Actors: User

Goals: Join an existing project.

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor sends a request to join as a collaborator on a project

Related use cases: Manage request to join project

Steps:

1. Actor clicks “Join project.”
2. Notification is sent to project administrator for review.

Alternatives: None.

Post-conditions: None.

3.3.41 Project Management Feature 5: Manage Request to Join Project Use Case Description (dani2918)

Actors: Project Administrator

Goals: Approve .

Pre-conditions: Actor is logged in, viewing desired project.

Summary: Actor approves/rejects a user who has requested to join as a collaborator on a project.

Related use cases: Request to join project


Steps:

1. Actor clicks “Review join requests.”
2. Actor reviews information about potential collaborator.
3. Actor clicks “Approve User” to approve a collaborator or “Reject user” to reject a collaborator.
4. System notifies user that they have been approved/rejected.

Alternatives: None.

Post-conditions: None.

3.3.42 Project Management Feature 4/5: Request/Manage Request to Join Project Sequence Diagram (dani2918)



3.3.43 Project Management Feature 6: Leave Project Use Case Description (dani2918)

Actors: User

Goals: Remove actor as a collaborator from project.

Pre-conditions: logged in, viewing desired project, collaborator on desired project, not project owner.

Summary: A member of a project leaves said project, leaving the project intact.

Related use cases: Delete project


Steps:

1. User clicks "Leave Project".
2. System prompts user to confirm decision.
3. User clicks "Confirm".
4. User is removed from project member list.

Alternatives: User clicks "Cancel" at step 4.

Post-conditions: None.

3.3.44 Project Management Feature 6: Leave Project Sequence Diagram (dani2918)



3.3.45 Project Management Feature 7: Invite to Project Use Case Description (dani2918)

Actors: Project Administrator, Authorized Project Collaborator (User).

Goals: Invite user(s) to collaborate on project

Pre-conditions: Actor is viewing project which he or she created, is logged in

Summary: A project administrator requests help from a user on a project. The sQuire system facilitates the invitation process

Related use cases: Respond to project invite

Steps:

1. Actor clicks "Invite User."
2. Actor enters the username(s) of the user(s) to be invited to the project.
3. Actor enters any message to the user(s) in a text box.
4. Actor clicks "Send invite."
5. System sends notification of invite to user(s).

Alternatives: Actor clicks "Cancel." **Post-conditions:** None.

3.3.46 Project Management Feature 8: Respond to Project Invite Use Case Diagram (dani2918)

Actors: User

Goals: Actor responds to an invitation to a project.

Pre-conditions: Actor is signed in, viewing invitation.

Summary: Actor receives notification that he or she has been invited to a project and either accepts the invitation or declines it.


Related use cases: Invite to project


Steps:

1. Actor clicks "Respond to Invitation."
2. Actor clicks "Accept" or "Reject."
3. Actor types any message to invitation-sender in text box.
4. Actor clicks "Confirm."

Alternatives: Actor clicks "Cancel."

Post-conditions: Actor becomes collaborator on project if invitation was accepted.

3.3.47 Project Management Feature 7/8: Invite/Respond to Project Invite Sequence Diagram (dani2918)

3.3.48 Use Case Diagram 6: File Editing

3.3.49 File Editing Feature 1: View Line Numbers Use Case Description

Name: View Line Numbers

Category: File Editing

Actor: User

Summary: Allows the user to view line numbers to the left of the document.

Purpose: Makes it easier to communicate position in code. It is also a useful metric to have.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Line Numbers* option.
4. System displays line numbers to the left of the document.

Relevant Classes:

1. **TextOperation**
-

3.3.50 File Editing Feature 1: View Line Numbers Sequence Diagram

3.3.51 File Editing Feature 2: View References Use Case Description

Name: View References

Category: File Editing

Actor: User

Summary: Allows the user to view the number of references to a given function.

Purpose: It is useful to know the number of references to a given function for optimization and debugging purposes.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A **code** file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View References* option.
4. System displays the number of references above each method declaration.

Relevant Classes:

1. **ColabFile**
 2. **LineHistory**
 3. **Project**
-

3.3.52 File Editing Feature 2: View References Sequence Diagram

3.3.53 File Editing Feature 3: View Dates Use Case Description

Name: View Dates

Category: File Editing

Actor: User

Summary: Allows the user to view the last date that each line of a document was edited.

Purpose: This provides a useful metric for how up-to-date parts of the document are.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has view permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Dates* option.
4. System displays the last date that each line of a document was edited.

Relevant Classes:

1. **LineHistory**
 2. **FileLineHistory**
-

3.3.54 File Editing Feature 3: View Dates Sequence Diagram

3.3.55 File Editing Feature 4: View Authors Use Case Description

Name: View Authors

Category: File Editing

Actor: User

Summary: Allows the user to view the last author that edited each of line of the document.

Purpose: This is an accountability tool allowing other users to identify who is responsible for a change to a document.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has read permission.
4. A file is open.

Steps:

1. User selects the *View* menu option.
2. System displays a drop-down with various options.
3. User selects the *View Authors* option.
4. System displays the name of the last editor of each line of the document.

Relevant Classes:

1. **FileLineHistory**
 2. **LineHistory**
-

3.3.56 File Editing Feature 4: View Author Sequence Diagram

3.3.57 File Editing Feature 5: Format Document Use Case Description

Name: Format Document

Category: File Editing

Actor: User

Summary: Allows the user to format the document to a specified format

Purpose: An easy tool for making sweeping changes to a large part of a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.
5. The document has formatting options set.

Steps:

1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Format Document* option.
4. System formats the current document to the formatting settings currently set.

Alternatives:

1. If no formatting settings are currently set, display a dialog box after step 3 and give the option for the user to do so now.

Relevant Classes:

1. **TextOperation**
-

3.3.58 File Editing Feature 6: Find/Replace Use Case Description

Name: Find/Replace

Category: File Editing

Actor: User

Summary: Allows the user to find and/or replace phrases.

Purpose: This is a powerful tool that allows a user to make safer, quicker, and more efficient changes to a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.

Steps:


1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Find/Replace* option.
4. System displays a small form in an unobtrusive location.
5. User enter the phrase to find and selects find.
6. System highlights and focuses on the first occurrence of the phrase and all highlights all other occurrences.

Alternatives:

1. User selects option to replace in step 5 and enters a phrase with which to replace the found occurrences of the searched phrase. The system replaces each occurrence.

Relevant Classes:

1. **Project**
-

3.3.59 File Editing Feature 6: Find Sequence Diagram

3.3.60 File Editing Feature 7: Comment Section Use Case Description

Name: Comment Section

Category: File Editing

Actor: User

Summary: Allows the user to comment out a part of a document.

Purpose: A useful and quick way to disable a large part of a document.

Preconditions:

1. Must be registered.
2. Must be logged in.
3. A file is open.
4. User has read/write permission.
5. Current open document supports commenting.

Steps:


1. User selects the *Edit* menu option.
2. System displays a drop-down with various options.
3. User selects the *Comment Section* option.
4. System comments the selected area.

Alternatives:

1. If document does not support commenting, display a dialog box telling the user.

Relevant Classes:

1. **TextOperation**
-

3.3.61 File Editing Feature 7: Comment Section Sequence Diagram

3.3.62 File Editing Feature 8: Display Typing User Use Case Description

Name: Display Typing User

Category: File Editing

Actors:

1. User
2. Other Users

Summary: As the user types, the system displays their name, their typing, and their caret, in a different color, to other users.

Purpose: Differentiate who is typing what.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A file is open.
5. Other users have the same document open.

Steps:

1. User begins typing.
2. System displays the user's typing, the user's name, and the user's caret, in a different color, to Other Users.
3. Other Users see User typing, his username, and his caret, in a different color.

Relevant Classes:

1. ColabFile
 2. Cursor
 3. Project
-

3.3.63 File Editing Feature 8: Display Typing User Sequence Diagram

Author: Eric Gentile-Quant
Reviewed by: Everyone

3.3.64 File Editing Feature 9: Display Syntax Errors Use Case Description

Name: Display Syntax Errors

Category: File Editing

Actor: User

Summary: As the user types code, the editor will underline syntax errors with a red line.

Purpose: Aids the user is writing correct code.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A supported code file is open.

Steps:

1. User begins typing.
2. System displays any syntax errors as a red underline under the incorrect section.

Relevant Classes:

1. **ColabFile**
 2. **Project**
-

3.3.65 File Editing Feature 9: Display Syntax Errors Sequence Diagram

Author: Eric Gentile-Quant
Reviewed by: Everyone

3.3.66 File Editing Feature 10: Display Syntax Highlighting Use Case Description

Name: Display Syntax Highlighting

Category: File Editing

Actor: User

Summary: As the user types code, the editor will change font color for different code structures and keywords.

Purpose: Aids the user is writing code and identifying key code parts.

Preconditions:


1. Must be registered.
2. Must be logged in.
3. User has read/write permission.
4. A supported code file is open.

Steps:

1. User begins typing.
2. System automatically colors special code structures and keywords.


Relevant Classes:

1. **Project**
-

3.3.67 File Editing Feature 10: Display Syntax Highlighting Sequence Diagram

Author: Eric Gentile-Quant
Reviewed by: Everyone

3.3.68 Use Case Diagram 7: File Management



3.3.69 File Management Feature 1: Open File Use Case Description

Actors: User

Summary: The user selects a file to open based on a filename, which is then opened by the software.

Purpose: To open a file in the program.

Preconditions: The desired file must already exist.


Steps:

1. User clicks Open File button.
2. System prompts the user to select file to open from a list of existing files.
3. User selects desired file and clicks Submit button.
4. System opens selected file and displays it.

Alternative 1: The User decides they don't want to open a file and presses Cancel at step 3.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

3.3.70 File Management Feature 1: Open File Sequence Diagram

Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

3.3.71 File Management Feature 2: Close File Use Case Description

Actors: User

Summary: The user chooses to close the file they are working on.

Purpose: To close a file in the program.

Preconditions: The desired file must already exist, and be already opened by the User.


Steps:

1. User clicks Close File button.
2. System closes the file and updates the Controller's status on the file being open.

Alternative 1: The file cannot be closed for some reason.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

3.3.72 File Management Feature 2: Close File Sequence Diagram

Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

3.3.73 File Management Feature 3: Save File Use Case Description

Actors: User

Summary: The user chooses to save the file they are currently working on.

Purpose: To save a file in the program.

Preconditions: The desired file must already exist, and be opened by the user.


Steps:

1. User clicks Save File button.
2. System prompts the user to choose a name to save the file under.
3. User selects desired name and clicks Submit button.
4. System saves selected file and allows the user to keep working.

Alternative 1: The User decides they don't want to save the file and presses Cancel at step 3.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

3.3.74 File Management Feature 3: Save File Sequence Diagram

Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

3.3.75 File Management Feature 4: Add File Use Case Description

Actors: User

Summary: The user chooses to add a file to the directory.

Purpose: To add a file to a directory.

Preconditions: The desired file must already exist.

Steps:


1. User clicks Add File button.
2. System prompts the user to choose a file to add to a directory..
3. User selects desired file and clicks Submit button.
4. System prompts the user to choose a directory to add the file to.
5. User selects directory to add the file to and click Submit button.
6. System adds the file to the selected directory and lets the user return to their work.

Alternative 1: The User decides they don't want to add the file and presses Cancel at step 3.


Alternative 2: The User decides, after they chose a file, not to add it to a directory and clicks Cancel at step 5.

Relevant Classes:

- **User** in **S3.4.5**
 - **UI** to be added.
 - **Project** to be added.
 - **File** to be added.
-

3.3.76 File Management Feature 4: Add File Sequence Diagram

Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

3.3.77 Use Case Diagram 8: Project User Management

3.3.78 Project User Management Feature 1: Add User to Project Use Case Description

Actors: User

Goals: Add a user to project

Pre-conditions: User has admin rights to project.

Summary: User adds a user to a project

Related use cases: Kick User

Steps:

1. User clicks add user button.
2. System prompts user to enter the username of the user they wish to invite.
3. User enters username.
4. System adds the specified user to the project, and notifies them.


Alternatives:

1. User enters an invalid username, in which case an error is reported

Post-conditions: None.

Relevant Classes:

- User
 - Project
 - UserManager
 - Permissions
 - Email
-

3.3.79 Project User Management Feature 1: Add User Sequence Diagram

Author: Brandon Ratcliff
Reviewed by: Entire Group

3.3.80 Project User Management Feature 2: Kick User Use Case Description

Actors: User

Goals: Kick a user from project.

Pre-conditions: User is an admin, and the user they wish to kick is a member of the project.

Summary: User removes a selected user from the Project

Related use cases: Add User


Steps:

1. User clicks Kick User button.
2. System displays list of Members of the project.
3. User selects one or more other users from the list and presses Remove.
4. System prompts User for verification.
5. User presses Confirm.
6. System removes the selected users from the project.

Alternatives: None.

Post-conditions: None.

- User
 - Project
 - UserManager
 - Permissions
-

3.3.81 Project User Management Feature 2: Kick User Sequence Diagram

Author: Brandon Ratcliff
Reviewed by: Entire Group

3.3.82 Project User Management Feature 3: Set User Permissions Use Case Description

Actors: User

Goals: Modify a user's permissions.

Pre-conditions: User has admin permissions, and the user whose permissions they wish to change is a member of the project

Summary: User modifies another User's permissions to the project.

Related use cases: None.


Steps:

1. User clicks Permissions Management button.
2. System displays permissions management window.
3. User selects the user whose permissions they want to edit.
4. System displays a list of toggles for the user's permissions.
5. User makes changes to the user's permissions.
6. System modifies the target User's permissions.

Alternatives: None.

Post-conditions: None.


- User
 - Project
 - UserManager
 - Permissions
-

3.3.83 Project User Management Feature 3: Set User Permissions Sequence Diagram

*For each feature, you should either provide a Use Case Description **or** a Non-task feature description, whichever is more appropriate.*

3.4 CLASS DIAGRAMS

3.4.1 Class Diagram 1: File Management



Author: Domn Werner
 Reviewers: Entire Group

3.4.2 Class Diagram Description 1: File Management Description


Interfaces:

- The *Observer* interface requires its implementers to implement a method with the following signature: **void Observe(T)**. The purpose of this method is for classes to implement ways in which to observe other classes. We foresee the **FileController** class implementing this interface in order to observe changes in **CollabFile** objects.
- The *Runnable* interface requires its implementers to implement a method with the following signature: **void Run(Task)** where **Task** is a method that can be run in a separate thread. The **FileController** class will implement this interface in order to execute its IO operations in a separate thread. This will keep the UI thread free and our program responsive.
- The *Serializable* interface requires its implementers to implement the **void Serialize<T>()** method and serializes objects of type **T**. It also requires the implementation of the **T Deserialize<T>()** method which will operate on a serialized string object and return an instantiated object of type **T**.
- The *Observable* interface requires its implementers to have a list of observers and a method to notify its observers of changes to itself. The purpose of this implementation is to communicate with the **FileController** object and notify it when a **CollabFile** changes.
- The *Downloadable* interface requires its implementers to implement a method with the following signature: **int Download()**. The purpose of this method is for classes to implement ways in which their objects can be downloaded. The **int** return type will be used as a status code. We foresee this interface being used with the **Project** and **CollabFile** classes, as the diagram shows, allowing users to download files or projects with the **Download()** method.

Classes:

- The **FileController** class will manage the **CollabFile** objects in the **Project** class. It will do so by storing a list of files and a dictionary of its methods that can be run in a separate thread. Its methods all deal with managing files. It will implement the *Observer* and *Runnable* interfaces. Refer to the interfaces list above to see the details of such implementations.
- The **Project** class represents the entire project that users work on. This includes users, files, permissions, etc. For the sake of simplicity, this diagram only lists properties and methods relating to file editing. Objects of type **Project** will have a **FileController** and a root **CollabFile** as per a file-tree structure. The **Project** class must also implement the *Downloadable* interface in order to specify how projects are downloaded. Refer to the interfaces list above to see the details of this implementation.
- the **CollabFile** class represents a file in a **Project**. It extends the **File** class for the purposes of allowing collaborative editing, among other project functions. It implements the *Serializable* interface to allow its information to be transported over the internet in the best possible format. This requires the implementation of the **void Serialize<T>()** and **T Deserialize<SerializedString>()** methods which will handle serialization and deserialization. This class also implements the *Observable* interface which will specify how it communicates with the **FileController** class in order to notify of relevant changes to **CollabFile** objects. This requires the implementation of a list of observers and a method to notify observers. Lastly, it implements the *Downloadable* interface which will specify how **CollabFile** objects are to be downloaded. Refer to the interfaces list above for more details of such implementations.

3.4.3 Class Diagram 2: File Editing



Author: Brandon Ratcliff
Reviewed by: Everyone

3.4.4 Class Diagram Description 2: File Editing Description

Editor:

- The *CollabFile* class is a class used in many of the other class diagrams in this project. It is the general class containing all the methods and variables for managing a file. It contains a **FileLineHistory** object. CollabFile has a list of **Cursor** objects, one for every user editing the file..
- The *User* class is a class used in many of the class diagrams. It represents a single user of the sQuire program.
- The *TimeStamp* class is used in several other places. It represents a date and time.
- The *FileLineHistory* class is a class that keeps track of who last edited every line in the file. This will be used to display the changes inside the editor. It does this by having an array (one element per line in the file) of **LineHistory** objects.
- The *LineHistory* class is contains the information used by the **FileLineHistory** class. It contains a **User** the last one to edit a particular line and a **Timestamp** (when the line was last edited). More fields can easily be added to this if it turns out there is more information we'd like to keep track of on a line-by-line basis.
- The *EditorWidget* class is something that we will (hopefully) not write ourselves. It will be the editor widget we use for providing the code editor. Preliminary research found **RSyntaxTextArea** (<https://github.com/bobbylight/RSyntaxTextArea>). This looks like a good fit because it has syntax highlighting, auto completion, code analysis, and of course, support from java. It also has a simple plugin architecture, so it looks like it would be easy to extend to our needs. More research needs to be done to figure out the exact class structure for this.
- The *Cursor* class is made up of a **User** and a position within a file- everything that is needed to display a users cursor inside the editor.

OperationalTransform:


I organized this one into a separate package because that's how I'm pretty sure we'll write it. The OperationalTransform algorithm is a collaborative editing algorithm used to allow multiple people to edit the same document at the same time, and keep the documents in sync. Ideally, we would use a pre-built library for this, as the algorithm is quite complex and there are lots of special cases, but I was unable to find one written in Java. Our best bet will probably be to port an existing library in another language. The clearest, best documented implementation I found was OT.js (<https://github.com/Operational-Transformation/ot.js/>). The following classes are the main data structures implemented by this version of Operational Transformation.

- The *TextOperation* class represents a sequence of **Operation** objects, or changes. The TextOperation can then be applied to a string, or transformed with another TextOperation (from another client) in order account for changes that occurred simultaneously. See the Operational Transformation algorithm for more details.
- The *Operation* class represents a specific operation. This contains an **OperationType**, a integer front, which specifies the number of characters before the change, a string s, which contains the actual character changed (ex, inserted or deleted). And then an integer back, which contains the number of characters until the end of the document.
- The *OperationType* Enum is used to specify what type of operation a **Operation** is. Type can be either an INSERT, when character(s) are inserted to a document, DELETE, when character(s) are deleted from a document, or RETAIN, used to shift other operations.

- the *Server* class is a class that will be running on the server to sync changes between clients. It's job it to listen for **TextOperations** from all connected clients, and when it receives one, broadcast that change to all connected clients.

3.4.5 Class Diagram 3: Authentication

Authentication




Authored by: Joel Doumit (doum6708)
Reviewed by: Team I.C.Y

3.4.6 Class Diagram Description 3: Authentication Description

Classes:

- The **User** class represents the main user of the entire program. It details the basic information of each individual user, and allows each user the ability to create an account, to log into an existing account, and once logged in, to log out of the user account. It also allows a user to change his/her password, which involves the other classes.
- The **Email** class allows the program to send emails to Users who have signed up, or are signing up. It stores User information as a series of strings to be used by the **send()** function, which sends validation codes to Users' email addresses.
- The **Validator** class will run validation functions when called to do so by the User. Upon a User indicating they would like to change/have forgotten their password, it generates a validation code for that particular User, which it then stores in a dictionary. This validation code is sent to Users by means of the **send()** function denoted earlier.


3.4.7 Class Diagram 4: User Preferences

3.4.8 Class Diagram Description 4: User Preferences Description

Classes:

- **User:** Represents the human user of the program. It will hold the user's profile information so that it can be validated later.
- **Preferences:** Holds all the user's account preferences. This includes profile picture, chat font, chat color, ect.
- **ModifyPref:** Allows the user to modify his or her's preferences.
- **Authentication:** Authenticates the user's username and password to allow access to make changes on their account.

3.4.9 Class Diagram 5: Communication




Authored By: Max Welch
Peer Reviewed By: Team I.C.Y.

3.4.10 Class Diagram Description 5: Communication Description

Classes:

- **TextChat:** The master class to manage the messages, users, and display of the system.
- **ChatDisplay:** Displays relevant information including most recent 20 messages and active users
- **User:** Users interacting with the chat system.
- **Message:** Messages sent by users to TextChat, contain a string, timestamp, and sender/receiver data.
- **Timestamp:** Recorded time of when message was sent.

3.4.11 Class Diagram 6: Project Browsing



Authored by: Matthew Daniel dani2918
 Reviewed by: Entire Group

3.4.12 Class Diagram Description 6: Project Browsing

Enums:

- The *Rating* enum produces a value based upon the user's desired rating of another user or a project.


Interfaces:

- The *Receives Feedback* interface requires its implementers to implement two methods: **int VoteOnUser(User)**, which returns a value based on a user's rating, and **string Comment(User)**, which leaves feedback in the form of a comment.

Classes:

- The **User** class will be the class, shared across many of the class diagrams, that stores information about a user. The User class will have not only the methods and fields shown in this diagram, but a concatenation of the ones shown here and all other methods and fields from the other diagrams. Here, the User class implements the ReceivesFeedback interface so that other users may leave comments/reviews of a User object, and so that they may receive an accompanying rating from one to five stars. In relation to browsing projects, a User is the agent who searches a ProjectBrowser object and works on a Project object.
- The **Project** class will also have the methods and fields of other class diagrams, similar to the User class above. Here, the Project class implements the ReceivesFeedback interface so that users may leave comments/reviews on projects, as well as vote up or down on projects that they come across. Projects are displayed in the ProjectBrowser class and worked on by users.
- The **ProjectBrowser** class contains a search-able list of zero or more projects tailored to a user's search. Users browse the list in order to find projects of interest.

3.4.13 Class Diagram 7: Project User Management




Written by: Brian Cartwright
Reviewed by: The whole team

3.4.14 Class Diagram Description 7: Project User Management Description

Classes:

- The **User** class contains the profiles of everyone who uses sQuire, and identifies anyone who tries to access a board.
- The **Project** class contains all of the information pertinent to an individual project, including one UserManager, which the client uses to control what kind of access each user has to that specific project.
- The **UserManager** class is referenced to check if a user has permission to read, modify, or run a project, or invite, ban, or change the permissions of another user. It does this by updating and checking against a HashMap of Permissions indexed by User. It records the User profile of the project creator to prevent the creator being demoted by another admin. It also contains a set of Permissions to use by default, before users are manually added to the project. The functions AddUser, KickUser, and SetPerms all modify the permissions HashMap after checking against it to make sure the active user has the authority to change the permissions of the target user.
- The **HashMap** class, in this case, functions as a permissions lookup table. It's indexed by User, and for each User in it there's one set of Permissions that it returns.
- The **Permissions** class is a set of bools that store whether each User has permission (within the instance's parent project) to read, write, execute the project, invite users, and/or modify the permissions of other users regarding the project.

3.4.15 Class Diagram 8: Project Management



4 REQUIREMENTS TRACEABILITY

This section shall contain traceability information from each system requirement in this specification to the system (or subsystem, if applicable) requirements it addresses. A tabular form is preferred, but not mandatory.

Feature Name	Req No.	Requirement Description	Priority	SDD	Alpha Release		Beta Release	
					Test Case(s)	Test Res.	Test Case(s)	Test Res.
	1.1							
	1.2							
	...							
	1.[n]							
	2.1							
	2.2							
	...							
	2.[n]							
	3.1							
	3.2							
	...							
	3.[n]							
...	...							
	[m].1							
	[m].2							
	...							
	[m.n]							

Priorities are: **M**andatory, **L**ow, **H**igh

SDD link is version and page number or function name.

Test cases and results are file names and **P**ass/**F**ail or % passing.

5 APPENDIX A. [insert name here]

Include copies of specifications, mockups, prototypes, etc. supplied or derived from the customer. Appendices are labeled A, B, . . . n. Reference each appendix as appropriate in the text of the document.

[insert appendix A here]

6 APPENDIX B. [insert name here]

[insert appendix B here]