


CS 4110

Programming Languages & Logics

Lecture 21
Advanced Types

19 October 2016



Announcements

- HW #5 due today at 11:59pm
- HW #6 out

Review

So far we've seen how to develop a type system for λ -calculus, and have developed mathematical tools for proving type soundness.

Today we'll extend our type system with a number of other additional features commonly found in real-world languages, including products, sums, references, and exceptions.

Products

Syntax

$$e ::= \dots \mid (e_1, e_2) \mid \#1\ e \mid \#2\ e$$
$$v ::= \dots \mid (v_1, v_2)$$

Products

Syntax

$$e ::= \dots \mid (e_1, e_2) \mid \#1\ e \mid \#2\ e$$
$$v ::= \dots \mid (v_1, v_2)$$

Semantics

$$E ::= \dots \mid (E, e) \mid (v, E) \mid \#1\ E \mid \#2\ E$$
$$\frac{}{\#1\ (v_1, v_2) \rightarrow v_1}$$
$$\frac{}{\#2\ (v_1, v_2) \rightarrow v_2}$$

Product Types

$$\tau_1 \times \tau_2$$

Product Types

$$\tau_1 \times \tau_2$$

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma \vdash e_2 : \tau_2}{\Gamma \vdash (e_1, e_2) : \tau_1 \times \tau_2}$$

Product Types

$$\tau_1 \times \tau_2$$

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma \vdash e_2 : \tau_2}{\Gamma \vdash (e_1, e_2) : \tau_1 \times \tau_2}$$

$$\frac{\Gamma \vdash e : \tau_1 \times \tau_2}{\Gamma \vdash \#1 e : \tau_1}$$

Product Types

$$\tau_1 \times \tau_2$$

$$\frac{\Gamma \vdash e_1 : \tau_1 \quad \Gamma \vdash e_2 : \tau_2}{\Gamma \vdash (e_1, e_2) : \tau_1 \times \tau_2}$$

$$\frac{\Gamma \vdash e : \tau_1 \times \tau_2}{\Gamma \vdash \#1 e : \tau_1}$$

$$\frac{\Gamma \vdash e : \tau_1 \times \tau_2}{\Gamma \vdash \#2 e : \tau_2}$$

Note the similarities to the natural deduction rules for conjunction.

Sums

Syntax

$$e ::= \dots \mid \text{inl}_{\tau_1 + \tau_2} e \mid \text{inr}_{\tau_1 + \tau_2} e \mid (\text{case } e_1 \text{ of } e_2 \mid e_3)$$
$$v ::= \dots \mid \text{inl}_{\tau_1 + \tau_2} v \mid \text{inr}_{\tau_1 + \tau_2} v$$

Sums

Syntax

$$\begin{aligned} e &::= \dots \mid \text{inl}_{\tau_1 + \tau_2} e \mid \text{inr}_{\tau_1 + \tau_2} e \mid (\text{case } e_1 \text{ of } e_2 \mid e_3) \\ v &::= \dots \mid \text{inl}_{\tau_1 + \tau_2} v \mid \text{inr}_{\tau_1 + \tau_2} v \end{aligned}$$

Semantics

$$E ::= \dots \mid \text{inl}_{\tau_1 + \tau_2} E \mid \text{inr}_{\tau_1 + \tau_2} E \mid (\text{case } E \text{ of } e_2 \mid e_3)$$

$$\frac{}{\text{case inl}_{\tau_1 + \tau_2} v \text{ of } e_2 \mid e_3 \rightarrow e_2 v}$$

$$\frac{}{\text{case inr}_{\tau_1 + \tau_2} v \text{ of } e_2 \mid e_3 \rightarrow e_3 v}$$

Sum Types

$$\tau ::= \cdots \mid \tau_1 + \tau_2$$

Sum Types

$$\tau ::= \cdots \mid \tau_1 + \tau_2$$

$$\frac{\Gamma \vdash e : \tau_1}{\Gamma \vdash \text{inl}_{\tau_1 + \tau_2} e : \tau_1 + \tau_2}$$

Sum Types

$$\tau ::= \cdots \mid \tau_1 + \tau_2$$

$$\frac{\Gamma \vdash e : \tau_1}{\Gamma \vdash \text{inl}_{\tau_1 + \tau_2} e : \tau_1 + \tau_2}$$

$$\frac{\Gamma \vdash e : \tau_2}{\Gamma \vdash \text{inr}_{\tau_1 + \tau_2} e : \tau_1 + \tau_2}$$

Sum Types

$$\tau ::= \cdots \mid \tau_1 + \tau_2$$

$$\frac{\Gamma \vdash e : \tau_1}{\Gamma \vdash \text{inl}_{\tau_1 + \tau_2} e : \tau_1 + \tau_2}$$

$$\frac{\Gamma \vdash e : \tau_2}{\Gamma \vdash \text{inr}_{\tau_1 + \tau_2} e : \tau_1 + \tau_2}$$

$$\frac{\Gamma \vdash e : \tau_1 + \tau_2 \quad \Gamma \vdash e_1 : \tau_1 \rightarrow \tau \quad \Gamma \vdash e_2 : \tau_2 \rightarrow \tau}{\Gamma \vdash \text{case } e \text{ of } e_1 \mid e_2 : \tau}$$

Example

```
let  $f = \lambda a:\mathbf{int} + (\mathbf{int} \rightarrow \mathbf{int}). \text{case } a \text{ of } (\lambda y. y + 1) \mid (\lambda g. g \ 35) \text{ in}$   
let  $h = \lambda x:\mathbf{int}. x + 7 \text{ in}$   
 $f(\text{inr}_{\mathbf{int} + (\mathbf{int} \rightarrow \mathbf{int})} h)$ 
```


Example

let $f = \lambda a:\mathbf{int} + (\mathbf{int} \rightarrow \mathbf{int}). \text{case } a \text{ of } (\lambda y. y + 1) \mid (\lambda g. g \ 35) \text{ in}$
let $h = \lambda x:\mathbf{int}. x + 7 \text{ in}$
 $f(\text{inr}_{\mathbf{int} + (\mathbf{int} \rightarrow \mathbf{int})} h)$

Question: what does this evaluate to?

References

Syntax

$$e ::= \dots \mid \text{ref } e \mid !e \mid e_1 := e_2 \mid \ell$$
$$v ::= \dots \mid \ell$$

References

Syntax

$$\begin{aligned} e &::= \dots \mid \text{ref } e \mid !e \mid e_1 := e_2 \mid \ell \\ v &::= \dots \mid \ell \end{aligned}$$

Semantics

$$E ::= \dots \mid \text{ref } E \mid !E \mid E := e \mid v := E$$

$$\frac{\ell \notin \text{dom}(\sigma)}{\langle \sigma, \text{ref } v \rangle \rightarrow \langle \sigma[\ell \mapsto v], \ell \rangle} \qquad \frac{\sigma(\ell) = v}{\langle \sigma, !\ell \rangle \rightarrow \langle \sigma, v \rangle}$$

$$\frac{}{\langle \sigma, \ell := v \rangle \rightarrow \langle \sigma[\ell \mapsto v], v \rangle}$$

Reference Types

$$\tau ::= \dots \mid \tau \textbf{ref}$$

Reference Types

$$\tau ::= \dots \mid \tau \mathbf{ref}$$

$$\frac{\Gamma \vdash e : \tau}{\Gamma \vdash \mathbf{ref} \, e : \tau \mathbf{ref}}$$

Reference Types

$$\tau ::= \dots \mid \tau \mathbf{ref}$$

$$\frac{\Gamma \vdash e : \tau}{\Gamma \vdash \mathbf{ref} \, e : \tau \mathbf{ref}}$$

$$\frac{\Gamma \vdash e : \tau \mathbf{ref}}{\Gamma \vdash !e : \tau}$$

Reference Types

$$\tau ::= \dots \mid \tau \mathbf{ref}$$

$$\frac{\Gamma \vdash e : \tau}{\Gamma \vdash \mathbf{ref} \, e : \tau \mathbf{ref}}$$

$$\frac{\Gamma \vdash e : \tau \mathbf{ref}}{\Gamma \vdash !e : \tau}$$

$$\frac{\Gamma \vdash e_1 : \tau \mathbf{ref} \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash e_1 := e_2 : \tau}$$

Question

Is this type system sound?

Question

Is this type system sound?

Well... what is the type of a location ℓ ?

Question

Is this type system sound?

Well... what is the type of a location ℓ ?

Oops!

Store Typings

Let Σ range over maps from locations to types

Store Typings

Let Σ range over maps from locations to types

$$\frac{\Gamma, \Sigma \vdash e : \tau}{\Gamma, \Sigma \vdash \text{ref } e : \tau \textbf{ref}}$$

Store Typings

Let Σ range over maps from locations to types

$$\frac{\Gamma, \Sigma \vdash e : \tau}{\Gamma, \Sigma \vdash \text{ref } e : \tau \textbf{ref}}$$

$$\frac{\Gamma, \Sigma \vdash e : \tau \textbf{ref}}{\Gamma, \Sigma \vdash !e : \tau}$$

Store Typings

Let Σ range over maps from locations to types

$$\frac{\Gamma, \Sigma \vdash e : \tau}{\Gamma, \Sigma \vdash \text{ref } e : \tau \textbf{ref}}$$

$$\frac{\Gamma, \Sigma \vdash e : \tau \textbf{ref}}{\Gamma, \Sigma \vdash !e : \tau}$$

$$\frac{\Gamma, \Sigma \vdash e_1 : \tau \textbf{ref} \quad \Gamma, \Sigma \vdash e_2 : \tau}{\Gamma, \Sigma \vdash e_1 := e_2 : \tau}$$

Store Typings

Let Σ range over maps from locations to types

$$\frac{\Gamma, \Sigma \vdash e : \tau}{\Gamma, \Sigma \vdash \text{ref } e : \tau \textbf{ref}}$$

$$\frac{\Gamma, \Sigma \vdash e : \tau \textbf{ref}}{\Gamma, \Sigma \vdash !e : \tau}$$

$$\frac{\Gamma, \Sigma \vdash e_1 : \tau \textbf{ref} \quad \Gamma, \Sigma \vdash e_2 : \tau}{\Gamma, \Sigma \vdash e_1 := e_2 : \tau}$$

$$\frac{\Sigma(\ell) = \tau}{\Gamma, \Sigma \vdash \ell : \tau \textbf{ref}}$$

Reference Types Metatheory

Definition

Store σ is *well-typed* with respect to typing context Γ and store typing Σ , written $\Gamma, \Sigma \vdash \sigma$, if $\text{dom}(\sigma) = \text{dom}(\Sigma)$ and for all $\ell \in \text{dom}(\sigma)$ we have $\Gamma, \Sigma \vdash \sigma(\ell) : \Sigma(\ell)$.

Reference Types Metatheory

Definition

Store σ is *well-typed* with respect to typing context Γ and store typing Σ , written $\Gamma, \Sigma \vdash \sigma$, if $\text{dom}(\sigma) = \text{dom}(\Sigma)$ and for all $\ell \in \text{dom}(\sigma)$ we have $\Gamma, \Sigma \vdash \sigma(\ell) : \Sigma(\ell)$.

Theorem (Type soundness)

If $\cdot, \Sigma \vdash e : \tau$ and $\cdot, \Sigma \vdash \sigma$ and $\langle e, \sigma \rangle \rightarrow^* \langle e', \sigma' \rangle$ then either e' is a value, or there exists e'' and σ'' such that $\langle e', \sigma' \rangle \rightarrow \langle e'', \sigma'' \rangle$.

Reference Types Metatheory

Definition

Store σ is *well-typed* with respect to typing context Γ and store typing Σ , written $\Gamma, \Sigma \vdash \sigma$, if $\text{dom}(\sigma) = \text{dom}(\Sigma)$ and for all $\ell \in \text{dom}(\sigma)$ we have $\Gamma, \Sigma \vdash \sigma(\ell) : \Sigma(\ell)$.

Theorem (Type soundness)

If $\cdot, \Sigma \vdash e : \tau$ and $\cdot, \Sigma \vdash \sigma$ and $\langle e, \sigma \rangle \rightarrow^* \langle e', \sigma' \rangle$ then either e' is a value, or there exists e'' and σ'' such that $\langle e', \sigma' \rangle \rightarrow \langle e'', \sigma'' \rangle$.

Lemma (Preservation)

If $\Gamma, \Sigma \vdash e : \tau$ and $\Gamma, \Sigma \vdash \sigma$ and $\langle e, \sigma \rangle \rightarrow \langle e', \sigma' \rangle$ then there exists some $\Sigma' \supseteq \Sigma$ such that $\Gamma, \Sigma' \vdash e' : \tau$ and $\Gamma, \Sigma' \vdash \sigma'$.

Landin's Knot

It turns out that using references we (re)-gain the ability define arbitrary recursive functions!

Landin's Knot

It turns out that using references we (re)-gain the ability define arbitrary recursive functions!

```
let  $r = \text{ref } \lambda x. 0$  in  
 $r := \lambda x:\text{int}. \text{if } x = 0 \text{ then } 1 \text{ else } x \times !r(x - 1)$ 
```

Landin's Knot

It turns out that using references we (re)-gain the ability define arbitrary recursive functions!

```
let  $r = \text{ref } \lambda x. 0$  in  
 $r := \lambda x: \text{int}. \text{if } x = 0 \text{ then } 1 \text{ else } x \times !r(x - 1)$ 
```

This trick is called “Landin’s knot” after its creator.

Fixpoints

Syntax

$$e ::= \dots \mid \text{fix } e$$

Fixpoints

Syntax

$$e ::= \dots \mid \text{fix } e$$

Semantics

$$E ::= \dots \mid \text{fix } E$$

$$\overline{\text{fix } \lambda x:\tau. e \rightarrow e\{(\text{fix } \lambda x:\tau. e)/x\}}$$

Fixpoints

Syntax

$$e ::= \dots \mid \text{fix } e$$

Semantics

$$E ::= \dots \mid \text{fix } E$$

$$\frac{}{\text{fix } \lambda x:\tau. e \rightarrow e\{(\text{fix } \lambda x:\tau. e)/x\}}$$

The typing rule for fix is left as an exercise...

Fixpoint Examples

With `fix`, we can define `letrec $x:\tau = e_1$ in e_2` as syntactic sugar:

$$\text{letrec } x:\tau = e_1 \text{ in } e_2 \triangleq \text{let } x = \text{fix } \lambda x:\tau. e_1 \text{ in } e_2$$

Fixpoint Examples

With `fix`, we can define `letrec $x:\tau = e_1$ in e_2` as syntactic sugar:

$$\text{letrec } x:\tau = e_1 \text{ in } e_2 \triangleq \text{let } x = \text{fix } \lambda x:\tau. e_1 \text{ in } e_2$$

We can also take fixpoints at other types. For example, consider the following expression,

```
fix  $\lambda x: (\mathbf{int} \rightarrow \mathbf{int}) \times (\mathbf{int} \rightarrow \mathbf{int}).$   
  ( $\lambda n:\mathbf{int}. \text{if } n = 0 \text{ then true else } (\#2\ x)\ (n - 1),$   
   $\lambda n:\mathbf{int}. \text{if } n = 0 \text{ then false else } (\#1\ x)\ (n - 1))$ 
```

which defines a pair of mutually recursive functions; the first returns true if and only if its argument is even; the second returns true if and only if its argument is odd.

Exceptions

Syntax

$e ::= \dots \mathbf{error} \mid \mathbf{try} \ e \ \mathbf{with} \ e$

Exceptions

Syntax

$$e ::= \dots \mathbf{error} \mid \mathbf{try} \ e \ \mathbf{with} \ e$$

Semantics

$$E ::= \dots \mid \mathbf{try} \ E \ \mathbf{with} \ e$$
$$\frac{}{E[\mathbf{error}] \rightarrow \mathbf{error}}$$

Exceptions

Syntax

$$e ::= \dots \mathbf{error} \mid \mathbf{try} \ e \ \mathbf{with} \ e$$

Semantics

$$E ::= \dots \mid \mathbf{try} \ E \ \mathbf{with} \ e$$
$$\frac{}{E[\mathbf{error}] \rightarrow \mathbf{error}}$$
$$\frac{}{\mathbf{try} \ \mathbf{error} \ \mathbf{with} \ e \rightarrow e}$$

Exceptions

Syntax

$$e ::= \dots \mathbf{error} \mid \mathbf{try} \ e \ \mathbf{with} \ e$$

Semantics

$$E ::= \dots \mid \mathbf{try} \ E \ \mathbf{with} \ e$$
$$\frac{}{E[\mathbf{error}] \rightarrow \mathbf{error}}$$
$$\frac{}{\mathbf{try} \ \mathbf{error} \ \mathbf{with} \ e \rightarrow e}$$
$$\mathbf{try} \ v \ \mathbf{with} \ e \rightarrow v$$

Exception Types

We don't need to add any new types...

$$\overline{\Gamma \vdash \mathbf{error} : \tau}$$

$$\frac{\Gamma \vdash e_1 : \tau \quad \Gamma \vdash e_2 : \tau}{\Gamma \vdash \mathbf{try} \, e_1 \, \mathbf{with} \, e_2 : \tau}$$

Exception Metatheory

Lemma (Progress)

If $\vdash e : \tau$ then either

- *e is a value or*
- *e is **error** or*
- *there exists e' such that $e \rightarrow e'$.*

Exception Metatheory

Lemma (Progress)

If $\vdash e : \tau$ then either

- *e is a value or*
- *e is **error** or*
- *there exists e' such that $e \rightarrow e'$.*

Theorem (Soundness)

If $\vdash e : \tau$ and $e \rightarrow^ e'$ and $e' \not\vdash$ then either*

- *e is a value or*
- *e is **error***