

CS 4110

Programming Languages & Logics

Lecture 32 Shared-Memory Parallelism



IMP with Parallel Composition

Here's a simple model of shared-memory parallelism: let's extend IMP with a new a parallel composition command.

IMP with Parallel Composition

Here's a simple model of shared-memory parallelism: let's extend IMP with a new a parallel composition command.

$$\begin{aligned} a &::= x \mid n \mid a_1 + a_2 \\ b &::= \mathbf{true} \mid \mathbf{false} \mid a_1 < a_2 \\ c &::= \mathbf{skip} \mid x := a \mid c_1; c_2 \mid \mathbf{if } b \mathbf{ then } c_1 \mathbf{ else } c_2 \mid \mathbf{while } b \mathbf{ do } c \\ &\quad \mid c_1 \parallel c_2 \end{aligned}$$

Operational Semantics

And add small-step operational semantics rules for $c_1 \parallel c_2$ that interleave the execution of c_1 and c_2 :

$$\frac{\langle \sigma, c_1 \rangle \rightarrow \langle \sigma', c'_1 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c'_1 \parallel c_2 \rangle}$$

Operational Semantics

And add small-step operational semantics rules for $c_1 \parallel c_2$ that interleave the execution of c_1 and c_2 :

$$\frac{\langle \sigma, c_1 \rangle \rightarrow \langle \sigma', c'_1 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c'_1 \parallel c_2 \rangle}$$

$$\frac{\langle \sigma, c_2 \rangle \rightarrow \langle \sigma', c'_2 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c_1 \parallel c'_2 \rangle}$$

Operational Semantics

And add small-step operational semantics rules for $c_1 \parallel c_2$ that interleave the execution of c_1 and c_2 :

$$\frac{\langle \sigma, c_1 \rangle \rightarrow \langle \sigma', c'_1 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c'_1 \parallel c_2 \rangle}$$

$$\frac{\langle \sigma, c_2 \rangle \rightarrow \langle \sigma', c'_2 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c_1 \parallel c'_2 \rangle}$$

$$\langle \sigma, \mathbf{skip} \parallel \mathbf{skip} \rangle \rightarrow \langle \sigma, \mathbf{skip} \rangle$$

Operational Semantics

And add small-step operational semantics rules for $c_1 \parallel c_2$ that interleave the execution of c_1 and c_2 :

$$\frac{\langle \sigma, c_1 \rangle \rightarrow \langle \sigma', c'_1 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c'_1 \parallel c_2 \rangle}$$

$$\frac{\langle \sigma, c_2 \rangle \rightarrow \langle \sigma', c'_2 \rangle}{\langle \sigma, c_1 \parallel c_2 \rangle \rightarrow \langle \sigma', c_1 \parallel c'_2 \rangle}$$

$$\langle \sigma, \mathbf{skip} \parallel \mathbf{skip} \rangle \rightarrow \langle \sigma, \mathbf{skip} \rangle$$

The rules allow either sub-command to take a step; two sub-commands can interleave read and write operations involving the same store.

Parallel Bank Account

What happens if we deposit into a bank account twice under parallel composition?

```
bal := 0;  
(bal := bal + 21.0  ||  bal := bal + 21.0)
```


Synchronization

Languages have **synchronization** constructs that control the interactions between threads.

Many languages have **mutual exclusion**, a.k.a. *locking*:

```
lock l;  
bal := bal + 21.0;  
unlock l
```

Synchronization

Languages have **synchronization** constructs that control the interactions between threads.

Many languages have **mutual exclusion**, a.k.a. *locking*:

```
lock l;  
bal := bal + 21.0;  
unlock l
```

A well-behaved alternative is **transactional memory**:

```
transaction {  
    bal := bal + 21.0  
}
```


Reasoning About Shared Memory

This program reads and writes two shared variables from two different “threads”:

```
x := 0; y := 0;  
(y := 1; tmp1 := x) ||  
(x := 1; tmp2 := y)
```

What can tmp1 and tmp2 be afterward?

Ordering Operations



Happens Before

The *happens before* relation is a partial order on **events** in a program execution.

See also Lamport, 1978: “Time, Clocks and the Ordering of Events in a Distributed System.”

Happens Before

The *happens before* relation is a partial order on **events** in a program execution.

Operation a happens before b , written $a \rightarrow b$, iff:

- a and b belong to the same thread and a comes before b in a single-threaded execution, or
- a sends an inter-thread message that b receives.

See also Lamport, 1978: “Time, Clocks and the Ordering of Events in a Distributed System.”

Happens Before

The *happens before* relation is a partial order on **events** in a program execution.

Operation a happens before b , written $a \rightarrow b$, iff:

- a and b belong to the same thread and a comes before b in a single-threaded execution, or
- a sends an inter-thread message that b receives.

(Also add transitivity: if $a \rightarrow b$ and $b \rightarrow c$, then $a \rightarrow c$.)

See also Lamport, 1978: “Time, Clocks and the Ordering of Events in a Distributed System.”

Happens Before

In modern multithreaded programming, messages are sent and received at *synchronization* events:

- $\text{unlock } l \rightarrow \text{lock } l$
- $\text{fork } t \rightarrow \text{first operation in thread } t$
- $\text{last operation in thread } t \rightarrow \text{join } t$


Legal Executions

Which executions of a multi-threaded program are possible?

Legal Executions

Which executions of a multi-threaded program are possible?


Model an execution as a total order $a \rightarrow_e b$ on the same set of events. For example:



Legal Executions

Which executions of a multi-threaded program are possible?

Model an execution as a total order $a \rightarrow_e b$ on the same set of events. For example:




Then ask: is $\rightarrow \subseteq \rightarrow_e$? If so, then we say that \rightarrow_e is a **sequentially consistent** execution.

Legal Executions

Which executions of a multi-threaded program are possible?

Model an execution as a total order $a \rightarrow_e b$ on the same set of events. For example:



Then ask: is $\rightarrow \subseteq \rightarrow_e$? If so, then we say that \rightarrow_e is a **sequentially consistent** execution.

Intuitively, \rightarrow_e is an *interleaving* that obeys \rightarrow .

Legal Executions

To see what a parallel program can do, we can enumerate all the SC executions and “run” them:

- $y := 1 \rightarrow \text{tmp1} := x \rightarrow x := 1 \rightarrow \text{tmp2} := y$

Legal Executions

To see what a parallel program can do, we can enumerate all the SC executions and “run” them:

- $y := 1 \rightarrow \text{tmp1} := x \rightarrow x := 1 \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 0, \text{tmp2} \mapsto 1$

Legal Executions

To see what a parallel program can do, we can enumerate all the SC executions and “run” them:

- $y := 1 \rightarrow \text{tmp1} := x \rightarrow x := 1 \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 0, \text{tmp2} \mapsto 1$
- $y := 1 \rightarrow x := 1 \rightarrow \text{tmp1} := x \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1$

Legal Executions

To see what a parallel program can do, we can enumerate all the SC executions and “run” them:

- $y := 1 \rightarrow \text{tmp1} := x \rightarrow x := 1 \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 0, \text{tmp2} \mapsto 1$
- $y := 1 \rightarrow x := 1 \rightarrow \text{tmp1} := x \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1$
- $y := 1 \rightarrow x := 1 \rightarrow \text{tmp2} := y \rightarrow \text{tmp1} := x$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1$
- $x := 1 \rightarrow y := 1 \rightarrow \text{tmp2} := y \rightarrow \text{tmp1} := x$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1$
- $x := 1 \rightarrow y := 1 \rightarrow \text{tmp1} := x \rightarrow \text{tmp2} := y$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1$
- $x := 1 \rightarrow \text{tmp2} := y \rightarrow y := 1 \rightarrow \text{tmp1} := x$
 $\implies \text{tmp1} \mapsto 1, \text{tmp2} \mapsto 0$

Legal Executions

Enumerating SC executions gets old fast, but lets us produce the set of possible final stores, σ :

$\{\text{tmp1} \mapsto 0, \text{tmp2} \mapsto 1\}$

$\{\text{tmp1} \mapsto 1, \text{tmp2} \mapsto 1\}$

$\{\text{tmp1} \mapsto 1, \text{tmp2} \mapsto 0\}$

So no sequentially consistent execution makes both tmp1 and tmp2 equal to zero.

That Same Program, in C

```
volatile int x, y, tmp1, tmp2;
```

```
// Thread 0: write x and read y.
```

```
void *t0(void *arg) {  
    x = 1;  
    tmp1 = y;  
    return 0;  
}
```

```
// Thread 1, the opposite: write y and read x.
```

```
void *t1(void *arg) {  
    y = 1;  
    tmp2 = x;  
    return 0;  
}
```

That Same Program, in C

```
void main() {  
    x = y = tmp1 = tmp2 = 0;  
  
    // Launch both threads.  
    pthread_t thread0, thread1;  
    pthread_create(&thread0, NULL, t0, NULL);  
    pthread_create(&thread1, NULL, t1, NULL);  
  
    // Wait for both threads to finish.  
    pthread_join(thread0, NULL);  
    pthread_join(thread1, NULL);  
  
    printf("%d %d\n", tmp1, tmp2);  
}
```

Weak Memory Models

No real parallel machine enforces sequential consistency!

Weak Memory Models

No real parallel machine enforces sequential consistency!

There are many reasons and/or excuses:

- Per-processor caching lets each CPU read values that other processors can't see yet.
- Private write buffers are critical for good performance with coherent caches.
- Lots of “obvious” compiler optimizations violate sequential consistency.

See also Boehm, 2005: “Threads cannot be implemented as a library.”

Weak Memory Models

Every machine (and every programming language) as a **memory model**. Memory models describe the set of legal executions.

Weak Memory Models

Every machine (and every programming language) as a **memory model**. Memory models describe the set of legal executions.

Sequential consistency is the *strongest* memory model out there: it allows the fewest different executions.

Real machines and languages have *weaker* memory models:

$$SC \geq \text{x86} \geq \text{ARM} \geq \text{C/C++} \geq \text{DRF0}$$

Data Races

A **data race** occurs when:

- There are two events a and b that are unordered in the happens-before relation ($a \not\rightarrow b$ and $b \not\rightarrow a$),
- both events access the same shared variable, and
- one or both of a and b is a write.

Data Races

A **data race** occurs when:

- There are two events a and b that are unordered in the happens-before relation ($a \not\rightarrow b$ and $b \not\rightarrow a$),
- both events access the same shared variable, and
- one or both of a and b is a write.

Our little example has *two* data races: one on x and one on y .

Data Races & Memory Models

Languages have recently agreed on one critical property:

data race free \Rightarrow sequentially consistent

As long as you avoid data races, you get sequential consistency on *any* machine in Java, C, and C++.

(In jargon: the *DRF implies SC* theorem.)

Data Races & Memory Models

Languages have recently agreed on one critical property:

data race free \Rightarrow sequentially consistent

As long as you avoid data races, you get sequential consistency on *any* machine in Java, C, and C++.

(In jargon: the *DRF implies SC* theorem.)

Languages still disagree about what happens when you *do* have a race. In C and C++, races allow **undefined behavior**.

Race-Free Programming

Data race detection is an active field of research.

One called [ThreadSanitizer](#) is included with recent Clang and GCC compilers:

```
$ cc -g -fsanitize=thread simple_race.c
```

```
$ ./a.out
```

```
WARNING: ThreadSanitizer: data race (pid=26327)
```

```
  Write of size 4 at 0x7f89554701d0 by thread T1:
```

```
    #0 Thread1(void*) simple_race.cc:8
```

```
Previous write of size 4 at 0x7f89554701d0 by thread T2:
```

```
    #0 Thread2(void*) simple_race.cc:13
```