

```

1  (*
2                                     CS 51 Lab 19
3                                     Conway's Game of Life Cellular Automaton
4  *)
5  (*
6                                     SOLUTION
7  *)
8  module G = Graphics ;;
9
10 (* Automaton parameters *)
11 let cGRID_SIZE = 100 ;;           (* width and height of grid in cells *)
12 let cSPARSITY = 5 ;;              (* inverse of proportion of cells initially live *)
13 let cRANDOMNESS = 0.00001 ;;      (* probability of randomly modifying a cell *)
14
15 (* Rendering parameters *)
16 let cCOLOR_LIVE = G.rgb 93 46 70 ;; (* color to depict live cells *)
17 let cCOLOR_DEAD = G.rgb 242 227 211 ;; (* background color *)
18 let cCOLOR_LEGEND = G.rgb 173 106 108 ;; (* color for textual legend *)
19 let cSIDE = 8 ;;                  (* width and height of cells (in pixels) *)
20 let cRENDER_FREQUENCY = 1         (* how frequently grid is rendered (in ticks) *) ;;
21
22 (* Font specification for rendering the legend. OCaml font handling is
23    platform dependent, so we leave this as `None`, but we provide the
24    functionality for use in the solution set. Feel free to play with
25    this or leave it as is. *)
26 let cFONT = Some "-adobe-times-bold-r-normal--34-240-100-100-p-177-iso8859-9"
27
28
29 (*-----
30    The Game of Life
31    *)
32
33 (*.....
34    Game of Life states and updates
35    *)
36
37 (* We take the opportunity to abstract the cell states as an
38    enumerated type *)
39 type life_state =
40   | Live
41   | Dead ;;
42
43 (* flipped state -- Returns the opposite state to `state`. *)
44 let flipped (state : life_state) : life_state =

```

```

45     match state with
46     | Live -> Dead
47     | Dead -> Live ;;
48
49     (* offset index off -- Returns the `index` offset by `off` allowing
50        for wraparound. *)
51     let rec offset (index : int) (off : int) : int =
52         if index + off < 0 then
53             cGRID_SIZE - (offset ~-index ~-off)
54         else
55             (index + off) mod cGRID_SIZE ;;
56
57     (* life_update grid i j -- Returns the updated value for cell at `i`,
58        `j` in the grid based on rules of Conway's Game of Life. In this
59        implementation, after updating as per the standard GoL update rule,
60        a cell's state is then flipped with probability given by
61        cRANDOMNESS. *)
62     let life_update (grid : life_state array array) (i : int) (j : int)
63         : life_state =
64
65         (* We give a few variant update rules for the Game of Life. These
66            lists are indexed by adjacency count to give the generated cell
67            status.
68
69                0      1      2      3      4      5      6      7      8
70                |      |      |      |      |      |      |      |      |
71                v      v      v      v      v      v      v      v      v *)
72         (* B3/S23: Conway's original game of life *)
73         let dead_update = [Dead; Dead; Dead; Live; Dead; Dead; Dead; Dead; Dead] in
74         let live_update = [Dead; Dead; Live; Live; Dead; Dead; Dead; Dead; Dead] in
75
76         (* B3/S12345: https://conwaylife.com/wiki/OCA:Maze
77            let dead_update = [Dead; Dead; Dead; Live; Dead; Dead; Dead; Dead; Dead] in
78            let live_update = [Dead; Live; Live; Live; Live; Live; Dead; Dead; Dead] in
79            *)
80         (* B36/S125: https://conwaylife.com/wiki/OCA:2x2
81            let dead_update = [Dead; Dead; Dead; Live; Dead; Dead; Live; Dead; Dead] in
82            let live_update = [Dead; Live; Live; Dead; Dead; Live; Dead; Dead; Dead] in
83            *)
84         (* B3678/34678: https://conwaylife.com/wiki/OCA:Day\_%26\_Night
85            let dead_update = [Dead; Dead; Dead; Live; Dead; Dead; Live; Live; Live] in
86            let live_update = [Dead; Dead; Dead; Live; Live; Dead; Live; Live; Live] in
87            *)
88
89     let neighbors = ref 0 in
90     for i' = ~-1 to ~+1 do
91         for j' = ~-1 to ~+1 do

```

```

91     let i_ind = offset i i' in
92     let j_ind = offset j j' in
93     neighbors := !neighbors
94               + match grid.(i_ind).(j_ind) with
95                 | Live -> 1
96                 | Dead -> 0
97     done
98 done;
99 (* determine new state based on neighbor count *)
100 let new_state =
101     match grid.(i).(j) with
102     | Live -> List.nth live_update (!neighbors - 1)
103     | Dead -> List.nth dead_update !neighbors in
104 (* randomly flip an occasional cell state *)
105 if Random.float 1.0 <= cRANDOMNESS then
106     flipped new_state
107 else
108     new_state ;;
109
110 (* life_random_state () -- Returns a random cell state. *)
111 let life_random_state () =
112     let states = [Live; Dead] in
113     List.nth states (Random.int (List.length states))
114
115 (*.....*)
116 Making the Game of Life
117 *)
118
119 (* GoL automaton specification *)
120
121 module LifeSpec : (Cellular.AUT_SPEC
122                   with type state = life_state) =
123 struct
124     type state = life_state
125     let initial : state = Dead
126     let grid_size : int = cGRID_SIZE
127     let random_state = life_random_state
128     let update = life_update
129     let name : string = "Conway's Life"
130     let cell_color (cell : state) : G.color =
131         match cell with
132         | Live -> cCOLOR_LIVE
133         | Dead -> cCOLOR_DEAD
134     let side_size : int = cSIDE
135     let legend_color : G.color = cCOLOR_LEGEND
136     let font : string option = cFONT

```

```

137     let render_frequency : int = cRENDER_FREQUENCY
138 end ;;
139
140 (* GoL automaton *)
141
142 module Aut = Cellular.Automaton (LifeSpec) ;;
143
144 (*.....
145 Running the automaton and displaying the results
146 *)
147
148 (* main seed -- Runs the automaton using the provided random 'seed'
149 (for replicability), displaying updates to the graphics window. *)
150 let main seed =
151
152     Random.init seed;      (* initialize randomness *)
153     Aut.graphics_init ();  (* ... and graphics window *)
154
155     let initial_grid = Aut.random_grid () in
156     Aut.run_grid initial_grid ;;
157
158 (* Run the automaton with user-supplied seed *)
159 let _ =
160     if Array.length Sys.argv <= 1 then
161         Printf.printf "Usage: %s <seed>\n where <seed> is integer seed\n"
162             Sys.argv.(0)
163     else
164         main (int_of_string Sys.argv.(1)) ;;
165

```