```
(*
                              CS51 Lab 10
            Time Complexity, Big-O, and Recurrence Equations
 *)
(*
                                SOLUTION
 *)

(*======================================================================
Readings:

    This lab builds on material from Chapter 14 of the textbook
    <http://book.cs51.io>, which should be read before the lab session.

Objective:

    This lab is intended to practice concepts concerning efficiency and
    complexity, including:
        Big O notation
        Recurrence equations
======================================================================*)

(* We open `CS51Utils` to provide access to the `Absbook` module, and
   timing functions such as `Absbook.call_timed`. You installed the
   `CS51Utils` package at the beginning of the course. You'll find the
   `Absbook` module source code in the file `absbook.ml` in the CS51
   utilities repository at <https://github.com/cs51/utils>. *)

open CS51Utils ;;

(*======================================================================
Part 1: Empirical analysis of functions

In the reading, we empirically determined the efficiency of mergesort
and insertion sort by timing these functions on the same inputs of
various lengths. The ability to perform empirical analysis of programs
will often prove useful.

    Throughout this lab you may find various functions in the
    `Absbook` module to be helpful, as well as OCaml's `Random`
    library module
    <https://caml.inria.fr/pub/docs/manual-ocaml/libref/Random.html>.

    In order to make use of the `Absbook` module from within `ocaml`
    or `utop`, you may need to inform these REPLs of information about
    the module's location. If you have trouble accessing `Absbook`
    functions, try the commands in the following example:

        % ocaml
                OCaml version 4.11.1

        # #use "topfind" ;;
```

```
        ...
        - : unit = ()
        # #require "CS51Utils" ;;
        ...
        # open CS51Utils ;;
        # Absbook.call_timed ;;
        - : ?count:int -> ('a -> 'b) -> 'a -> 'b * float = <fun>

(*......................................................................
Exercise 1: Write a function `random_list` that creates a list of a
specified length of random integers between 0 and 999 inclusive. Hint:
You may find the `List.init` function to be helpful.
......................................................................*)

let random_list (length : int) : int list =
  List.init length (fun _ -> Random.int 1000) ;;

(*......................................................................
Exercise 2: Write a function `time_sort` that, given an `int list ->
int list` sorting function and a list of integers, returns a `float`
indicating how long in milliseconds that the sort takes. Hint: You may
find the `Absbook.call_timed` function to be helpful.
......................................................................*)

let time_sort (sort : int list -> int list) (lst : int list) : float =
  snd (Absbook.call_timed sort lst) ;;

(* We've provided implementations of merge sort and insertion sort
here as modules satisfying the `SORT` signature so that you have some
things to time. *)

module type SORT =
  sig
    (* sort xs -- Return the list `xs` sorted in increasing
       order by OCaml's `<` operator. *)
    val sort : 'a list -> 'a list
  end ;;

module InsertSort : SORT =
  struct
    let rec insert (xs : 'a list) (x : 'a) : 'a list =
      match xs with
      | [] -> [x]
      | hd :: tl -> if x < hd then x :: xs
                    else hd :: (insert tl x) ;;

    let rec sort (xs : 'a list) : 'a list =
      match xs with
      | [] -> []
      | hd :: tl -> insert (sort tl) hd ;;
  end ;;

module MergeSort : SORT =
  struct
```

```
    let rec split (xs : 'a list) : 'a list * 'a list =
      match xs with
      | [] -> [], []
      | [x] -> [x], []
      | first :: second :: rest -> let rest1, rest2 = split rest in
                                   first :: rest1, second :: rest2

    let rec merge (xs : 'a list) (ys : 'a list) : 'a list =
      match xs, ys with
      | [], _ -> ys
      | _, [] -> xs
      | x :: xs_tl, y :: ys_tl ->
         if x < y then x :: (merge xs_tl ys)
         else y :: (merge xs ys_tl)

    let rec sort (xs : 'a list) : 'a list =
      match xs with
      | []
      | _ :: [] -> xs
      | _ -> let first, second = split xs in
             merge (sort first) (sort second)
  end ;;

(*....................................................................
Exercise 3: How many functions does the `InsertionSort` module
provide? How many functions does the `MergeSort` module
provide? Define the variables below accordingly (replacing the `-1`
values).
....................................................................*)

(* Both modules provide a function

       sort : ('a -> 'a -> bool) -> 'a list -> 'a list

   and *no other functions*, as specified by the SORT signature. In
   particular, the functions `insert`, `split`, and `merge` are not
   accessible outside the module. *)

let insertion_sort_provides : int = 1 ;;
let merge_sort_provides : int = 1 ;;

(*....................................................................
Exercise 4: Compare the time it takes for merge sort and insertion
sort to run on lists of random ints of length 10 and 1000. Use the
implementation of merge and insertion sort above.
....................................................................*)

(* A first attempt to fill in the table may have included running the
   following code:

     time_sort InsertSort.sort (random_list 10) ;;
     time_sort InsertSort.sort (random_list 1000) ;;
     time_sort MergeSort.sort  (random_list 10) ;;
     time_sort MergeSort.sort  (random_list 1000) ;;
```

However, this method of comparing the functions will not be entirely accurate: merge sort and insertion sort are running on different input lists. Though the lists are the same length, they may be unsorted to a different degree. Just as when conducting scientific experiments in a laboratory, we need to keep everything but our subject of interest (in this case the sorting function) constant to create a fair comparison.

Thus, our method of filling in the table looked as below:

```
  let shortlist : int list = random_list 10 ;;
  let longlist : int list = random_list 1000 ;;

  time_sort InsertSort.sort shortlist ;;
  time_sort InsertSort.sort longlist ;;
  time_sort MergeSort.sort  shortlist ;;
  time_sort MergeSort.sort  longlist ;;
```

Using this method, we generated the following times:

	List length 10	List length 1000
	Time (msecs)	Time (msecs)
Insertion Sort	0.00286	7.853
Merge Sort	0.00691	1.002

In summary, merge sort is a little slower on the short list but much faster on the long list, consistent with its better asymptotic complexity. (Your numbers may vary of course.)

Generally when running experiments, it is good practice to run more than one trial. We can do this for our timing as well to increase our confidence in the time each algorithm takes. We may start by writing a function that runs a number of trials and averages the time of the result.

```
let run_sort_trials (num : int)
                    (timer : (int list -> int list) -> int list -> float)
                    (sort : (int list -> int list))
                    (input : int list)
                  : float =
    let average (lst : float list) =
      (List.fold_left ( +. ) 0. lst)
      /. float_of_int (List.length lst) in
    List.init num (fun _ -> timer sort input)
    |> average ;;
```

We can then find the average of 50 trials for each list length.

```
run_sort_trials 50 time_sort InsertSort.sort shortlist ;;
run_sort_trials 50 time_sort InsertSort.sort longlist ;;
```

```
   run_sort_trials 50 time_sort MergeSort.sort  shortlist ;;
   run_sort_trials 50 time_sort MergeSort.sort  longlist ;;

                  |    50 Trial Average  |  50 Trial Average
                  |    List length 10    |  List length 1000
                  |    Time (msecs)      |  Time (msecs)
   ---------------------------------------------------------
   Insertion Sort |    0.00134           |   7.2716
   ---------------------------------------------------------
   Merge Sort     |    0.00373           |   1.1035
   ---------------------------------------------------------

   The numbers we report below are all based on averaging 50 trials,
   as here.
 *)

(*======================================================================
Part 2: Big-O

......................................................................
Exercise 5: In the reading for this lab, we saw that big-O notation is
a generic way of expressing the growth rate of a function. For each of
the functions defined below, state in which big-O class(es) the
function belongs.

To allow us to check answers, we've defined an OCaml data type,
`complexity`, with various commonly used big-O classes. The
name-to-function mapping is set out below. We will use informal
function notation in this lab. For more on informal versus formal
notation, please refer to the reading for today's lab.

    Constant    -> O(1)
    Logarithmic -> O(log(n))
    Linear      -> O(n)
    LogLinear   -> O(n log(n))
    Quadratic   -> O(n^2)
    Cubic       -> O(n^3)
    Exponential -> O(2^n)

Because functions can be in more than one complexity class, the format
of the solution to each exercise is a list of complexity classes. By
way of example, we've done the first problem (Exercise 5a) for you.
......................................................................*)

type complexity =
    | Constant
    | Logarithmic
    | Linear
    | LogLinear
    | Quadratic
    | Cubic
    | Exponential ;;

(* f(x) = 2^x + x^3 *)
```

```
let exercise5a () : complexity list =
  [Exponential] ;;

(* f(x) = 0 *)
let exercise5b () : complexity list =
  [Constant; Logarithmic; Linear; LogLinear; Quadratic; Cubic; Exponential] ;;

(* f(x) = 3 x^2 + 2 x + 4  *)
let exercise5c () : complexity list =
  [Quadratic; Cubic; Exponential] ;;

(* f(x) = (2 x - 3) log(x) + 100 x *)
let exercise5d () : complexity list =
  [LogLinear; Quadratic; Cubic; Exponential] ;;

(* f(x) = x (x^2 + x) *)
let exercise5e () : complexity list =
  [Cubic; Exponential] ;;

(* Note: Often, we are most interested in the tightest big-O class a
   function belongs to. When discussing functions such as f(x) = x^2,
   you may hear someone say f is O(x^2). However, for f to be O(g), f
   simply grows as slow or slower than g. Thus, we could also say that
   for f(x) = x^2, f is O(2^x).  We will be explicit regarding
   situations in which we would like you to determine a tight big-O
   bound (that is, the slowest growing function class that f is a part
   of) or a generic big-O bound (any function class f is a part of, as
   we asked for in this problem). *)

(* One advantage of big-O is that we can disregard constants in
considering asymptotic performance of functions. We saw empirically
that on large inputs, merge sort worked faster than insertion
sort. The ability to disregard constants tells us that merge sort will
eventually be faster than insertion sort, even if we add a constant
amount of time to merge sort's performance.

Let's actually do this and test the results empirically!

Here is a version of merge sort that inserts a small constant delay
(50 milliseconds), to simulate a version of the function with the same
asymptotic complexity but that is a constant amount slower. *)

module DelayMergeSort : SORT =
  struct
    (* DelayMergeSort first sleeps for a predetermined period of time,
       then runs our generic MergeSort sort.  This sleep will add a
       constant amount of time to each run of DelayMergeSort.  *)
    let sort (xs : 'a list) : 'a list =
      let () = Unix.sleepf 0.05 in
      MergeSort.sort xs  ;;
  end ;;

(*....................................................................
Exercise 6: Additive constants
```

```
Fill in the table below.
..................................................................*)

(*               | Length 10    | Length 1000  | Length 10000
                 | Time (msecs) | Time (msecs) | Time (msecs)
-----------------------------------------------------------------
Insertion Sort   |    0.00134   |   7.2716     |  868.56
-----------------------------------------------------------------
Delay Merge Sort |   54.223     |  57.144      |   73.369
-----------------------------------------------------------------*)

(* You likely found that InsertSort was faster than DelayMergeSort,
even on a list of length 1000. Increase the length of the list being
sorted by DelayMergeSort and InsertSort until DelayMergeSort runs
faster than InsertSort. Record the size of a list for which this is
true below. *)

let exercise6 = 10000 ;;

(* Big-O also allows us to disregard constant *multiplicative*
factors. In the next exercise, we work with a version of MergeSort
that sorts a given list twice rather than once.  However long
MergeSort takes, DoubleMergeSort will thus take twice as long. *)

module DoubleMergeSort : SORT =
  struct
    (* By sorting the list twice, we double the time MergeSort
       takes *)
    let sort (xs : 'a list) : 'a list =
      let _ = MergeSort.sort xs in
      MergeSort.sort xs  ;;
  end ;;

(*..................................................................
Exercise 7: Multiplicative constant factors

Complete the same empirical analysis as above to compare the
asymptotic behavior of InsertSort and DoubleMergeSort, and fill in the
table below.
..................................................................*)

(*                | Length 10    | Length 1000  | Length 10000
                  | Time (msecs) | Time (msecs) | Time (msecs)
------------------------------------------------------------------
Insertion Sort    |    0.00134   |   7.2716     |  868.56
------------------------------------------------------------------
Double Merge Sort |    0.00600   |   1.7112     |   24.418
------------------------------------------------------------------*)

(* Now record a list length for which you found DoubleMergeSort sorted
faster than InsertSort. *)

let exercise7 = 1000 ;;
```

```
(* An additional nice property of big-O is the ability to disregard
lower-order terms of a function. In the reading, we found that:

    Time_mergesort(n) = c * n log n + d

In this exercise, we will work with a version of MergeSort that will
add an additional k * n term to the completion time of MergeSort. *)

module ExtraTermMergeSort : SORT =
  struct
    let sort (xs : 'a list) : 'a list =
      (* We map the identity function over all of the elements of the
         list and throw away the result, so as to waste time of O(n),
         where n is the number of elements in the list *)
      let _ = List.map (fun x -> x) xs in
      MergeSort.sort xs;;
  end ;;

(*.....................................................................
Exercise 8: Lower Order Terms

Complete the same empirical analysis as above to compare the
asymptotic behavior of InsertSort and ExtraTermMergeSort, and fill in
the table below.
.....................................................................*)

(*                | Length 10    | Length 1000  | Length 10000
                  | Time (msecs) | Time (msecs) | Time (msecs)
------------------------------------------------------------------
Insertion Sort    |    0.00134   |   7.2716     |  868.56
------------------------------------------------------------------
Extra Term MSort  |    0.00422   |   1.0078     |   12.765
------------------------------------------------------------------*)

(* Now record a list length for which ExtraTermMergeSort works faster
than InsertSort. *)
let exercise8 = 1000 ;;

(*.....................................................................
Exercise 9: More big-O

As in Exercise 5, for each of the functions below, state to which
big-O classes the function belongs. See Exercise 5 for an example.

As a reminder, the big-O classes defined in our complexity ADT are

    type complexity =
        | Constant
        | Logarithmic
        | Linear
        | LogLinear
        | Quadratic
        | Cubic
```

```
        | Exponential ;;
..............................................................*)

(* f(x) = 10000 *)
let exercise9a () : complexity list =
  [Constant; Logarithmic; Linear; LogLinear; Quadratic; Cubic; Exponential] ;;

(* f(x) = 50x^100 + x^2 *)
let exercise9b () : complexity list =
  [Exponential] ;;

(* f(x) = 30xlog(x) + 50x + 70 *)
let exercise9c () : complexity list =
  [LogLinear; Quadratic; Cubic; Exponential] ;;

(* f(x) = 30x^2 * log(x) *)
let exercise9d () : complexity list =
  [Cubic; Exponential] ;;
(* Note: This is a bit tricky. Because we are multiplying 30x^2 and
   log(x), we can't simply disregard the log(x), as we could do if
   adding it. 30x^2 * log(x) will not be quadratic, as the log(x) will
   grow faster than any constant we multiply x^2 by. However, log(x)
   grows slower than x, so we know x^2 * log(x) will grow more slowly
   than x^2 * x, so f must grow more slowly than x^3, making this
   function O(x^3) and O(2^x) *)

(* f(x) = x + 60log(x) *)
let exercise9e () : complexity list =
  [Linear; LogLinear; Quadratic; Cubic; Exponential] ;;

(*======================================================================
Part 3: Recurrence Equations

Once we know the complexity of a function, we can use big-O notation
to compare that function's asymptotic performance with other
functions. However, a function's complexity may not be immediately
obvious. Recurrence equations provide an analytical way to determine
the complexity of a function.

Recurrence equations generally consider two cases:

1. A base case
2. A recursive case

Once you have formulated the recursive case, you can use the method of
"unfolding" described in the reading to determine the time complexity
of the functions.

In each of the exercises below, we present a function in OCaml. Your
task is to define the recurrence equations for that function, and then
to solve the recurrence equations via unfolding, to generate a
closed-form equation and form a conclusion about the time complexity
of the function in big-O notation.
```

```
To facilitate automated testing of the recurrence equations you come
up with, we ask you to present them in the form of an OCaml
function. (We provide an example below.)  We encourage you to first
complete the problem on paper, with the notation from the chapter and
using the unfolding method, and then transfer your solutions
here. When finding the time complexity, we would like you to use the
tightest possible big-O class.

Many of the recurrences have various constants. We have defined a
global variable, `k`, for you to use for *all* of the constants in your
OCaml formulation of the recurrence equations. Again, the example
below should clarify. *)

let k = 5;;

(* An example of the method we would like you to use for presenting
your recurrence equations and complexity is provided below, based on
the `insert` function from the reading. *)

(*.....................................................................
                        RECURRENCE EXAMPLE
.....................................................................*)
let rec insert xs x =
    match xs with
    | [] -> [x]
    | h :: t -> if x > h then h :: (insert t x)
                  else x :: xs ;;
(*.....................................................................
Complete the recurrence equations and time complexity of this
function:
.....................................................................*)

(*
let time_insert (n : int) : int =
    failwith "time_insert not yet implemented" ;;

let insert_complexity () : complexity =
    failwith "insert_complexity not yet implemented" ;;
*)

(*.....................................................................
                            SOLUTION

We saw in the reading that the `insert` function has the following
recurrence equations:

T_insert(0) = c
T_insert(n) = max(k_1 + T_insert(n-1), k_2) ≤ k_1 + T_insert(n-1) + k_2
            = k + T_insert(n-1)

We express these equations with the following Ocaml function. Rather
than write two equations, as you might on paper, we write the base
case and recursive case as branches of an if/then/else
expression. Although the recurrence equations have two constants (c
```

```
and k), we use the single OCaml variable `k` to play both of those
roles.  Please follow that format in all of the following exercises.
.....................................................................*)

let rec time_insert (n : int) : int =
  if n = 0 then k
  else k + time_insert (n - 1) ;;

(* (Note that this function will run forever on inputs below 0. We
would normally expect you to handle invalid inputs. However, for the
purpose of practicing recurrence equations, you may assume inputs will
always be positive or nonnegative as the equations require.)

For the time complexity, we use a value from the complexity type to
express the tightest big-O bound for this linear function. *)

let insert_complexity () : complexity =
  Linear ;;

(* Now it's time for you to construct and solve some recurrence
equations, and add them to the lab using the method above.

                            END OF EXAMPLE
 *)

(*.....................................................................
Exercise 10: Sum recurrence equations

Formulate the recurrence equations and determine the time complexity
of the `sum` function, defined below.
.....................................................................*)

let rec sum (x : int list) : int =
  match x with
  | [] -> 0
  | h :: t -> h + sum t;;

(* Describe the time complexity recurrence equations for `sum` as an
OCaml function of `n`, the length of the list. *)
let rec time_sum (n : int) : int =
  if n = 0 then k
  else k + time_sum (n - 1) ;;

(* What is its complexity? *)
let sum_complexity () : complexity =
  Linear ;;

(*.....................................................................
Exercise 11: Divider Recurrence Equations

Formulate the recurrence equations and determine the time complexity
of `divider`, defined below, in terms of the value of its argument
`x`.
.....................................................................*)
```

```
593
594 let rec divider (x : int) : int =
595   if x < 0 then
596     raise (Invalid_argument "only positive numbers accepted")
597   else if x <= 1 then 0
598   else 1 + divider (x / 2) ;;
599
600 let rec time_divider (n : int) : int =
601   if n = 0 || n = 1 then k
602   else k + time_divider (n / 2) ;;
603
604 (* Note: Initially it may seem that `divider`'s input "size" can never
605    change: The input is an int, and only ever one int. However,
606    divider will repeat a given number of times depending on the value
607    of the argument. Thus the size of the input in divider is actually
608    the value of the integer input, rather than the length of a list
609    input as we had previously seen.
610
611    We complete the unfolding process as below:
612      T_div(n) = k + T_div(n / 2)
613               = k + k + T_div(n / 4)
614               = k + k + k + T_div(n / 8)
615               = k + k + k + ... + T_div(1)
616               = k + k + k + ... + q
617
618    How many k's will we have in the end?  We will have as many k's as
619    times that we divide n by 2 before hitting 1 (or 0). This is
620    approximately log base 2 of n.
621
622      Thus, T_div(n) = k*log(n) + q
623                     = O(log(n))
624  *)
625
626 let divider_complexity () : complexity =
627   Logarithmic;;
628
629 (*.....................................................................
630 Exercise 12: Find_min recurrence equations
631
632 Formulate the recurrence equations and determine the time complexity
633 of `find_min` as defined below. The `find_min` function contains a
634 helper function, `split`. First find the recurrence equations and time
635 complexity of `split`, as you may find this helpful in determining the
636 time complexity of `find_min`.
637 .....................................................................*)
638
639 let rec find_min (xs : int list) : int =
640
641   let rec split (xs : 'a list) =
642     match xs with
643     | [] -> [], []
644     | [x] -> [x], []
645     | first :: second :: rest -> let rest1, rest2 = split rest in
646                                  first :: rest1, second :: rest2 in
```

```
  match xs with
  | [] -> raise (Invalid_argument "Empty List")
  | [x] -> x
  | _ -> let xs1, xs2 = split xs in
         min (find_min xs1) (find_min xs2) ;;

let rec time_split (n : int) : int =
  if n = 0 || n = 1 then k
  else k + time_split (n - 2) ;;

(* Split considers 2 elements at a time, thus we subtract 2 in the
   recursive case. We can unfold as below:

   T_split(0) = T_split(1) = q
   T_split(n) = k + T_split(n - 2)
              = k + k + T_split(n - 4)
              = k + k + ... + T(0)
              = k + k + .... + q

   How many k's will we have? Not exactly n, as we subtracted
   2 each unfold. Instead, we will have n/2. Our closed
   form solution is thus:

   T_split(n) = k * (n / 2) + q

   However, with regards to big-O, this division by two can be
   disregarded, and we have that T_split is O(n).  *)

let split_complexity () : complexity =
  Linear ;;

let rec time_find_min (n : int) : int =
  if n = 0 || n = 1 then k
  else k + (time_split n) + 2 * time_find_min (n / 2) ;;

(* When unfolding `find_min`, you may have recognized the "Divide and
   Conquer" pattern discussed in the reading.  You also had to know
   the time complexity of `split` to determine the time complexity of
   `find_min`. Often, it can be useful to consider each helper
   function's complexity separately. You can then use the derived
   closed form solutions when calculating the time complexity of the
   larger function.

   T_fm(0) = T_fm(1) = c
   T_fm(n) = k + T_split(n) + 2T_fm(n/2)    <-   We can immediately substitute our
   T_fm(n) = k + k * (n / 2) + q + 2T_fm(n/2)    closed form solution for T_split
   T_fm(n) = k + k * (n / 2) + q + k + 2T_split(n/2) + 4T_fm(n/4)
   T_fm(n) = k + k * (n / 2) + q + k + 2k * (n / 4) + 2q + 4T_fm(n/4)
   T_fm(n) = k + k * (n / 2) + q + k + k * (n / 2) + 2q + 4T_fm(n/4)
   ....

   We will end up unfolding log(n) times total. Each time we unfold we
   add a constant related to the time to match and call functions, and
```

```
    terms relating to the splitting time. In total, our constant k
    will be summed log(n) times, giving us a k * log(n) term in our
    closed form solution.

    Splitting adds two terms each time, one that is constant (q), and one
    that is linear in the size of the list being split (k * n / 2). The linear
    term stays a consistent k * n / 2. Though we make more splits, the
    size of the list halves, and these forces cancel each other
    out. (Ignoring for a moment the constant in the split closed
    form solution, 2T_split(n/2) becomes 2(k * n / 4) = k * n / 2). As
    we unfold log(n) times, adding a k * n / 2 term each time, we will
    have a term of log(n) * k * n / 2 = k * n log(n) / 2 in our closed
    form.

    We can now return to the constant in the closed form solution of
    T_split.  How does this constant affect the closed form
    solution. Let's look only at what happens to this constant in each
    unfold:

    T_fm(n) = k + k * (n / 2) + q + k + k * (n / 2) + 2q + 4T_fm(n/4)
    T_fm(n) = ..... + q + .... + 2q + 4T_fm(n/4)
    T_fm(n) = ..... + q + .... + 2q + .... + 4q + 8T_fm(n/8)

    Each time we unfold, we double the number of q's we add.
    Thus, at the k'th unfold, we add 2^k * q to our equation.
    In the base case, we are at the log(n)th unfold. Though we have
    been vague thus far, we assume a log base 2 for simplicity of
    computation. Thus at the k'th unfold we add 2^(log(n)) * q.
    This simplifies to n * q. As each term added is double the
    term before, the total amount of steps added from this
    component is less than 2 * n * q. Thus, this constant adds a linear
    term to our closed form solution.

    The last component of our closed form solution is the constant, c,
    that encompasses the time the two base cases take.

    Gathering all our terms, we have:
    T_fm(n) = k * log(n) + (k / 2) * n log(n) + 2 * q * n + c

    To find the closest big O class, we need only look at the largest
    term. This term is (k / 2) * n log(n). We can drop constant factors,
    finding that `find_min` is O(n log(n))
  *)

let find_min_complexity () : complexity =
    LogLinear ;;

(*=====================================================================
Part 4: Tradeoffs

Consider the three implementations of multiplication below:
  *)

let sign_product (x : int) (y : int) : int =
```

```
    let sign (x : int) : int =
        if x >= 0 then 1 else ~-1 in
    (sign x) * (sign y) ;;

(* 1. Repeated addition simply adds `x` to itself `y` times. To
multiply two n-digit numbers together using this algorithm takes time
O(n 10^n). It is thus tremendously inefficient. *)

let mult_repeated_addition (x : int) (y : int) : int =
  let rec helper (y : int) (sum : int) =
    if y < 0 then raise (Invalid_argument "negative input")
    else if y = 0 then 0
    else helper (y - 1) (sum + (abs x)) in
  helper (abs y) 0 * (sign_product x y) ;;

(* 2. The gradeschool multiplication algorithm is the algorithm one
would use when doing multiplication of large numbers on paper. To
multiply two n-digit numbers together using this algorithm takes time
O(n^2) *)

let mult_grade_school (x : int) (y : int) : int =
  let product_sign = sign_product x y in
  let x = abs x in
  let y = abs y in
  let base = 10 in
  let single_digit_mult (x : int) (y : int) =
    let rec helper x carry placevalue =
      if x = 0 then carry * placevalue
      else let prod = y * (x mod base) + carry in
           let new_carry, place = (prod / base, prod mod base) in
           place * placevalue +
             helper  (x / base) new_carry (placevalue * base)
    in if y < 0 || y > 9 then
         raise (Invalid_argument "multiple digit or neg. y")
       else helper x 0 1 in
  let rec iterate_y y placevalue =
    if y = 0 then 0
    else placevalue * single_digit_mult x (y mod 10)
         + iterate_y (y / 10) (placevalue * base) in
  product_sign * iterate_y y 1 ;;

(* 3. The Karatsuba algorithm is a multiplication algorithm that
utilizes a divide-and-conquer approach. It was devised in 1960 by
23-year-old student Anatoly Karatsuba after his Professor Andrey
Kolmogorov conjectured that the fastest possible multiplication
algorithm would be lower bounded (that is, no faster than) O(n^2).
Karatsuba's algorithm disproved that conjecture. To multiply two
n-digit numbers, Karatsuba's algorithm runs in O(n^(log_2 3)), that
is, n to the power of log base 2 of 3, which is about n^1.4.

*You do not need to understand the algorithm for this class*, but can
find out more on Wikipedia if interested:
https://en.wikipedia.org/wiki/Karatsuba_algorithm *)

```

```
let mult_karatsuba (x : int) (y : int) : int =
  let tens_power (power : int) : int =
    let num_string = "1" ^ (String.make power '0') in
    int_of_string num_string in
  let rec karatsuba x y =
    if x < 10 || y < 10 then  x * y
    else let num_digits_x = String.length (string_of_int x) in
         let num_digits_y = String.length (string_of_int y)  in
         let min_digits = min num_digits_x num_digits_y in
         let half_place = tens_power (min_digits / 2) in
         let highx, lowx = (x / half_place, x mod half_place) in
         let highy, lowy = (y / half_place, y mod half_place) in
         let a = karatsuba lowx lowy in
         let b = karatsuba (lowx + highx) (lowy + highy) in
         let c = karatsuba highx highy in
         c * half_place * half_place
         + half_place * (b - c - a) + a in
  (sign_product x y) * karatsuba (abs x) (abs y) ;;

(*.....................................................................
Exercise 13: Write a function `time_multiply` that, given a
multiplication function and two integers, times how long in seconds
the algorithm takes to multiply the integers.
.....................................................................*)

let time_multiply (mult : int -> int -> int)
                  (x : int)
                  (y : int)
                : float =
  let _result, time = Absbook.call_timed
                        (fun (x, y) -> mult x y)
                        (x, y) in
  time /. 1000. ;;

(*.....................................................................
Exercise 14: Fill in the table below:
.....................................................................*)

(* Here's what we found. Of course, your results might vary.

                       |    15 * 50           |  1241342345 *
                       |                      |  3237461243
                       |    Time (msecs)      |  Time (msecs)
-----------------------------------------------------------------
Repeated Addition      |     0.00286          |  83500.
-----------------------------------------------------------------
Grade School Algorithm |     0.00310          |      0.0129
-----------------------------------------------------------------
Karatsuba              |     0.00787          |      0.0281
-----------------------------------------------------------------
OCaml Native ( * )     |     0.00119          |    ~ 0
-----------------------------------------------------------------
   *)

```

```
(* Questions to consider:

       1. Which algorithm above was easiest to understand?
       2. Which algorithm was likely easiest to code?
       3. Which was fastest on small numbers?
       4. Which was fastest on large numbers?
       5. What size integers do you typically multiply?
       6. Which algorithm, then, would you consider the best?
 *)
```