

# OBJECT ORIENTED PROGRAMMING 7

---

DATA C88C

March 4, 2024

---

## 1 Object Oriented Programming

---

### 1.1 Introduction

---

This week, you were introduced to the programming paradigm known as Object-Oriented Programming. If you've programmed in a language like Java or C++, this concept should already be familiar to you.

Object-oriented programming (OOP) is heavily based on the idea of data abstraction. Think of objects as how you would an object in real life.

For our example, let's think of your laptop. First of all, it must have gotten its design from somewhere and that blueprint is called a **class**. The laptop itself is an **instance** of that class. If your friend has the same laptop as you, those laptops are just different instances of the same class.

Your laptop performs many actions, e.g. turning on, displaying text, etc. Those are called **methods**. It also has properties, e.g. screen resolution, how much memory it has, that scratch mark you hope no one else sees. Those are called **attributes**. If it's an attribute that's the same for all instances, it's called a **class attribute**. So, if you were wondering how many instances of your laptop exists, that would be a class attribute because no matter which instance got asked that, it would be the same. If you were wondering how many scratches your laptop has, that's an **instance attribute** because that number depends on each instance.

When discussing objects and classes, it is helpful to distinguish between the definition of a class and the instantiation of a class, or an object. The instantiation is referred to as an "object", whereas the definition is the "class". Following our example, `OurClass` is a class, while `new_bar` is an instantiation of that class, also referred to as an object.

---

## 1.2 Methods

---

To define a method, we write it almost exactly the same way as when we define functions. However, the first argument we always include is `self`, which we use to refer to the instance we used to call the method.

```
class OurClass(ParentClass):  
    def method(self, arg):  
        # body goes here
```

---

## 1.3 Classes

---

When defining a class, we use the following syntax:

```
class OurClass(ParentClass):  
    # Class definition with methods and class attributes
```

where `OurClass` is the name of the new class and `ParentClass` is the name of the class it inherits from. (We'll talk more about inheritance later). When the `ParentClass` field is missing (i.e. just `class OurClass:`), classes inherit from Python's built-in object class.

---

## 1.4 Dot Notation

---

Finally, to use a class or instance's attributes, we use "dot notation", which is aptly named for the use of the magic dot. The dot asks the class for the value of the attribute. So, if we have an attribute, `bar`, of a class or instance, `foo`, we access it by saying: "`foo.bar`" which says "Almighty `foo` class, what is the value of the attribute `bar`?"

Typically, attributes are defined in the `__init__` function of a class:

```
class OurClass(ParentClass):  
    bar = "Fruit Bar" # class attribute  
    def __init__(self, bar_name):  
        self.bar = bar_name # instance attribute  
    def method(self, arg):  
        # body goes here
```

Once an object is constructed, you can also access the attribute by using dot notation *outside* of the class definition:

```
>>> new_bar = OurClass('Crazy Bar')  
>>> new_bar.bar  
'Crazy Bar'
```

1. What is the relationship between a class and an ADT?

2. What is the definition of a Class? What is the definition of an Instance?

### 3. What is a Class Attribute? What is an Instance Attribute?

#### 4. What Would Python Display?

```
class Foo():
    x = 'bam'
    def __init__(self, x):
        self.x = x
    def baz(self):
        return self.x

class Bar():
    x = 'boom'
    def __init__(self, x):
        Foo.__init__(self, 'er' + x)
    def baz(self):
        return Bar.x + Foo.baz(self)

>>> foo = Foo('boo')
>>> Foo.x

>>> foo.x

>>> foo.baz()

>>> Foo.baz()

>>> Foo.baz(foo)

>>> bar = Bar('ang')
>>> Bar.x

>>> bar.x

>>> bar.baz()
```

---

## 1.6 OOP Questions

---

As a starting example, consider the classes `Skittle` and `Bag`, which will be used to represent a single piece of Skittles candy and a bag of Skittles respectively.

```
class Skittle:
    """A Skittle object has a color to describe it."""
    def __init__(self, color):
        self.color = color


class Bag:
    """A Bag is a collection of Skittles. All bags share the
    number of Bags ever made (sold) and each bag keeps track
    of its Skittles in a list.
    """
    number_sold = 0

    def __init__(self):
        self.skittles = []
        Bag.number_sold += 1

    def tag_line(self):
        """Print the Skittles tag line."""
        print("Taste the rainbow!")

    def print_bag(self):
        print([s.color for s in self.skittles])

    def take_skittle(self):
        """Take the first skittle in the bag (from the front
        of the skittles list).
        """
        return self.skittles.pop(0)

    def add_skittle(self, s):
        """Add a skittle to the bag."""
        self.skittles.append(s)
```

In this example, we have the attribute `number_sold`, which is a class attribute. Also, you see this strange method called `__init__`. That is called when you make a new instance of the class. So, if you write `a = Bag()`, that makes a new instance of the `Bag` class (calling `__init__` to do so) and then returns `self`, which you can think of as a dictionary that holds all of the attributes of the object.

To make a new class attribute, you use the name of the class with dot notation: `Bag.new_var = 10` makes a new class attribute `new_var` in the `Bag` class and assigns it the value of 10. To make a new instance attribute, you use the name of the instance attribute: `a.new_var2 = 10`.

Attribute lookup works similarly to environment diagrams. You look to see if some instance attribute has that name. If it doesn't, then you look up the name in the class attributes.

5. What does Python print for each of the following:

```
>>> johns_bag = Bag()
>>> johns_bag.print_bag()

>>> for color in ['blue', 'red', 'green', 'red']:
...     johns_bag.add_skittle(Skittle(color))
>>> johns_bag.print_bag()

>>> s = johns_bag.take_skittle()
>>> print(s.color)

>>> johns_bag.number_sold

>>> Bag.number_sold

>>> soumyas_bag = Bag()
>>> soumyas_bag.print_bag()

>>> johns_bag.print_bag()

>>> Bag.number_sold

>>> soumyas_bag.number_sold
```

6. Write a new method for the `Bag` class called `take_all`, which takes all the `Skittles` in the current bag and prints the color of the each `Skittle` taken from the bag.

```
def take_all(self):  
    """  
    >>> my_bag = Bag()  
    >>> for color in ['red', 'orange', 'yellow']:  
    ...     my_bag.add_skittle(Skittle(color))  
    >>> my_bag.print_bag()  
    ['red', 'orange', 'yellow']  
    >>> my_bag.take_all()  
    red  
    orange  
    yellow  
    >>> my_bag.print_bag()  
    []  
    """
```

7. Write a new method for the `Bag` class called `take_color`, which takes a color and removes (and returns) a `Skittle` of that color from the bag. If there is no `Skittle` of that color, then it returns `None`.

```
def take_color(self, color):
    """
    >>> my_bag = Bag()
    >>> for color in ['red', 'orange', 'yellow']:
    ...     my_bag.add_skittle(Skittle(color))
    >>> my_bag.print_bag()
    ['red', 'orange', 'yellow']
    >>> my_skittle = my_bag.take_color('red')
    >>> my_skittle.color
    red
    >>> my_bag.print_bag()
    ['orange', 'yellow']
    >>> none_skittle = my_bag.take_color('blue')
    >>> none_skittle
    >>> my_bag.print_bag()
    ['orange', 'yellow']
    """
```