

Welcome to Data C88C!

Lecture 19: Efficiency

Monday, July 28th, 2025

Week 6

Summer 2025

Instructor: Eric Kim (ekim555@berkeley.edu)

Announcements

- "Clarification of due dates for Project01, Project02": [\[link\]](#)
 - **Project01 ("Maps")**: due Friday July 25th, 11:59 PM PST
 - Late due date (for 75% credit [\[link\]](#)): Tuesday July 29th, 11:59 PM PST
- Mid-semester survey feedback: [\[link\]](#)
 - If 75% of the class completes this form by Monday July 28th at 11:59 PM, everyone will receive 1 point of extra credit! If this goal is not met, nobody will receive the extra point.
 - As of today (3pm PST): ~50% of the class has completed the survey
- Midterm regrades: due this Friday
- August 1st: Change Grade Option deadline

Lecture Overview

- Efficiency
 - Orders of growth
 - "Big-O" notation
- (For fun) P vs NP

Linked List Practice

Spring 2023 Midterm 2 Question 3(b)


Definition. A *prefix sum* of a sequence of numbers is the sum of the first n elements for some positive length n.

Implement `tens`, which takes a non-empty linked list of numbers `s` represented as a `Link` instance. It prints all of the prefix sums of `s` that are multiples of 10 in increasing order of the length of the prefix.

```
def tens(s):
    """Print all prefix sums of Link s that are multiples of ten.
    >>> tens(Link(3, Link(9, Link(8, Link(10, Link(0, Link(14, Link(6)))))))
    20
    30
    30
    50
    """
    def f(suffix, total):
        if total % 10 == 0:
            print(total)

        if _suffix is not Link.empty_:
            _f(suffix.rest, total + suffix.first)

    f(s.rest, s.first)
```



Tree Class

Tree Class

A Tree has a label and a list of branches; each branch is a Tree

```
class Tree:
    def __init__(self, label, branches=[]):
        self.label = label
        for branch in branches:
            assert isinstance(branch, Tree)
        self.branches = list(branches)
```

```
def fib_tree(n):
    if n == 0 or n == 1:
        return Tree(n)
    else:
        left = fib_tree(n-2)
        right = fib_tree(n-1)
        fib_n = left.label + right.label
        return Tree(fib_n, [left, right])
```



```
def tree(label, branches=[]):
    for branch in branches:
        assert is_tree(branch)
    return [label] + list(branches)
def label(tree):
    return tree[0]
def branches(tree):
    return tree[1:]
def fib_tree(n):
    if n == 0 or n == 1:
        return tree(n)
    else:
        left = fib_tree(n-2)
        right = fib_tree(n-1)
        fib_n = label(left) + label(right)
        return tree(fib_n, [left, right])
```

Tree Practice

Example: Count Twins


Implement `twins`, which takes a Tree `t`. It return the number of pairs of sibling nodes whose labels are equal.

```
def twins(t):  
    """Count the pairs of sibling nodes with equal labels.  
  
    >>> t1 = Tree(3, [Tree(4, [Tree(5), Tree(6)]), Tree(4, [Tree(5), Tree(5)])])  
    >>> twins(t1)    # 4 and 5  
    2  
    >>> twins(Tree(1, [Tree(1, [Tree(2)]), Tree(2, [Tree(2)])]))  
    0  
    >>> twins(Tree(8, [t1, t1, t1]))    # 3 pairs of twins at the top, plus 2 in each branch  
    9  
    """  
  
    count = 0  
    n = len(t.branches)  
    for i in range(n-1):  
        for j in range(i+1, n):  
            if t.branches[i].label == t.branches[j].label:  
                count += 1  
    return count + sum([twins(b) for b in t.branches])
```



Recursive Computation of the Fibonacci Sequence

Our first example of tree recursion:



```
def fib(n):
    if n == 0:
        return 0
    elif n == 1:
        return 1
    else:
        return fib(n-2) + fib(n-1)
```

Memoization

Memoization

Idea: Remember the results that have been computed before


```
def memo(f):  
    cache = {}  
    def memoized(n):  
        if n not in cache:  
            cache[n] = f(n)  
        return cache[n]  
    return memoized
```

Keys are arguments that map to return values

Same behavior as f, if f is a pure function

(Demo)


Memoized Tree Recursion



Measuring Efficiency

How to measure efficiency?

- **Idea:** use seconds ("wall clock time") to quantify how "fast" a code/function runs
 - **Downside:** time-based measurements will change based on which machine I run the benchmark on.
- **Idea:** instead, let's pursue a generic, hardware-agnostic way of measuring how "fast (or slow)" a program is: by counting simple operations*
-



Python: counting operations

- In Python, the following operations are considered a "single operation":
 - creating a new primitive variable
 - reading/writing to a variable
 - integer/float arithmetic**
 - accessing an attribute
- Functions/methods: the runtime is the total number of operations in the function body
- Common list methods that are considered a "single operation" [\[link\]](#): creating a new list, appending to a list
- Tip: it's not enough to "count lines" to estimate how much work a function does, as one line can be more expensive than other lines.


** Fun fact: in Python, integers are implemented as "bignum" that allow them to increase in value arbitrarily large (bounded by your computer's available CPU memory), but at the expense of mathematical operations (+, *, etc) taking longer if your integer grows larger. But, for the purposes of this class, let's assume integer operations are a single operation.

Floats (eg 3.14), however, do not have infinite range: they're bounded by the limits as dictated by the IEEE floating point format [\[link\]](#)

Example: counting operations in Python code

Let `lst_nums` be a list of integers with length N

	Number of operations	
<code>def f1(lst_nums):</code>		
<code> x = 0</code>	1 (create variable x and assign it the value 0)	
<code> x = x + 2</code>	3 (read x, add 2, write to x)	
<code> tmp_nums = []</code>	2 (create tmp_nums and assign it to a new list instance)	
<code> tmp_nums.append(42)</code>	2: read tmp_nums, call the append method (which is itself a single operation)	
<code> total = 0</code>	1: create variable total and assign it the value 0	
<code> for num in lst_nums:</code>		Repeat N times => Total operations: 4 * N
<code> total = total + num</code>	4 (per iter): read total, read num, add total + num, write to total	
<code> return total</code>	1: read and return total to caller	

Total operations for `f1()`: 10 + (4 * N)  O(N)

Tip: O(N) notation lets us not worry about this tedious bookkeeping, and instead let us think about the "big picture" of performance

Orders of Growth

Notation: $\Omega(N)$ vs $O(N)$ vs $\Theta(N)$

Let $R(N)$ be a function that outputs the number of operations of a function f , in terms of the input problem size N .

$\Omega(R(N))$: a lower-bound on growth

$O(R(N))$: an upper-bound on growth

$\Theta(R(N))$: a "tight" bound on growth: the growth of a function is $\Theta(R(N))$ if $R(N)$ provides both a lower-bound AND upper-bound on the growth.

Note: $\Omega()$ and $O()$ can be loose bounds. Ex: $\Omega(1)$ and $O(\text{infinity})$ are technically valid bounds for all functions, though not very useful bounds. In this class, for assignments/exams we'll only accept tight bounds for $\Omega()$ and $O()$.

In this class: we'll generally only ask questions about tight bounds on $O()$.
In classes like cs170 ("Algorithms"), you will study this topic in much greater detail

Aside: in practice, many people use " $O(R(N))$ " when they actually mean " $\Theta(R(N))$ ". Be mindful about the distinction, as there is a subtle difference

Common Orders of Growth

Exponential growth. E.g., recursive `fib`

Incrementing n multiplies *time* by a constant

Quadratic growth.

Incrementing n increases *time* by n times a constant

Linear growth.

Incrementing n increases *time* by a constant

Logarithmic growth.

Doubling n only increments *time* by a constant

Constant growth. Increasing n doesn't affect time

(reference) Examples

Order of growth	Example function
$O(1)$	<pre>def f1(n): return n * 2</pre>
$O(N)$	<pre>def f2(nums): total = 0 for n in nums: total += n return total</pre>
$O(N^2)$	<pre>def f3(nums): total = 0 for n1 in nums: for n2 in nums: total += n1 * n2 return total</pre>
$O(N^3)$	<pre>def f3(nums): total = 0 for n1 in nums: for n2 in nums: total += f2(nums) return total</pre>

(reference) Examples

Order of growth	Example function
$O(\log(N))$	<pre>def f4(n): n_cur, out = n, 0 while n_cur > 1: out += n_cur n_cur = n_cur // 2 return out</pre>
$O(2^N)$	<pre>def fib(n): if n == 0 or n == 1: return n return fib(n - 1) + fib(n - 2)</pre>

$$O(1) < O(\log(N)) < O(N) < O(N^2) < O(2^N)$$

Spring 2023 Midterm 2 Question 3(a) Part (iii)

Definition. A *prefix sum* of a sequence of numbers is the sum of the first n elements for some positive length n .

(1 pt) What is the order of growth of the time to run `prefix(s)` in terms of the length of `s`? Assume `append` and `+` take one step (constant time) for any arguments.

```
def prefix(s):  
    "Return a list of all prefix sums of list s."  
    t = 0  
    result = []  
    for x in s:  
        t = t + x  
        result.append(t)  
    return result
```

Answer: $O(s)$

Follow-up Question: what is the order of growth for this alternate implementation?

```
def prefix_alt(s):  
    "Return a list of all prefix sums of list s."  
    t = 0  
    result = []  
    for i in range(len(s)):  
        result.append(s[:i])  
    return result
```

Answer: $O(s^2)$

Recall: Python slice creates a copy, eg is an $O(N)$ operation, where N is the number of elements to copy
And:

$$1 + 2 + 3 + \dots + N = N * (N + 1) / 2$$


P vs NP

- One of the central, unanswered questions in theoretical computer science involves the orders of growth of algorithms
- **Tractable orders of growth:** polynomial and smaller
 - ex: $O(1)$, $O(\log(N))$, $O(N)$, $O(N^2)$, $O(N^3)$, ...
 - These are algorithms that we (humanity) can reasonably solve for very large problem sizes
- **Intractable orders of growth:**
 - ex: $O(2^N)$, $O(N^N)$, $O(N!)$
 - These are algorithms that we can only solve for small/medium problem sizes

List contains: checking if an element is in a list (`elem in lst`) is $O(N)$, a **tractable** order of growth.


Traveling Salesman Problem [\[link\]](#): Given a list of cities and the distances between each pair of cities, what is the shortest possible route that visits each city exactly once and returns to the origin city.

Held-Karp algorithm [\[link\]](#): $O(n^2 2^n)$ where n is the number of cities



P vs NP

- Let's define the following sets of problems
- **P**: "easy" problems
 - Can **verify** in **polynomial time**
 - Can **solve** in **polynomial time**
- **NP**: set of problems that are easy to verify, but (currently) unknown if easy to solve
 - Can **verify** in **polynomial time**
 - Solving can be more expensive than polynomial time (eg exponential)



The Big Question: does the **set P** equal the **set NP**?


In other words: if a problem is easy to verify, does it also mean that it's easy to solve (**implies $P = NP$**)?

Or: is it possible that some problems are fundamentally difficult to solve (**implies $P \neq NP$**)?

NP-Complete


- Some very smart people have shown that
 - (1) There exists a class of problems, **NP-Complete**, that is verifiable in polynomial time (in NP), and
 - (2) All other problems in NP can be **converted to any NP-Complete problem** in polynomial time
- NP-Complete examples
 - Traveling Salesman Problem (TSP)
 - Knapsack problem [[link](#)]
 - ...
- Currently (as of 2025), no known efficient (polynomial) algorithm exists to solve any NP-Complete problem.

Crucially: if anyone finds an efficient (polynomial) algorithm to ANY NP-Complete problem, then we've found an efficient algorithm to ALL NP problems, which means we've discovered that: **P = NP**



Implications of $P = NP$

- Most modern cryptographic digital security becomes broken / insecure*
 - public-key cryptography
 - Cryptographic hashing, which powers blockchain technology!
- Automatic mathematical proof solvers would take a gigantic leap forward



* as always, "it depends". If the algorithm is something like $O(n^{100})$ or has a gigantic constant factor, then the algorithm may be impractical in practice

P vs NP: What do experts think?

"Since 2002, [William Gasarch](#) has conducted three polls of researchers concerning this... Confidence that $P \neq NP$ has been increasing – in 2019, **88% believed $P \neq NP$** , as opposed to **83% in 2012** and **61% in 2002**. When restricted to experts, the 2019 answers became **99% believed $P \neq NP$** ". [[link_source](#)]