

**TASK: Add booleans, comparisons, and if to this language**

What are your motivating examples?

(\* Any changes to grammar and expr? \*)

```
(*
expr := <number>
      | (<op> <expr>)
      | (let (<name> <expr>) <expr>)
      | (+ <expr> <expr>)
```

```
op := inc | dec
*)
```

```
type op =
| Inc
| Dec
```

```
type expr =
| ENum of int
| EOp of op * expr
| EId of string
| ELet of string * expr * expr
| EPlus of expr * expr
```

```
let int_of_string_opt s =
  try
    Some(int_of_string s)
  with
    Failure _ -> None
```

```
let rec sexp_to_expr (se : Sexp.t) : expr =
  match se with
  (* Which cases need to change?
    Which new cases are needed? *)
```

```
let parse (s : string) : expr =
  sexp_to_expr (Sexp.of_string s)
```

```
(* Compiles a source program string to an x86 string *)
let compile (program : string) : string =
  let ast = parse program in
  let instrs = e_to_is ast 1 [] in
  let instrs_str = (String.concat "\n" instrs) in
  sprintf "
section .text
global our_code_starts_here
our_code_starts_here:
  %s
  ret\n" instrs_str

(* Any changes to compile? *)
```

A C-style reminder

cmp compares a register  
to a value (or other register)  
and sets status bits for jumps.

je is "jump if equal". There are  
jg (jump greater), jle (jump less  
than or equal), and more, jne  
(jump not equal)

open Printf

```
let stackloc i = (i * 8)
let stackval i = sprintf "[rsp - %d]" (stackloc i)
type tenv = (string * int) list
```

```
let rec find (env : tenv) (x : string) : int option =
  match env with
  | [] -> None
  | (y, i)::rest ->
    if y = x then Some(i) else find rest x
```

```
let rec e_to_is (e : expr) (si : int) (env : tenv) =
  match e with
  (* Which cases need to change?
    Which new cases are needed? *)
```

```
if(0) answer = 5;
else answer = 2;
```

```
mov rax, 0
cmp rax, 0
je else_branch
mov rax, 5
jmp after_if
else_branch:
mov rax, 2
after_if:
```

```
#include <stdio.h>

extern int our_code_starts_here()
asm("our_code_starts_here");

int main(int argc, char** argv) {
  int result = our_code_starts_here();
  printf("%d\n", result);
  return 0;
}
```

(\* Any changes to main? \*)

Value	Representation (bits)	Representation	
		hex	decimal
	63-bit, 2's complement number <b>tag bit</b> (1=num, 0=bool)		
9	0000 0000 0000 ... 0000 0000 0001 <b>0011</b>	0x000...0013	19
-2	1111 1111 1111 ... 1111 1111 1111 <b>1101</b>	0xFFFF...FFFD	-3
33	0000 0000 0000 ... 0000 0000 _____	0x000...00__	__
true	1111 1111 1111 ... 1111 1111 1111 <b>1110</b>	0xFFFF...FFFE	-2
false	<b>0111</b> 1111 1111 ... 1111 1111 1111 <b>1110</b>	0x7FF...FFFE	
	<div> <div></div> <div></div> </div> true/false      62 bits for future value representations!		

```

let rec e_to_is (e : expr) si env =
  match e with
  | ENum(n) ->

      | EBool(b) (* b is true or false *) ->

```