




"(+ 39 (- 5 4))"

[("(", "+", "39", "(", "-", "5", "4", ")")]



```
type Sexp.t =
  | List of Sexp.t list
  | Atom of string
```

---

## Recursive Datatypes and Functions – Templates

```
type 'a lst =
  | Empty
  | Link of 'a * 'a lst
```

```
let rec lf (l : 'a lst) ... : ... =
  match l with
  | Empty -> ... base case ...
  | Link(fst, rest) ->
    ... fst ...
    ... (lf rest ...) ...
```

```
type op = Inc | Dec
```

```
type expr =
  | ENum of int
  | EOp of op * expr
```

```
let rec ef (e : expr) ... : ... =
  match e with
  | ENum(n) -> ... base case ...
  | EOp1(op, arg) ->
    ... op ...
    ... (ef arg ...) ...
```

```
type 'a tree =
  | Leaf
  | Node of 'a * 'a tree * 'a tree
```

```
let rec tf (t : 'a tree) ... : ... =
  match t with
  | Leaf -> ... base case ...
  | Node(val, left, right) ->
    ... fst ...
    ... (tf left ...) ...
    ... (tf right ...) ...
```

```
let rec expr_to_instrs (e : expr) =
  match e with
  | ENum(i) -> [sprintf "mov rax, %d" i]
  | EOp(op, e) ->
    let arg_instrs = expr_to_instrs e in
    match op with
    | Inc -> arg_instrs @ ["add rax, 1"]
    | Dec -> arg_instrs @ ["sub rax, 1"]
```

```
open Sexplib.Sexp
module Sexp = Sexplib.Sexp
```

```
(*
expr := <number>
      | (<op> <expr>)
op   := inc | dec
*)
```

```
type op =
| Inc
| Dec
```

```
type expr =
| ENum of int
| EOp of op * expr
```

```
let rec sexp_to_expr (se : Sexp.t) : expr =
  match se with
  | Atom(s) -> ENum(int_of_string s)
  | List(sexps) ->
      match sexps with
      | [Atom("inc"); arg] -> EOp(Inc, sexp_to_expr arg)
      | [Atom("dec"); arg] -> EOp(Dec, sexp_to_expr arg)
      | _ -> failwith "Parse error"
```

```
let parse (s : string) : expr =
  sexp_to_expr (Sexp.of_string s)
```

```
open Printf
```

```
let rec expr_to_instrs (e : expr) : string list =
  match e with
  | ENum(i) -> [sprintf "mov rax, %d" i]
  | EOp(op, e) ->
      let arg_exprs = expr_to_instrs e in
      match op with
      | Inc -> arg_exprs @ ["add rax, 1"]
      | Dec -> arg_exprs @ ["sub rax, 1"]
```

```
(* Compiles a source program string to an x86 string *)
```

```
let compile (program : string) : string =
  let ast = parse program in
  let instrs = expr_to_instrs ast in
  let instrs_str = (String.concat "\n" instrs) in
  sprintf "
```

```
section .text
global our_code_starts_here
our_code_starts_here:
  %s
  ret\n" instrs_str;;
```

```
let () =
  let input_file = (open_in (Sys.argv.(1))) in
  let input_program = (input_line input_file) in
  let program = (compile input_program) in
  printf "%s\n" program;;
```

"(inc (dec 4))"  $\longrightarrow$  EOp(Inc, EOp(Dec, ENum(4)))  $\longrightarrow$

```
open Sexplib.Sexp
module Sexp = Sexplib.Sexp
```

```
type op =
| Inc
| Dec
```

```
type expr =
| ENum of int
| EOp of op * expr
(* Add the cases for ELet and EId! *)
```

```
let rec sexp_to_expr (se : Sexp.t) : expr =
  match se with
  | Atom(s) ->
```

```
  | List(sexps) ->
      match sexps with
      | [Atom("inc"); arg] -> EOp(Inc, sexp_to_expr arg)
      | [Atom("dec"); arg] -> EOp(Dec, sexp_to_expr arg)
      (* Add the case for ELet! *)
```

```
  | _ -> failwith "Parse error"
```

```
(*
expr := <number>
      | (<op> <expr>)
      | (let (<name> <expr>) <expr>)
      | <name>
```

```
op   := inc | dec
*)
```

```
open Printf
```

```
(* FILL the ELet case and anything else for the header! *)
```

```
let rec expr_to_instrs
  match e with
```

```
  | ENum(i) -> [sprintf "mov eax, %d" i]
  | EOp(op, e) ->
      let arg_exprs = expr_to_instrs e
      match op with
      | Inc -> arg_exprs @ ["add rax, 1"]
      | Dec -> arg_exprs @ ["sub rax, 1"]
```

in



- What assembly code is generated for this input program (on worksheet)?

`(inc (dec 4))`

- A:        `mov rax, 4`  
          `add rax, 1`  
          `sub rax, 1`
- B:        `add rax, 1`  
          `sub rax, 1`  
          `mov rax, 4`
- C:        `mov rax, 4`  
          `sub rax, 1`  
          `add rax, 1`

- Which of these is a good definition for the ELet variant of the expr definition?

- A:       | ELet of expr \* expr \* expr
- B:       | ELet of string \* expr
- C:       | ELet of string \* expr \* expr
- D:       | ELet of string \* int \* expr

- Which of these correctly parses let expressions?

- A:

```
| [Atom("let"); bind; body]->  
  match bind with  
  | [name; e] -> ELet(name, e, body)
```

- B:

```
| [Atom("let"); bind; body]->  
  match bind with  
  | [name; e] ->  
    ELet(name, sexp_to_expr e, sexp_to_expr body)
```

- C:

```
| [Atom("let"); name; e; body]->  
  ELet(name, sexp_to_expr e, sexp_to_expr body)
```

- D:

```
| [Atom("let"); Atom(name); bind; body]->  
  ELet(name, sexp_to_expr e, sexp_to_expr body)
```

- E:

```
| [Atom("let"); List(bind); body]->  
  match bind with  
  | [Atom(name); e] ->  
    ELet(name, sexp_to_expr e, sexp_to_expr body)
```

- Which of these matches the grammar extended with let and identifiers?

- A:        (let x 5 x)
- B:        (let (x 5) x)
- C:        (let x 10)
- D:        (let 10 x 10)
- E:        (let 10 x)



- Which of these matches the grammar on the left?

- A:       (+ 1 2)
- B:       (inc 3 3)
- C:       (inc (inc 4))
- D:       (inc dec 3)
- E:       (inc x)

