

## USER AND UPDATING CODE

### Open pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>2.4.3</version>
    <relativePath /> <!-- lookup parent from repository -->
  </parent>
  <groupId>com.p3</groupId>
  <artifactId>UserManager</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>UserManager</name>
  <description>Searching for a Specific User and Updating the User
Information.</description>
  <properties>
    <java.version>1.8</java.version>
  </properties>
  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.projectlombok</groupId>
      <artifactId>lombok</artifactId>
      <optional>true</optional>
    </dependency>
  </dependencies>
</project>
```

```

</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-test</artifactId>
    <scope>test</scope>
</dependency>
<dependency>
    <groupId>org.apache.tomcat.embed</groupId>
    <artifactId>tomcat-embed-jasper</artifactId>
    <scope>provided</scope>
</dependency>

<dependency>
    <groupId>javax.xml.bind</groupId>
    <artifactId>jaxb-api</artifactId>
</dependency>

<dependency>
    <groupId>org.javassist</groupId>
    <artifactId>javassist</artifactId>
    <version>3.25.0-GA</version>
</dependency>

<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <scope>runtime</scope>
    <optional>true</optional>
</dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
            <configuration>

```

```

                <excludes>
                    <exclude>

<groupId>org.projectlombok</groupId>
                        <artifactId>lombok</artifactId>
                    </exclude>
                </excludes>
            </configuration>
        </plugin>
    </plugins>
</build>

</project>
Src/main/java

```

```

package com.p3.UserManager;

import org.springframework.boot.SpringApplication;

import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication

public class UserManagerApplication {

    public static void main(String[] args) {

        SpringApplication.run(UserManagerApplication.class, args);

    }

}

```

### Create package com.p3.UserManager.controller

```

package com.example.UserManager.controller;

import org.springframework.boot.web.servlet.error.ErrorController;

import org.springframework.web.bind.annotation.RequestMapping;

public class AppErrorController implements ErrorController {

    @RequestMapping("/error")

```

```

public String handleError() {

    //do something like logging

    return "error";

}

@Override

public String getErrorPath() {

    return null;

}

}

```

## **MainController.java**

```

package com.p3.UserManager.controller;

import org.springframework.stereotype.Controller;

import org.springframework.ui.ModelMap;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.RequestParam;

@Controller

public class MainController {

    @GetMapping(value = "/")

    public String showIndexPage(ModelMap model,

    @RequestParam(value = "name", required = false, defaultValue = "World") String name)

    {

        model.addAttribute("name", name);

        return "index";

    }

}

```

```
}
```

## **UserController.java**

```
package com.p3.UserManager.controller;

import org.slf4j.Logger;

import org.slf4j.LoggerFactory;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Controller;

import org.springframework.ui.ModelMap;

import org.springframework.web.bind.annotation.GetMapping;

import org.springframework.web.bind.annotation.ModelAttribute;

import org.springframework.web.bind.annotation.PostMapping;

import org.springframework.web.bind.annotation.RequestMapping;

import org.springframework.web.bind.annotation.RequestMethod;

import org.springframework.web.bind.annotation.RequestParam;

import com.example.UserManager.entities.User;

import com.example.UserManager.services.UserService;

@Controller

public class UserController {

    //controls the functionality of the user entity

    @Autowired

    private UserService userService;

    Logger logger = LoggerFactory.getLogger(UserController.class);

    @GetMapping("/users")

    public String showUsers(ModelMap model) {
```

```

        logger.info("Getting all users");

        Iterable<User> users = userService.GetAllUsers();

        logger.info("Passing users to view");

        model.addAttribute("users", users );

        return "users";
    }

    @RequestMapping(value = "/search/{id}", method = RequestMethod.POST)
    public String searchUser(ModelMap model, @RequestParam("id") int id) {

        logger.info("Searching for a user");

        User user = userService.GetUserById(id);

        logger.info("Passing Searched User to View");

        model.addAttribute("userSearch", user);

        return "search";
    }

    @PostMapping("search/update")
    public String updateUser(ModelMap model, @ModelAttribute("update") User
user) {

        logger.info("Updating a User");

        userService.UpdateUser(user);

        model.addAttribute("updatedUser", user);

        return "update";
    }
}

```

**UserExceptionHandler.java**

```

package com.p3.UserManager.controller;

import org.springframework.http.HttpStatus;

import org.springframework.http.ResponseEntity;

import org.springframework.web.bind.annotation.ControllerAdvice;

import org.springframework.web.bind.annotation.ExceptionHandler;

import com.example.UserManager.exceptions.UserNotFoundException;

@ControllerAdvice

public class UserExceptionHandler {

    @ExceptionHandler(value=UserNotFoundException.class)

    public ResponseEntity<Object> exception(UserNotFoundException ex) {

        return new ResponseEntity<>("Product not found",
        HttpStatus.NOT_FOUND);

    }

}

```

## **User.java**

```

package com.p3.UserManager.entities;

import javax.persistence.Entity;

import javax.persistence.GeneratedValue;

import javax.persistence.GenerationType;

import javax.persistence.Id;

@Entity

public class User { //The Entity of a User; What it is.

    @Id

    @GeneratedValue(strategy=GenerationType.AUTO)

```

```
private Integer id;

private String name;

private String email;

private String password;

public User() {
    super();
}

public User(Integer id, String name, String email, String password) {
    super();
    this.id = id;
    this.name = name;
    this.email = email;
    this.password = password;
}

public Integer getId() {
    return id;
}

public void setId(Integer id) {
    this.id = id;
}

public String getName() {
    return name;
}

public void setName(String name) {
```



```

        this.name = name;
    }

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) {
        this.email = email;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }

    @Override
    public String toString() {
        return (id.toString() + " " + name + " " + email + " " + password);
    }
}

```

### **UserNotFoundException.java**

```

package com.p3.UserManager.exceptions;

public class UserNotFoundException extends RuntimeException {
    private static final long serialVersionUID = 1L;
}

```

### Create package **com.p3.UserManager.repositories**

```
package com.p3.UserManager.repositories;

import org.springframework.data.repository.CrudRepository;

import org.springframework.stereotype.Repository;

import com.example.UserManager.entities.User;

@Repository

public interface UserRepository extends CrudRepository<User, Integer> {

    public User findByName(String name);

}
```

### Create package **com.p3.UserManager.services**

```
package com.p3.UserManager.services;

import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.stereotype.Service;

import com.example.UserManager.entities.User;

import com.example.UserManager.exceptions.UserNotFoundException;

import com.example.UserManager.repositories.UserRepository;

@Service

public class UserService {

    @Autowired

    private UserRepository userRepository;

    public Iterable<User> GetAllUsers() {

        return userRepository.findAll();

    }

}
```

```

        public User GetUserByName(String name) {

            return userRepository.findByName(name);

        }

        public User GetUserById(Integer id) {

            Optional<User> foundUser = userRepository.findById(id);

            if(!foundUser.isPresent()) throw new UserNotFoundException();

            return foundUser.get();

        }

        public User updateUser(User userToUpdate) {

            return userRepository.save(userToUpdate);

        }

    }

```

## **Src/main/resources**

### **application.properties**

```

spring.jpa.hibernate.ddl-auto=update
spring.datasource.url=jdbc:mysql://localhost:3306/work
spring.datasource.username=root
spring.datasource.password=12345
logging.level.org.springframework.web: DEBUG
spring.mvc.view.prefix=/WEB-INF/jsp/
spring.mvc.view.suffix=.jsp
server.port=8080

```

## **src/main/webapp/WEB-INF/jsp**

### **error.jsp**

```

<!DOCTYPE html>
<html>
<body>
<h1>Something went wrong! </h1>

```

```
<h2>Our Engineers are on it</h2>
<a href="/">Go Home</a>
</body>
</html>
```

## index.jsp

```
<html>
<body>
<h2>Spring Application</h2>

<h2 class="hello-title">Hello ${name}!</h2>
<a href="users">List Users</a>
<form action="search/{id}" method="post">
Enter ID Number: <input name="id" type="text" id="id" placeholder="1" required/>
<input name="Submit" type="submit"/>
</form>

</body>
</html>
```

## search.jsp

```
<%@ page language="java" contentType="text/html; charset=UTF-8"
    pageEncoding="UTF-8"%>
<%@ taglib prefix="form" uri="http://www.springframework.org/tags/form"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
    "http://www.w3.org/TR/html4/loose.dtd">

<html>
<style>
table {
    float: left;
}

th {
    border-bottom: 1px solid black;
    text-align: left;
}
</style>
<body>

    <h2>Search for User</h2>

    <table>
```

```

        <tr>
            <th>ID</th>
            <th>Name</th>
            <th>Email</th>
            <th>Password</th>
        </tr>
        <tr>
            <td>${userSearch.id}</td>
            <td>${userSearch.name}</td>
            <td>${userSearch.email}</td>
            <td>${userSearch.password}</td>
        </tr>
    </table>

    <br />
    <br />
    <br />
    <br />
    <br />
    <br />
    <form:form action="update" method="post" commandName="update">
        <h3>Update This User?</h3>
        <p>User ID: ${userSearch.id}</p>
        <input type="hidden" name="id" id="id" value="${userSearch.id}"
        required/>
        <label for="name">New Name:</label><br/>
        <input type="text" name="name" id="name"
        value="${userSearch.name}" required/><br/>
        <label for="email">New Email:</label> <br/>
        <input type="text" name="email" id="email"
        value="${userSearch.email}" required/><br/>
        <label for="password">New Password:</label><br/>
        <input type="text" name="password" id="password"
        value="${userSearch.password}" required/><br/><br/>
        <input type="submit" value="Submit"/>
    </form:form>
    <br />
    <br />
    <a href="/">Return to Menu</a>
</body>
</html>

```

**update.jsp**

```
<html>
```

```
<body>
<h2>Update Successful</h2>
Updated User Credentials: ${updatedUser.toString()}
<br/><br/>
<a href="/">Return to Menu</a>
</body>
</html>
```

### users.jsp

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<html>
<style>
table {
float: left;
}

table, th, td {
border: 1px solid black;
}
</style>
<head></head>
<body>
    <h2>Users Page</h2>
    <table>
    <tr><th>ID</th><th>Name</th><th>Email</th><th>Password</th></tr>
    <c:forEach items="${users}" var="user" varStatus="count">
        <tr id="${count.index}">
            <td>${user.id}</td>
            <td>${user.name}</td>
            <td>${user.email}</td>
            <td>${user.password}</td>
        </tr>
    </c:forEach>
    </table>
</body>
</html>
```