

SOURCE CODE

Open pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>
  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>2.4.4</version>
    <relativePath /> <!-- lookup parent from repository -->
  </parent>
  <groupId>com.project</groupId>
  <artifactId>SpringSecurity</artifactId>
  <version>0.0.1-SNAPSHOT</version>
  <name>SpringSecurity</name>
  <description>Demo project for Spring Boot</description>
  <properties>
    <java.version>1.8</java.version>
  </properties>
  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jdbc</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-jdbc</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-data-jpa</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-jersey</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
```

```

</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-security</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-web-services</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-thymeleaf</artifactId>
</dependency>
<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-devtools</artifactId>
    <scope>runtime</scope>
    <optional>true</optional>
</dependency>

<dependency>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-test</artifactId>
    <scope>test</scope>
</dependency>
<dependency>
    <groupId>org.springframework.security</groupId>
    <artifactId>spring-security-test</artifactId>
    <scope>test</scope>
</dependency>

<dependency>
    <groupId>org.apache.tomcat.embed</groupId>
    <artifactId>tomcat-embed-jasper</artifactId>
    <scope>provided</scope>
</dependency>
</dependencies>

<build>
    <plugins>
        <plugin>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-maven-plugin</artifactId>
        </plugin>
    </plugins>
</build>

```

```
        </plugins>
    </build>

</project>
```

Src/main/java

MvcConfig.java

```
package com.project.SpringSecurity;

import org.springframework.context.annotation.Configuration;
import org.springframework.web.servlet.config.annotation.ViewControllerRegistry;
import org.springframework.web.servlet.config.annotation.WebMvcConfigurer;

@Configuration

public class MvcConfig implements WebMvcConfigurer{

    public void addViewControllers(ViewControllerRegistry registry) {

        registry.addViewController("/index").setViewName("index");
        registry.addViewController("/").setViewName("index");
        registry.addViewController("/login").setViewName("login");
        registry.addViewController("/welcome").setViewName("welcome");

    }

}
```

SpringSecurityApplication.java

```
package com.project.SpringSecurity;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.data.jpa.repository.config.EnableJpaRepositories;
import com.project.SpringSecurity.repositories.UsersRepository;
```

```

@SpringBootApplication

@EnableJpaRepositories(basePackageClasses = UsersRepository.class)

public class SpringSecurityApplication {

    public static void main(String[] args) {

        SpringApplication.run(SpringSecurityApplication.class, args);

    }

}

```

WebSecurityConfig.java

```

package com.project.SpringSecurity;

import org.slf4j.Logger;

import org.slf4j.LoggerFactory;

import org.springframework.beans.factory.annotation.Autowired;

import org.springframework.context.annotation.Bean;

import org.springframework.context.annotation.Configuration;

import
org.springframework.security.config.annotation.authentication.builders.AuthenticationManage
rBuilder;

import org.springframework.security.config.annotation.web.builders.HttpSecurity;

import
org.springframework.security.config.annotation.web.configuration.EnableWebSecurity;

import
org.springframework.security.config.annotation.web.configuration.WebSecurityConfigurerAda
pter;

import org.springframework.security.core.userdetails.UserDetailsService;

import org.springframework.security.crypto.password.NoOpPasswordEncoder;

import org.springframework.security.crypto.password.PasswordEncoder;

```

```

@SuppressWarnings("deprecation")

@Configuration

@EnableWebSecurity

public class WebSecurityConfig extends WebSecurityConfigurerAdapter {

    Logger logger = LoggerFactory.getLogger(WebSecurityConfig.class);

    @Autowired

    UserDetailsService userDetailsService;

    @Bean

    public PasswordEncoder getPasswordEncoder() {

        return NoOpPasswordEncoder.getInstance();

    }

    @Autowired

    public void configureGlobal(AuthenticationManagerBuilder auth) throws
Exception {

        auth.userDetailsService(userDetailsService);

    }

    @Override

    protected void configure(HttpSecurity http) throws Exception {

        http.authorizeRequests()

            .antMatchers("/", "/index").permitAll()

            .anyRequest().authenticated()

            .and()

            .formLogin()

            .loginPage("/login")

```

```

        .defaultSuccessUrl("/welcome")
        .failureUrl("/login?error=true")
        .permitAll()
    .and()
        .logout()
        .logoutSuccessUrl("/login?logout=true")
        .invalidateHttpSession(true)
        .permitAll()
    .and()
        .csrf()
        .disable();
}
}

```

MyUserDetails.java

```

package com.project.SpringSecurity.entities;

import java.util.Collection;

import org.springframework.security.core.GrantedAuthority;
import org.springframework.security.core.userdetails.UserDetails;

public class MyUserDetails implements UserDetails{

    private static final long serialVersionUID = 1L;

    private String userName;

    private String password;

    public MyUserDetails() {

    }
}

```

```
        public MyUserDetails(User user) {

            this.userName = user.getName();

            this.password = user.getPassword();

        }

        @Override

        public Collection<? extends GrantedAuthority> getAuthorities() {

            return null;

        }

        @Override

        public String getPassword() {

            return password;

        }

        @Override

        public String getUsername() {

            return userName;

        }

        @Override

        public boolean isAccountNonExpired() {

            return true;

        }

        @Override

        public boolean isAccountNonLocked() {

            return true;

        }

    }
```

```
        @Override

        public boolean isCredentialsNonExpired() {

            return true;

        }

        @Override

        public boolean isEnabled() {

            return true;

        }

    }
}
```

User.java

```
package com.project.SpringSecurity.entities;

import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.Table;

@Entity
@Table(name="user")

public class User {

    @Id

    @GeneratedValue(strategy=GenerationType.AUTO)

    private Integer id;

    private String name;

    private String password;

}
```



```

    public User() {
        super();
    }

    public User(String name, String password) {
        super();
        this.name = name;
        this.password = password;
    }

    public String getName() {
        return name;
    }

    public void setName(String name) {
        this.name = name;
    }

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }
}

```

UsersRepository.java

```

package com.project.SpringSecurity.repositories;

import java.util.Optional;

```

```

import org.springframework.data.repository.CrudRepository;
import org.springframework.stereotype.Repository;
import com.project.SpringSecurity.entities.User;

@Repository
public interface UsersRepository extends CrudRepository<User, Integer>{

    public Optional<User> findUserByName(String name);
}

```

MyUserDetailsService.java

```

package com.project.SpringSecurity.services;

import java.util.Optional;

import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.security.core.userdetails.UserDetailsService;
import org.springframework.security.core.userdetails.UsernameNotFoundException;
import org.springframework.stereotype.Service;

import com.project.SpringSecurity.entities.MyUserDetails;
import com.project.SpringSecurity.entities.User;
import com.project.SpringSecurity.repositories.UsersRepository;

@Service
public class MyUserDetailsService implements UserDetailsService {

    @Autowired
    UsersRepository userRepo;

    public User GetUserByName(String name) {

        Optional<User> user = userRepo.findUserByName(name);

        if(!user.isPresent()) throw new RuntimeException();
    }
}

```

```

        return user.get();
    }

    @Override

    public org.springframework.security.core.userdetails.UserDetails
    loadUserByUsername(String username)

        throws UsernameNotFoundException {

        return new MyUserDetails(GetUserByName(username));
    }
}

```

Src/main/resources

application.properties

```

spring.jpa.hibernate.ddl-auto=update
spring.jpa.hibernate.naming-strategy=org.hibernate.cfg.ImprovedNamingStrategy
spring.jpa.properties.hibernate.dialect=org.hibernate.dialect.MySQL5Dialect
spring.datasource.url=jdbc:mysql://localhost:3306/work
spring.datasource.username=root
spring.datasource.password=12345
logging.level.org.springframework.web: DEBUG
spring.thymeleaf.prefix=/WEB-INF/jsp/
spring.thymeleaf.suffix=.jsp
server.port=8080
server.error.whitelabel.enabled=false

```

src/main/webapp/WEB-INF/jsp

index.jsp

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml"
      xmlns:th="http://www.thymeleaf.org"
      xmlns:sec="http://www.thymeleaf.org/thymeleaf-extras-springsecurity3"
      xmlns:layout="http://www.ultraq.net.nz/thymeleaf/layout">
<head>
<title>Greetings!</title>
</head>
<body>
    <h1>Welcome!</h1>

```

```

        <p>
            Click <a th:href="@{/welcome}">here</a> to see a greeting.
        </p>
    </body>
</html>

```

login.jsp

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:th="https://www.thymeleaf.org"
    xmlns:sec="https://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
    <head>
        <title>Login</title>
    </head>
    <body>
        <div th:if="${param.error}">
            Invalid username or password.
        </div>
        <div th:if="${param.logout}">
            You have been logged out.
        </div>
        <form th:action="@{/login}" method="post">
            <div><label> User Name : <input type="text" name="username"/> </label></div>
            <div><label> Password: <input type="password" name="password"/>
        </label></div>
            <div><input type="submit" value="Sign In"/></div>
        </form>

        <a href="/">Return to Main Page</a>
    </body>
</html>

```

welcome.jsp

```

<!DOCTYPE html>
<html xmlns="http://www.w3.org/1999/xhtml" xmlns:th="https://www.thymeleaf.org"
    xmlns:sec="https://www.thymeleaf.org/thymeleaf-extras-springsecurity3">
    <head>
        <title>Welcome!</title>
    </head>
    <body>
        <h1 th:inline="text">Hello [[${#httpServletRequest.remoteUser}]]!</h1>
        <form th:action="@{/logout}" method="post">
            <input type="submit" value="Sign Out"/>
        </form>
    </body>
</html>

```

```
</form>  
</body>  
</html>
```